



Camera Models M24

Model:**Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M24M-IT-D22**

In/Outdoor, IP66, -30 to +60 °C

Super Wide Angle (22mm, 90°, F 2.0),

VGA (640x480 pixels), color

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA

1 lux (f=1/60s) • 0.05 lux (f=1/1s)

Ethernet 10/100, USB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE (IEEE 802.3af) • Via ExtIO

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

598 EUR (MX-M24M-IT-D22)**M24M-Sec**

In/Outdoor, IP66, -30 to +60 °C

Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm

3MEGA (2048x1536 pixels), color

Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA • 20 fps 3MEGA

1 lux (f=1/60s) • 0.05 lux (f=1/1s)

Ethernet 10/100, USB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE (IEEE 802.3af) • Via ExtIO

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

798 EUR (MX-M24M-Sec)**M24M-Sec-Night**

In/Outdoor, IP66, -30 to +60 °C

Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm

MEGA (1280x960 pixels), B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA

0,1 lux (f=1/60s) • 0.005 lux (f=1/1s)

Ethernet 10/100, USB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE (IEEE 802.3af) • Via ExtIO

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

798 EUR (MX-M24M-Sec-Night)**Model:****Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M24M-Sec-CSVario**

In/Outdoor, IP66, -30 to +60 °C

CSVario 24-54 (24 bis 54mm) F1.6-2.3

3MEGA (2048x1536 pixels), color

Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA • 20 fps 3MEGA

1 lux (f=1/60s) • 0.05 lux (f=1/1s)

Ethernet 10/100, USB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE (IEEE 802.3af) • Via ExtIO

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

998 EUR (MX-M24M-Sec-CSVario)**M24M-Sec-D11**

In/Outdoor, IP66, -30 to +60 °C

Hemispheric (11mm, 360°, F 2.0)

3MEGA (2048x1536 pixels), color

Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA • 20 fps 3MEGA

1 lux (f=1/60s) • 0.05 lux (f=1/1s)

Ethernet 10/100, USB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE (IEEE 802.3af) • Via ExtIO

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

858 EUR (MX-M24M-Sec-D11)**M24M-Sec-Night-N11**

In/Outdoor, IP66, -30 to +60 °C

Hemispheric (11mm, 360°, F 2.0)

MEGA (1280x960 pixels), SW

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA • 30 fps MEGA

0,1 lux (f=1/60sec) • 0.005 lux (f=1/1sec)

Ethernet 10/100, USB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE (IEEE 802.3af) • Via ExtIO

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

858 EUR (MX-M24M-Sec-Night-N11)

Accessories M22/M24

Part Name:**Description:****Prices:****Ethernet patch cable for M24 (1/2/5/10 m)**

- 2x RJ45 plug with special MOBOTIX seal
- 1, 2, 5 or 10 m long

from 8 EUR (MX-OPT-CBL-LAN-1)**M12/M22/M24-Pole Mount**

- 3mm stainless steel, white
- Pole mounting
- Pole circumference from 60 to 180mm
- 2 x stainless steel straps, screws and washers included

78 EUR (MX-MH-SecureFlex-ESWS)**ExtIO**

- Each with 2 In- and Output contacts 8-24V
- Microphone with adjustable volume control, speaker, status LEDs
- USB interface, illumination sensor
- Temperature sensor, 2 buttons

198 EUR (MX-ExtIO)

Camera Models M12

Model:**Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M12M-Web-D43**

In/Outdoor, IP65, -30 to +60 °C

Wide Angle only (43mm, F 2.0), no other lens available

3MEGA (2048x1536 pixels), color

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

1 lux (t=1/60s) • 0.05 lux (t=1/1s)

ISDN, Ethernet 10/100

./.

./.

PoE or MX30V • ./.

Logo generator, FTP, E-Mail

7 day schedule • Reduced

FTP, triggered by events/time schedule

798 EUR (MX-M12M-Web-D43)**M12D-IT-DNight-D43N43**

Dual lens Outdoor, IP65, -30 to +60 °C

2 Wide Angles (43mm, F 2.0), DNight: automatic Day/Night switching

2 x VGA (je 640x480 pixels), color & B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA

0,1 lux (t=1/60s) • 0.005 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

1,098 EUR (MX-M12D-IT-DNight-D43N43)**M12D-Sec-D22D135**

Dual lens Outdoor, IP65, -30 to +60 °C

Super Wide Angle (22mm, 90°, F 2.0), tele (135mm, F 2.5)

2 x 3MEGA (je 2048x1536 pixels), color

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

1 lux (t=1/60s) • 0.05 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

1,248 EUR (MX-M12D-Sec-D22D135)**Model:****Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M12D-Sec-DNight-D43N43**

Dual lens Outdoor, IP65, -30 to +60 °C

2 Wide Angles (43mm, F 2.0), DNight: automatic Day/Night switching

1 x 3MEGA (2048x1536 pixels), color
1 x MEGA (1280x960 pixels), B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

0,1 lux (t=1/60s) • 0.005 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

1,248 EUR (MX-M12D-Sec-DNight-D43N43)**M12D-Sec-DNight-D22N22**

Dual lens Outdoor, IP65, -30 to +60 °C

2 Super Wide Angles (22mm, F 2.0), DNight: automatic Day/Night switching

1 x 3MEGA (2048x1536 pixels), color
1 x MEGA (1280x960 pixels), B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

0,1 lux (t=1/60s) • 0.005 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

1,348 EUR (MX-M12D-Sec-DNight-D22N22)**M12D-Sec-R16**

Dual lens Outdoor, IP65, -30 to +60 °C

Super Wide Angle (22mm, 90°, F 2.0), 43mm, 135mm

1 x 3MEGA (2048x1536 pixels), color
1 x MEGA (1280x960 pixels), B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

1 lux (t=1/60s) • 0.05 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

16 GB internal flash installed

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

from 1,498 EUR (MX-M12D-Sec-R16)

Accessories M12

Part Name:**Description:****Prices:****Cam-IO-PoE/AC/ACplus**

- Interface for external sensors and equipment (door contact, light, etc.)
- 2xRelais-Out, 2xInput, backup, audio
- Power supply via network / 230V / 230V battery buffered
- Compatible with M12 cameras

from 298 EUR (MX-CAMIO)**M12/M22/M24-Pole Mount**

- 3mm stainless steel, white
- Pole mounting
- Pole circumference from 60 to 180mm
- 2 x stainless steel straps, screws and washers included

78 EUR (MX-MH-SecureFlex-ESWS)




M12 mounted to pole






M12 mounted to wall and ceiling



Camera Models D24/Q24

<p>Model:</p> <p>Indoor/Outdoor:</p> <p>Lenses: (eq. 35mm)</p> <p>Resolution:</p> <p>Pan/Tilt/Zoom:</p> <p>Frame Rate (max.):</p> <p>Sensitivity:</p> <p>Interfaces:</p> <p>Internal DVR:</p> <p>Audio/Telephony:</p> <p>Power Sup. • In/Out:</p> <p>Software Features:</p> <p>Arming • Triggering:</p> <p>External Storage:</p> <p>Prices:</p>	 <p>D24Mi-Basic-D22</p> <p>Indoor, IP54, -20 to + 50 °C</p> <p>Super Wide Angle (22mm, 90°, F 2.0)</p> <p>VGA (640x480 pixels), color</p> <p>./.</p> <p>16 fps CIF • 16 fps VGA</p> <p>1 lux (f=1/60s) • 0.05 lux (f=1/1s)</p> <p>Ethernet 10/100</p> <p>./.</p> <p>./.</p> <p>PoE (IEEE 802.3af) • ./.</p> <p>FTP, e-mail, video alarm management, VideoMotion, Multiview, event search</p> <p>./.</p> <p>./.</p> <p>448 EUR (MX-D24Mi-Basic-D22)</p>	 <p>D24M-IT-D22</p> <p>In/Outdoor, IP65, -30 to +60 °C</p> <p>Super Wide Angle (22mm, 90°, F 2.0)</p> <p>VGA (640x480 pixels), color</p> <p>Continuous 8x zoom & pan/tilt (digital)</p> <p>30 fps CIF • 30 fps VGA</p> <p>1 lux (f=1/60s) • 0.05 lux (f=1/1s)</p> <p>Ethernet 10/100, USB, MxBus</p> <p>Up to 64 GB with MicroSD card</p> <p>Bidirectional, IP telephony (VoIP via ExtIO)</p> <p>PoE (IEEE 802.3af) • Via ExtIO</p> <p>FTP, e-mail, video alarm management, VideoMotion, Multiview, event search</p> <p>365 day schedule • Multiple events</p> <p>Up to 1 TB on PC/Server/NAS</p> <p>548 EUR (MX-D24M-IT-D22)</p>	 <p>D24M-Sec/Sec-Night</p> <p>In/Outdoor, IP65, -30 to +60 °C</p> <p>Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm</p> <p>D24M-Sec: 3MEGA (2048x1536 pixels), color</p> <p>D24M-Sec-Night: MEGA (1280x960 pixels), B/W</p> <p>Continuous 8x zoom & pan/tilt (digital)</p> <p>30 fps CIF • 30 fps VGA • 30 fps MEGA</p> <p>1 lux (f=1/60sec) • 0.05 lux (f=1/1sec), color; 0,1 lux (f=1/60sec) • 0.005 lux (f=1/1sec), BW</p> <p>Ethernet 10/100, USB, MxBus</p> <p>Up to 64 GB with MicroSD card</p> <p>Bidirectional, IP telephony (VoIP via ExtIO)</p> <p>PoE (IEEE 802.3af) • Via ExtIO</p> <p>FTP, e-mail, video alarm management, VideoMotion, Multiview, event search</p> <p>365 day schedule • Multiple events</p> <p>Up to 1 Terabyte on PC/Server/NAS</p> <p>748 EUR (MX-D24M-Sec/Sec-Night)</p>
--	---	---	---

<p>Model:</p> <p>Indoor/Outdoor:</p> <p>Lenses: (eq. 35mm)</p> <p>Resolution:</p> <p>Pan/Tilt/Zoom:</p> <p>Frame Rate (max.):</p> <p>Sensitivity:</p> <p>Interfaces:</p> <p>Internal DVR:</p> <p>Audio/Telephony:</p> <p>Power Sup. • In/Out:</p> <p>Software Features:</p> <p>Arming • Triggering:</p> <p>External Storage:</p> <p>Prices:</p>	 <p>Q24M-Basic</p> <p>Indoor, IP54, -30 to +60 °C</p> <p>Hemispheric (11mm, 360°, F 2.0), Super Wide Angle (22mm, 90°, F 2.0)</p> <p>VGA (640x480 pixels), color</p> <p>Digital PTZ via MxControlCenter</p> <p>16 fps CIF • 16 fps VGA</p> <p>1 lux (f=1/60s) • 0.05 lux (f=1/1s)</p> <p>Ethernet 10/100</p> <p>./.</p> <p>./.</p> <p>PoE (IEEE 802.3af) • ./.</p> <p>Distortion correction in MxCC, FTP, E-mail, video alarm manag., Multiview</p> <p>./.</p> <p>./.</p> <p>598 EUR (MX-Q24Mi-Basic-D11)</p>	 <p>Q24M-Sec</p> <p>In/Outdoor, IP65, -30 to +60 °C</p> <p>Hemispheric (11mm, 360°, F 2.0), Super Wide Angle (22mm, 90°, F 2.0)</p> <p>3MEGA (2048x1536 pixels), color</p> <p>Continuous 8x zoom & pan/tilt (digital)</p> <p>30 fps MEGA • 20 fps 3MEGA</p> <p>1 lux (f=1/60s) • 0.05 lux (f=1/1s)</p> <p>Ethernet 10/100, USB, MxBus</p> <p>Up to 64 GB with MicroSD card</p> <p>Bidirectional, IP telephony (VoIP)</p> <p>PoE (IEEE 802.3af) • Via ExtIO</p> <p>FTP, e-mail, video alarm management, VideoMotion, Multiview, event search</p> <p>365 day schedule • Multiple events</p> <p>Up to 1 Terabyte on PC/Server/NAS</p> <p>798 EUR (MX-Q24M-Sec-D11)</p>	 <p>Q24M-Sec-Night</p> <p>In/Outdoor, IP65, -30 to +60 °C</p> <p>Hemispheric (11mm, 360°, F 2.0) Super Wide Angle (22mm, 90°, F 2.0)</p> <p>MEGA (1280x960 Pixel), B/W</p> <p>Continuous 8x zoom & pan/tilt (digital)</p> <p>30 fps CIF • 30 fps VGA • 30 fps MEGA</p> <p>0,1 lux (f=1/60sec) • 0.005 lux (f=1/1sec)</p> <p>Ethernet 10/100, USB, MxBus</p> <p>Up to 64 GB with MicroSD card</p> <p>Bidirectional, IP telephony (VoIP)</p> <p>PoE (IEEE 802.3af) • Via ExtIO</p> <p>FTP, e-mail, video alarm management, VideoMotion, Multiview, event search</p> <p>365 day schedule • Multiple events</p> <p>Up to 1 Terabyte on PC/Server/NAS</p> <p>798 EUR (MX-Q24M-Sec-Night-N11)</p>
--	---	--	---

Accessories D22/D24/Q22/Q24 (More accessories at www.mobotix.com)

<p>Part Name:</p> <p>Description:</p> <p>Prices:</p>	 <p>D22/D24 Vandalism Set</p> <ul style="list-style-type: none"> Reinforced dome (3mm Polyc.) Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated) <p>98 EUR (MX-D24M-Vandal)</p>	 <p>D22/D24/Q22/Q24 On-Wall Set IP65</p> <ul style="list-style-type: none"> On-wall mount incl. mounting parts Concealed cabling Ø 165x37mm Excluding camera <p>98 EUR (MX-OPT-AP)</p>	 <p>D22/D24/Q22/Q24 10° On-Wall Set IP65</p> <ul style="list-style-type: none"> Includes on-wall mount and assembly parts for installing a camera at a 10° tilt angle Excluding camera <p>98 EUR (MX-OPT-AP-10DEG)</p>
	 <p>D22/D24/Q22/Q24 In-Ceiling Set</p> <ul style="list-style-type: none"> In-ceiling set incl. mounting parts Easy mounting from front Also available in black Excluding camera <p>98 EUR (MX-OPT-IC)</p>	 <p>D22/D24/Q22/Q24 Wall Mount</p> <ul style="list-style-type: none"> Weather protection (IP65) for D22, D24, Q22, Q24 cameras Covers RJ45 wall outlets Space for expansion modules (WLAN) <p>98 EUR (MX-OPT-WH)</p>	 <p>D22/D24/Q22/Q24 Pole and Corner Mount</p> <ul style="list-style-type: none"> 3mm stainless steel, powder-coated Pole diam.: 60 to 180mm Incl. mounting supplies <p>98 EUR (MX-OPT-MH)</p>
	<p>Can be ordered with stainless steel cover Mx-OPT-IC-ESMA</p>		

Camera Models D14

Model:**Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****D14Di-IT**

Dual lens Indoor, IP54, -30 to +60 °C

2 Super Wide Angles (22mm, 90°, F 2.0)
32mm, 43mm, 65mm, 135mm

2 x VGA (je 640x480), color & B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA

1 lux (f=1/60s) • 0.05 lux (f=1/1s)

Ethernet 10/100, RS232, MiniUSB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V

FTP, e-mail, video alarm management,
VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

998 EUR (MX-D14Di-IT)**D14Di-Sec**

Dual lens Indoor, IP54, -30 to +60 °C

2 Super Wide Angles (22mm, 90°, F 2.0)
32mm, 43mm, 65mm, 135mm1 x 3MEGA (2048x1536 pixels), color
1 x MEGA (1280x960 pixels), B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA • 20 fps 3MEGA

1 lux (f=1/60s) • 0.05 lux (f=1/1s)

Ethernet 10/100, RS232, MiniUSB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V

FTP, e-mail, video alarm management,
VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

1,248 EUR (MX-D14Di-Sec)**D14Di-Sec-180°**

Dual lens Indoor, IP54, -30 to +60 °C

2 Super Wide Angles (22mm, 90°, F 2.0)

2 x MEGA (2560x960 pixels), B/W

Continuous 8x zoom & pan/tilt (digital)

30 fps VGA • 30 fps MEGA • 20 fps 3MEGA

1 lux (f=1/60s) • 0.05 lux (f=1/1s)

Ethernet 10/100, RS232, MiniUSB, MxBus

Up to 64 GB with MicroSD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V

FTP, e-mail, video alarm management,
VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

1,248 EUR (MX-D14Di-Sec-180°)

Accessories D14

Part Name:**Description:****D14 Pole and Corner Mount**

- 3mm stainless steel, powder-coated
- Pole diam.: 60 to 180mm
- Incl. mounting supplies

Prices:**98 EUR (MX-MH-Dome-ESWS)****D14 Wall Mount**

- Weatherproof (IP65) for D14D-Dome
- Robust and UV resistant PBT
- Covers RJ45 wall outlets and PatchBox
- Possible to fit WLAN or GSM/GPRS
- Incl. ETH patch cable (1m)

148 EUR (MX-WH-Dome)

D14 mounted to corner



D14 mounted to pole

**Part Name:****Description:****D14 Vandalism Set**

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (matt or polished)

Prices:**148 EUR (MX-D14-Vandal-ESPO/ESMA)****D14 Vandalism Set**

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (white, silver or black powder-coated)

148 EUR (MX-D14-Vandal-PUWH/PUGR/PUBL)

Accessories All Cams

Part Name:**Description:****PoE Power Adapter Set**

- Power supply via network cabling
- All cameras supplied by PoE

Prices:**98 EUR (MX-NPA-PoE-Set-INT)****Network Power Rack for 4/8/20 cameras**

- Power supply for DIN rails
- For M12, M22, D12, Q22, V12, DevKit series

from 398 EUR (MX-NPR-4/NPR-8/NPR-20)**Outdoor PatchBox**

- Weatherproof universal network connector for installation cable, MOBOTIX patch cable and standard patch cable

48 EUR (MX-OPT-Patch1-EXT)**Part Name:****Description:****Mx2Wire Pure White**

- Ethernet and PoE using two-wire cable
- Up to 500 meters/up to 30 Mbps (netto)
- 7 watts via PoE

Prices:**Set price (2 units) 298 EUR (MX-2Wire-Set-PW)****ExtIO**

- Each with 2 In- and Output contacts 8-24V
- Microphone with adjustable volume control, speaker, status LEDs
- USB interface, illumination sensor,
- Temperature sensor, 2 buttons
- For all cameras except M1, M10, D10 und V10

198 EUR (MX-ExtIO)**Cam-IO-PoE/AC/ACplus**

- Interface for external sensors and equipment (door contact, light, etc.)
- 2xRelais-Out, 2xInput, backup, audio
- Power supply via network / 230V / 230V battery buffered
- Compatible with M12 cameras

from 298 EUR (MX-CAMIO)

CamIO AC & ACPlus:
As long as stocks last!