

## Camera Models M24

**Model:****Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M24M-IT-D22**

In/Outdoor, IP66, -22 to + 144 °F  
Super Wide Angle (22mm, 90°, F 2.0),  
VGA (640x480 pixels), color  
Continuous 8x zoom & pan/tilt (digital)  
30 fps CIF • 30 fps VGA  
1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
Ethernet 10/100, USB, MxBus  
Up to 64 GB with MicroSD card  
Bidirectional, IP telephony (VoIP)  
PoE (IEEE 802.3af) • Via ExtIO  
FTP, e-mail, video alarm management,  
VideoMotion, Multiview, event search  
365 day schedule • Multiple events  
Up to 1 TB on PC/Server/NAS

**\$798 (MX-M24M-IT-D22)****M24M-Sec**

In/Outdoor, IP66, -22 to + 144 °F  
Super Wide Angle (22mm, 90°, F 2.0), 32mm,  
43mm, 65mm, 135mm  
3MEGA (2048x1536 pixels), color  
Continuous 8x zoom & pan/tilt (digital)  
30 fps VGA • 30 fps MEGA • 20 fps 3MEGA  
1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
Ethernet 10/100, USB, MxBus  
Up to 64 GB with MicroSD card  
Bidirectional, IP telephony (VoIP)  
PoE (IEEE 802.3af) • Via ExtIO  
FTP, e-mail, video alarm management,  
VideoMotion, Multiview, event search  
365 day schedule • Multiple events  
Up to 1 TB on PC/Server/NAS

**\$998 (MX-M24M-Sec)****M24M-Sec-Night**

In/Outdoor, IP66, -22 to + 144 °F  
Super Wide Angle (22mm, 90°, F 2.0), 32mm,  
43mm, 65mm, 135mm  
MEGA (1280x960 pixels), B/W  
Continuous 8x zoom & pan/tilt (digital)  
30 fps VGA • 30 fps MEGA  
0,1 lux (f=1/60s) • 0.005 lux (f=1/1s)  
Ethernet 10/100, USB, MxBus  
Up to 64 GB with MicroSD card  
Bidirectional, IP telephony (VoIP)  
PoE (IEEE 802.3af) • Via ExtIO  
FTP, e-mail, video alarm management,  
VideoMotion, Multiview, event search  
365 day schedule • Multiple events  
Up to 1 TB on PC/Server/NAS

**\$998 (MX-M24M-Sec-Night)****Model:****Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M24M-Sec-CSVario**

In/Outdoor, IP66, -22 to + 144 °F  
CSVario 24-54 (24 bis 54mm)  
F1.6-2.3  
3MEGA (2048x1536 pixels), color  
Continuous 8x zoom & pan/tilt (digital)  
30 fps VGA • 30 fps MEGA • 20 fps 3MEGA  
1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
Ethernet 10/100, USB, MxBus  
Up to 64 GB with MicroSD card  
Bidirectional, IP telephony (VoIP)  
PoE (IEEE 802.3af) • Via ExtIO  
FTP, e-mail, video alarm management,  
VideoMotion, Multiview, event search  
365 day schedule • Multiple events  
Up to 1 TB on PC/Server/NAS

**\$1,398 (MX-M24M-Sec-CSVario)****M24M-Sec-D11**

In/Outdoor, IP66, -22 to + 144 °F  
Hemispheric (11mm, 360°, F 2.0)  
3MEGA (2048x1536 pixels), color  
Continuous 8x zoom & pan/tilt (digital)  
30 fps VGA • 30 fps MEGA • 20 fps 3MEGA  
1 lux (f=1/60s) • 0.05 lux (f=1/1s)  
Ethernet 10/100, USB, MxBus  
Up to 64 GB with MicroSD card  
Bidirectional, IP telephony (VoIP)  
PoE (IEEE 802.3af) • Via ExtIO  
FTP, e-mail, video alarm management,  
VideoMotion, Multiview, event search  
365 day schedule • Multiple events  
Up to 1 TB on PC/Server/NAS

**\$1,258 (MX-M24M-Sec-D11)****M24M-Sec-Night-N11**

In/Outdoor, IP66, -22 to + 144 °F  
Hemispheric (11mm, 360°, F 2.0)  
MEGA (1280x960 pixels), SW  
Continuous 8x zoom & pan/tilt (digital)  
30 fps CIF • 30 fps VGA • 30 fps MEGA  
0,1 lux (f=1/60sec) • 0.005 lux (f=1/1sec)  
Ethernet 10/100, USB, MxBus  
Up to 64 GB with MicroSD card  
Bidirectional, IP telephony (VoIP)  
PoE (IEEE 802.3af) • Via ExtIO  
FTP, e-mail, video alarm management,  
VideoMotion, Multiview, event search  
365 day schedule • Multiple events  
Up to 1 TB on PC/Server/NAS

**\$1,258 (MX-M24M-Sec-Night-N11)**

## Accessories M22/M24

**Part Name:****Description:****Ethernet patch cable for M24 (1/2/5/10 m)**

- 2x RJ45 plug with special MOBOTIX seal
- 1, 2, 5 or 10 m long

**Prices:****from \$12 (MX-OPT-CBL-LAN-1)****M12/M22/M24-Pole Mount**

- 3mm stainless steel, white
- Pole mounting
- Pole circumference from 60 to 180mm
- 2 x stainless steel straps, screws and washers included

**\$128 (MX-MH-SecureFlex-ESWS)****ExtIO**

- Each with 2 In- and Output contacts 8-24V
- Microphone with adjustable volume control, speaker, status LEDs
- USB interface, illumination sensor
- Temperature sensor, 2 buttons

**\$298 (MX-ExtIO)**

## Camera Models M12

**Model:****Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M12M-Web-D43**

In/Outdoor, IP65, -22 to + 144 °F

Wide Angle only (43mm, F 2.0), no other lens available

3MEGA (2048x1536 pixels), color

Continuous 8x zoom &amp; pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

1 lux (t=1/60s) • 0.05 lux (t=1/1s)

ISDN, Ethernet 10/100

./.

./.

PoE or MX30V • ./.

Logo generator, FTP, E-Mail

7 day schedule • Reduced

FTP, triggered by events/time schedule

**\$998 (MX-M12M-Web-D43)****M12D-IT-DNight-D43N43**

Dual lens Outdoor, IP65, -22 to + 144 °F

2 Wide Angles (43mm, F 2.0), DNight: automatic Day/Night switching  
2 x VGA (je 640x480 pixels), color & B/W

Continuous 8x zoom &amp; pan/tilt (digital)

30 fps CIF • 30 fps VGA

0,1 lux (t=1/60s) • 0.005 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

**\$1,198 (MX-M12D-IT-DNight-D43N43)****M12D-Sec-D22D135**

Dual lens Outdoor, IP65, -22 to + 144 °F

Super Wide Angle (22mm, 90°, F 2.0), tele (135mm, F 2.5)

2 x 3MEGA (je 2048x1536 pixels), color

Continuous 8x zoom &amp; pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

1 lux (t=1/60s) • 0.05 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

**\$1,498 (MX-M12D-Sec-D22D135)****Model:****Indoor/Outdoor:****Lenses:** (eq. 35mm)**Resolution:****Pan/Tilt/Zoom:****Frame Rate (max.):****Sensitivity:****Interfaces:****Internal DVR:****Audio/Telephony:****Power Sup. • In/Out:****Software Features:****Arming • Triggering:****External Storage:****Prices:****M12D-Sec-DNight-D43N43**

Dual lens Outdoor, IP65, -22 to + 144 °F

2 Wide Angles (43mm, F 2.0), DNight: automatic Day/Night switching

1 x 3MEGA (2048x1536 pixels), color  
1 x MEGA (1280x960 pixels), B/W

Continuous 8x zoom &amp; pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

0,1 lux (t=1/60s) • 0.005 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

**\$1,498 (MX-M12D-Sec-DNight-D43N43)****M12D-Sec-DNight-D22N22**

Dual lens Outdoor, IP65, -22 to + 144 °F

2 Super Wide Angles (22mm, F 2.0), DNight: automatic Day/Night switching

1 x 3MEGA (2048x1536 pixels), color  
1 x MEGA (1280x960 pixels), B/W

Continuous 8x zoom &amp; pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

0,1 lux (t=1/60s) • 0.005 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

Up to 64 GB with SD card

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

**\$1,598 (MX-M12D-Sec-DNight-D22N22)****M12D-Sec-R16**

Dual lens Outdoor, IP65, -22 to + 144 °F

Super Wide Angle (22mm, 90°, F 2.0), 43mm, 135mm

1 x 3MEGA (2048x1536 pixels), color  
1 x MEGA (1280x960 pixels), B/W

Continuous 8x zoom &amp; pan/tilt (digital)

30 fps CIF • 30 fps VGA • 14 fps MEGA

1 lux (t=1/60s) • 0.05 lux (t=1/1s)

ISDN, Ethernet 10/100, RS232

16 GB internal flash installed

Bidirectional, IP telephony (VoIP)

PoE or MX30V • 3xIN, 1xOUT

FTP, e-mail, video alarm management, VideoMotion, Multiview, event search

365 day schedule • Multiple events

Up to 1 TB on PC/Server/NAS

**from \$1,848 (MX-M12D-Sec-R16)**

## Accessories M12

**Part Name:****Description:****Prices:****Cam-IO-PoE/AC/ACplus**

- Interface for external sensors and equipment (door contact, light, etc.)
- 2xRelais-Out, 2xInput, backup, audio
- Power supply via network / 230V / 230V battery buffered
- Compatible with M12 cameras

**from \$398 (MX-CAMIO)****M12/M22/M24-Pole Mount**

- 3mm stainless steel, white
- Pole mounting
- Pole circumference from 60 to 180mm
- 2 x stainless steel straps, screws and washers included

**\$128 (MX-MH-SecureFlex-ESWS)**

## M12 mounted to pole



## M12 mounted to wall and ceiling






# HiRes IP Cameras And Accessories



The HiRes Video Company

## Camera Models D24/Q24

			
<b>Model:</b>	<b>D24Mi-Basic-D22</b>	<b>D24M-IT-D22</b>	<b>D24M-Sec/Sec-Night</b>
<b>Indoor/Outdoor:</b>	Indoor, IP54, -22 to + 144 °F	In/Outdoor, IP65, -22 to + 144 °F	In/Outdoor, IP65, -22 to + 144 °F
<b>Lenses:</b> (eq. 35mm)	Super Wide Angle (22mm, 90°, F 2.0)	Super Wide Angle (22mm, 90°, F 2.0)	Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
<b>Resolution:</b>	VGA (640x480 pixels), color	VGA (640x480 pixels), color	D24M-Sec: 3MEGA (2048x1536 pixels), color D24M-Sec-Night: MEGA (1280x960 pixels), B/W
<b>Pan/Tilt/Zoom:</b>	./.	Continuous 8x zoom & pan/tilt (digital)	Continuous 8x zoom & pan/tilt (digital)
<b>Frame Rate (max.):</b>	16 fps CIF • 16 fps VGA	30 fps CIF • 30 fps VGA	30 fps CIF • 30 fps VGA • 30 fps MEGA
<b>Sensitivity:</b>	1 lux (t=1/60s) • 0.05 lux (t=1/1s)	1 lux (t=1/60s) • 0.05 lux (t=1/1s)	1 lux (t=1/60sec) • 0.05 lux (t=1/1sec), color; 0,1 lux (t=1/60sec) • 0.005 lux (t=1/1sec), BW
<b>Interfaces:</b>	Ethernet 10/100	Ethernet 10/100, USB, MxBus	Ethernet 10/100, USB, MxBus
<b>Internal DVR:</b>	./.	Up to 64 GB with MicroSD card	Up to 64 GB with MicroSD card
<b>Audio/Telephony:</b>	./.	Bidirectional, IP telephony (VoIP via ExtIO)	Bidirectional, IP telephony (VoIP via ExtIO)
<b>Power Sup. • In/Out:</b>	PoE (IEEE 802.3af) • ./.	PoE (IEEE 802.3af) • Via ExtIO	PoE (IEEE 802.3af) • Via ExtIO
<b>Software Features:</b>	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search
<b>Arming • Triggering:</b>	./.	365 day schedule • Multiple events	365 day schedule • Multiple events
<b>External Storage:</b>	./.	Up to 1 TB on PC/Server/NAS	Up to 1 Terabyte on PC/Server/NAS
<b>Prices:</b>	<b>\$648 (MX-D24Mi-Basic-D22)</b>	<b>\$748 (MX-D24M-IT-D22)</b>	<b>\$948 (MX-D24M-Sec/Sec-Night)</b>

			
<b>Model:</b>	<b>Q24M-Basic</b>	<b>Q24M-Sec</b>	<b>Q24M-Sec-Night</b>
<b>Indoor/Outdoor:</b>	Indoor, IP54, -22 to + 144 °F	In/Outdoor, IP65, -22 to + 144 °F	In/Outdoor, IP65, -22 to + 144 °F
<b>Lenses:</b> (eq. 35mm)	Hemispheric (11mm, 360°, F 2.0), Super Wide Angle (22mm, 90°, F 2.0)	Hemispheric (11mm, 360°, F 2.0), Super Wide Angle (22mm, 90°, F 2.0)	Hemispheric (11mm, 360°, F 2.0), Super Wide Angle (22mm, 90°, F 2.0)
<b>Resolution:</b>	VGA (640x480 pixels), color	3MEGA (2048x1536 pixels), color	MEGA (1280x960 Pixel), B/W
<b>Pan/Tilt/Zoom:</b>	Digital PTZ via MxControlCenter	Continuous 8x zoom & pan/tilt (digital)	Continuous 8x zoom & pan/tilt (digital)
<b>Frame Rate (max.):</b>	16 fps CIF • 16 fps VGA	30 fps MEGA • 20 fps 3MEGA	30 fps CIF • 30 fps VGA • 30 fps MEGA
<b>Sensitivity:</b>	1 lux (t=1/60s) • 0.05 lux (t=1/1s)	1 lux (t=1/60s) • 0.05 lux (t=1/1s)	0,1 lux (t=1/60sec) • 0.005 lux (t=1/1sec)
<b>Interfaces:</b>	Ethernet 10/100	Ethernet 10/100, USB, MxBus	Ethernet 10/100, USB, MxBus
<b>Internal DVR:</b>	./.	Up to 64 GB with MicroSD card	Up to 64 GB with MicroSD card
<b>Audio/Telephony:</b>	./.	Bidirectional, IP telephony (VoIP)	Bidirectional, IP telephony (VoIP)
<b>Power Sup. • In/Out:</b>	PoE (IEEE 802.3af) • ./.	PoE (IEEE 802.3af) • Via ExtIO	PoE (IEEE 802.3af) • Via ExtIO
<b>Software Features:</b>	Distortion correction in MxCC, FTP, E-mail, video alarm manag., Multiview	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search
<b>Arming • Triggering:</b>	./.	365 day schedule • Multiple events	365 day schedule • Multiple events
<b>External Storage:</b>	./.	Up to 1 Terabyte on PC/Server/NAS	Up to 1 Terabyte on PC/Server/NAS
<b>Prices:</b>	<b>\$798 (MX-Q24Mi-Basic-D11)</b>	<b>\$998 (MX-Q24M-Sec-D11)</b>	<b>\$998 (MX-Q24M-Sec-Night-N11)</b>




## Accessories D22/D24/Q22/Q24 (More accessories at www.mobotix.com)

			
<b>Part Name:</b>	<b>D22/D24 Vandalism Set</b>	<b>D22/D24/Q22/Q24 On-Wall Set IP65</b>	<b>D22/D24/Q22/Q24 10° On-Wall Set IP65</b>
<b>Description:</b>	<ul style="list-style-type: none"> <li>Reinforced dome (3mm Polyc.)</li> <li>Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated)</li> </ul>	<ul style="list-style-type: none"> <li>On-wall mount incl. mounting parts</li> <li>Concealed cabling</li> <li>Ø 165x37mm</li> <li>Excluding camera</li> </ul>	<ul style="list-style-type: none"> <li>Includes on-wall mount and assembly parts for installing a camera at a 10° tilt angle</li> <li>Excluding camera</li> </ul>
<b>Prices:</b>	<b>\$148 (MX-D24M-Vandal)</b>	<b>\$148 (MX-OPT-AP)</b>	<b>\$148 (MX-OPT-AP-10DEG)</b>

			
<b>Part Name:</b>	<b>D22/D24/Q22/Q24 In-Ceiling Set</b>	<b>D22/D24/Q22/Q24 Wall Mount</b>	<b>D22/D24/Q22/Q24 Pole and Corner Mount</b>
<b>Description:</b>	<ul style="list-style-type: none"> <li>In-ceiling set incl. mounting parts</li> <li>Easy mounting from front</li> <li>Also available in black</li> <li>Excluding camera</li> </ul>	<ul style="list-style-type: none"> <li>Weather protection (IP65) for D22, D24, Q22, Q24 cameras</li> <li>Covers RJ45 wall outlets</li> <li>Space for expansion modules (WLAN)</li> </ul>	<ul style="list-style-type: none"> <li>3mm stainless steel, powder-coated</li> <li>Pole diam.: 60 to 180mm</li> <li>Incl. mounting supplies</li> </ul>
<b>Prices:</b>	<b>\$148 (MX-OPT-IC)</b>	<b>\$148 (MX-OPT-WH)</b>	<b>\$148 (MX-OPT-MH)</b>

Can be ordered with stainless steel cover Mx-OPT-IC-ESMA

## Camera Models D14

			
<b>Model:</b>	<b>D14Di-IT</b>	<b>D14Di-Sec</b>	<b>D14Di-Sec-180°</b>
<b>Indoor/Outdoor:</b>	Dual lens Indoor, IP54, -22 to +144 °F	Dual lens Indoor, IP54, -22 to +144 °F	Dual lens Indoor, IP54, -22 to +144 °F
<b>Lenses:</b> (eq. 35mm)	2 Super Wide Angles (22mm, 90°, F 2.0) 32mm, 43mm, 65mm, 135mm	2 Super Wide Angles (22mm, 90°, F 2.0) 32mm, 43mm, 65mm, 135mm	2 Super Wide Angles (22mm, 90°, F 2.0)
<b>Resolution:</b>	2 x VGA (je 640x480), color & B/W	1 x 3MEGA (2048x1536 pixels), color 1 x MEGA (1280x960 pixels), B/W	2 x MEGA (2560x960 pixels), B/W
<b>Pan/Tilt/Zoom:</b>	Continuous 8x zoom & pan/tilt (digital)	Continuous 8x zoom & pan/tilt (digital)	Continuous 8x zoom & pan/tilt (digital)
<b>Frame Rate (max.):</b>	30 fps VGA • 30 fps MEGA	30 fps VGA • 30 fps MEGA • 20 fps 3MEGA	30 fps VGA • 30 fps MEGA • 20 fps 3MEGA
<b>Sensitivity:</b>	1 lux (f=1/60s) • 0.05 lux (f=1/1s)	1 lux (f=1/60s) • 0.05 lux (f=1/1s)	1 lux (f=1/60s) • 0.05 lux (f=1/1s)
<b>Interfaces:</b>	Ethernet 10/100, RS232, MiniUSB, MxBus	Ethernet 10/100, RS232, MiniUSB, MxBus	Ethernet 10/100, RS232, MiniUSB, MxBus
<b>Internal DVR:</b>	Up to 64 GB with MicroSD card	Up to 64 GB with MicroSD card	Up to 64 GB with MicroSD card
<b>Audio/Telephony:</b>	Bidirectional, IP telephony (VoIP)	Bidirectional, IP telephony (VoIP)	Bidirectional, IP telephony (VoIP)
<b>Power Sup. • In/Out:</b>	PoE or MX30V	PoE or MX30V	PoE or MX30V
<b>Software Features:</b>	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search	FTP, e-mail, video alarm management, VideoMotion, Multiview, event search
<b>Arming • Triggering:</b>	365 day schedule • Multiple events	365 day schedule • Multiple events	365 day schedule • Multiple events
<b>External Storage:</b>	Up to 1 TB on PC/Server/NAS	Up to 1 TB on PC/Server/NAS	Up to 1 TB on PC/Server/NAS
<b>Prices:</b>	<b>\$1,328 (MX-D14Di-IT)</b>	<b>\$1,628 (MX-D14Di-Sec)</b>	<b>\$1,628 (MX-D14Di-Sec-180°)</b>

## Accessories D14

<b>Part Name:</b>	<b>D14 Pole and Corner Mount</b>	<b>D14 Wall Mount</b>
<b>Description:</b>	<ul style="list-style-type: none"> <li>• 3mm stainless steel, powder-coated</li> <li>• Pole diam.: 60 to 180mm</li> <li>• Incl. mounting supplies</li> </ul>	<ul style="list-style-type: none"> <li>• Weatherproof (IP65) for D14D-Dome</li> <li>• Robust and UV resistant PBT</li> <li>• Covers RJ45 wall outlets and PatchBox</li> <li>• Possible to fit WLAN or GSM/GPRS</li> <li>• Incl. ETH patch cable (1m)</li> </ul>
<b>Prices:</b>	<b>\$148 (MX-MH-Dome-ESWS)</b>	<b>\$148 (MX-WH-Dome)</b>
<b>Part Name:</b>	<b>D14 Vandalism Set</b>	<b>D14 Vandalism Set</b>
<b>Description:</b>	<ul style="list-style-type: none"> <li>• Reinforced dome (3mm Polyc.)</li> <li>• Stainless steel vandalism ring (matt or polished)</li> </ul>	<ul style="list-style-type: none"> <li>• Reinforced dome (3mm Polyc.)</li> <li>• Stainless steel vandalism ring (white, silver or black powder-coated)</li> </ul>
<b>Prices:</b>	<b>\$248 (MX-D14-Vandal-ESPO/ESMA)</b>	<b>\$248 (MX-D14-Vandal-PUWH/PUGR/PUBL)</b>



## Accessories All Cams

<b>Part Name:</b>	<b>PoE Power Adapter Set</b>	<b>Network Power Rack for 4/8/20 cameras</b>	<b>Outdoor PatchBox</b>
<b>Description:</b>	<ul style="list-style-type: none"> <li>• Power supply via network cabling</li> <li>• All cameras supplied by PoE</li> </ul>	<ul style="list-style-type: none"> <li>• Power supply for DIN rails</li> <li>• For M12, M22, D12, D22, Q22, V12, DevKit series</li> </ul>	<ul style="list-style-type: none"> <li>• Weatherproof universal network connector for installation cable, MOBOTIX patch cable and standard patch cable</li> </ul>
<b>Prices:</b>	<b>\$138 (MX-NPA-PoE-Set-INT)</b>	<b>from \$398 (MX-NPR-4/NPR-8/NPR-20)</b>	<b>\$68 (MX-OPT-Patch1-EXT)</b>
<b>Part Name:</b>	<b>Mx2Wire Pure White</b>	<b>ExtIO</b>	<b>Cam-IO-PoE/AC/ACplus</b>
<b>Description:</b>	<ul style="list-style-type: none"> <li>• Ethernet and PoE using two-wire cable</li> <li>• Up to 500 meters/up to 30 Mbps (netto)</li> <li>• 7 watts via PoE</li> </ul>	<ul style="list-style-type: none"> <li>• Each with 2 In- and Output contacts 8-24V</li> <li>• Microphone with adjustable volume control, speaker, status LEDs</li> <li>• USB interface, illumination sensor,</li> <li>• Temperature sensor, 2 buttons</li> <li>• For all cameras except M1, M10, D10 und V10</li> </ul>	<ul style="list-style-type: none"> <li>• Interface for external sensors and equipment (door contact, light, etc.)</li> <li>• 2xRelais-Out, 2xInput, backup, audio</li> <li>• Power supply via network / 230V / 230V battery buffered</li> <li>• Compatible with M12 cameras</li> </ul>
<b>Prices:</b>	<b>Set price (2 units) \$448 (MX-2Wire-Set-PW)</b>	<b>\$298 (MX-ExtIO)</b>	<b>from \$398 (MX-CAMIO)</b>

**CamIO AC & ACPlus:**  
As long as stocks last!