



reddot design award
honourable mention 2009

Q24 with in-ceiling mount



Allround Easy. Allround Secure.

An elegant, ultra compact and weatherproof IP dome camera. Thanks to the 360° allround view to capture an entire room, a panorama function and a quad view to show images from four different angles simultaneously, the Q24 can be used in all new applications.

Original panorama image from Q24M

Mounted to a wall at 2.3 meters in a bank



High-Resolution 180° Panorama

Powerful performance in complete video solutions ...

- Complete panorama view, ideal for access control
- Quad view to show images from four different angles simultaneously
- Digital, continuous zooming and panning
- Robust and maintenance-free, without mechanically moving parts
- Event-controlled, complete room recording directly in the camera (4 GB MicroSD card incl.)
- Alarm function, speaker and microphone integrated

... starting at **£548*** incl. video management software

*MSRP (Manufacturer's suggested retail prices) • Prices ex-works Langmeil, Germany (EXW) • Excluding VAT and any other handling charges • Calculated at FXR 1EUR = 0,9087GBP, 28.10.2009
Information subject to change without notice! • © MOBOTIX AG




Q24 – The Perfect Overview

The Q24 provides a hemispherical 360° allround view with just one lens. Only one camera is needed to view all four corners of a room. The fish-eye effect, typical of this lens, can be digitally switched off already in the live images.

Technical Specifications Q24 Hemispheric	
Models	Basic, Sec, Sec-Night
Lenses	L11 (hemispherical), L22 (90° x 67°)
Sensitivity	Color: 1 lux (t=1/60 s), 0.05 lux (t=1/1 s) B/W: 0.1 lux (t=1/60 s), 0.005 lux (t=1/1 s)
Sensor	1/2" CMOS, progressive scan
Max. image resolution	Color: 2048 x 1536 (3MEGA), Black/White: 1280 x 960 (MEGA)
Image format	Free image format selection (from 160x120 to 2048x1536); with L11: PTZ view, Quad view, panorama broad view image, double panorama view, panorama focus with 3 views
Max frame rate (M-JPEG) (Live/Recording)	VGA: 25 fps, TV-PAL: 18 fps, MEGA: 8 fps, 3MEGA: 4 fps
Video stream (MxPEG) (Live/Recording/Audio)	VGA: 30 fps, TV-PAL: 30 fps, MEGA: 30 fps, 3MEGA: 20 fps
Image compression	MxPEG, M-JPEG, JPEG, H.264 (only Video-VoIP)
Internal DVR	MicroSD slot (camera-internal video recording up to 64 GB)
External storage	Directly on NAS and PC/Server without additional recording software
Software (inclusive)	Video management software MxEasy, Control room software MxControlCenter
Image processing	Backlight compensation, automatic white balance, image distortion correction (panorama image correction included), video sensor (motion detection)
Virtual PTZ	Digital Pan/Tilt/Zoom, continuous 8x zoom
Alarm/Events	Triggering of events by integrated multiple-window motion detection, temperature sensor, notification over email, FTP, IP telephony (VoIP, SIP), visual/acoustic alarm, pre- and post-alarm images
Audio	Integrated microphone and speaker, lip-synchronous audio, two-way speaker, audio recording
Interfaces	Ethernet 10/100, USB, MxBus
Video phone	VoIP, SIP, two-way speaker, remote control via DTMF signaling, event notification
Security	User-/Group management, HTTPS/SSL, IP address filter, IEEE 802.1x, intrusion detection, digital image signature
Certificates	EMC (EN50121-4, EN55022, EN55024, EN61000-6-2, FCC part15B, AS/NZS3548)
Power supply	Power over Ethernet (IEEE 802.3af): PoE class variable depending on operating mode; power consumption; typ. 3 W; with PoE switch/MOBOTIX PoE - Adapter
Operating conditions	IP65 (DIN EN 60529), -30 to +60 °C (-22 to +140 °F)
Dimensions	Ø x H: 16 x 5 cm, Weight: ca. 450 g
Standard delivery	Housing (high-resistance composites – PBT-PC), white, incl. 360° lens, mounting parts, allen wrench, patch cable - 50 cm, manual, software, 4 GB MicroSD (except Basic)

Technical information subject to change without notice:

Q24 Hemispheric		Available Accessories Q24 Hemispheric Camera	
<p>Standard Housing MX-Q24M-Sec</p>  <ul style="list-style-type: none"> • Hemispherical allround view 360° • For wall and ceiling mounting • White or black • Robust and maintenance-free, without mechanically moving parts 	<p>Vandalism Housing MX-Q24M-Sec-Vandal</p>  <ul style="list-style-type: none"> • Stainless steel vandalism housing incl. lens protection • Polished, matt 	<p>In-Ceiling-Set MX-OPT-IC</p>  <ul style="list-style-type: none"> • In-Ceiling set incl. mounting parts • Easy mounting from front • Ø 150 mm installation dimension • White or black • Can be ordered with stainless steel cover (MX-OPT-IC-ESMA) 	<p>ExtIO Extension Module MX-ExtIO</p>  <ul style="list-style-type: none"> • Microphone/Speaker • PIR sensor for motion detection, temperature sensor • 2 signal inputs, 2 signal outputs, 2 illuminated buttons

Quad view (mounted to a ceiling)	Broad view image (mounted to a wall)	3 views simultaneously
	 <p>High-Resolution 180° Panorama</p>	

Q24 – Quad View

A Q24 can replace four cameras and simultaneously show images from 4 different angles on the monitor. Each of the four views has a virtual PTZ function and can be adjusted separately. With the Q24, MOBOTIX yet again demonstrates the innovative power that makes the company a market leader for megapixel video security systems.