

Megapixel
1280 x 960
software zoom

30 Frames/s
VGA (640 x 480)
10 F/s Mega

-22°F ... +140°F
Weatherproof
- 30° ... +60°C, IP65
no heating necessary

IEEE 802.3af
PoE
network power
even in winter

microphone & speaker
Audio
bi-directional via IP
variable framerates

SIP-Client with video
IP-Telephony
alarm notify,
cam remote control

Video motion
multiple windows
precision pixel-based

lip-synchronized audio
Recording
event-ringbuffer
30 cams each 30 F/s

Live viewing
30 cams at 30 F/s
all on one screen

Backlight
safe using CMOS
without mechanical iris

Wall bracket
with cable cover
for RJ45 wall outlet

Robust
no moving parts
fiber glass housing

* Sold only to distributors or commercial clients • Prices excl. VAT/sales tax • Set price without camera • Subject to change without notice

D22: MOBOTIX IP-Dome

High Resolution And Inexpensive

NEW

D22 Basic



Ø 129 mm

Basic 448,-*

*Camera prices include
MxControlCenter software*

- Indoor dome camera (IP54) with lenses available from Super Wide-Angle (90°) to tele (15°)
- Includes L22 Super Wide-Angle lens (90°)
- For indoor use
- Surveillance of a complete room with only one camera
- PoE power supply according to IEEE 802.3af
- Image resolution VGA 640x480, 16 fps VGA

D22 IT (VGA) and SECURE (MEGA)



Ø 160 mm



IT 548,-*
SEC 748,-*

- Outdoor dome camera (IP65) with lenses available from Super Wide-Angle (90°) to tele (15°)
- Includes L22 Super Wide-Angle lens (90°)
- Connectors for external speaker and microphone, for VoIP and SIP telephony
- PoE power supply according to IEEE 802.3af
- IT: max. resolution 640x480, 30 fps VGA
- SEC: max. resolution 1280x960, 10 fps MEGA

D22 IT/SEC + Vandalism Set



Ø 160 mm



Set 98,-*

- Vandalism Set for IT and Secure models
- Consists of stainless steel cover (matt, polished, white, silver or black powder-coated), security screws
- Reinforced dome (3 mm polycarbonate)
- Ideally suited for surveillance at extremely critical locations
- Temp. range -30 to +60°C (-22 to +140°F), IP65

D22 IT/SEC + On Wall Set



Ø 165 x 37 mm



Set 98,-*

- On-Wall Set for IT and Secure camera models
- Consists of On-Wall Mount and mounting parts
- Also conforms to U.S. installation standards
- Reliably protects the cabling and allows integrating additional modules within the On-Wall Mount
- Temp. range -30 to +60°C (-22 to +140°F), IP65

D22 IT/SEC + Outdoor Wall Mount



Set 98,-*

- Outdoor Wall Mount for IT and Secure camera models
- Consists of Outdoor Wall Mount and mounting parts
- Covers RJ45 wall outlets
- Space for expansion modules (battery, 3G, WiFi, etc.)
- Easily mounted to poles using Pole Mount

D22 IT/SEC + In Ceiling Set



Set 98,-*

- In-Ceiling Set for IT and Secure camera models
- Concealed installation in ceilings
- Suitable for hidden surveillance

MOBOTIX HiRes IP Cameras D22



... the new face of IP video

NEW
D22 FixDome



Model: **D22Mi-Basic-D22**
Indoor/Outdoor: Indoor, IP54, -30..+50°C
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): 16 fps VGA • 16 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0.05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Video Ring Buffer: 2 MB
Audio/Telephony: ./.
Power Sup. • In/Out: PoE or MX30V • N/A
Software Features: FTP, e-mail, video alarm management, video motion, MultiView, event search
Arming • Triggering: ./.
External Storage: ./.
Lenses: (eq. 35mm) Super Wide-Angle (22mm, 90°, F 2.0)

Prices: 448 EUR



Model: **D22M-IT-D22**
Indoor/Outdoor: In/Outdoor, IP65 weatherpr., -30..+60°C
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): **30 fps VGA** • 30 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0.05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. audio
Video Ring Buffer: 32 MB/up to 1 Terabyte externally
Audio/Telephony: Bidirectional, VoIP, IP Telephony
Power Sup. • In/Out: PoE or MX30V • Via Mini USB
Software Features: FTP, e-mail, video alarm management, video motion, MultiView, event search
Arming • Triggering: Annual time table • Event logic
External Storage: Ring buffer on PC/server/NAS
Lenses: (eq. 35mm) Super Wide-Angle (22mm, 90°, F 2.0)

Prices: 548 EUR



Model: **D22M-IT-Night-N22**
Indoor/Outdoor: In/Outdoor, IP65 weatherpr., -30..+60°C
Resolution: VGA (640x480 pixels), **BW**
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): **30 fps VGA** • 30 fps CIF
Sensitivity: 0.1 lux (t=1/60sec) • 0.005 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. audio
Video Ring Buffer: 32 MB/up to 1 Terabyte externally
Audio/Telephony: Bidirectional, VoIP, IP Telephony
Power Sup. • In/Out: PoE or MX30V • Via Mini USB
Software Features: FTP, e-mail, video alarm management, video motion, MultiView, event search
Arming • Triggering: Annual time table • Event logic
External Storage: Ring buffer on PC/server/NAS
Lenses: (eq. 35mm) Super Wide-Angle (22mm, 90°, F 2.0)

Prices: 548 EUR



Model: **D22M-Sec**
Indoor/Outdoor: In/Outdoor, IP65 weatherpr., -30..+60°C
Resolution: **MEGA** (1280x960 pixels), color
Pan/Tilt/Zoom: 1x, 2x, 4x • Zoom & Pan/Tilt (digital)
Frame Rate (Mono): **30 fps VGA** • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0.05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. audio
Video Ring Buffer: 64 MB/up to 1 Terabyte externally
Audio/Telephony: Bidirectional, VoIP, IP Telephony
Power Sup. • In/Out: PoE or MX30V • Via Mini USB
Software Features: FTP, e-mail, video alarm management, video motion, MultiView, event search
Arming • Triggering: Annual time table • Event logic
External Storage: Ring buffer on PC/server/NAS
Lenses: (eq. 35mm) Super Wide-Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm

Prices: 748 EUR



Model: **D22M-Sec-Night**
Indoor/Outdoor: In/Outdoor, IP65 weatherpr., -30..+60°C
Resolution: **MEGA** (1280x960 pixels), **BW**
Pan/Tilt/Zoom: 1x, 2x, 4x • Zoom & Pan/Tilt (digital)
Frame Rate (Mono): **30 fps VGA** • 30 fps CIF • 10 fps Mega
Sensitivity: 0.1 lux (t=1/60sec) • 0.005 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. audio
Video Ring Buffer: 64 MB/up to 1 Terabyte externally
Audio/Telephony: Bidirectional, VoIP, IP Telephony
Power Sup. • In/Out: PoE or MX30V • Via Mini USB
Software Features: FTP, e-mail, video alarm management, video motion, MultiView, event search
Arming • Triggering: Annual time table • Event logic
External Storage: Ring buffer on PC/server/NAS
Lenses: (eq. 35mm) Super Wide-Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm

Prices: 748 EUR

MOBOTIX Cost Benefits

- Increased resolution reduces amount of cameras needed
- Reduced installation costs
- Intelligent recording technology reduces required storage
- Event-controlled image rate minimizes storage costs
- No additional power (standard PoE) and no heating required
- Backup power requirement reduced by 8 times
- Robust and practically maintenance free
- No software and no license costs
- Unlimited scalability and high return of investment
- Additional functions and other extras included

L22 Super Wide Angle (90° x 67°)



L32 Wide Angle (60° x 45°)



L43 Wide Angle (45° x 34°)



L65 Tele (31° x 23°)



L135 Tele (15° x 11°)



V24-54 CSVario*



Lenses 1/2", M14 lens distortion can be removed using MxControlCenter

* M22M special order

MOBOTIX accessories for D22 IT/SECURE models (see other products in the price list)



Part Name: **D22 Vandalism Set**
Description:

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated)

Prices: 98 EUR



Part Name: **D22 On-Wall Set**
Description:

- On-wall mount incl. mounting parts
- Concealed cabling
- Ø 165x37mm/6.5x1.5in

Prices: 98 EUR



Part Name: **D22 In-Ceiling Set**
Description:

- In-ceiling set incl. mounting parts
- Concealed camera positioning
- Ø 150mm/5.9in diameter


Prices: 98 EUR



Part Name: **D22 Corner and Pole Mount**
Description:

- 3mm stainless steel, powder-coated
- Pole diam.: 60 to 180mm/2.4 to 7.1in
- Incl. mounting supplies

Prices: 98 EUR



Part Name: **D22 Wall Mount**
Description:

- Weather protection (IP65) for D22
- Covers RJ45 wall outlets
- Space for expansion modules (WiFi)

Prices: 98 EUR

