

Hemispheric IP Video Door Station



Better Overview. Increased Security.

With the IP Video Door Station, MOBOTIX is introducing a new product line in the area of door communication and access control that supports the VoIP/SIP video telephone standard. The T24 records all events outside the house door with sound; automatically when the doorbell is rang, with movement in the image or upon triggering a contact.

Complete video solution with powerful performance ...

- Complete Panorama view from wall to wall and from floor to ceiling thanks to Hemispheric technology
- Recording with sound of all activities in front of the door, automatically around the clock
- Two-way video worldwide via IP telephony or computer with remote door-opening function
- Integrated messaging features for leaving and retrieving messages directly at the door
- Keyless entry using PIN code or transponder with intelligent time control
- Simple installation, optional use of two existing bell wires instead of network cable

... see separate brochure for building technology

Complete Panorama View For Superior Overview


The high-resolution Hemispheric door camera with 3.1 megapixel image sensor and internal MicroSD storage allows monitoring of the entire entrance area. Complete Panorama view from wall to wall and floor to ceiling.






Technical Specifications T24







The HiRes Video Company

MOBOTIX



T24 Modules				Available Colors
<p>T24M Hemispheric Camera</p>  <ul style="list-style-type: none"> Complete panorama view Speaker and microphone 2 function keys 	<p>Code & RFID Module</p>  <ul style="list-style-type: none"> Keyless Entry per Pin code or transponder Integrated messaging feature 	<p>Backlit Information Module</p>  <ul style="list-style-type: none"> Optional with Mx2wire unit (integrated) To connect the T24 via 2 bell wires (data and power) 	<p>Security Door Opener</p>  <ul style="list-style-type: none"> Integrated door gong Backup power supply with battery 2 buttons, 2 LEDs 2 signal inputs, 1 signal output 	<p>Colors</p>  <ul style="list-style-type: none"> Available in white, metallic silver, dark gray and amber Modern, discreet design

Accessories			
<p>Frames (Without Modules)</p>  <ul style="list-style-type: none"> Available as On-Wall or In-Ceiling model Weatherproof (IP65) For 1 to 3 modules Optional with theft protection 	<p>Siedle Vario Installation System</p>  <ul style="list-style-type: none"> Can be combined with T24M and IO circuit board 	<p>IO Circuit Board for Siedle Vario Installation Systems</p>  <ul style="list-style-type: none"> Connection board joins T24M camera with original Siedle modules Simple installation inside Siedle frame 	<p>Grandstream VoIP Videophone</p>  <ul style="list-style-type: none"> Video remote station for T24 Comfortable camera operation, event research, door and light control

Simple And Cost-Effective Installation

The MOBOTIX IP Video Door Station can be connected and supplied with power via a network cable or – thanks to the Mx2wire technology – via two bell wires. Siedle Vario installation systems can also be upgraded with the T24M camera.