



Infomodul Mx2wire+
MX-2wirePlus-Info1-EXT

Farbvarianten Infomodul:

- Weiß (PW)
- Silber (SV)
- Dunkelgrau (DG)
- Schwarz (BL)
- Amber (AM)



Farbvariante Indoor-Einheit:

- Weiß (PW)

31130-001 DE-EN_03/2016

Montage:


Das wetterfeste Infomodul Mx2wire (IP65) wird in den Rahmen der Türstation eingesetzt, die Indoor-Einheit muss im wettergeschützten Bereich montiert werden.

Eine ausführliche Montageanleitung inklusive Schaltplänen finden Sie im **T25 Systemhandbuch Teil 1** (Systemübersicht und Montage). Das Handbuch können Sie als PDF-Dokument kostenlos von der MOBOTIX-Webseite herunterladen: www.mobotix.com > **Support** > **Betriebsanleitungen**.

Achtung:

Die zulässige Umgebungstemperatur für eine T25 Türstation mit Infomodul Mx2wire liegt im Bereich **-30 bis +50 °C**.

Zur Aktivierung der **LED-Beleuchtung des Infomoduls Mx2wire** muss **vor** der Montage die kleine schwarze Steckbrücke („Jumper“) auf der Platine **vorsichtig** abgezogen werden (z. B. mit Pinzette oder kleiner Zange).



LED-Beleuchtung
deaktiviert



LED-Beleuchtung
aktiviert

Lieferumfang:



Infomodul Mx2wire für die Außenstation, vormontiert:

1x	Gehäuse mit Platine und Anschlüssen
1x	Beschriftbares Infofeld mit Abdeckung
1x	Gehäusedichtung

Indoor-Einheit, vormontiert:

1x	Gehäuse mit Platine und Edelstahlschraube 2x11 mm
1x	Frontblende inkl. Edelstahlschraube M3x12 mm
1x	Rahmen konvex

Montagematerial und Zubehör:

4x	Selbstschneidende Edelstahlschrauben 3x10 mm
1x	Torx-Schlüssel
4x	Torx-Schrauben M3,5x40 mm mit Unterlegscheiben u. Dübeln
1x	Aufputzdose 35 mm Höhe inkl. Stopfen 8-adrig
2x	Stopfen für Kabel (3-5 und 5-7 mm, altern. zu Stopfen 8-adrig)
2x	Zusatzrahmen (konkav und plan, altern. zu konvex)
1x	Hohlraumdose

Innovationsschmiede - Made in Germany

Die in Deutschland börsennotierte MOBOTIX AG gilt nicht nur als innovativer Technologiemoor der Netzwerk-Kamera-Technik; ihr dezentrales Konzept lässt hochauflösende Videosysteme überhaupt erst rentabel werden.

MOBOTIX AG • D-67722 Langmeil • Tel: +49 6302 9816-0 • Fax: +49 6302 9816-190 • info@mobotix.com



Color options Info Module:

- Pure White (PW)
- Silver (SV)
- Dark Gray (DG)
- Black (BL)
- Amber (AM)

Color option Indoor Unit:

- Pure White (PW)

Installation:


The weatherproof Info Module Mx2wire (IP65) is inserted into the frame of the door station, the Indoor Unit needs to be mounted in a weather-protected location.

You will find a detailed installation manual, including circuit diagrams, in the **T25 System Manual Part 1** (System Overview And Installation). The manual can be downloaded free-of-charge as a PDF document from the MOBOTIX website: www.mobotix.com > **Support** > **Manuals**.

Caution:

The T25 Video Door Station with Info Module Mx2wire has an operating temperature range of **-30°C to +50°C (-22°F to +122°F)**.

To activate the **LED illumination of the Info Module Mx2wire**, you need to **cautiously** remove the small black jumper on the circuit board (using tweezers or small pliers) **before** mounting the module itself.



LED illumination deactivated



LED illumination activated

Standard Delivery:



Info Module Mx2wire for outdoor station, pre-assembled:

1x	Housing and circuit board
1x	Info field with cover (for labeling)
1x	Seal



Indoor Unit, pre-assembled:

1x	Housing and circuit board including stainless steel screw (2x11 mm)
1x	Front panel including stainless steel screw (M3x12 mm)
1x	Convex frame



Mounting hardware and accessories:

4x	Self-tapping stainless steel screws (3x10 mm)
1x	Torx wrench
4x	Torx screws (M3.5x40 mm), washers (3.5 mm), screw anchors
1x	Surface-mounted socket, height of 35 mm, including 8-wire plug
2x	Plugs for cables (3 to 5 mm and 5 to 7 mm, alternative to 8-wire plug)
2x	Additional frames (concave and flat, alternative to convex)
1x	Cavity socket

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX AG • D-67722 Langmeil • Tel: +49 6302 9816-103 • Fax: +49 6302 9816-190 • sales@mobotix.com