

Product Overview

August 2018



BeyondHumanVision

MOBOTIX

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group
MOBOTIX • 16.08.2018 • MOBOTIX accepts no liability arising from printing errors, mistakes and changes. • Revision 16.08.2018

Professional Video Systems Outdoor

BeyondHumanVision

MOBOTIX

M16B AllroundDual Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-M16B	4047438030915	29,5 cm
	M16B Body, For M16 Sensor Modules (Day/Night)	85258091	19,5 cm
	M16 camera module for connecting one or two M16/M15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.764 g	18,0 cm
			10,4 l
	Mx-M16B-6D6N036	4047438030922	29,5 cm
	M16B Complete Cam 6MP, 2x B036 (Day & Night)	85258091	19,5 cm
	IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.981 g	18,0 cm
			10,4 l
	Mx-M16B-6D6N041	4047438030939	29,5 cm
	M16B Complete Cam 6MP, 2x B041 (Day & Night)	85258091	19,5 cm
	IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.974 g	18,0 cm
			10,4 l
	Mx-M16B-6D6N061	4047438030946	29,5 cm
	M16B Complete Cam 6MP, 2x B061 (Day & Night)	85258091	19,5 cm
	IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	18,0 cm
			10,4 l
	Mx-M16B-6D6N079	4047438030953	29,5 cm
	M16B Complete Cam 6MP, 2x B079 (Day & Night)	85258091	19,5 cm
	IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.971 g	18,0 cm
			10,4 l

**Mx-M16B-6D6N119****M16B Complete Cam 6MP, 2x B119 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030960	29,5 cm
85258091	19,5 cm
1.970 9	18,0 cm
	10,4 l

**Mx-M16B-6D6N237****M16B Complete Cam 6MP, 2x B237 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B237 distant tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030977	29,5 cm
85258091	19,5 cm
1.981 9	18,0 cm
	10,4 l

D16B DualDome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-D16B	4047438030588	39,5 cm
	D16B Body, For D16B/D15 Sensor Modules (Day/Night)	85258091	29,5 cm
	IP camera module for connecting one or two D16/D15 sensor modules or a D16/D15 lens bridge FIX/PAN (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module/bridge): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 15° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Incl. 1x standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.277 g	9,0 cm
			10,5 l
	Mx-D16B-F-6D6N036	4047438030595	39,5 cm
	D16B Complete Cam 6MP, 2x B036 (Day & Night)	85258091	29,5 cm
	IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.646 g	18,0 cm
			21,0 l
	Mx-D16B-F-6D6N041	4047438030601	39,5 cm
	D16B Complete Cam 6MP, 2x B041 (Day & Night)	85258091	29,5 cm
	IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.627 g	18,0 cm
			21,0 l
	Mx-D16B-F-6D6N061	4047438030618	39,5 cm
	D16B Complete Cam 6MP, 2x B061 (Day & Night)	85258091	29,5 cm
	IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.642 g	18,0 cm
			21,0 l
	Mx-D16B-F-6D6N079	4047438030625	39,5 cm
	D16B Complete Cam 6MP, 2x B079 (Day & Night)	85258091	29,5 cm
	IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.645 g	18,0 cm
			21,0 l
	Mx-D16B-F-6D6N119	4047438030632	39,5 cm
	D16B Complete Cam 6MP, 2x B119 (Day & Night)	85258091	29,5 cm
	IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.630 g	18,0 cm
			21,0 l

**Mx-D16B-F-6D6N237****D16B Complete Cam 6MP, 2x B237 (Day & Night)**

IP camera with two parallel aligned lens units • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B237 tele (f/1.8, horizontal image angle 15°) • Equipment line: Secure • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box

4047438030649	39,5 cm
85258091	29,5 cm
1.641 9	18,0 cm
	21,0 l

**Mx-D16B-P-6D6D041****D16B Complete Cam 2x 6MP, Panorama 180° (Day)**

IP camera with PAN lens bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030656	39,5 cm
85258091	29,5 cm
1.650 9	18,0 cm
	21,0 l

**Mx-D16B-P-6N6N041****D16B Complete Cam 2x 6MP, Panorama 180° (Night)**

IP camera with PAN sensor bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030663	39,5 cm
85258091	29,5 cm
1.642 9	18,0 cm
	21,0 l

V16B Vandalism Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-V16B-6D041	4047438031462	26,0 cm
	V16B Complete Cam 6MP, 1x B041 (Day)	85258091	26,0 cm
	V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.600 g	26,0 cm
			17,6 l
	Mx-V16B-6D079	4047438031479	26,0 cm
	V16B Complete Cam 6MP, 1x B079 (Day)	85258091	26,0 cm
	V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.600 g	26,0 cm
			17,6 l
	Mx-V16B-6D6D041	4047438031486	26,0 cm
	V16B Complete Cam 6MP, 2x B041 (Day)	85258091	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x Color (day), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
			17,6 l
	Mx-V16B-6D6D079	4047438031493	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B079 (Day)	85258091	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
			17,6 l
	Mx-V16B-6D6N041	4047438031509	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B041 (Day & Night)	85258091	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
			17,6 l
	Mx-V16B-6D6N079	4047438031516	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B079 (Day & Night)	85258091	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
			17,6 l
	Mx-V16B-6N6N041	4047438031523	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B041 (Night)	85258091	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
			17,6 l

**Mx-V16B-6N6N079****V16B Complete Cam 2x 6MP, 2x B079 (Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031530 26,0 cm

85258091 26,0 cm

4.700 g 26,0 cm

17,6 l

S16B DualFlex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S16B	4047438031400 19,6 cm
	S16B Body, For S16B/S15 Sensor Modules	85258091 14,8 cm
	S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP66/IK06, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio (I/O); RS232 via MX Interface Box	660 g 9,0 cm
		2,6 l
	Mx-S16B-S1	4047438031417 29,6 cm
	S16B Complete Cam, Set 1, 6MP, 1x B016 (Day)	85258091 19,6 cm
	S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal)	720 g 9,0 cm
		5,2 l
	Mx-S16B-S2	4047438031424 29,6 cm
	S16B Complete Cam, Set 2, 6MP, 2x B016 (Day)	85258091 19,6 cm
	S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	1.700 g 9,0 cm
		5,2 l
	Mx-S16B-S3	4047438031431 29,6 cm
	S16B Complete Cam, Set 3, 6MP, 2x B016 (Day & Night)	85258091 19,6 cm
	S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	1.700 g 9,0 cm
		5,2 l

S26B Flex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S26B-6D016	4047438031448	19,5 cm
	S26B Complete Cam 6MP, B016 (Day)	85258091	15,0 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	685 g	9,0 cm
			2,6 l
	Mx-S26B-6N016	4047438031455	19,5 cm
	S26B Complete Cam 6MP, B016 (Night)	85258091	15,0 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	685 g	9,0 cm
			2,6 l

M26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M26B-6D	4047438031042	29,5 cm
	M26B Body 6MP (Day)	85258091	19,5 cm
	IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.337 g	18,0 cm
			10,4 l
	Mx-M26B-6D016	4047438031059	29,5 cm
	M26B Complete Cam 6MP, B016 (Day)	85258091	19,5 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.342 g	18,0 cm
			10,4 l
	Mx-M26B-6D036	4047438031066	29,5 cm
	M26B Complete Cam 6MP, B036 (Day)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.365 g	18,0 cm
			10,4 l
	Mx-M26B-6D041	4047438031073	29,5 cm
	M26B Complete Cam 6MP, B041 (Day)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.354 g	18,0 cm
			10,4 l
	Mx-M26B-6D061	4047438031080	29,5 cm
	M26B Complete Cam 6MP, B061 (Day)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.361 g	18,0 cm
			10,4 l
	Mx-M26B-6D079	4047438031097	29,5 cm
	M26B Complete Cam 6MP, B079 (Day)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.359 g	18,0 cm
			10,4 l
	Mx-M26B-6D119	4047438031103	29,5 cm
	M26B Complete Cam 6MP, B119 (Day)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.359 g	18,0 cm
			10,4 l

	Mx-M26B-6D237	4047438031110	29,5 cm
	M26B Complete Cam 6MP, B237 (Day)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.359 g	18,0 cm
			10,4 l
	Mx-M26B-6D500	4047438031127	29,6 cm
	M26B Complete Cam 6MP, B500 (Day)	85258091	19,6 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	2.000 g	18,0 cm
			10,4 l
	Mx-M26B-6N	4047438031134	29,5 cm
	M26B Body 6MP (Night)	85258091	19,5 cm
	IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.344 g	18,0 cm
			10,4 l
	Mx-M26B-6N016	4047438031141	29,5 cm
	M26B Complete Cam 6MP, B016 (Night)	85258091	19,5 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.342 g	18,0 cm
			10,4 l
	Mx-M26B-6N036	4047438031158	29,5 cm
	M26B Complete Cam 6MP, B036 (Night)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.365 g	18,0 cm
			10,4 l
	Mx-M26B-6N041	4047438031165	29,5 cm
	M26B Complete Cam 6MP, B041 (Night)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.354 g	18,0 cm
			10,4 l
	Mx-M26B-6N061	4047438031172	29,5 cm
	M26B Complete Cam 6MP, B061 (Night)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.361 g	18,0 cm
			10,4 l

	Mx-M26B-6N079	4047438031189	29,5 cm
	M26B Complete Cam 6MP, B079 (Night)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.359	9 18,0 cm
			10,4 l
	Mx-M26B-6N119	4047438031196	29,5 cm
	M26B Complete Cam 6MP, B119 (Night)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.359	9 18,0 cm
			10,4 l
	Mx-M26B-6N237	4047438031202	29,5 cm
	M26B Complete Cam 6MP, B237 (Night)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.359	9 18,0 cm
			10,4 l
	Mx-M26B-6N500	4047438031219	29,5 cm
	M26B Complete Cam 6MP, B500 (Night)	85258091	19,5 cm
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.366	9 18,0 cm
			10,4 l

D26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-D26B-6D	4047438030670	19,5 cm
	D26B Body 6MP (Day)	85258091	18,0 cm
	D26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	799 g	15,0 cm
			5,3 l
	Mx-D26B-6D036	4047438030687	19,5 cm
	D26B Complete Cam 6MP, B036 (Day)	85258091	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	814 g	15,0 cm
			5,3 l
	Mx-D26B-6D041	4047438030694	19,5 cm
	D26B Complete Cam 6MP, B041 (Day)	85258091	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	762 g	15,0 cm
			5,3 l
	Mx-D26B-6D061	4047438030700	19,5 cm
	D26B Complete Cam 6MP, B061 (Day)	85258091	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	814 g	15,0 cm
			5,3 l
	Mx-D26B-6D079	4047438030717	19,6 cm
	D26B Complete Cam 6MP, B079 (Day)	85258091	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessor)	1.580 g	14,8 cm
			5,2 l
	Mx-D26B-6D119	4047438030724	19,6 cm
	D26B Complete Cam 6MP, B119 (Day)	85258091	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.580 g	14,8 cm
			5,2 l
	Mx-D26B-6D237	4047438030731	19,5 cm
	D26B Complete Cam 6MP, B237 (Day)	85258091	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	815 g	15,0 cm
			5,3 l

	Mx-D26B-6N	4047438030748	19,5 cm
	D26B Body 6MP (Night)	85258091	18,0 cm
		799 g	15,0 cm
			5,3 l
	Mx-D26B-6N036	4047438030755	19,5 cm
	D26B Complete Cam 6MP, B036 (Night)	85258091	18,0 cm
		814 g	15,0 cm
			5,3 l
	Mx-D26B-6N041	4047438030762	19,6 cm
	D26B Complete Cam 6MP, B041 (Night)	85258091	18,0 cm
		1.580 g	14,8 cm
			5,2 l
	Mx-D26B-6N061	4047438030779	19,6 cm
	D26B Complete Cam 6MP, B061 (Night)	85258091	18,0 cm
		1.580 g	14,8 cm
			5,2 l
	Mx-D26B-6N079	4047438030786	19,6 cm
	D26B Complete Cam 6MP, B079 (Night)	85258091	18,0 cm
		1.580 g	14,8 cm
			5,2 l
	Mx-D26B-6N119	4047438030793	19,6 cm
	D26B Complete Cam 6MP, B119 (Night)	85258091	18,0 cm
		1.580 g	14,8 cm
			5,2 l
	Mx-D26B-6N237	4047438030809	19,6 cm
	D26B Complete Cam 6MP, B237 (Night)	85258091	18,0 cm
		1.580 g	14,8 cm
			5,2 l

Q26B Hemispheric Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-Q26B-6D016	4047438031387	29,5 cm
	Q26B Complete Cam 6MP, B016 (Day)	85258091	19,5 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	853 g	9,0 cm
			5,2 l
	Mx-Q26B-6N016	4047438031394	29,5 cm
	Q26B Complete Cam 6MP, B016 (Night)	85258091	19,5 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	855 g	9,0 cm
			5,2 l

Professional Video Systems Indoor

BeyondHumanVision

MOBOTIX

c26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-c26B-6D	4047438030489	19,5 cm
	c26B Body 6MP (Day)	85258091	15,0 cm
	c26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	431 g	9,0 cm
			2,6 l
	Mx-c26B-6D016	4047438030496	19,5 cm
	c26B Complete Cam 6MP, B016, Day	85258091	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	433 g	9,0 cm
			2,6 l
	Mx-c26B-6D036	4047438030502	19,5 cm
	c26B Complete Cam 6MP, B036, Day	85258091	15,0 cm
	IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	444 g	9,0 cm
			2,6 l
	Mx-c26B-6N	4047438030519	19,5 cm
	c26B Body 6MP (Night)	85258091	15,0 cm
	c26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	431 g	9,0 cm
			2,6 l
	Mx-c26B-6N016	4047438030526	19,5 cm
	c26B Complete Cam 6MP, B016, Night	85258091	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	433 g	9,0 cm
			2,6 l
	Mx-c26B-6N036	4047438030533	19,5 cm
	c26B Complete Cam 6MP, B036, Night	85258091	15,0 cm
	IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	444 g	9,0 cm
			2,6 l

**Mx-c26B-AU-6D016****c26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030540	19,5 cm
85258091	15,0 cm
442 9	9,0 cm
	2,6 l

**Mx-c26B-AU-6D036****c26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030557	19,5 cm
85258091	15,0 cm
446 9	9,0 cm
	2,6 l

**Mx-c26B-AU-6N016****c26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030564	19,5 cm
85258091	15,0 cm
452 9	9,0 cm
	2,6 l

**Mx-c26B-AU-6N036****c26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030571	19,5 cm
85258091	15,0 cm
446 9	9,0 cm
	2,6 l

i26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-i26B-6D	4047438030816	19,6 cm
	i26B Body 6MP (Day)	85258091	14,8 cm
	i26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	9,0 cm
			2,6 l
	Mx-i26B-6D016	4047438030823	19,5 cm
	i26B Complete Cam 6MP, B016, Day	85258091	15,0 cm
	Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	423 g	9,0 cm
			2,6 l
	Mx-i26B-6D036	4047438030830	19,5 cm
	i26B Complete Cam 6MP, B036, Day	85258091	15,0 cm
	IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	440 g	9,0 cm
			2,6 l
	Mx-i26B-6N	4047438030847	19,6 cm
	i26B Body 6MP (Night)	85258091	14,8 cm
	i26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	420 g	9,0 cm
			2,6 l
	Mx-i26B-6N016	4047438030854	19,5 cm
	i26B Complete Cam 6MP, B016, Night	85258091	15,0 cm
	Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	423 g	9,0 cm
			2,6 l
	Mx-i26B-6N036	4047438030861	19,5 cm
	i26B Complete Cam 6MP, B036, Night	85258091	15,0 cm
	IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	440 g	9,0 cm
			2,6 l

**Mx-i26B-AU-6D016****i26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030878 19,5 cm
85258091 15,0 cm
429 9 9,0 cm
2,6 l

**Mx-i26B-AU-6D036****i26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030885 19,5 cm
85258091 15,0 cm
437 9 9,0 cm
2,6 l

**Mx-i26B-AU-6N016****i26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030892 19,5 cm
85258091 15,0 cm
429 9 9,0 cm
2,6 l

**Mx-i26B-AU-6N036****i26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438030908 19,5 cm
85258091 15,0 cm
437 9 9,0 cm
2,6 l

p26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-p26B-6D	4047438031226	19,5 cm
	p26B Body 6MP, Day	85258091	18,0 cm
	p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	582 g	15,0 cm
			5,3 l
	Mx-p26B-6D016	4047438031233	19,5 cm
	p26B Complete Cam 6MP, B016, Day	85258091	18,0 cm
	Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	574 g	15,0 cm
			5,3 l
	Mx-p26B-6D036	4047438031240	19,5 cm
	p26B Complete Cam 6MP, B036, Day	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	596 g	15,0 cm
			5,3 l
	Mx-p26B-6D061	4047438031257	19,6 cm
	p26B Complete Cam 6MP, B061, Day	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	480 g	14,8 cm
			5,2 l
	Mx-p26B-6D079	4047438031264	19,5 cm
	p26B Complete Cam 6MP, B079, Day	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	596 g	15,0 cm
			5,3 l
	Mx-p26B-6D119	4047438031271	19,6 cm
	p26B Complete Cam 6MP, B119, Day	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	480 g	14,8 cm
			5,2 l

	Mx-p26B-6D237	4047438031288	19,6 cm
	p26B Complete Cam 6MP, B237, Day	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Distant Tele lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	480	14,8 cm
			5,2 l
	Mx-p26B-6N	4047438031295	19,5 cm
	p26B Body 6MP, Night	85258091	18,0 cm
	p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	582	15,0 cm
			5,3 l
	Mx-p26B-6N016	4047438031301	19,5 cm
	p26B Complete Cam 6MP, B016, Night	85258091	18,0 cm
	Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	574	15,0 cm
			5,3 l
	Mx-p26B-6N036	4047438031318	19,6 cm
	p26B Complete Cam 6MP, B036, Night	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	480	14,8 cm
			5,2 l
	Mx-p26B-AU-6D	4047438031325	19,5 cm
	p26B Body 6MP, Day, Audio Package	85258091	18,0 cm
	p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	591	15,0 cm
			5,3 l
	Mx-p26B-AU-6D016	4047438031332	19,6 cm
	p26B Complete Cam 6MP, B016, Day, Audio Package	85258091	18,0 cm
	Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	480	14,8 cm
			5,2 l
	Mx-p26B-AU-6D036	4047438031349	19,6 cm
	p26B Complete Cam 6MP, B036, Day, Audio Package	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white	480	14,8 cm
			5,2 l

**Mx-p26B-AU-6N****p26B Body 6MP, Night, Audio Package**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031356	19,6 cm
85258091	18,0 cm
480 9	14,8 cm
	5,2 l

**Mx-p26B-AU-6N016****p26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031363	19,6 cm
85258091	18,0 cm
480 9	14,8 cm
	5,2 l

**Mx-p26B-AU-6N036****p26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

4047438031370	19,6 cm
85258091	18,0 cm
480 9	14,8 cm
	5,2 l

v26B Indoor Dome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-v26B-6D	4047438031547	19,5 cm
	v26B Body 6MP, Day, White	85258091	18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white	726 g	15,0 cm
			5,3 l
	Mx-v26B-6D-b	4047438031554	19,5 cm
	v26B Body 6MP, Day, Black	85258091	18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: black	726 g	15,0 cm
			5,3 l
	Mx-v26B-6D036	4047438031561	19,5 cm
	v26B Complete Cam 6MP, B036, Day, White	85258091	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white	737 g	15,0 cm
			5,3 l
	Mx-v26B-6N	4047438031578	19,5 cm
	v26B Body 6MP, Night, White	85258091	18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white	726 g	15,0 cm
			5,3 l
	Mx-v26B-6N-b	4047438031585	19,5 cm
	v26B Body 6MP, Night, Black	85258091	18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IO-IC), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: black	726 g	15,0 cm
			5,3 l

Professional Video Systems Thermal

M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-M16TB-R079	4047438030984	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R079 (45°)	85258091	19,6 cm
	IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	2.480 g	18,0 cm
			10,4 l
	Mx-M16TB-R119	4047438030991	29,5 cm
	M16B Thermographic Camera TR, 50 mK, R119 (25°)	85258091	19,5 cm
	IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	1.936 g	18,0 cm
			10,4 l
	Mx-M16TB-R237	4047438031004	29,5 cm
	M16B Thermographic Camera TR, 50 mK, R237 (17°)	85258091	19,5 cm
	IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	1.942 g	18,0 cm
			10,4 l
	Mx-M16TB-T079	4047438031011	29,6 cm
	M16B Thermographic Camera 50 mK, T079 (45°)	85258091	19,6 cm
	IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	2.460 g	18,0 cm
			10,4 l
	Mx-M16TB-T119	4047438031028	29,6 cm
	M16B Thermographic Camera 50 mK, T119 (25°)	85258091	19,6 cm
	IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	2.460 g	18,0 cm
			10,4 l

**Mx-M16TB-T237****M16B Thermographic Camera 50 mK, T237 (17°)**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

4047438031035	29,5 cm
85258091	19,5 cm
1.946 9	18,0 cm
	10,4 l

Sensor Modules Thermal For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-SMA-TS-R079	4047438030090	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TS-R119	4047438030106	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TS-R237	4047438030113	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TP-R079	4047438030120	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,8 cm
			5,2 l
	Mx-O-SMA-TP-R119	4047438030137	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,8 cm
			5,2 l
	Mx-O-SMA-TP-R237	4047438030144	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,8 cm
			5,2 l
	Mx-O-SMA-TP-R079-b	4047438030151	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	890 g	14,8 cm
			5,2 l

	Mx-O-SMA-TP-R119-b PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	4047438030168 90275000 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-O-SMA-TP-R237-b PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	4047438030175 90275000 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-O-SMA-TS-T079 Thermal Sensor Module For S16/S15, 50 mK, B079 (45°) Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	4047438029049 90275000 650 g	17,5 cm 14,0 cm 13,5 cm 3,3 l
	Mx-O-SMA-TS-T119 Thermal Sensor Module For S16/S15, 50 mK, B119 (25°) Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	4047438029056 90275000 650 g	17,5 cm 14,0 cm 13,5 cm 3,3 l
	Mx-O-SMA-TS-T237 Thermal Sensor Module For S16/S15, 50 mK, B237 (17°) Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	4047438029063 90275000 650 g	17,5 cm 14,0 cm 13,5 cm 3,3 l
	Mx-O-SMA-TP-T079 PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	4047438029070 90275000 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-O-SMA-TP-T119 PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	4047438029087 90275000 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-O-SMA-TP-T237 PTMount Thermal For S16/S15, 50 mK, B237 (17°), White PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	4047438029094 90275000 890 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

**Mx-O-SMA-TP-T079-b****PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030021 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-T119-b****PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030038 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-T237-b****PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black

4047438030045 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

MOBOTIX MOVE Cameras

MOBOTIX MOVE Speed Dome Cameras

MOBOTIX MOVE Speed Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SD1A-330	4047438031646	42,5 cm
	MOBOTIX MOVE SpeedDome SD-330	85258091	26,2 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-330 • Weatherproof motor-driven ONVIF S / G Dome PTZ camera • Up to 30x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 129 mm, viewing angle HxV: 62 ° - 2 ° x 47 ° - 2 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30 B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3at or DC 12V (2.12 A) or AC 24V; max 25.4 W • Warranty: 2 years	5.700 g	35,0 cm
			39,0 l
	Mx-SD1A-340-IR	4047438031653	40,2 cm
	MOBOTIX MOVE SpeedDome SD-340-IR	85258091	25,0 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-340-IR • Weatherproof, motorized ONVIF S / G dome PTZ camera with built-in IR LEDs (up to 200m) for day and night use • Up to 40x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 170 mm, viewing angle HxV: 62 ° - 2 ° x 49 ° - 1 °) with "One Push" autofocus and P-iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -40 to 55°C, Humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30B / s (H.264 , with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: UPoE (Universal PoE) or DC 12V (3.25 A) or AC 24V; max 39 W • Warranty: 2 years	5.600 g	37,0 cm
			37,2 l

MOBOTIX MOVE Vandal Dome Camera

MOBOTIX MOVE Vandal Dome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VD1A-4-IR	4047438031639	17,5 cm
	MOBOTIX MOVE VandalDome VD-4-IR	85258091	17,5 cm
	MOBOTIX MOVE VandalDome Network Camera VD-4-IR • Weatherproof ONVIF S / G dome camera with integrated IR LEDs (up to 30 m) for day and night operation • Image sensor: 4MP (2688 x 1512), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.7: 3 to 9 mm, viewing angle HxV: 103 ° -35 ° x 53 ° -23 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 65°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.050 g	17,0 cm
			5,2 l

MOBOTIX MOVE Bullet Camera


MOBOTIX MOVE Bullet Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-BC1A-4-IR	4047438031622	28,5 cm
	MOBOTIX MOVE BulletCamera BC-4-IR	85258091	20,0 cm
	MOBOTIX MOVE Bullet Network Camera BC-4-IR • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 30m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.7: 3 to 9 mm, viewing angle HxV: 103 ° -35 ° x 53 ° -23 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 65°C, humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 2 years	1.237 g	17,5 cm
			10,0 l

Optics

Sensor Modules 6MP For S16A/S16B And

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-O-SMA-S-6D016	4047438029100	10,5 cm
	Sensor Module 6MP, B016 (Day), White	90021900	6,8 cm
	Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,5 cm
			0,7 l
	Mx-O-SMA-S-6D036	4047438029117	10,5 cm
	Sensor Module 6MP, B036 (Day), White	90021900	6,8 cm
	Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,5 cm
			0,7 l
	Mx-O-SMA-S-6D041	4047438029124	10,5 cm
	Sensor Module 6MP, B041 (Day), White	90021900	6,8 cm
	Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,5 cm
			0,7 l
	Mx-O-SMA-S-6D061	4047438029131	10,5 cm
	Sensor Module 6MP, B061 (Day), White	90021900	6,8 cm
	Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,5 cm
			0,7 l
	Mx-O-SMA-S-6D079	4047438029148	10,5 cm
	Sensor Module 6MP, B079 (Day), White	90021900	6,8 cm
	Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,5 cm
			0,7 l
	Mx-O-SMA-S-6D119	4047438029155	10,5 cm
	Sensor Module 6MP, B119 (Day), White	90021900	6,8 cm
	Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,5 cm
			0,7 l
	Mx-O-SMA-S-6D237	4047438029162	10,5 cm
	Sensor Module 6MP, B237 (Day), White	90021900	6,8 cm
	Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,5 cm
			0,7 l

 	Mx-O-SMA-S-6D500 Sensor Module 6MP, B500 (Day), White Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029179 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 	Mx-O-SMA-S-6DCSV Sensor Module 6MP, CSVario 4,5-10 mm (Day), White Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438030052 90021900 190 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 	Mx-O-SMA-S-6DCS Sensor Module 6MP, CS-Mount (Day), White Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438030076 90021900 146 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 	Mx-O-SMA-S-6N016 Sensor Module 6MP, B016 (Night), White Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029186 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 	Mx-O-SMA-S-6N036 Sensor Module 6MP, B036 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029193 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 	Mx-O-SMA-S-6N041 Sensor Module 6MP, B041 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029209 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 	Mx-O-SMA-S-6N061 Sensor Module 6MP, B061 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029216 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 	Mx-O-SMA-S-6N079 Sensor Module 6MP, B079 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029223 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l

	Mx-O-SMA-S-6N119 Sensor Module 6MP, B119 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029230 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N237 Sensor Module 6MP, B237 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029247 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N500 Sensor Module 6MP, B500 (Night), White Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438029254 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6NCSV Sensor Module 6MP, CSVario 4,5-10 mm (Night), White Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS (focal length 4.5 -10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438030069 90021900 190 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6NCS Sensor Module 6MP, CS-Mount (Night), White Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438030083 90021900 146 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L016 Sensor Module 6MP, B016 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029261 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L036 Sensor Module 6MP, B036 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029278 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L041 Sensor Module 6MP, B041 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029285 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l

	Mx-O-SMA-S-6L061 Sensor Module 6MP, B061 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029292 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L079 Sensor Module 6MP, B079 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029308 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L119 Sensor Module 6MP, B119 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029315 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L237 Sensor Module 6MP, B237 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029322 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L500 Sensor Module 6MP, B500 (Night LPF), White Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438029339 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6D016-b Sensor Module 6MP, B016 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029346 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6D036-b Sensor Module 6MP, B036 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029353 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6D041-b Sensor Module 6MP, B041 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029360 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l

	Mx-O-SMA-S-6D061-b Sensor Module 6MP, B061 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029377 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6D079-b Sensor Module 6MP, B079 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029384 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6D119-b Sensor Module 6MP, B119 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029391 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6D237-b Sensor Module 6MP, B237 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029407 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6D500-b Sensor Module 6MP, B500 (Day), Black Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438029414 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N016-b Sensor Module 6MP, B016 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029421 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N036-b Sensor Module 6MP, B036 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029438 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N041-b Sensor Module 6MP, B041 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029445 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l

	Mx-O-SMA-S-6N061-b Sensor Module 6MP, B061 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029452 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N079-b Sensor Module 6MP, B079 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029469 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N119-b Sensor Module 6MP, B119 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029476 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N237-b Sensor Module 6MP, B237 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029483 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6N500-b Sensor Module 6MP, B500 (Night), Black Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438029490 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L016-b Sensor Module 6MP, B016 (Night LPF), Black Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438029506 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L036-b Sensor Module 6MP, B036 (Night LPF), Black Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438029513 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
	Mx-O-SMA-S-6L041-b Sensor Module 6MP, B041 (Night LPF), Black Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438029520 90021900 144 g	10,5 cm 6,8 cm 10,5 cm 0,7 l

**Mx-O-SMA-S-6L061-b****Sensor Module 6MP, B061 (Night LPF), Black**

Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029537 10,5 cm
90021900 6,8 cm
144 g 10,5 cm
0,7 l

**Mx-O-SMA-S-6L079-b****Sensor Module 6MP, B079 (Night LPF), Black**

Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029544 10,5 cm
90021900 6,8 cm
144 g 10,5 cm
0,7 l

**Mx-O-SMA-S-6L119-b****Sensor Module 6MP, B119 (Night LPF), Black**

Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029551 10,5 cm
90021900 6,8 cm
144 g 10,5 cm
0,7 l

**Mx-O-SMA-S-6L237-b****Sensor Module 6MP, B237 (Night LPF), Black**

Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black



4047438029568 10,5 cm
90021900 6,8 cm
144 g 10,5 cm
0,7 l





**Mx-O-SMA-S-6L500-b****Sensor Module 6MP, B500 (Night LPF), Black**




Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029575 10,5 cm
90021900 6,8 cm
144 g 10,5 cm
0,7 l

BlockFlexMounts 6MP For S16A/S16B

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-O-SMA-B-6D016	4047438029797	9,8 cm
	BlockFlexMount 6MP, Incl. Hemispheric B016 (Day)	90021900	7,5 cm
	Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	9,0 cm
			0,7 l
	Mx-O-SMA-B-6D036	4047438029803	9,8 cm
	BlockFlexMount 6MP, Incl. B036 (Day)	90021900	7,5 cm
	Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	9,0 cm
			0,7 l
	Mx-O-SMA-B-6D041	4047438029810	10,0 cm
	BlockFlexMount 6MP, Incl. B041 (Day)	90021900	7,5 cm
	Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	134 g	9,0 cm
			0,7 l
	Mx-O-SMA-B-6D061	4047438029827	10,0 cm
	BlockFlexMount 6MP, Incl. B061 (Day)	90021900	7,5 cm
	Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	136 g	9,0 cm
			0,7 l
	Mx-O-SMA-B-6D079	4047438029834	10,0 cm
	BlockFlexMount 6MP, Incl. B079 (Day)	90021900	7,5 cm
	Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	134 g	9,0 cm
			0,7 l
	Mx-O-SMA-B-6D119	4047438029841	10,0 cm
	BlockFlexMount 6MP, Incl. B119 (Day)	90021900	7,5 cm
	Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	130 g	9,0 cm
			0,7 l
	Mx-O-SMA-B-6D237	4047438029858	10,0 cm
	BlockFlexMount 6MP, Incl. B237 (Day)	90021900	7,5 cm
	Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	134 g	9,0 cm
			0,7 l

	Mx-O-SMA-B-6D500 BlockFlexMount 6MP, incl. B500 (Day) Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029865 10,0 cm 90021900 7,5 cm 150 g 9,0 cm 0,7 l
	Mx-O-SMA-B-6DCS BlockFlexMount 6MP, For CS Mount Lens (Day) Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029766 9,8 cm 90021900 7,5 cm 155 g 9,0 cm 0,7 l
	Mx-O-SMA-B-6N016 BlockFlexMount 6MP, Incl. Hemispheric B016 (Night) Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029872 9,8 cm 90021900 7,5 cm 155 g 9,0 cm 0,7 l
	Mx-O-SMA-B-6N036 BlockFlexMount 6MP, Incl. B036 (Night) Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029889 9,8 cm 90021900 7,5 cm 155 g 9,0 cm 0,7 l
	Mx-O-SMA-B-6N041 BlockFlexMount 6MP, Incl. B041 (Night) Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029896 9,8 cm 90021900 7,5 cm 155 g 9,0 cm 0,7 l
	Mx-O-SMA-B-6N061 BlockFlexMount 6MP, Incl. B061 (Night) Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029902 9,8 cm 90021900 7,5 cm 155 g 9,0 cm 0,7 l
	Mx-O-SMA-B-6N079 BlockFlexMount 6MP, Incl. B079 (Night) Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029919 10,0 cm 90021900 7,5 cm 134 g 9,0 cm 0,7 l
	Mx-O-SMA-B-6N119 BlockFlexMount 6MP, Incl. B119 (Night) Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029926 10,0 cm 90021900 7,5 cm 130 g 9,0 cm 0,7 l

	Mx-O-SMA-B-6N237 BlockFlexMount 6MP, Incl. B237 (Night) Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029933 90021900 134 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6N500 BlockFlexMount 6MP, Incl. B500 (Night) Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029940 90021900 155 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6NCS BlockFlexMount 6MP, For CS Mount Lens (Night) Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029773 90021900 102 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6L036 BlockFlexMount 6MP, Incl. B036 (Night LPF) Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029957 90021900 136 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6L041 BlockFlexMount 6MP, Incl. B041 (Night LPF) Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029964 90021900 132 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6L061 BlockFlexMount 6MP, Incl. B061 (Night LPF) Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029971 90021900 134 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6L079 BlockFlexMount 6MP, Incl. B079 (Night LPF) Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029988 90021900 134 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6L119 BlockFlexMount 6MP, Incl. B119 (Night LPF) Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438029995 90021900 130 g	10,0 cm 7,5 cm 9,0 cm 0,7 l

**Mx-O-SMA-B-6L237****BlockFlexMount 6MP, Incl. B237 (Night LPF)**


Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030007	10,0 cm
90021900	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L500****BlockFlexMount 6MP, Incl. B500 (Night LPF)**

Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030014	10,0 cm
90021900	7,5 cm
150 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6LCS****BlockFlexMount 6MP, For CS Mount Lens (Night LPF)**

Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029780	10,0 cm
90021900	7,5 cm
104 9	9,0 cm
	0,7 l

Sensor Modules 6MP For D16A/D16B

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-O-SDA-F-6D6N	4047438030182	19,5 cm
	Sensor Bridge FIX For D16/D15, 2x 6MP (Day & Night)	90021900	18,0 cm
	Day & Night sensor bridge for D16/D15 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)	346 g	15,0 cm
			5,3 l
	Mx-O-SDA-P-6D6D	4047438030199	19,5 cm
	Sensor Bridge PAN/180° For D16/D15, 2x 6MP (Day)	90021900	18,0 cm
	Panorama/180° sensor bridge for D16/D15 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	346 g	15,0 cm
			5,3 l
	Mx-O-SDA-P-6N6N	4047438030205	19,5 cm
	Sensor Bridge PAN-N/180° for D16/D15, 2x 6MP (Night)	90021900	18,0 cm
	Panorama/180° sensor bridge for D16/D15 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	344 g	15,0 cm
			5,3 l
	Mx-O-SDA-S-6D036	4047438029582	9,0 cm
	Sensor Module D16/D15 6MP, Incl. B036 (Day)	90021900	7,5 cm
	Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	68 g	5,0 cm
			0,3 l
	Mx-O-SDA-S-6D041	4047438029599	9,0 cm
	Sensor Module D16/D15 6MP, Incl. B041 (Day)	90021900	7,5 cm
	Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	66 g	5,0 cm
			0,3 l
	Mx-O-SDA-S-6D061	4047438029605	9,0 cm
	Sensor Module D16/D15 6MP, Incl. B061 (Day)	90021900	7,5 cm
	Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)	68 g	5,0 cm
			0,3 l
	Mx-O-SDA-S-6D079	4047438029612	9,0 cm
	Sensor Module D16/D15 6MP, Incl. B079 (Day)	90021900	7,5 cm
	Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)	68 g	5,0 cm
			0,3 l

 	Mx-O-SDA-S-6D119 Sensor Module D16/D15 6MP, Incl. B119 (Day) Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029629 90021900 64 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	Mx-O-SDA-S-6D237 Sensor Module D16/D15 6MP, Incl. B237 (Day) Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029636 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	Mx-O-SDA-S-6N036 Sensor Module D16/D15 6MP, Incl. B036 (Night) Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029643 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	Mx-O-SDA-S-6N041 Sensor Module D16/D15 6MP, Incl. B041 (Night) Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438029650 90021900 66 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	Mx-O-SDA-S-6N061 Sensor Module D16/D15 6MP, Incl. B061 (Night) Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438029667 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	Mx-O-SDA-S-6N079 Sensor Module D16/D15 6MP, Incl. B079 (Night) Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438029674 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	Mx-O-SDA-S-6N119 Sensor Module D16/D15 6MP, Incl. B119 (Night) Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438029681 90021900 64 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
 	Mx-O-SDA-S-6N237 Sensor Module D16/D15 6MP, Incl. B237 (Night) Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438029698 90021900 68 g	9,0 cm 7,5 cm 5,0 cm 0,3 l

 	Mx-O-SDA-S-6L036 Sensor Module D16/D15 6MP, Incl. B036 (Night LPF) Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438029704 90021900 64 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
 	Mx-O-SDA-S-6L041 Sensor Module D16/D15 6MP, Incl. B041 (Night LPF) Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438029711 90021900 64 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
 	Mx-O-SDA-S-6L061 Sensor Module D16/D15 6MP, Incl. B061 (Night LPF) Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438029728 90021900 64 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
 	Mx-O-SDA-S-6L079 Sensor Module D16/D15 6MP, Incl. B079 (Night LPF) Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438029735 90021900 64 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
 	Mx-O-SDA-S-6L119 Sensor Module D16/D15 6MP, Incl. B119 (Night LPF) Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438029742 90021900 64 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
 	Mx-O-SDA-S-6L237 Sensor Module D16/D15 6MP, Incl. B237 (Night LPF) Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438029759 90021900 64 g	7,5 cm 4,9 cm 9,0 cm 0,3 l

Camera Accessories

HD Premium Lenses

Article No. / Name / Description		EAN / HS / weight	dimen.
	MX-B036	4047438026536	9,0 cm
	Ultra Wide Lens B036, Focal Length: 3.6 mm	90021900	7,5 cm
	Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B041	4047438026543	9,0 cm
	Super Wide Lens B041, Focal Length: 4.1 mm	90021900	7,5 cm
	Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B061	4047438026550	9,0 cm
	Wide Lens B061, Focal Length: 6.1 mm	90021900	7,5 cm
	Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 60° x 45° (up to 5MP resolution) and 70.5° x 46° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B079	4047438026567	9,0 cm
	Standard Lens B079, Focal Length: 7.9 mm	90021900	7,5 cm
	Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B119	4047438026574	9,0 cm
	Tele Lens B119, Focal Length: 11.9 mm	90021900	7,5 cm
	Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 31° x 23° (up to 5MP resolution) and 36° x 24.5° (6MP resolution)	30 g	5,0 cm
			0,3 l
	MX-B237	4047438026581	9,0 cm
	Distant Tele Lens B237, Focal Length: 23.7 mm	90021900	7,5 cm
	Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B500	4047438026598	9,0 cm
	Super Tele Lens B500, Focal Length: 50 mm	90021900	7,5 cm
	Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5 • Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)	52 g	5,0 cm
			0,3 l

**MX-B045-100-CS****CSVario Lens For Cameras With CS-Mount**

CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm • Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical): 39°-89° x 29°-65°

4047438026604	9,0 cm
90021900	7,5 cm
66 g	5,0 cm
	0,3 l

**MX-SM-OPT-POL****Polarization Filter For Sensor Modules**

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

4047438019781	9,0 cm
90079100	7,5 cm
28 g	5,0 cm
	0,3 l

Domes & Housings

Article No. / Name / Description		EAN / HS / weight	dimen.
	MX-M24M-OPT-LCSK	4047438012980	9,0 cm
	Replacement Lens Cover M2x, Standard	90079100	7,5 cm
	Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)	32 g	5,0 cm
			0,3 l
	MX-M24M-OPT-LCSG	4047438012997	9,0 cm
	Replacement Lens Cover M2x, With Glass Pane	90079100	7,5 cm
	Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	38 g	5,0 cm
			0,3 l
	MX-M24M-OPT-LCGL	4047438013000	9,0 cm
	Replacement Lens Cover M2x, Extended	90079100	7,5 cm
	Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	44 g	5,0 cm
			0,3 l
	MX-OPT-DK-L11	4047438016469	9,0 cm
	Replacement Cover Hemispheric	90079100	7,5 cm
	Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	24 g	5,0 cm
			0,3 l
	MX-D15-OPT-DCT	4047438018227	19,6 cm
	Replacement Cover D1x/v2x, Standard	90079100	14,8 cm
	Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)	54 g	9,0 cm
			2,6 l
	MX-D15-OPT-DCS	4047438018210	19,6 cm
	Replacement Cover D1x/v2x, Tinted	90079100	14,8 cm
	Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments	54 g	9,0 cm
			2,6 l
	MX-D15-DCT-XL	4047438027519	19,5 cm
	Replacement Cover D1x FIX/PAN, XL	90079100	18,0 cm
	Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)	281 g	15,0 cm
			5,3 l

	MX-D15-DCS-XL	4047438027526	19,6 cm
	Replacement Cover D1x PAN/FIX, XL Tinted	90079100	18,0 cm
	Suitable for: D1x PAN/180° and FIX/Day&Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)	60 g	14,8 cm
			5,2 l
	MX-D24M-OPT-DCT	4047438011419	19,5 cm
	Replacement Cover D2x, Standard	90079100	15,0 cm
	Suitable for: D2x • With sealing ring	150 g	9,0 cm
			2,6 l
	MX-D24M-OPT-DCS	4047438011402	19,5 cm
	Replacement Cover D2x, Tinted	90079100	15,0 cm
	Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments	150 g	9,0 cm
			2,6 l
	MX-D15-Vandal-ESMA	4047438018173	39,5 cm
	Vandalism Set For D1x, Matt	90079100	29,5 cm
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.012 g	9,0 cm
			10,5 l
	MX-D15-Vandal-ESPO	4047438018166	39,5 cm
	Vandalism Set For D1x, Polished	90079100	29,5 cm
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.012 g	9,0 cm
			10,5 l
	MX-D15-Vandal-PUBL	4047438018203	39,5 cm
	Vandalism Set For D1x, Black	90079100	29,5 cm
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.012 g	9,0 cm
			10,5 l
	MX-D15-Vandal-PUGR	4047438018180	39,5 cm
	Vandalism Set For D1x, Gray	90079100	29,5 cm
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.012 g	9,0 cm
			10,5 l
	MX-D15-Vandal-PUWH	4047438018197	39,5 cm
	Vandalism Set For D1x, White	90079100	29,5 cm
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.012 g	9,0 cm
			10,5 l

	MX-D15-DCT-V	4047438027533	19,5 cm
	Replacement Cover D1x/v2x, Vandalism	90079100	18,0 cm
	Reinforced replacement cover (polycarbonate, 3 mm) for D1x and v25 Vandalism Sets • Suitable for: D1x and v2x • Not for D1x PAN/180° and FIX/Day&Night models (XL cover needed)	278 g	15,0 cm
			5,3 l
	MX-D24M-Vandal-ESMA	4047438011143	30,5 cm
	Vandalism Set For D2x, Matt	90079100	24,0 cm
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	672 g	12,0 cm
			8,8 l
	MX-D24M-Vandal-ESPO	4047438011150	30,5 cm
	Vandalism Set For D2x, Polished	90079100	24,0 cm
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	668 g	12,0 cm
			8,8 l
	MX-D24M-Vandal-PUBL	4047438011181	30,5 cm
	Vandalism Set For D2x, Black	90079100	24,0 cm
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	676 g	12,0 cm
			8,8 l
	MX-D24M-Vandal-PUGR	4047438011174	30,5 cm
	Vandalism Set For D2x, Gray	90079100	24,0 cm
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	676 g	12,0 cm
			8,8 l
	MX-D24M-Vandal-PUWH	4047438011167	30,5 cm
	Vandalism Set For D2x, White	90079100	24,0 cm
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	682 g	12,0 cm
			8,8 l
	MX-D25-DCT-V	4047438027700	19,6 cm
	Replacement D2x, Vandalism	90079100	18,0 cm
	Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring	60 g	14,8 cm
			5,2 l
	MX-Q24M-Vandal-ESMA	4047438011273	28,5 cm
	Vandalism Set For Q2x, Matt	90079100	19,5 cm
	Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available	590 g	9,0 cm
			5,0 l

**MX-Q24M-Vandal-ESPO****Vandalism Set For Q2x, Polished**

Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish polished • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available

4047438011280	28,5 cm
90079100	19,5 cm
590 g	9,0 cm
	5,0 l

**MX-MT-v25-V****Vandalism Set For v2x**

Suitable for: v2x without On-Wall Mounting Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027601	28,5 cm
90079100	19,5 cm
502 g	9,0 cm
	5,0 l

**MX-MT-v25-V-XL****Vandalism Set For v2x With On-Wall Mounting Set**

Suitable for: v2x with On-Wall Mounting Set with Audio • XL stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only with mounted On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027625	28,5 cm
90079100	19,5 cm
680 g	9,0 cm
	5,0 l

Mounts For S16A/S16B

Article No. / Name / Description		EAN / HS / weight	dimen.
	MX-FLEX-OPT-DM-PW	4047438017626	19,5 cm
	DualMount S1x, White	90079100	15,0 cm
	For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	414 g	9,0 cm
			2,6 l
	MX-FLEX-OPT-SM-PW	4047438016407	19,5 cm
	SurroundMount S1x, White	90079100	15,0 cm
	For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all 6MP Sensor modules (B016 to B500 and CS Mount) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	392 g	9,0 cm
			2,6 l
	MX-PTMount-OPT-PW	4047438021166	19,5 cm
	PTMount S1x, White	90079100	18,0 cm
	Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white	634 g	15,0 cm
			5,3 l
	MX-FLEX-OPT-DM-BL	4047438021869	19,5 cm
	DualMount S1x, Black	90079100	15,0 cm
	For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all screwable sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	414 g	9,0 cm
			2,6 l
	MX-FLEX-OPT-SM-BL	4047438021845	19,5 cm
	SurroundMount S1x, Black	90079100	15,0 cm
	For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all screwable sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	392 g	9,0 cm
			2,6 l
	MX-PTMount-OPT-BL	4047438021852	19,5 cm
	PTMount S1x, Black	90079100	18,0 cm
	Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	634 g	15,0 cm
			5,3 l
	MX-HALO-EXT-PW	4047438017664	13,5 cm
	HaloMount S1x, White	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	175 g	4,5 cm
			0,7 l

	MX-HALO-EXT-BL	4047438017671	13,5 cm
	HaloMount S1x, Black	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •	175 g	4,5 cm
			0,7 l
	MX-HALO-EXT-CM	4047438017633	13,5 cm
	HaloMount S1x, Matt Chrome	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	175 g	4,5 cm
			0,7 l
	MX-HALO-EXT-CO	4047438017640	13,5 cm
	HaloMount S1x, Chrome	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	175 g	4,5 cm
			0,7 l
	MX-HALO-EXT-NG	4047438017657	13,5 cm
	HaloMount S1x, Brushed Nickel	90079100	12,0 cm
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	175 g	4,5 cm
			0,7 l
	MX-HALO-SP-EXT-PW	4047438017688	13,5 cm
	SpeakerMount S1x, White	85182200	12,0 cm
	Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included	273 g	4,5 cm
			0,7 l
	MX-HALO-SP-EXT-CM	4047438017695	13,5 cm
	SpeakerMount S1x, Matt Chrome	85182200	12,0 cm
	Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included	273 g	4,5 cm
			0,7 l
	MX-S14-OPT-MK-CW	4047438016384	10,0 cm
	Extension Set Sensor Module, 40 mm And 15°	90079100	7,5 cm
	Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut	96 g	9,0 cm
			0,7 l
	MX-S14-OPT-MK-EX	4047438016391	10,5 cm
	Extension Sensor Module, 40 mm	90079100	6,8 cm
	1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions	62 g	10,5 cm
			0,7 l

**MX-FLEX-OPT-AM-BL****AudioMount S26/S1xM, Self-Adhesive**

Suitable for: S26, S15M, S14M • Easy, quick and concealed mounting with adhesive foil (e.g. behind a stainless steel plate) • Speaker and microphone with camera connection cable included • Use of the camera as a door station by connecting an external doorbell (e.g., connected via MX-232-IO-Box)

4047438019873 24,0 cm

85299065 13,6 cm

386 g 5,3 cm

1,7 l

Camera Mounts

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-M-OWA-AU	4047438030328	19,5 cm
	On-Wall Mounting Set With Audio For v26, White	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	510 g	15,0 cm
			5,3 l
	Mx-M-OWA-AU-b	4047438030335	19,5 cm
	On-Wall Mounting Set With Audio For v26, Black	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	510 g	15,0 cm
			5,3 l
	MX-MT-OW2-AUD	4047438027632	19,5 cm
	On-Wall Mounting Set With Audio For v25, White	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	500 g	15,0 cm
			5,3 l
	MX-MT-OW2-AUD-b	4047438027670	19,5 cm
	On-Wall Mounting Set With Audio For v25, Black	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	500 g	15,0 cm
			5,3 l
	MX-MT-TUBE	4047438027557	28,5 cm
	MxTubeMount Ceiling Suspension System	90079100	19,5 cm
	For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color/material of choice	870 g	9,0 cm
			5,0 l
	MX-MT-TUBE100	4047438027687	106,0 cm
	MxTube, 1 m	90079100	4,0 cm
	Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	700 g	4,0 cm
			1,7 l
	MX-MT-TUBE200	4047438027564	212,5 cm
	MxTube, 2 m	90079100	4,0 cm
	Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	1.390 g	4,0 cm
			3,4 l

	MX-OPT-UP1 Cavity Wall Installation Set i2x Cavity Wall Installation Set for the i2x • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations	4047438022118 90079100 158 g	15,0 cm 9,5 cm 9,0 cm 1,3 l
	MX-OPT-AP2 On-Wall Mounting Set For i2x Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white	4047438025898 90079100 136 g	15,0 cm 9,5 cm 9,0 cm 1,3 l
	MX-MT-OW-1 On-Wall Mounting Set For c2x/p2x Suitable for: c2x und p2x • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g. two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White	4047438027083 90079100 514 g	19,5 cm 18,0 cm 15,0 cm 5,3 l
	MX-MT-CM-1 Corner Mounting Set For c2x Suitable for: c2x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g. c2x with 103° lens B036) to capture an entire room • Color: White	4047438027076 90079100 448 g	28,5 cm 19,5 cm 9,0 cm 5,0 l
	MX-OPT-AP On-Wall Mounting Set For Q2x/D2x/ExtIO Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm	4047438011358 90079100 612 g	28,5 cm 19,5 cm 9,0 cm 5,0 l
	MX-OPT-AP-10DEG On-Wall Mounting Set For Q2x/D2x/ExtIO, 10° Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm	4047438010283 90079100 552 g	28,5 cm 19,5 cm 9,0 cm 5,0 l
	MX-D15-OPT-WHMH-Set Wall & Pole/Corner Mount Set For D1x Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	4047438018159 90079100 6.280 g	41,0 cm 31,0 cm 39,0 cm 49,6 l
	MX-OPT-WHMH-Set Wall & Pole/Corner Mount Set For Q2x/D2x/ExtIO Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	4047438011396 90079100 3.380 g	41,0 cm 31,0 cm 20,0 cm 25,4 l

	MX-WH-Dome	4047438002233	39,5 cm
	Wall Mount For D1x	90079100	29,5 cm
	Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts	2.020 g	18,0 cm
			21,0 l
	MX-OPT-WH	4047438011372	29,5 cm
	Wall Mount For Q2x/D2x/ExtIO	90079100	19,5 cm
	Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts	886 g	18,0 cm
			10,4 l
	MX-WH-SecureFlex	4047438002219	20,0 cm
	Wall/Ceiling Mount For M12/M10/M1	90079100	15,0 cm
	Suitable for: M12/M10/M1 (not M15) • Shock-resistant fiberglass-reinforced composite (PBT), white • Patented tamper-proof concealed cabling • Can be turned left/right 90°, tilted downwards 70° • Includes stainless steel mounting set, caps and dowels	390 g	11,0 cm
			3,3 l
	MX-MH-Dome-ESWS	4047438002240	34,0 cm
	Pole/Corner Mount For MX-WH-Dome	90079100	18,5 cm
	Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	3.000 g	11,5 cm
			7,2 l
	MX-MH-SecureFlex-ESWS	4047438002226	20,0 cm
	Pole Mount For M1x/M2x	90079100	15,2 cm
	Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	1.230 g	8,0 cm
			2,4 l
	MX-OPT-MH	4047438011389	21,0 cm
	Pole/Corner Mount For MX-OPT-WH	90079100	20,0 cm
	Suitable for: Q2x, D2x, ExtIO • Mount for fastening the wall mount MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WHMH-Set) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	2.050 g	17,0 cm
			7,1 l
	MX-OPT-IC-ESMA	4047438011433	29,6 cm
	In-Ceiling Set For Q2x/D2x/ExtIO, Matt	90079100	19,6 cm
	Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm	724 g	9,0 cm
			5,2 l
	MX-OPT-IC-ESPO	4047438011426	29,6 cm
	In-Ceiling Set For Q2x/D2x/ExtIO, Polished	90079100	19,6 cm
	Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm	724 g	9,0 cm
			5,2 l

**MX-OPT-IC****In-Ceiling Set For Q2x/D2x/ExtIO, White**

Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011365	28,5 cm
90079100	19,5 cm
412 g	9,0 cm
	5,0 l

**MX-OPT-TW-Demo-1****Demo Table/Wall Mount For Q2x/D2x**

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055	15,0 cm
90079100	9,5 cm
170 g	9,0 cm
	1,3 l

MOBOTIX Cables

Article No. / Name / Description		EAN / HS / weight	dimen.
	MX-FLEX-OPT-CBL-015	4047438019941	9,8 cm
	Sensor Module Cable For M15/M16, 0.15 m	85444210	7,5 cm
	Length: 0.15 m/0,5 ft, to connect one sensor module (inside camera housing), angled plugs, only for M15/M16	16 g	9,0 cm
			0,7 l
	MX-FLEX-OPT-CBL-05	4047438018890	10,0 cm
	Sensor Cable For S1x, 0.5 m	85444210	7,5 cm
	Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	66 g	9,0 cm
			0,7 l
	MX-FLEX-OPT-CBL-1	4047438018883	10,0 cm
	Sensor Cable For S1x, 1 m	85444210	7,5 cm
	Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	80 g	9,0 cm
			0,7 l
	MX-FLEX-OPT-CBL-2	4047438018876	10,0 cm
	Sensor Cable For S1x, 2 m	85444210	7,5 cm
	Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module	116 g	9,0 cm
			0,7 l
	MX-FLEX-OPT-CBL-3	4047438024303	10,0 cm
	Sensor Cable For S1x (6MP/Thermal), 3 m	85444210	7,5 cm
	Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S15/S16 camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules	144 g	9,0 cm
			0,7 l
	MX-CBL-MU-EN-AB-05	4047438016728	9,8 cm
	USB Device Cable For M/Q/T2x, 0.5 m	85444210	7,5 cm
	MiniUSB angled > USB-A straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device	52 g	9,0 cm
			0,7 l
	MX-CBL-MU-EN-AB-2	4047438016711	10,0 cm
	USB Device Cable For M/Q/T2x, 2 m	85444210	7,5 cm
	MiniUSB angled > USB-A straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB-Gerät	102 g	9,0 cm
			0,7 l


	MX-CBL-MU-EN-AB-5 USB Device Cable For M/Q/T2x, 5 m MiniUSB angled > USB-A straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device	4047438016704 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-EN-PG-05 ExtIO Cable For M/Q/T2x, 0,5 m MiniUSB angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO	4047438020947 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-EN-PG-2 ExtIO Cable For M/Q/T2x, 2 m MiniUSB angled > MiniUSB+ angled • Length 2 m/6,6 m • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO	4047438020930 85444210 102 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-EN-PG-5 ExtIO Cable for M/Q/T2x, 5 m MiniUSB angled > MiniUSB+ angled • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO	4047438020923 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-AB-05 USB Device Cable For D25/D26, 0,5 m MiniUSB+ angled > USB-A straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect ext. USB device	4047438020916 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-AB-2 USB Device Cable For D25/D26, 2 m MiniUSB+ angled > USB-A straight • Length 2 m/6,6 ft • For D25/D26 • to connect ext. USB device	4047438020909 85444210 102 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-AB-5 USB Device Cable For D25/D26, 5 m MiniUSB+ angled > USB-A straight • Length 5 m/16,4 ft • For D25/D26 • To connect ext. USB device	4047438020893 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-EN-PG-05 ExtIO Cable For D25/D26, 0,5 m MiniUSB+ angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-ExtIO	4047438020886 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

	MX-CBL-MU-EN-PG-EN-PG-2 ExtIO Cable For D25/D26, 2 m MiniUSB+ angled > MiniUSB+ angled • Length 2 m/6,6 ft • For D25/D26 • To connect MX-ExtIO	4047438020879 85444210 102 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-EN-PG-5 ExtIO Cable For D25/D26, 5 m MiniUSB+ angled > MiniUSB+ angled • Length 5 m/16,4 ft • For D25/D26 • To connect MX-ExtIO	4047438020862 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-STR-05 232-IO-Box Cable For D25/D26, 0.5 m MiniUSB+ angled > MiniUSB straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-232-IO-Box	4047438020855 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-STR-2 232-IO-Box Cable For D25/D26, 2 m MiniUSB+ angled > MiniUSB straight • Length 2 m/6,6 ft • For D25/D26 • To connect MX-232-IO-Box	4047438020848 85444210 102 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-PG-STR-5 232-IO-Box Cable For D25/D26, 5 m MiniUSB+ angled > MiniUSB straight • Length 5 m/16,4 ft • For D25/D26 • To connect MX-232-IO-Box	4047438020831 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-STR-05 232-IO-Box Cable For M/Q/T2x, 0.5 m MiniUSB angled > MiniUSB straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box	4047438016667 85444210 48 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-STR-2 232-IO-Box Cable For M/Q/T2x, 2 m MiniUSB angled > MiniUSB straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box	4047438016650 85444210 94 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-EN-STR-5 232-IO-Box Cable For M/Q/T2x, 5 m MiniUSB angled > MiniUSB straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box	4047438016643 85444210 188 g	10,0 cm 7,5 cm 9,0 cm 0,7 l

	MX-CBL-MU-STR-05 232-IO-Box Cable For D/S/V1x, 0.5 m MiniUSB straight > MiniUSB straight • Length 0,5 m/1,6 ft • For D15/D16, S15/S16, V15/V16 • To connect MX-232-IO-Box	4047438016605 85444210 50 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-STR-2 232-IO-Box Cable For D/S/V1x, 2 m MiniUSB straight > MiniUSB straight • Length 2 m/6,6 ft • For D15/D16, S15/S16, V15/V16 • To connect MX-232-IO-Box	4047438016599 85444210 94 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-STR-5 232-IO-Box Cable For D/S/V1x, 5 m MiniUSB straight > MiniUSB straight • Length 5 m/16,4 ft • For D15/D16, S15/S16, V15/V16 • To connect MX-232-IO-Box	4047438016445 85444210 184 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-STR-AB-05 USB Device Cable For D/S/V1x, 0.5 m MiniUSB straight > USB-A straight • Length 0,5 m/1,6 ft • For D15/D16, S15/S16, V15/V16 • To connect ext. USB device	4047438016698 85444210 56 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-STR-AB-2 USB Device Cable For D/S/V1x, 2 m MiniUSB straight > USB-A straight • Length 2 m/6,6 ft • D15/D16, S15/S16, V15/V16 • To connect ext. USB device	4047438016681 85444210 102 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-STR-AB-5 USB Device Cable For D/S/V1x, 5 m MiniUSB straight > USB-A straight • Length 5 m/16,4 ft • For D15/D16, S15/S16, V15/V16 • To connect ext. USB device	4047438016674 85444210 196 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-STR-EN-PG-05 ExtIO Cable For D/S/V1x, 0.5 m MiniUSB straight > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D15/D16, S15/S16, V15/V16 • To connect MX-ExtIO	4047438020978 85444210 52 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-CBL-MU-STR-EN-PG-2 ExtIO Cable For D/S/V1x, 2 m MiniUSB straight > MiniUSB+ angled • Length 2 m/6,6 ft • For D15/D16, S15/S16, V15/V16 • To connect MX-ExtIO	4047438020961 85444210 102 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

	MX-CBL-MU-STR-EN-PG-5 ExtIO Cable For D/S/V1x, 5 m MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D15/D16, S15/S16, V15/V16 • To connect MX-ExtIO	4047438020954 85444210 194 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-OPT-CBL-LAN-1 Ethernet Patch Cable, 1 m Ethernet Patch Cable for MOBOTIX systems • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012300 85444210 36 g	23,5 cm 15,0 cm 2,0 cm 0,7 l
	MX-OPT-CBL-LAN-10 Ethernet Patch Cable, 10 m Ethernet Patch Cable for MOBOTIX systems • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012331 85444210 264 g	27,0 cm 17,0 cm 4,0 cm 1,8 l
	MX-OPT-CBL-LAN-2 Ethernet Patch Cable, 2 m Ethernet Patch Cable for MOBOTIX systems • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012317 85444210 62 g	23,5 cm 15,0 cm 2,0 cm 0,7 l
	MX-OPT-CBL-LAN-5 Ethernet Patch Cable, 5 m Ethernet Patch Cable for MOBOTIX systems • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012324 85444210 144 g	23,5 cm 15,0 cm 4,0 cm 1,4 l
	MX-FLEX-IO-CBL-015 IO Connection Cable For M15/M16, 0.15 m Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15/M16 (inside camera housing)	4047438019958 85444210 10 g	13,5 cm 8,0 cm 2,0 cm 0,2 l
	MX-CBL-NPA-BAT-2 NPA Battery Cable, 2 m NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft	4047438013949 85444210 68 g	10,0 cm 7,5 cm 9,0 cm 0,7 l

Other Camera Accessories

Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-OPT-Ring-L10-L12-BL Sealing Ring For Hemispheric Sensor Modules, Black Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black	4047438021241 7,5 cm 90079100 4,9 cm 16 g 9,0 cm 0,3 l
	MX-OPT-Ring-L10-L12-PW Sealing Ring For Hemispheric Sensor Modules, White Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white	4047438021234 7,5 cm 90079100 4,9 cm 16 g 9,0 cm 0,3 l
	MX-OPT-SEC-SCREWS-SET Security Screw Set With Allen Bit For M1x/M2x Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)	4047438021265 7,5 cm 90079100 4,9 cm 120 g 9,0 cm 0,3 l
	MX-SM-Blind-PW Blind Module M1x For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.	4047438019965 9,0 cm 90079100 7,5 cm 46 g 5,0 cm 0,3 l

MOBOTIX MOVE Accessories





MOBOTIX MOVE Accessories


	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-SD-DCS	4047438031776	26,0 cm
	Tinted Dome For MOBOTIX MOVE SD-330	90079100	25,5 cm
	Tinted replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330 • For particularly bright environments	300 g	17,0 cm
			11,3 l
	Mx-A-SD-DCT	4047438031783	26,0 cm
	Dome (Standard) For MOBOTIX MOVE SD-330	90079100	25,5 cm
	Standard replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330	300 g	17,0 cm
			11,3 l
	Mx-A-VD-DCS	4047438031714	16,1 cm
	Tinted Dome For MOBOTIX MOVE VD-4-IR	90079100	16,1 cm
	Tinted replacement dome for particularly bright environments • Suitable for MOBOTIX MOVE VandalDome VD-4-IR	210 g	11,5 cm
			3,0 l
	Mx-A-VD-DCT	4047438031721	16,1 cm
	Dome (Standard) For MOBOTIX MOVE VD-4-IR	90079100	16,1 cm
	VD Standard replacement dome • Suitable for MOBOTIX MOVE VandalDome VD-4-IR	250 g	11,5 cm
			3,0 l
	Mx-M-BC-P	4047438031677	17,3 cm
	Pole Mount For MOBOTIX MOVE BC-4-IR	90079100	17,3 cm
	BC Pole Mount suitable for MOBOTIX MOVE BulletCamera BC-4-IR	1.000 g	16,7 cm
			5,0 l
	Mx-M-BC-W	4047438031660	17,3 cm
	Wall Mount For MOBOTIX MOVE BC-4-IR	90079100	17,3 cm
	BC Wall Mount suitable for MOBOTIX MOVE BulletCamera BC-4-IR	840 g	10,7 cm
			3,2 l
	Mx-M-SD-C	4047438031769	21,0 cm
	Corner Mount For MOBOTIX MOVE SD-330/SD-340-IR	90079100	12,5 cm
	SD Corner Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)	2.170 g	25,0 cm
			6,6 l

	Mx-M-SD-P Pole Mount For MOBOTIX MOVE SD-330/SD-340-IR SD Pole Mount suitable for MOBOTIX MOVE SpeedDome SD-330 und SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)	4047438031752 90079100 1.580 g	31,0 cm 15,5 cm 26,0 cm 12,5 l
	Mx-M-SD-W Wall Mount For MOBOTIX MOVE SD-330/SD-340-IR SD Wall Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)	4047438031745 90079100 840 g	21,6 cm 12,7 cm 15,0 cm 4,1 l
	Mx-M-VD-C Corner Mount For MOBOTIX MOVE VD-4-IR VD Corner Mount suitable for MOBOTIX MOVE VandalDome VD-4-IR	4047438031738 90079100 2.170 g	21,0 cm 12,5 cm 25,0 cm 6,6 l
	Mx-M-VD-IC In-Ceiling Set For MOBOTIX MOVE VD-4-IR VD In-Ceiling Set suitable for MOBOTIX MOVE VandalDome VD-4-IR	4047438031684 90079100 800 g	23,4 cm 23,4 cm 12,8 cm 7,0 l
	Mx-M-VD-P Pole Mount For MOBOTIX MOVE VD-4-IR VD-Pole Mount suitable for MOBOTIX MOVE VandalDome VD-4-IR	4047438031707 90079100 1.580 g	31,0 cm 15,5 cm 26,0 cm 12,5 l
	Mx-M-VD-W Wall Mount For MOBOTIX MOVE VD-4-IR VD Wall Mount Set (2-piece) suitable for MOBOTIX MOVE VandalDome VD-4-IR	4047438031691 90079100 1.400 g	31,0 cm 22,0 cm 18,0 cm 12,3 l

System Components

Interface Boxes

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-OPT-BPA1-EXT	4047438025881	10,5 cm
	MX-BPA-Box	85299065	6,8 cm
	Power supply for several MxBus modules of one MxBus line • 2x2 connection terminals for MxBus • 2 connection terminals for external power supply from 12 to 48 V DC (2 terminals) • Max. output rating: 9 W • IP66/IK08, -30 bis 60 °C / -22 to 140 °F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	120 g	10,5 cm 0,7 l
	MX-OPT-NPA1-EXT	4047438015424	10,0 cm
	MX-NPA-Box	85043180	7,5 cm
	Weatherproof PoE Injector (IEEE 802.3af) and network connector • Needs external power supply units and batteries from 12 to 57 V DC • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Important: only use with original MOBOTIX patch cables • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	140 g	9,0 cm 0,7 l
	MX-Overvoltage-Protection-Box-LSA	4047438018470	10,0 cm
	Network Connector with Surge Protection, LSA Version	85299065	7,5 cm
	Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	146 g	9,0 cm 0,7 l
	MX-Overvoltage-Protection-Box-RJ45	4047438018463	10,0 cm
	Network Connector with Surge Protection, RJ45 Version	85299065	7,5 cm
	Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	150 g	9,0 cm 0,7 l
	MX-OPT-Input1-EXT	4047438021227	10,0 cm
	MX-Input-Box	85299065	7,5 cm
	Weatherproof connection of external sensors • Connection to camera using MxBus • 6 self-powered inputs for connection up to 6 external sensors • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	148 g	9,0 cm 0,7 l
	MX-OPT-Output1-EXT	4047438021944	10,5 cm
	MX-Output-Box	85299065	6,8 cm
	Weatherproof connection of external devices and power relays • Connection to the camera via MxBus • Six self-powered outputs (12 V, each 10 mA) • Two isolated outputs (can be switched to "self-powered" using a jumper: 12 V, max. 50 mA) • Protection class IP66/IK07, -30 to 60 °C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	120 g	10,5 cm 0,7 l
	MX-OPT-RS1-EXT	4047438015417	10,5 cm
	MX-232-IO-Box	85299065	6,8 cm
	Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	120 g	10,5 cm 0,7 l


**MX-OPT-GPS1-EXT**

4047438015400 10,5 cm

MX-GPS-Box

85299065 6,8 cm

Weatherproof GPS time base for MOBOTIX systems • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP66/IK08, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

120 g 10,5 cm
0,7 l**MX-PROX-BOX**

4047438025935 10,5 cm

MX-Proximity-Box

85299065 6,8 cm

Weatherproof proximity sensor for MOBOTIX systems • Accurate detection of approaching objects based on radar microwave technology • Covered area (horizontal x vertical): 80° x 34° • Detection range: up to 8m/26 ft. (person), up to 20m/66 ft. (vehicle) • Camera connection and supply via MxBus • Protection class IP66/IK07, -20 to 60°C / -4 to 140°F • Box can also be mounted behind walls (e.g. wooden, plastic, glass or dry walls) • It is not possible to install the MX-Proximity-Box behind some materials since they absorb or reflect the radar waves (e.g., metal or metal-coated surfaces). Other materials are better suited since they absorb radar waves only slightly (e.g., uncoated glass, plastics, various wood-based materials, drywall).

165 g 10,5 cm
0,7 l**MX-OPT-DIGI-INT**

4047438028790 10,5 cm

MxDigitizer For S1x

85299065 6,8 cm

Interface box to connect one analog camera directly to a S1x Body as alternative image source (instead of one sensor module) • Up to two MxDigitizer boxes or two analog cameras can be connected to one S1x Body • Easy integration of analog cameras into the MOBOTIX IP video system incl. the support of MOBOTIX integrated image analysis tools (e.g. MxActivitySensor) • Box digitizes the analog signal input (NTSC/PAL) • Output format PAL: 704 x 525 pixels, up to 25 frames per second • Output format NTSC: 640 x 480 pixels, up to 30 frames per second • BNC connection of analog camera to MxDigitizer • Sensor cable connection of MxDigitizer to S1x Body (to be ordered separately, maximum length 3 m/9.8 ft) • Operating conditions: Indoors, 0 to 40°C (32 to 104°F) • Color: white

120 g 10,5 cm
0,7 l

MxDisplay+

Article No. / Name / Description	EAN / HS / weight	dimen.
 MX-DISPLAY3 MxDisplay+, White MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white	4047438027151 85285291 425 g	19,5 cm 15,0 cm 9,0 cm 2,6 l
 MX-DISPLAY3-b MxDisplay+, Black MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black	4047438027168 85285291 300 g	13,8 cm 6,5 cm 14,8 cm 1,3 l
 MX-DISPLAY3-EXT MxDisplay+ Outdoor, White Weatherproof MxDisplay+ for mounting outdoors or in rooms with special requirements • Operating conditions: IP65, -30 to 60°C (-22 to 140°F) • Remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking • HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus • Ethernet, RFID and WiFi (2.4 & 5 GHz), Bluetooth V3.0 HS • MxBus and Bluetooth available with upcoming software update • 1x admin card • Mounting parts • Frame and in-wall housing to be ordered separately (e.g., FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white	4047438028776 85285291 300 g	13,8 cm 6,5 cm 14,8 cm 1,3 l
 MX-DISPLAY3-EXT-b MxDisplay+ Outdoor, Black Weatherproof MxDisplay+ for mounting outdoors or in rooms with special requirements • Operating conditions: IP65, -30 to 60°C (-22 to 140°F) • Remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking • HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus • Ethernet, RFID and WiFi (2.4 & 5 GHz), Bluetooth V3.0 HS • MxBus and Bluetooth available with upcoming software update • 1x admin card • Mounting parts • Frame and in-wall housing to be ordered separately (e.g., FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black	4047438028783 85285291 300 g	13,8 cm 6,5 cm 14,8 cm 1,3 l

Mx2wire+ Media Converter



Article No. / Name / Description

EAN / HS / weight dimen.

MX-2WirePlus-Set-PW

4047438015356 19,5 cm

Mx2wire+ Set, Ethernet And PoE Via Two-Wire-Cable

85176200 15,0 cm

Mx2wire+ turns an existing two-wire cable into a modern multimedia cable • Ethernet and PoE data transfer using a two-wire cable • Simple connection of 10/100 Mbps Ethernet end devices (e.g., IP camera, IP telephone) • Power supply for Mx2wire+ and end device via PoE/PoE+ or 48-57 V DC, 600 mA • Connected end devices are supplied with up to 13 watts via PoE (PoE class 3) • Maximum data transfer range of 500 m and data rate of up to 50 Mbps (depending on distance) • No need for expensive and time-consuming installation of network cables • Perfect for wireless communication is not possible (due to distance to sender, thickness of walls, etc.) • Network extension, including PoE, by connecting a Cat7 cable of up to 500 m in length as a two-wire cable • Simple installation in standard sockets (surface- or flush-mounted) • Two LEDs display current connection and supply statuses • Developed, produced and patented by MOBOTIX Germany • Ambient temperature: -30 to 50°C / -22 to 122°F • Complete set consisting of two Mx2wire+ units, on-walls sockets and mounting parts

508 g 9,0 cm

2,6 l

T25 Complete Kits

Article No. / Name / Description	EAN / HS / weight	dimen.
 MX-T25-SMART-SET1 T25 Smart Access Set 1 T25 IP Video Door Station with MxDisplay+ as preconfigured complete set for use in family homes • Delivery outdoor remote station (IP65, -30 to 50°C, -22 to 122°F): CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) and Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • BellRFID module with one big key with blue functional bar, 1x admin and 6x user card, MX-OPT-IO2 Ethernet board, double frame set for in-wall or on-wall installation, pen for plastic film, mounting material • Delivery indoor remote station: MX-DISPLAY3, FlatMount Frame with In-Wall-Housing • All devices and frames colored in white	4047438028769	34,0 cm
	85258091	34,0 cm
	2.500 g	16,0 cm
		18,5 l
 MX-T25-SMART-SET2 T25 Smart Access Set 2 T25 IP Video Door Station with MxDisplay+ and MxSwitch • Preconfigured complete set for use in family homes • Delivery outdoor remote station (IP65, -30 to 50°C, -22 to 122°F): CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) and Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • BellRFID module with one big key with blue functional bar, 1x admin and 6x user card, MX-OPT-IO2 Ethernet board, double frame set for in-wall or on-wall installation, pen for plastic film, mounting material • Delivery indoor remote station: MX-DISPLAY3, FlatMount Frame with In-Wall-Housing • All devices and frames colored in white	4047438028875	34,0 cm
	85258091	34,0 cm
	2.700 g	16,0 cm
		18,5 l
 MX-T25-SET1 T25 6MP Set 1, Ethernet, Keypad, White Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	4047438025362	34,5 cm
	85258091	34,0 cm
	3.000 g	16,0 cm
		18,8 l
 MX-T25-SET2 T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, White Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • InfoModule (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	4047438025379	34,5 cm
	85258091	34,0 cm
	3.000 g	16,0 cm
		18,8 l
 MX-T25-SET3 T25 6MP Set 3, Ethernet, Keypad, DoorMaster, White Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	4047438025386	34,5 cm
	85258091	34,0 cm
	3.000 g	16,0 cm
		18,8 l

T25 Complete Kits (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These kits can also be ordered from the standard program as individual components for self-assembly.

Please note: Black colored IP Video Door Stations should NOT be exposed to direct sunlight (risk of overheating on dark surfaces).

	Article No. / Name / Description	EAN / HS / weight	dimen.
 	MX-T25-SET1-d	4047438025522	34,0 cm
	T25 6MP Set 1, Ethernet, Keypad, Dark Gray Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Dark Gray	85258091 3.000 g	34,0 cm 16,0 cm 18,5 l
 	MX-T25-SET1-b	4047438025447	34,5 cm
	T25 6MP Set 1, Ethernet, Keypad, Black Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black	85258091 3.000 g	34,0 cm 16,0 cm 18,8 l
 	MX-T25-SET1-s	4047438025607	34,5 cm
	T25 6MP Set 1, Ethernet, Keypad, Silver Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver	85258091 3.000 g	34,0 cm 16,0 cm 18,8 l
 	MX-T25-SET2-s	4047438025614	34,5 cm
	T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Silver Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver	85258091 3.000 g	34,0 cm 16,0 cm 18,8 l
 	MX-T25-SET2-d	4047438025539	34,0 cm
	T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Dark Gray Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Dark Gray	85258091 3.000 g	34,0 cm 16,0 cm 18,5 l
 	MX-T25-SET2-b	4047438025454	34,5 cm
	T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Black Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black	85258091 3.000 g	34,0 cm 16,0 cm 18,8 l

**MX-T25-SET3-s****T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Silver**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122° F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver

4047438025621 34,5 cm
85258091 34,0 cm
3.000 g 16,0 cm
18,8 l

**MX-T25-SET3-d****T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Dark Gray**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122° F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Dark Gray


4047438025546 34,0 cm
85258091 34,0 cm
3.000 g 16,0 cm
18,5 l

**MX-T25-SET3-b****T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Black**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122° F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black

4047438025461 34,5 cm
85258091 34,0 cm
3.000 g 16,0 cm
18,8 l


Functional Enhancement & IR Illuminators

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-TCLIENTA	4047438028899	9,8 cm
	MxThinClient	84714900	7,5 cm
	PoE-supplied IP video device to transfer live pictures of cameras and door stations to a monitor/TV set • Password protected web interface • Automatic change of video source via sequencer (time-controlled) or via MxMessageSystem (event-controlled) • Input (connection to PoE switch): 1x Ethernet 100Base-T (RJ45) • Output (connection to monitor/TV set): 1x HDMI Type D (MicroHDMI) • Connection cables (Ethernet, HDMI) are not included • Indoor-use only: Protection class IP20, ambient temperature 0 to 40 °C (32 to 104°F) • With the supplied adhesive strips, the device can easily be attached to the backside of the monitor/TV	200 g	9,0 cm
			0,7 l
	MX-ExtIO	4047438009850	28,5 cm
	ExtIO Extension Module For All MOBOTIX Cameras	85299065	19,5 cm
	ExtIO Weatherproof extension for all MOBOTIX cameras (except Basic models) • Power supply: PoE (Class 2, IEEE 802.3af) or USB (connection cable to be ordered individually) • Microphone/speaker • Line-in / Line-out • PIR sensor for motion detection • Temperature sensor • 2 buttons (e.g., lights, door bell) • 2 galvanically separated inputs • 2 galvanically separated outputs • Protection class IP65, -30 to 60° C / -22 to 140°F • Robust housing made of fiber-reinforced plastic PBT-GF30 • Mounting to a wall or ceiling, optionally with MOBOTIX mounting accessories (to be ordered individually) • Connecting via Network or USB	744 g	9,0 cm
			5,0 l
	MX-MULTISENSE1	4047438028851	10,5 cm
	MxMultiSense Indoor (HS Code 8299065)	85299065	6,8 cm
	Multi-sensor module for indoor use with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor and acoustic sensor (sound pressure) • Camera connection and supply via MxBus • MxBus cable length up to 100 m / 330 ft. • Power consumption: typ. 0.1 W • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX sensor module mounts and standard mounts for recessed spotlights • Protection class meets IP40 • IK05 • Ambient temperature: 0 to 40°C / 32 to 104°F • Housing color: white	110 g	10,5 cm
			0,7 l
	MX-MULTISENSE1-EXT	4047438028905	10,5 cm
	MxMultiSense Outdoor (HS code 85299065)	85299065	6,8 cm
	Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (±0.1°C / 0.18°F) and acoustic sensor (level of sound waves) • Camera connection and supply via MxBus: power consumption approx. 0.3 W, MxBus cable length up to 100 m / 330 ft. • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX mounts for sensor modules and standard mounts for recessed spotlights • Protection class IP66 • IK05 • Ambient temperature -20 to 60°C / -4 to 140°F • Housing color: white	110 g	10,5 cm
			0,7 l
	MX-OPT-IO3-INT	4047438025928	10,7 cm
	Extension Module For c25, i25, p25 And v25	85299065	5,2 cm
	Extension module for the indoor cameras x25 (to be mounted on the backside) • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window • contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x • isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA • per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l
	Mx-A-IOA-IC	4047438029032	10,7 cm
	Extension Module For All Indoor Cameras x26A/x26B	85299065	5,2 cm
	Expansion module for Indoor Cameras c26A/B, i26A/B, p26A/B and v26A/B (installed on the back) • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by the x26B Indoor Cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l

**Mx-A-SPA****MxSplitProtect Installation Box, IP66**

Weatherproof installation box with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces (weatherproof): 1 LSA (with shield clip) for Ethernet 2 100Base-T, 2 MxRJ45 for Ethernet 100Base-T with PoE Mode A, 1 protective earth terminal • IP66 and IK08, ambient temperature: -30°C to 60°C (-22°F to 140°F) • Accessories (available separately): MxSplitProtectHR Hat Rail module (Mx-A-SPA-HR), cover with camera mount in three versions (Mx-A-SPCA-M/-H/-V), pole mount (MX-MH-SecureFlex-ESWS) • Housing color: white

4047438030229	30,5 cm
85299065	24,0 cm
1.184 9	16,0 cm
	11,7 l

**Mx-A-SPA-HR****MxSplitProtectHR Hat Rail Module**

Compatible with MxSplitProtect Installation Box (Mx-A-SPA): Hat rail module (for 35 mm DIN rails) with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces: 3x RJ45 for Ethernet 100Base-T, 1x protective earth terminal • Only use in indoor areas, ambient temperature: 0°C to 40°C (32°F to 104°F) • Accessories (available separately): MxSwitch (MX-SWITCH1) • Housing color: gray

4047438030236	10,0 cm
85299065	7,5 cm
130 9	9,0 cm
	0,7 l

**Mx-A-SPCA-M****MxSplitProtect Cover, M-Cameras**

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to install the standard VarioFlex wall mount of an M15/M16/M25/M26 camera directly to the cover • Color: white

4047438028820	19,5 cm
85299065	18,0 cm
514 9	15,0 cm
	5,3 l

**Mx-A-SPCA-H****MxSplitProtect Cover, Horizontal**


Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (vertically) install a Q2x (orD2x) camera with a 15° tilt angle without an additional mount directly to the cover • Color: white

4047438028837	19,5 cm
85299065	18,0 cm
570 9	15,0 cm
	5,3 l

**Mx-A-SPCA-V****MxSplitProtect Cover, Vertical**


Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (horizontally) install a Q2x/D2x camera without an additional mount directly to the cover • Color: white

4047438028844	19,5 cm
85299065	18,0 cm
482 9	15,0 cm
	5,3 l

**Mx-A-IRA-120****MxIRLight Infrared Illuminator (860 nm), 120°x120°**



Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030342	20,5 cm
85394900	17,5 cm
1.098 9	12,5 cm
	4,5 l

**Mx-A-IRA-90****MxIRLight Infrared Illuminator (860 nm), 90°x90°**

Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030359	20,5 cm
85394900	17,5 cm
1.112 9	12,5 cm
	4,5 l

	Mx-A-IRA-60	4047438030366	20,5 cm
	MxIRLight Infrared Illuminator (860 nm), 60°x60°	85394900	17,5 cm
	Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	1.116 g	12,5 cm
			4,5 l
	Mx-A-IRA-45	4047438030373	20,5 cm
	MxIRLight Infrared Illuminator (860 nm), 45°x45°	85394900	17,5 cm
	Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	1.124 g	12,5 cm
			4,5 l
	Mx-A-IRA-30	4047438030380	20,5 cm
	MxIRLight Infrared Illuminator (860 nm), 30°x30°	85394900	17,5 cm
	Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	1.096 g	12,5 cm
			4,5 l
	Mx-A-IRA-15	4047438030397	20,5 cm
	MxIRLight Infrared Illuminator (860 nm), 15°x15°	85394900	17,5 cm
	Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	1.090 g	12,5 cm
			4,5 l
	Mx-M-IRA-ML	4047438030403	19,5 cm
	MxIRLight Mounting Brackets For M1x	85399090	5,5 cm
	Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white	216 g	3,5 cm
			0,4 l
	Mx-M-IRA-M	4047438030410	14,0 cm
	MxIRLight Mounting Brackets For M2x	85399090	5,5 cm
	Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white	150 g	3,5 cm
			0,3 l

T25 Camera Module

Article No. / Name / Description		EAN / HS / weight	dimen.
	MX-T25-D016	4047438025263	19,5 cm
	CamCore T25, 6MP, B016, Day, White	85258091	15,0 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	396 g	9,0 cm
			2,6 l
	MX-T25-D016-s	4047438025270	19,5 cm
	CamCore T25, 6MP, B016, Day, Silver	85258091	15,0 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	396 g	9,0 cm
			2,6 l
	MX-T25-D016-d	4047438025287	19,5 cm
	CamCore T25, 6MP, B016, Day, Dark Gray	85258091	15,0 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray	396 g	9,0 cm
			2,6 l
	MX-T25-D016-b	4047438025300	19,5 cm
	CamCore T25, 6MP, B016, Day, Black	85258091	15,0 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	396 g	9,0 cm
			2,6 l
	MX-T25-N016	4047438025317	19,5 cm
	CamCore T25, 6MP, B016, Night, White	85258091	15,0 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	396 g	9,0 cm
			2,6 l
	MX-T25-N016-s	4047438025324	19,5 cm
	CamCore T25, 6MP, B016, Night, Silver	85258091	15,0 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	396 g	9,0 cm
			2,6 l
	MX-T25-N016-d	4047438025331	19,5 cm
	CamCore T25, 6MP, B016, Night, Dark Gray	85258091	15,0 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray	396 g	9,0 cm
			2,6 l

**MX-T25-N016-b****CamCore T25, 6MP, B016, Night, Black**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night)
• HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black

4047438025355	19,5 cm
85258091	15,0 cm
396 g	9,0 cm
	2,6 l

BellRFID Module

Article No. / Name / Description	EAN / HS / weight	dimen.
 MX-Bell1-Button-F1 BellRFID Bell Button Set F1 1 big key with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017190 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
 MX-Bell1-Button-F2 BellRFID Bell Button Set F2 2 medium-sized keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017176 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
 MX-Bell1-Button-F3 BellRFID Bell Button Set F3 1 medium-sized and 2 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017527 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
 MX-Bell1-Button-F4 BellRFID Bell Button Set F4 4 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017183 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
 MX-Bell1-Button-05 BellRFID Bell Button Set 05 5 small keys (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017534 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
 MX-Bell1-Button-XL1 BellRFID Bell Button Set XL1 1 big XL key (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	4047438017169 85299065 94 g	10,3 cm 1,7 cm 10,3 cm 0,2 l
 MX-Bell1-Core-EXT-PW BellRFID Base Module, White BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438017152 85299065 346 g	19,5 cm 15,0 cm 9,0 cm 2,6 l

**MX-Bell1-Core-EXT-SV****BellRFID Base Module, Silver**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

4047438017114	19,5 cm
85299065	15,0 cm
346 9	9,0 cm
	2,6 l

**MX-Bell1-Core-EXT-DG****BellRFID Base Module, Dark Gray**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to +50°C / -22 to 122°F • Color: Dark Gray

4047438017121	19,5 cm
85299065	15,0 cm
346 9	9,0 cm
	2,6 l

**MX-Bell1-Core-EXT-BL****BellRFID Base Module, Black**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

4047438017145	19,5 cm
85299065	15,0 cm
346 9	9,0 cm
	2,6 l

PoE Power Supply

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-SWITCH1	4047438028882	15,0 cm
	MxSwitch For DIN Rail Mounting	85176200	9,5 cm
	PoE+ Switch for the top-hat rail • 5x RJ45 port with 100 MBit/s (1x uplink, 4x PoE+ with max. 75 W) • Supply: 48 V DC, max. 75 W • Simplified cabling for door stations due to available connectivity for anti-theft protection, door opener and MxBus • MxBus, anti-theft protection, door and lock contact can be connected via separate wires of the ethernet cable	310 g	9,0 cm
			1,3 l
	MX-NPA-PoE-EU-Set	4047438012249	15,0 cm
	PoE Power Adapter Set, EU	85043180	9,5 cm
	PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	268 g	9,0 cm
			1,3 l
	MX-NPA-PoE-INT-Set	4047438012256	15,0 cm
	PoE Power Adapter Set, INT	85043180	9,5 cm
	PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	314 g	9,0 cm
			1,3 l
	MX-NPA-PoE-RJ	4047438013932	9,0 cm
	PoE Power Adapter	85043180	7,5 cm
	PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed	60 g	5,0 cm
			0,3 l
	MX-SNT-INT-PoE	4047438013925	9,8 cm
	Universal Power Supply With 4 Power Plugs	85043180	7,5 cm
	For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F	160 g	9,0 cm
			0,7 l

KeypadRFID Module

Article No. / Name / Description	EAN / HS / weight	dimen.
 MX-Keypad1-EXT-PW Keypad With RFID Technology, White Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438014946 85371091 330 g	19,5 cm 15,0 cm 9,0 cm 2,6 l
 MX-Keypad1-EXT-SV Keypad With RFID Technology, Silver Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	4047438014984 85371091 330 g	19,5 cm 15,0 cm 9,0 cm 2,6 l
 MX-Keypad1-EXT-DG Keypad With RFID Technology, Dark Gray Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	4047438014977 85371091 330 g	19,5 cm 15,0 cm 9,0 cm 2,6 l
 MX-Keypad1-EXT-BL Keypad With RFID Technology, Black Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	4047438014960 85371091 330 g	19,5 cm 15,0 cm 9,0 cm 2,6 l

Info Module

Article No. / Name / Description	EAN / HS / weight	dimen.
 MX-Info1-EXT-PW Info Module With LEDs, White Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438014991 19,5 cm 85414090 15,0 cm 282 g 9,0 cm 2,6 l	
 MX-Info1-EXT-SV Info Module With LEDs, Silver Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	4047438015035 19,5 cm 85414090 15,0 cm 282 g 9,0 cm 2,6 l	
 MX-Info1-EXT-DG Info Module With LEDs, Dark Gray Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	4047438015028 19,5 cm 85414090 15,0 cm 282 g 9,0 cm 2,6 l	
 MX-Info1-EXT-BL Info Module With LEDs, Black Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	4047438015011 19,5 cm 85414090 15,0 cm 282 g 9,0 cm 2,6 l	


Info Module Mx2Wire+






Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-2wirePlus-Info1-EXT-PW Info Module Mx2wire+ With LEDs, White Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438015042 19,5 cm 85176200 15,0 cm 520 g 9,0 cm 2,6 l
	MX-2wirePlus-Info1-EXT-SV Info Module Mx2wire+ With LEDs, Silver Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	4047438015080 19,5 cm 85176200 15,0 cm 522 g 9,0 cm 2,6 l
	MX-2wirePlus-Info1-EXT-DG Info Module Mx2wire+ With LEDs, Dark Gray Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	4047438015073 19,5 cm 85176200 15,0 cm 521 g 9,0 cm 2,6 l
	MX-2wirePlus-Info1-EXT-BL Info Module Mx2wire+ With LEDs, Black Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	4047438015066 19,5 cm 85176200 15,0 cm 519 g 9,0 cm 2,6 l



MX-DoorMaster





Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-Door2-INT-ON-PW	4047438021876 15,0 cm
	DoorMaster For On-Wall Mounting	85363010 9,5 cm
	Security Door Opener with integrated access code memory for on-wall mounting • Complete set including DoorMaster module, on-wall housing, three device frames, neutral housing covering, battery pack and mounting parts • Suitable for: IP Video Door Station with T2x and S1x as door camera • Built-in backup power supply (battery) for access modules • Doorbell • Direct connection and power supply for electric Door Opener und door sensors • Interface und power supply: MxBus • Two status LEDs, two function buttons, integrated • Speaker (doorbell) • Two galvanically separated inputs (AC/DC, selfpowered • up to 48 V) • Isolated relay output (AC/DC, 24 V/1 A) or port for standard door openers (6 to 12 V AC) • Outlet for MOBOTIX anti theft protection (12 V DC) • Protection class: IP20 • Ambient temperature: -5 to 40 °C / 23 to 104 °F • Color: white	412 g 9,0 cm
		1,3 l
	MX-Door2-INT-PW	4047438019934 15,0 cm
	DoorMaster For In-Wall Mounting	85363010 9,5 cm
	Security door opener with internal access code memory: A MOBOTIX door station may be coupled with the MOBOTIX MX-DoorMaster, making it impossible to open the door by forcibly removing the system and bypassing the connecting cable • 2nd product generation, suitable for: IP video door stations with an T2x and S1x as door camera • Integrated (rechargeable) battery power supply for access modules • Security door opener/bell with access code storage (protected against manipulation) • Connection for door opener, door sensor and door lock sensor • Interface and power supply: MxBus (max. 50 m distance to door station) • User interfaces: 2 status LEDs, 2 function buttons, integrated speaker (doorbell) • Inputs: 2 galvanically separated inputs with shared ground connection (AC/DC, self-powered up to 48 V) • Outputs: 1 isolated relay output (AC/DC, 24 V/1 A) or 1 connector for standard door opener (6 to 12 V AC), 1 output for MOBOTIX theft protection (12 V DC) • Protection class: IP20 (DIN EN 60529) • Operating temperature: -5 to 40°C / 23 to 104°F (DIN EN 50155) • Switch time: max. 5 s	322 g 9,0 cm
		1,3 l

Frames & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-OPT-Frame-1-EXT-PW	4047438014892	13,5 cm
	Single Frame, White	90079100	14,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection •	268 g	5,5 cm
	Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White		1,1 l
	MX-OPT-Frame-1-EXT-SV	4047438014939	13,5 cm
	Single Frame, Silver	90079100	14,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection •	268 g	5,5 cm
	Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver		1,1 l
	MX-OPT-Frame-1-EXT-DG	4047438014922	13,5 cm
	Single Frame, Dark Gray	90079100	14,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection •	268 g	5,5 cm
	Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Dark Gray		1,1 l
	MX-OPT-Frame-1-EXT-BL	4047438014915	13,5 cm
	Single Frame, Black	90079100	14,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection •	268 g	5,5 cm
	Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Black		1,1 l
	MX-OPT-Box-1-EXT-ON-PW	4047438015202	14,5 cm
	Single On-Wall-Housing, White	90079100	13,5 cm
	Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White	286 g	3,5 cm
			0,7 l
	MX-OPT-Box-1-EXT-ON-SV	4047438015240	14,5 cm
	Single On-Wall-Housing, Silver	90079100	13,5 cm
	Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver	286 g	3,5 cm

	MX-OPT-Box-1-EXT-ON-BL	4047438015226	14,5 cm
	Single On-Wall-Housing, Black	90079100	13,5 cm
	Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Black	286 g	3,5 cm
			0,7 l
	MX-OPT-Box-1-EXT-IN	4047438015271	14,5 cm
	Single In-Wall-Housing	90079100	13,5 cm
	Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	186 g	3,5 cm
			0,7 l
	MX-OPT-Frame-2-EXT-PW	4047438014847	23,5 cm
	Double Frame, White	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White	333 g	3,5 cm
			1,1 l
	MX-OPT-Frame-2-EXT-SV	4047438014885	23,5 cm
	Double Frame, Silver	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver	333 g	3,5 cm
			1,1 l
	MX-OPT-Frame-2-EXT-DG	4047438014878	23,5 cm
	Double Frame, Dark Gray	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray	333 g	5,0 cm
			1,6 l
	MX-OPT-Frame-2-EXT-BL	4047438014861	23,5 cm
	Double Frame, Black	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black	333 g	3,5 cm
			1,1 l
	MX-OPT-Box-2-EXT-ON-PW	4047438015158	23,5 cm
	Double On-Wall-Housing, White	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White	430 g	3,5 cm
			1,1 l
	MX-OPT-Box-2-EXT-ON-SV	4047438015196	23,5 cm
	Double On-Wall-Housing, Silver	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver	430 g	3,5 cm
			1,1 l

	MX-OPT-Box-2-EXT-ON-DG	4047438015189	23,5 cm
	Double On-Wall-Housing, Dark Gray	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray	430 g	3,0 cm
			1,0 l
	MX-OPT-Box-2-EXT-ON-BL	4047438015172	23,5 cm
	Double On-Wall-Housing, Black	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black	430 g	3,5 cm
			1,1 l
	MX-OPT-Box-2-EXT-IN	4047438015264	23,5 cm
	Double In-Wall-Housing	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	270 g	3,5 cm
			1,1 l
	MX-OPT-Frame-3-EXT-PW	4047438014793	33,5 cm
	Triple Frame, White	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: White	426 g	5,5 cm
			2,5 l
	MX-OPT-Frame-3-EXT-SV	4047438014830	33,5 cm
	Triple Frame, Silver	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Silver	426 g	5,5 cm
			2,5 l
	MX-OPT-Frame-3-EXT-DG	4047438014823	33,5 cm
	Triple Frame, Dark Gray	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Dark Gray	426 g	5,0 cm
			2,3 l
	MX-OPT-Frame-3-EXT-BL	4047438014816	33,5 cm
	Triple Frame, Black	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Black	426 g	5,5 cm
			2,5 l
	MX-OPT-Box-3-EXT-ON-PW	4047438015103	33,5 cm
	Triple On-Wall-Housing, White	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White	574 g	3,5 cm
			1,6 l


	MX-OPT-Box-3-EXT-ON-SV	4047438015141	33,5 cm
	Triple On-Wall-Housing, Silver	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver	574 g	3,5 cm
			1,6 l
	MX-OPT-Box-3-EXT-ON-DG	4047438015134	33,5 cm
	Triple On-Wall-Housing, Dark Gray	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray	574 g	3,0 cm
			1,4 l
	MX-OPT-Box-3-EXT-ON-BL	4047438015127	33,5 cm
	Triple On-Wall-Housing, Black	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black	574 g	3,5 cm
			1,6 l
	MX-OPT-Box-3-EXT-IN	4047438015257	33,5 cm
	Triple In-Wall-Housing	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	362 g	3,5 cm
			1,6 l
	MX-OPT-Frame-4-EXT-PW	4047438017398	25,0 cm
	Quad Frame, White	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: White	516 g	5,5 cm
			3,4 l
	MX-OPT-Frame-4-EXT-SV	4047438017435	25,0 cm
	Quad Frame, Silver	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Silver	516 g	5,5 cm
			3,4 l
	MX-OPT-Frame-4-EXT-DG	4047438017428	25,0 cm
	Quad Frame, Dark Gray	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Dark Gray	516 g	5,5 cm
			3,4 l
	MX-OPT-Frame-4-EXT-BL	4047438017411	25,0 cm
	Quad Frame, Black	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Black	516 g	5,5 cm
			3,4 l

	MX-OPT-Box-4-EXT-ON-PW	4047438017442	25,0 cm
	Quad On-Wall-Housing, White	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: White	620 g	3,3 cm
			2,1 l
	MX-OPT-Box-4-EXT-ON-SV	4047438017480	25,0 cm
	Quad On-Wall-Housing, Silver	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Silver	620 g	3,3 cm
			2,1 l
	MX-OPT-Box-4-EXT-ON-DG	4047438017473	25,0 cm
	Quad On-Wall-Housing, Dark Gray	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Dark Gray	620 g	5,5 cm
			3,4 l
	MX-OPT-Box-4-EXT-ON-BL	4047438017466	25,0 cm
	Quad On-Wall-Housing, Black	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Black	620 g	3,3 cm
			2,1 l
	MX-OPT-Box-4-EXT-IN	4047438017497	25,0 cm
	Quad In-Wall-Housing	90079100	25,0 cm
	Suitable for: 4 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 218 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	434 g	3,3 cm
			2,1 l
	MX-OPT-FlatMount-EXT-PW	4047438019811	14,7 cm
	FlatMount Frame, white	90079100	13,7 cm
	For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white	190 g	5,5 cm
			1,1 l
	MX-OPT-FlatMount-EXT-BL	4047438019835	14,7 cm
	FlatMount Frame, black	90079100	13,7 cm
	For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: black	190 g	5,5 cm
			1,1 l
	MX-OPT-FlatMount-Box-EXT-IN	4047438019866	13,8 cm
	FlatMount Frame In-Wall Housing	90079100	6,5 cm
	In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm	130 g	13,8 cm
			1,2 l

Building Automation Accessories

Article No. / Name / Description		EAN / HS / weight	dimen.
	MX-AdminCard1	4047438015288	8,5 cm
	Admin RFID Transponder Card (Red)	85235200	5,5 cm
	For system configuration IP Video Door Station via KeypadRFID and BellRFID •	2 g	0,1 cm
	Type/encryption: MIFARE DESFire EV1 3K3DES/AES		0,0 l
	MX-UserCard1	4047438015295	8,5 cm
	User RFID Transponder Card (Blue)	85235200	5,5 cm
	For keyless entry via with KeypadRFID or BellRFID (IP video door station) •	2 g	0,1 cm
	Type/encryption: MIFARE DESFire EV1 3K3DES/AES		0,0 l
	MX-OPT-IO1	4047438013307	9,8 cm
	Extended Terminal Board (IO Module)	85299065	7,5 cm
	Suitable for: T2x, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).	86 g	9,0 cm
			0,7 l
	MX-OPT-IO2	4047438014786	9,8 cm
	Ethernet Terminal Board	85299065	7,5 cm
	Suitable for: T2x • The Ethernet terminal board is used to connect the door station for the versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module	60 g	9,0 cm
			0,7 l

Software & Services

**Article No. / Name / Description****EAN / HS / weight dimen.****Mx-SW-MC-POS**

4047438031615

0,0 cm

MxMC POS Single Cash Point License

0,0 cm

MOBOTIX license for connecting a cash register to an MxMC workstation (as of MxMC 1.7) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

0 g

0,0 cm

0,0 l

Article No. / Name / Description				EAN / HS / weight	dimen.
	Mx-WE-DTVS-1			4047438031974	cm
	1 Year Warranty Extension For Dual Thermal Systems S16				cm
	3+1 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.		g		cm
					l
	Mx-WE-DTVS-2			4047438031981	cm
	2 Years Warranty Extension For Dual Thermal Systems S16				cm
	3+2 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.		g		cm
					l
	Mx-WE-DTVS-3			4047438031998	cm
	3 Years Warranty Extension For Dual Thermal Systems S16				cm
	3+3 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.		g		cm
					l
	Mx-WE-DTVS-4			4047438032001	cm
	4 Years Warranty Extension For Dual Thermal Systems S16				cm
	3+4 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.		g		cm
					l
	Mx-WE-DTVS-5			4047438032018	cm
	5 Years Warranty Extension For Dual Thermal Systems S16				cm
	3+5 Years warranty for Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.		g		cm
					l
	Mx-WE-IVS-1			4047438031820	cm
	1 Year Warranty Extension For Indoor Video Systems				cm
	3+1 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.		g		cm
					l
	Mx-WE-IVS-2			4047438031837	cm
	2 Years Warranty Extension For Indoor Video Systems				cm
	3+2 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.		g		cm
					l

**Mx-WE-IVS-3****3 Years Warranty Extension For Indoor Video Systems**

3+3 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031844

cm

g

cm

l

**Mx-WE-IVS-4****4 Years Warranty Extension For Indoor Video Systems**

3+4 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031851

cm

g

cm

cm

l

**Mx-WE-IVS-5****5 Years Warranty Extension For Indoor Video Systems**

3+5 Years Warranty For Indoor Video Systems (Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031868

cm

g

cm

cm

l

**Mx-WE-OVS-1****1 Year Warranty Extension For Outdoor Video Systems**

3+1 Year Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031875

cm

g

cm

cm

l

**Mx-WE-OVS-2****2 Years Warranty Extension For Outdoor Video Systems**

3+2 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031882

cm

g

cm

cm

l

**Mx-WE-OVS-3****3 Years Warranty Extension For Outdoor Video Systems**

3+3 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031899

cm

g

cm

cm

l

**Mx-WE-OVS-4****4 Years Warranty Extension For Outdoor Video Systems**

3+4 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031905

cm

g

cm

cm

l

**Mx-WE-OVS-5****5 Years Warranty Extension For Outdoor Video Systems**

3+5 Years Warranty For Outdoor Video Systems (Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031912</

**Mx-WE-STVS-1**

4047438031929

cm

1 Year Warranty Extension For Single Thermal Systems

3+1 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

g

cm

l

**Mx-WE-STVS-2**

4047438031936

cm

2 Years Warranty Extension For Single Thermal Systems

3+2 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

g

cm

cm

l

**Mx-WE-STVS-3**

4047438031943

cm

3 Years Warranty Extension For Single Thermal Systems

3+3 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

g

cm

cm

l

**Mx-WE-STVS-4**

4047438031950

cm

4 Years Warranty Extension For Single Thermal Systems

3+4 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

g

cm

cm

l

**Mx-WE-STVS-5**

4047438031967

cm

5 Years Warranty Extension For Single Thermal Systems

3+5 Years warranty for Mx6 thermal video systems • Notes: The warranty extension covers a S16 DualFlex with a maximum of one connected thermal sensor module or an M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

g

cm

cm

l