

Technical Specifications

MOBOTIX VAXTOR License Plate Recognition App

Worldwide usable with over 99% accuracy

The Certified VAXTOR License Plate Recognition App recognizes, based on deep learning processes, characters from all over the world (Latin, Hebrew, Asian and Arabic characters). The application can be used at maximum speeds of up to 160 km/h and on several lanes and is characterized by an extremely high hit probability of over 99 percent.

Via a blocking or permission list, authorized, blocked or searched vehicles can be defined specifically. For example, a gate or barrier in an access road can open or be blocked automatically.

- Subject to license, single payment for unlimited use
- Recognition of license plates with global country coverage
- With over 99% accuracy optimally suited for license plate based access control
- Use of blocking and permission lists possible
- LPR application with full 4K resolution possible
- App-integrated Smart Data Data Interface for data retrieval with MxManagementCenter version 2.4 or higher (e.g. to search for specific license plates, even across multiple LPR cameras)



Technical Specifications MOBOTIX VAXTOR License Plate Recognition App

Product Information

Product Name VAXTOR License Plate Recognition App

Order Code Mx-APP-VX-LPR

Supported MOBOTIX Cam- Mx-M73A, Mx-S74A

eras

Minimum Camera Firmware V7.0.6.18

MxManagementCenter ■ min. MxMC v2.3.1

Integration

Configuration: Advanced Config license required

Recognition Log: Smart Data Interface license required

Product Features

App Features	License plate recognition of one- and two-line license plates
	Latin, Hebrew, Arabic and Asian characters
	Recognition log (Smart Data / Event Search via MxManagementCenter)
	MOBOTIX events via MxMessageSystem
	Global country coverage

■ Two lists for individual actions (e.g. access granted/denied, alarm, etc.)

■ Free flow and signaled mode for LPR & ADR

Maximum number of lanes 2

Maximum number of 1000 per list

enrolled license plates

Meta Data / Statistic JSON

formats

Trial License 30-day trial license pre-installed

MxMessageSystem sup-

ported

Interfaces

Milestone X-Protect

Vaxtor Helix

Generic 3rd party integration via XML

Compare supported camera's interfaces

MOBOTIX Events Yes

ONVIF Events Yes (Generic message event)

Supported Regions

Supported license plates https://community.mobotix.com/t/vaxtor-lpr-app-supported-license-plates-

countries

Scene Requirements

Character Height 20px - 50px (depending on the plate type)

Maximum Vertical Angle 30°

Maximum Horizontal Angle < 25°

Maximum Tilt Angle < 25°

Technical App Specifications

MOBOTIX App support Yes

Synchronous / Asyn-

Asynchronous

chronous App

Accuracy Min. 99% (considering scene requirements)

Processed number of

frames per second

Typ. 10 fps

Detection time

Typ. 100 – 120 ms