

Technical Specifications

MOBOTIX ActivitySensor AI App

Smart Activity Analytics

The app's artificial intelligence-based algorithms detect and classify user-defined motion and objects in up to 20 detection areas. Best suited for: Utilities, Health Care, Energy & Mining; Industry & Production; Government; Traffic & Transportation; Retail; Healthcare; Education & Science

- Motion detection of user-defined objects such as persons and/or vehicles
- Detection and classification of objects based on artificial intelligence
- Detection and specification of the motion direction MOBOTIX events via MxMessageSystem
- Consolidated event search via MxManagementCenter Smart Data Interface
- Definition of up to 20 detection areas within the camera's field of view



MOBOTIX

Technical Specifications MOBOTIX MOBOTIX ActivitySensor AI App

Product Information

Product Name	MOBOTIX ActivitySensor AI App	
Order Code	-/-	
Supported MOBOTIX Cameras	M73, S74, D71	
Minimum Camera Firmware v7.3.1.x		
MxManagementCenter com- min. MxMC v2.5		

Configuration: Advanced Config license requiredEvent Search: Smart Data Interface license included

Product Features

patibility

App Features	 Motion detection of user-defined objects such as persons and/or vehicles Detection and classification of objects based on artificial intelligence Detection and specification of the motion direction MOBOTIX events via MxMessageSystem Consolidated event search via MxManagementCenterSmart Data Inter-
	face
	Definition of up to 20 detection areas within the camera's field of view
Maximum number of recog- 20	
nition areas	

Recognized objects	Persons, Cars, Trucks, Buses, Motorcycles, Bicycles
Supported image sensor types	Day, Night, Day/Night
Dual / Multi Sensor usage	No (See Hardware Requirements below)
MxMessageSystem sup- ported	Yes
MOBOTIX Events	Yes
ONVIF Events	Yes (Generic Message event)

Hardware / Scene Requirements

Camera Sensor Connector Connector 1

NOTE! Only one image sensor can be used

Object Recognition as basis for MOBOTIX ActivitySensor Al

Recommended installation wall-mounted

position (camera)

Recommended installation 2m - 5m

height (camera)

Recommended viewing 0° - 30° (wall mount perspective)

angle on object

Minimum object size 1/20 of image height (15px at CIF resolution)

Technical App Specifications

Synchronous / Asynchronous App asynchronous

Processed frame rate typ. 5 fps

Detection average accuracy Persons: >90%; Vehicles: >85%

