

Compact Dome. Limitless Potential!

MOBOTIX 7 – Dome



Available model variants
D71 | v71 Indoor

- **Finely crafted and convenient:** can be manually adjusted on three axes
- **Flexible thanks to a range of lenses** with a viewing angle of between 15° and 95°
- **Automatic day/night switching**
- **Robust** with vandal resistant aluminum housing
- **Integrated audio function** for direct communication
- **Open to enable intelligent video analysis** with camera apps
- **Made in Germany** for optimum cybersecurity




Learn more now
www.mobotix.com

MOBOTIX
BeyondHumanVision

MOBOTIX Certified Apps at a glance

<https://www.mobotix.com/en/mobotix-certified-apps>



MOBOTIX 7 – Dome

Technical Data

A Proven Classic with New Class

Discreet appearance and abundant in options: These are the MOBOTIX dome cameras D71 and v71 Indoor. The compact single lens cameras are protected by their impact-resistant dome. Three manually adjustable axes allow you to **perfectly orient** the configurable optics **in a very convenient way**. The D71 and the v71 become **infinitely flexible** with the intelligent video analysis apps onboard the MOBOTIX 7 platform. These apps can be programmed individually.

MOBOTIX 7 – Video analysis Has Never Been So Comprehensive!

The D71/v71 are part of the **MOBOTIX 7 platform** with its intelligent video analysis apps. A large number of existing Certified Apps already cover numerous applications, such as loitering, unattended baggage or facial recognition. You can also develop and implement your own camera apps. This is how new solutions are created time and time again. We will be happy to support you with the programming. **All currently available Certified Apps** are pre-installed and **can be tried free of charge for 30 days!**

Features	MOBOTIX D71	MOBOTIX v71 Indoor
Ambient temperature range	-40 to 65° C	-10 to 50 °C
Image sensor	4K or 4MP LowLight	4K or 4MP LowLight
Autom. day/night switching	✓	✓
IR light integrated (up to 30m)	✓	✓
Integrated microphone/speaker	✓	✓
ONVIF compatibility	Profile S, T, G	Profile S, T, G
Video codecs	MxPEG+, MJPEG, H264/5	MxPEG+, MJPEG, H264/5
Interfaces	RJ45, USB-C, I/O, LineIn/LineOut	RJ45, USB-C
Power supply	PoE+	PoE+, PoE (with reduced illumination and without USB peripherals)

EN_09/22

MOBOTIX AG • Kaiserstrasse • 67722 Langmeil • Germany • sales@mobotix.com

MOBOTIX is a registered trademark of MOBOTIX AG in the European Union, the USA, and other countries. This may only be transferred to trade or commercial partners. Subject to change. MOBOTIX does not assume any liability for technical errors, printing errors or omissions. All rights reserved. © MOBOTIX AG 2022

MOBOTIX
BeyondHumanVision