

Technical Specifications

MOBOTIX Barcode Reader App

MOBOTIX Barcode Reader App

For high-performance capture of almost all commercially available barcode types in video streams. Codes can be read reliably even under difficult conditions. Perspective distortions are compensated, low contrast and faded imprints are compensated. Thus, the app is suitable for industrial use.

- Reader supports more than 40 common 1D, 2D and Stacked barcode types (e.g. QR Code, Data Matrix Code, Dot Code, etc.)
- Optimized for difficult barcode reads (e.g. damaged, faded or distorted barcodes, barcodes on difficult surfaces, DPM codes)
- Quick reading of one or multiple barcodes in motion
- Definition of up to 20 detection areas within the camera's field of view
- MOBOTIX events via MxMessageSystem
- Supports the reporting of barcode reads via generic XML, JSON and MODBUS/TCP



MOBOTIX

Beyond Human Vision

Product Information

Product Name	MOBOTIX Barcode Reader App	
Supported MOBOTIX Cameras	D71, M73, S74, v71, p71	
Minimum Camera Firmware V7.3.1.x		
MxManagementCenter Integration	 min. MxMC v2.7 Advanced Config license required Event Search: Smart Data Interface license included 	
MOBOTIX HUB com- patibility	 min. MOBOTIX HUB version: 2021 R1 min. MOBOTIX HUB license level for Analytics Events: L2 min. MOBOTIX HUB license level for MOBOTIX Event Search Plug-In : L4 	

App Features	 Reader supports more than 40 common 1D, 2D and Stacked barcode types (e.g. QR Code, Data Matrix Code, Dot Code, etc.) Optimized for difficult barcode reads (e.g. damaged, faded or distorted barcodes, barcodes on difficult sur- faces, DPM codes) Quick reading of one or multiple barcodes in motion Definition of up to 20 detection areas within the camera's field of view MOBOTIX events via MxMessageSystem supports the reporting of barcode reads via generic XML, JSON and MODBUS/TCP
Supported Barcode Types	https://community.mobotix.com/t/mobotix-barcode-reader-sup- ported-barcode-types/5675
Maximum number of recognition areas	20
Supported image sensor types	Day, Night, Day/Night
Dual / Multi Sensor usage	Yes
MxMessageSystem supported	Yes
MOBOTIX events	Yes
ONVIF Events	Yes (Generic Message events)

Product Features

Scene Requirements

Recommended code height	20 - 50px (depending on barcode type)
Maximum Vertical Angle	30°
Maximum Horizontal Angle	< 25°
Maximum Tilt Angle	< 25°

Technical App Specifications

Synchronous / Asynchronous App	Synchronous
Simultaneous execution of other apps	Yes (depending on performance expectations)
Accuracy	> 99% (considering scene requirements)
Processed number of frames per second	typ. 15 fps
Detection time	typ. 200 ms



EN_11/22 MOBOTIX AG • Kaiserstrasse • D-67722 Langmeil • Tel.: +49 6302 9816-103 • sales@mobotix.com • www.mobotix.com MOBOTIX is a trademark of MOBOTIX AG registered in the European Union, the U.S.A., and in other countries. Subject to change without notice. MOBOTIX do not assume any liability for technical or editorial errors or omissions contained herein. All rights reserved. © MOBOTIX