

# **Technical Specifications**

### **MOBOTIX Object Recognition App**

#### **Object Recognition Based on Artificial Intelligence**

The app's artificial intelligence-based algorithms collect behavioral data on individuals and objects. In a heat map, the most frequented locations in the detection are color-coded. Furthermore movements in defined restricted areas can be detected.

- Free of charge and license-free.
- Motion detection in (defined) restricted areas.
- Person/object counting based on motion detection (optional: accumulated).
- Creates Heatmaps.
- Auto-generated counting and heat map reports.
- Can be used with all cameras of the MOBOTIX 7 system platform.

#### Best suited for the requirements of the following industries:

Utilities, Energy & Mining; Industry & Production, Government, Traffic & Transportation, Retail, Healthcare, Education & Science



**MOBOTIX** 

# **Technical Specifications MOBOTIX Object Recognition App**

**NOTE!** The English version of this document may be more current.

#### **Product Information**

Product Name	MOBOTIX Object Recognition App
Supported MOBOTIX Cameras	Mx-M73A, Mx-S74A
Minimum Camera Firmware	V7.0.6.x
MxManagementCenter Integration	<ul><li>min. MxMC v2.4</li><li>Advanced Config license required</li></ul>

#### **Product Features**

App Features	Analytics features:	
	<ul> <li>Deep learning object recognition as basis for MxAnalytics features</li> <li>Restricted Area (Motion Detection)</li> </ul> Basicfeatures:	
	<ul> <li>time table to enable MxAnalytics only within defined schedules (e.g. opening hours)</li> <li>MOBOTIX events via MxMessageSystem</li> </ul>	
Recognized objects	<ul> <li>Persons</li> <li>Vehicles: Car, Truck, Bus, Motorcycle, Bicycle, Boat, Airplane, Train</li> <li>Animals: Bird, Cat, Dog, Horse, Sheep, Cow, Elephant, Bear, Zebra, Giraffe</li> </ul>	
Supported image sensor types	Day, Night, Day/Night	
Dual / Multi Sensor usage	No	
MxMessageSystem supported	Yes	
MOBOTIX events	Yes	
ONVIF Events	Yes (Generic Message events)	

## **Hardware Requirements**

Camera Sensor Connector Connector 1 (Only one image sensor usable)

#### **Scene Requirements for Object Recognition**

Recommended camera position	wall mounted	
Recommended installation height (camera)	2m - 4m	
Recommended viewing angle on object 0° - 30° (wall mount perspective)		
Minimum object size	1/10 of image height	

## **Technical App Specifications**

Synchronous / Asynchronous App	Asynchronous
Detection accuracy	Person: > 90% Vehicle: > 80%
Counting accuracy	> 90%
Processed number of frames per second	typ. 5 fps

