

# **Technical Specifications**

## **MOBOTIX Object Recognition App**

#### **Object Recognition Based on Artificial Intelligence**

The app's artificial intelligence-based algorithms collect behavioral data on individuals and objects. In a heat map, the most frequented locations in the detection are color-coded. Furthermore movements in defined restricted areas can be detected.

- Free of charge and license-free.
- Motion detection in (defined) restricted areas.
- Person/object counting based on motion detection (optional: accumulated).
- Creates Heatmaps.
- Auto-generated counting and heat map reports.
- Can be used with all cameras of the MOBOTIX 7 system platform.





Beyond Human Vision

#### Best suited for the requirements of the following industries:

Utilities, Energy & Mining; Industry & Production, Government, Traffic & Transportation, Retail, Healthcare, Education & Science

## **Product Information**

Product Name	MOBOTIX Object Recognition App
Supported MOBOTIX Cameras	Mx-M73A, Mx-S74A
Minimum Camera Firmware	V7.0.6.x
MxManagementCenter Integration	min. MxMC v2.4
	<ul> <li>Advanced Config license required</li> </ul>

### **Product Features**

App Features	Analytics features:
	<ul> <li>Deep learning object recognition as basis for MxAnalytics features</li> <li>Restricted Area (Motion Detection)</li> <li>Basicfeatures:</li> </ul>
	<ul> <li>time table to enable MxAnalytics only within defined schedules (e.g. opening hours)</li> <li>MOBOTIX events via MxMessageSystem</li> </ul>
Recognized objects	<ul> <li>Persons</li> <li>Vehicles: Car, Truck, Bus, Motorcycle, Bicycle, Boat, Airplane, Train</li> <li>Animals: Bird, Cat, Dog, Horse, Sheep, Cow, Elephant, Bear, Zebra, Giraffe</li> </ul>
Supported image sensor types	Day, Night, Day/Night
Dual / Multi Sensor usage	No
MxMessageSystem sup- ported	Yes
MOBOTIX events	Yes
ONVIF Events	Yes (Generic Message events)

#### **Hardware Requirements**

Camera Sensor Connector Connector 1 (Only one image sensor usable)

#### **Scene Requirements for Object Recognition**

Recommended camera position	wall mounted	
Recommended installation height (camera)	2m - 4m	
Recommended viewing angle on object 0° - 30° (wall mount perspective)		
Minimum object size	1/10 of image height	

#### **Technical App Specifications**

Synchronous / Asynchronous App	Asynchronous
Detection accuracy	Person: > 90% Vehicle: > 80%
Counting accuracy	> 90%
Processed number of frames per second	typ. 5 fps



EN\_03/23 MOBOTIX AG • Kaiserstrasse • D-67722 Langmeil • Tel.: +49 6302 9816-103 • sales@mobotix.com • www.mobotix.com MOBOTIX is a trademark of MOBOTIX AG registered in the European Union, the U.S.A., and in other countries. Subject to change without notice. MOBOTIX do not assume any liability for technical or editorial errors or omissions contained herein. All rights reserved. © MOBOTIX