

MOBOTIX Price List

23 August 2023 English



BeyondHumanVision

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group
MOBOTIX • 23.08.2023 • MOBOTIX accepts no liability arising from printing errors, mistakes and changes. • Revision 23.08.2023

MOBOTIX

Professional Video Systems Outdoor

BeyondHumanVision

MOBOTIX

M73A

MOBOTIX 7 Solution Platform

Weatherproof (IP66) Fixed Network Camera (Body) in two color variants, modular design with separately orderable optical 4K UHD image sensor modules (optimized for day, night or day & night use) and separately orderable function modules for easy insertion in the front panel (3 module openings, can be assigned as required), module connection via MOBOTIX sensor cables pre-positioned in the camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M73A-LSA	4047438036825	29,6 cm
	M73 Body with LSA Connector Box (white)	85258900	26,8 cm
		2.500 g	18,0 cm
	M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA terminal for weatherproof network connection via laying cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)		14,3 l
	Mx-M73A-LSA-wg	4047438036832	29,6 cm
	M73 Body with LSA Connector Box (white-gray)	85258900	26,8 cm
		2.500 g	18,0 cm
	M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA terminal for weatherproof network connection via laying cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white-gray • Warranty: 5 years (optionally extendable up to 8 years)		14,3 l
	Mx-M73A-RJ45	4047438034982	29,6 cm
	M73 Body with RJ45 Connector Box (white)	85258900	26,8 cm
		2.500 g	18,0 cm
	M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)		14,3 l

**Mx-M73A-RJ45-wg****M73 Body with RJ45 Connector Box (white-gray)**

M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT -30GF • Color: white-gray • Warranty: 5 years (optionally extendable up to 8 years)

4047438034999	29,6 cm
85258900	26,8 cm
2.500 g	18,0 cm
	14,3 l

D71 Dome Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-D71A-4DN050 D71 Complete Camera 4MP Ultra LowLight DN050 (Day) D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438039741 19,6 cm 85258900 18,0 cm 1.180 g 14,8 cm 5,2 l	
 Mx-D71A-4DN080 D71 Complete Camera 4MP Ultra LowLight DN080 (Day) D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438039758 19,6 cm 85258900 18,0 cm 1.180 g 14,8 cm 5,2 l	
 Mx-D71A-4DN100 D71 Complete Camera 4MP Ultra LowLight DN100 (Day) D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438039765 19,6 cm 85258900 18,0 cm 1.180 g 14,8 cm 5,2 l	
 Mx-D71A-4DN150 D71 Complete Camera 4MP Ultra LowLight DN150 (Day) D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438039772 19,6 cm 85258900 18,0 cm 1.180 g 14,8 cm 5,2 l	
 Mx-D71A-4DN280 D71 Complete Camera 4MP Ultra LowLight DN280 (Day) D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438039789 19,6 cm 85258900 18,0 cm 1.180 g 14,8 cm 5,2 l	

**Mx-D71A-8DN050****D71 Complete Camera 4K DN050 (Day(Night), 95°x50°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039697 19,6 cm
85258900 18,0 cm
1.180 9 14,8 cm
5,2 l

**Mx-D71A-8DN080****D71 Complete Camera 4K DN080 (Day(Night), 60°x33°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039703 19,6 cm
85258900 18,0 cm
1.180 9 14,8 cm
5,2 l

**Mx-D71A-8DN100****D71 Complete Camera 4K DN100 (Day(Night), 45°x25°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039710 19,6 cm
85258900 18,0 cm
1.180 9 14,8 cm
5,2 l

**Mx-D71A-8DN150****D71 Complete Camera 4K DN150 (Day(Night), 30°x17°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039727 19,6 cm
85258900 18,0 cm
1.180 9 14,8 cm
5,2 l

**Mx-D71A-8DN280****D71 Complete Camera 4K DN280 (Day(Night), 15°x8,5°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039734 19,6 cm
85258900 18,0 cm
1.180 9 14,8 cm
5,2 l

Q71A Hemispheric Camera



Article No. / Name / Description

EAN / HS / weight dimen.

Mx-Q71A-12DN016

4047438039796

19,6 cm

Q71 Complete Camera 12MP, DN016 (Day/Night), 360°

85258900

18,0 cm

Q71 camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 • 12MP image sensor • 4K effective resolution: 2880x2880 (hemispheric original image) • Max. Frame rate (4K): 20 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR and white light LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • IP66 • IK10 except on the lens • Operating temperature range: -40 to +65 °C • Built-in speaker and microphone - Line In & Out - Input & Output • USB-C • 8GB memory card included

1.050 g

14,8 cm

5,2 l

M16B AllroundDual Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16B	4047438030915	29,6 cm
	M16B Body, For M16 Sensor Modules (Day/Night)	85258900	19,6 cm
	M16 camera module for connecting one or two M16/M15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.764 g	18,0 cm
		10,4 l	
	Mx-M16B-6D6N036	4047438030922	29,6 cm
	M16B Complete Cam 6MP, 2x B036 (Day & Night)	85258900	19,6 cm
	IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.981 g	18,0 cm
		10,4 l	
	Mx-M16B-6D6N041	4047438030939	29,6 cm
	M16B Complete Cam 6MP, 2x B041 (Day & Night)	85258900	19,6 cm
	IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.974 g	18,0 cm
		10,4 l	
	Mx-M16B-6D6N061	4047438030946	29,6 cm
	M16B Complete Cam 6MP, 2x B061 (Day & Night)	85258900	19,6 cm
	IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	18,0 cm
		10,4 l	

**Mx-M16B-6D6N079****M16B Complete Cam 6MP, 2x B079 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030953	29,6 cm
85258900	19,6 cm
1.971 9	18,0 cm
	10,4 l

**Mx-M16B-6D6N119****M16B Complete Cam 6MP, 2x B119 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030960	29,6 cm
85258900	19,6 cm
1.970 9	18,0 cm
	10,4 l

**Mx-M16B-6D6N237****M16B Complete Cam 6MP, 2x B237 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B237 distant tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030977	29,6 cm
85258900	19,6 cm
1.981 9	18,0 cm
	10,4 l

D16B DualDome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-D16B D16B Body, For D16B/D15 Sensor Modules (Day/Night) IP camera module for connecting one or two D16/D15 sensor modules or a D16/D15 lens bridge FIX/PAN (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module/bridge): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 31° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Incl. 1x standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030588 85258900 1.277 g	39,5 cm 29,6 cm 9,0 cm 10,5 l
	Mx-D16B-F-6D6N036 D16B Complete Cam 6MP, 2x B036 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030595 85258900 1.646 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	Mx-D16B-F-6D6N041 D16B Complete Cam 6MP, 2x B041 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030601 85258900 1.627 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	Mx-D16B-F-6D6N061 D16B Complete Cam 6MP, 2x B061 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030618 85258900 1.642 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	Mx-D16B-F-6D6N079 D16B Complete Cam 6MP, 2x B079 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030625 85258900 1.645 g	39,5 cm 29,6 cm 18,0 cm 21,0 l

**Mx-D16B-F-6D6N119****D16B Complete Cam 6MP, 2x B119 (Day & Night)**

IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

4047438030632	39,5 cm
85258900	29,6 cm
1.630 9	18,0 cm
	21,0 l

**Mx-D16B-P-6D6D041****D16B Complete Cam 2x 6MP, Panorama 180° (Day)**

IP camera with PAN lens bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030656	39,5 cm
85258900	29,6 cm
1.650 9	18,0 cm
	21,0 l

**Mx-D16B-P-6N6N041****D16B Complete Cam 2x 6MP, Panorama 180° (Night)**

IP camera with PAN sensor bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030663	39,5 cm
85258900	29,6 cm
1.642 9	18,0 cm
	21,0 l

V16B Vandalism Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-V16B-6D041	4047438031462	26,0 cm
	V16B Complete Cam 6MP, 1x B041 (Day)	85258900	26,0 cm
	V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.600 g	26,0 cm
		17,6 l	
	Mx-V16B-6D079	4047438031479	26,0 cm
	V16B Complete Cam 6MP, 1x B079 (Day)	85258900	26,0 cm
	V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.600 g	26,0 cm
		17,6 l	
	Mx-V16B-6D6D041	4047438031486	26,0 cm
	V16B Complete Cam 6MP, 2x B041 (Day)	85258900	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x Color (day), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
		17,6 l	
	Mx-V16B-6D6D079	4047438031493	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B079 (Day)	85258900	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
		17,6 l	
	Mx-V16B-6D6N041	4047438031509	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B041 (Day & Night)	85258900	26,0 cm
	V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	4.700 g	26,0 cm
		17,6 l	

**Mx-V16B-6D6N079****V16B Complete Cam 2x 6MP, 2x B079 (Day & Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031516 26,0 cm
85258900 26,0 cm
4.700 g 26,0 cm
17,6 l

**Mx-V16B-6N6N041****V16B Complete Cam 2x 6MP, 2x B041 (Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031523 26,0 cm
85258900 26,0 cm
4.700 g 26,0 cm
17,6 l

**Mx-V16B-6N6N079****V16B Complete Cam 2x 6MP, 2x B079 (Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031530 26,0 cm
85258900 26,0 cm
4.700 g 26,0 cm
17,6 l

S74A

Article No. / Name / Description

EAN / HS / weight dimen.

**Mx-S74A**

4047438035552 29,6 cm

S74 Body for 4 Sensor- and Functional Modules

85258900 19,6 cm

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 or 1x LSA board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

1.400 g 9,0 cm

5,2 l

**Mx-S74A-LSA**

4047438047814 29,6 cm

S74 Body for 4 Sensor- and Functional Modules with LSA

85258900 19,6 cm

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

1.525 g 9,0 cm

5,2 l

**Mx-S74A-RJ45**

4047438047807 29,6 cm

S74 Body for 4 Sensor- and Functional Modules with RJ45

85258900 19,6 cm

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

1.520 g 9,0 cm

5,2 l

**Mx-S74A-SET****S74 Set with 2x 12DN016 sensor modules**

S74A IP camera (set) incl. built-in AudioI/O and RJ45 plug-in board + 2x 3m sensor cable (Mx-A-S7A-CBL03) + 2x 12DN016 sensor module (12MP, Day/Night, Hemispheric, white, Mx-O-M7SA-12DN016) • for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board (with 12/24 VDC Power Supply) for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047999	29,6 cm
85258900	19,6 cm
1.980 9	18,0 cm
	10,4 l

**Mx-S74A-VDC****S74 Body for 4 Sensor- and Functional Modules with RJ45**

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board (with 12/24 VDC Power Supply) for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047821	29,6 cm
85258900	19,6 cm
1.510 9	9,0 cm
	5,2 l

S16B DualFlex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S16B	4047438031400	19,6 cm
	S16B Body, For S16B/S15 Sensor Modules	85258900	14,8 cm
	S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP66/IK06, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio (I/O); RS232 via MX Interface Box	660 g	9,0 cm 2,6 l
	Mx-S16B-S1	4047438031417	29,6 cm
	S16B Complete Cam, Set 1, 6MP, 1x B016 (Day)	85258900	19,6 cm
	S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal)	720 g	9,0 cm 5,2 l
	Mx-S16B-S2	4047438031424	29,6 cm
	S16B Complete Cam, Set 2, 6MP, 2x B016 (Day)	85258900	19,6 cm
	S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	1.700 g	9,0 cm 5,2 l
	Mx-S16B-S3	4047438031431	29,6 cm
	S16B Complete Cam, Set 3, 6MP, 2x B016 (Day & Night)	85258900	19,6 cm
	S16 camera module (body) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66	1.700 g	9,0 cm 5,2 l

S26B Flex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S26B-6D016	4047438031448	19,6 cm
	S26B Complete Cam 6MP, B016 (Day)	85258900	15,0 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	685 g	9,0 cm
			2,6 l
	Mx-S26B-6N016	4047438031455	19,6 cm
	S26B Complete Cam 6MP, B016 (Night)	85258900	15,0 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	685 g	9,0 cm
			2,6 l

M26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M26B-6D	4047438031042	29,6 cm
	M26B Body 6MP (Day)	85258900	19,6 cm
	IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.337 g	18,0 cm
			10,4 l
	Mx-M26B-6D016	4047438031059	29,6 cm
	M26B Complete Cam 6MP, B016 (Day)	85258900	19,6 cm
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.342 g	18,0 cm
			10,4 l
	Mx-M26B-6D036	4047438031066	29,6 cm
	M26B Complete Cam 6MP, B036 (Day)	85258900	19,6 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.365 g	18,0 cm
			10,4 l
	Mx-M26B-6D041	4047438031073	29,6 cm
	M26B Complete Cam 6MP, B041 (Day)	85258900	19,6 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.354 g	18,0 cm
			10,4 l
	Mx-M26B-6D061	4047438031080	29,6 cm
	M26B Complete Cam 6MP, B061 (Day)	85258900	19,6 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.361 g	18,0 cm
			10,4 l

**Mx-M26B-6D079****M26B Complete Cam 6MP, B079 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031097 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6D119****M26B Complete Cam 6MP, B119 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031103 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6D237****M26B Complete Cam 6MP, B237 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031110 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6D500****M26B Complete Cam 6MP, B500 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031127 29,6 cm
85258900 19,6 cm
2.000 G 18,0 cm
10,4 l

**Mx-M26B-6N****M26B Body 6MP (Night)**

IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031134 29,6 cm
85258900 19,6 cm
1.344 G 18,0 cm
10,4 l

**Mx-M26B-6N016****M26B Complete Cam 6MP, B016 (Night)**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031141 29,6 cm
85258900 19,6 cm
1.342 G 18,0 cm
10,4 l

**Mx-M26B-6N036****M26B Complete Cam 6MP, B036 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031158 29,6 cm
85258900 19,6 cm
1.365 G 18,0 cm
10,4 l

**Mx-M26B-6N041****M26B Complete Cam 6MP, B041 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031165 29,6 cm
85258900 19,6 cm
1.354 G 18,0 cm
10,4 l

**Mx-M26B-6N061****M26B Complete Cam 6MP, B061 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031172 29,6 cm
85258900 19,6 cm
1.361 G 18,0 cm
10,4 l

**Mx-M26B-6N079****M26B Complete Cam 6MP, B079 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031189 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6N119****M26B Complete Cam 6MP, B119 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031196	29,6 cm
85258900	19,6 cm
1.359 G	18,0 cm
	10,4 l

**Mx-M26B-6N237****M26B Complete Cam 6MP, B237 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031202	29,6 cm
85258900	19,6 cm
1.359 G	18,0 cm
	10,4 l

**Mx-M26B-6N500****M26B Complete Cam 6MP, B500 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031219	29,6 cm
85258900	19,6 cm
1.366 G	18,0 cm
	10,4 l

D26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-D26B-6D	4047438030670	19,6 cm
	D26B Body 6MP (Day)	85258900	18,0 cm
	D26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	799 g	14,8 cm
			5,2 l
	Mx-D26B-6D036	4047438030687	19,6 cm
	D26B Complete Cam 6MP, B036 (Day)	85258900	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	814 g	14,8 cm
			5,2 l
	Mx-D26B-6D041	4047438030694	19,6 cm
	D26B Complete Cam 6MP, B041 (Day)	85258900	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	762 g	14,8 cm
			5,2 l
	Mx-D26B-6D061	4047438030700	19,6 cm
	D26B Complete Cam 6MP, B061 (Day)	85258900	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	814 g	14,8 cm
			5,2 l
	Mx-D26B-6D079	4047438030717	19,6 cm
	D26B Complete Cam 6MP, B079 (Day)	85258900	18,0 cm
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessor)	1.580 g	14,8 cm
			5,2 l

**Mx-D26B-6D119****D26B Complete Cam 6MP, B119 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030724 19,6 cm
85258900 18,0 cm
1.580 g 14,8 cm
5,2 l

**Mx-D26B-6D237****D26B Complete Cam 6MP, B237 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50° C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030731 19,6 cm
85258900 18,0 cm
815 g 14,8 cm
5,2 l

**Mx-D26B-6N****D26B Body 6MP (Night)**

D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030748 19,6 cm
85258900 18,0 cm
799 g 14,8 cm
5,2 l

**Mx-D26B-6N036****D26B Complete Cam 6MP, B036 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030755 19,6 cm
85258900 18,0 cm
814 g 14,8 cm
5,2 l

**Mx-D26B-6N041****D26B Complete Cam 6MP, B041 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030762 19,6 cm
85258900 18,0 cm
1.580 g 14,8 cm
5,2 l

**Mx-D26B-6N061****D26B Complete Cam 6MP, B061 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030779 19,6 cm
85258900 18,0 cm
1.580 g 14,8 cm
5,2 l

**Mx-D26B-6N079****D26B Complete Cam 6MP, B079 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030786 19,6 cm
85258900 18,0 cm
1.580 9 14,8 cm
5,2 l

**Mx-D26B-6N119****D26B Complete Cam 6MP, B119 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030793 19,6 cm
85258900 18,0 cm
1.580 9 14,8 cm
5,2 l

**Mx-D26B-6N237****D26B Complete Cam 6MP, B237 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030809 19,6 cm
85258900 18,0 cm
1.580 9 14,8 cm
5,2 l

Q26B Hemispheric Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-Q26B-6D016	4047438031387 29,6 cm
	Q26B Complete Cam 6MP, B016 (Day)	85258900 19,6 cm
		853 9 9,0 cm
		5,2 l
Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)		
	Mx-Q26B-6N016	4047438031394 29,6 cm
	Q26B Complete Cam 6MP, B016 (Night)	85258900 19,6 cm
		855 9 9,0 cm
		5,2 l
Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)		

Professional Video Systems Indoor

BeyondHumanVision

MOBOTIX

c71A Indoor Camera



Article No. / Name / Description

EAN / HS / weight dimen.

Mx-c71A-8DN016

4047438041027

19,6 cm

c71 Indoor Complete Camera 4k, DN016 (Day/Night)

85258900

18,0 cm

c71 Indoor camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 • 4k image sensor • 4MP effective resolution: 2160x2160 (hemispheric original image) • Max. Frame rate (4MP): 30 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

1.040 g

14,8 cm

5,2 l

p71A Indoor Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-p71A-4DN040 p71 Indoor Complete Camera 4MP Ultra LowLight DN040 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041164 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 Mx-p71A-4DN050 p71 Indoor Complete Camera 4MP Ultra LowLight DN050 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041171 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 Mx-p71A-4DN080 p71 Indoor Complete Camera 4MP Ultra LowLight DN080 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041188 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 Mx-p71A-4DN100 p71 Indoor Complete Camera 4MP Ultra LowLight DN100 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041195 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 Mx-p71A-4DN150 p71 Indoor Complete Camera 4MP Ultra LowLight DN150 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041201 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

**Mx-p71A-4DN280****p71 Indoor Complete Camera 4MP Ultra LowLight DN280**

p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041218 19,6 cm
85258900 18,0 cm
1.175 9 14,8 cm
5,2 l

**Mx-p71A-8DN040****p71 Indoor Complete Camera 4K DN040 (Day/Night), 120°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041041 19,6 cm
85258900 18,0 cm
1.175 9 14,8 cm
5,2 l

**Mx-p71A-8DN050****p71 Indoor Complete Camera 4K DN050 (Day/Night), 95°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041058 19,6 cm
85258900 18,0 cm
1.175 9 14,8 cm
5,2 l

**Mx-p71A-8DN080****p71 Indoor Complete Camera 4K DN080 (Day(Night), 60°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041065 19,6 cm
85258900 18,0 cm
1.175 9 14,8 cm
5,2 l

**Mx-p71A-8DN100****p71 Indoor Complete Camera 4K DN100 (Day(Night), 45°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041072 19,6 cm
85258900 18,0 cm
1.175 9 14,8 cm
5,2 l

**Mx-p71A-8DN150****p71 Indoor Complete Camera 4K DN150 (Day(Night), 30°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041089 19,6 cm
85258900 18,0 cm
1.175 9 14,8 cm
5,2 l

**Mx-p71A-8DN280****p71 Indoor Complete Camera 4K DN280 (Day(Night), 15°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041096 19,6 cm

85258900 18,0 cm

1.175 g 14,8 cm

5,2 l

v71A Indoor Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-v71A-4DN050 v71 Indoor Complete Camera 4MP Ultra LowLight DN050 - v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438040921 19,6 cm 85258900 18,0 cm 1.050 g 14,8 cm 5,2 l	
 Mx-v71A-4DN080 v71 Indoor Complete Camera 4MP Ultra LowLight DN080 - v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438040938 19,6 cm 85258900 18,0 cm 1.050 g 14,8 cm 5,2 l	
 Mx-v71A-4DN100 v71 Indoor Complete Camera 4MP Ultra LowLight DN100 - v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438040945 19,6 cm 85258900 18,0 cm 1.050 g 14,8 cm 5,2 l	
 Mx-v71A-4DN150 v71 Indoor Complete Camera 4MP Ultra LowLight DN150 - v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438040952 19,6 cm 85258900 18,0 cm 1.050 g 14,8 cm 5,2 l	
 Mx-v71A-4DN280 v71 Indoor Complete Camera 4MP Ultra LowLight DN280 - v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438040969 19,6 cm 85258900 18,0 cm 1.050 g 14,8 cm 5,2 l	

**Mx-v71A-8DN050****v71 Indoor Complete Camera 4K DN050 - 95°x50°**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040822 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

**Mx-v71A-8DN080****v71 Indoor Complete Camera 4K DN080 - 60°x33° (Day**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040839 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

**Mx-v71A-8DN100****v71 Indoor Complete Camera 4K DN100 - 45°x25° (Day**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040846 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

**Mx-v71A-8DN150****v71 Indoor Complete Camera 4K DN150 - 30°x17° (Day**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040853 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

**Mx-v71A-8DN280****v71 Indoor Complete Camera 4K DN280 - 15°x8,5° (Day**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040860 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

c26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-c26B-6D	4047438030489	19,6 cm
	c26B Body 6MP (Day)	85258900	15,0 cm
	c26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	431 g	9,0 cm
			2,6 l
	Mx-c26B-6D016	4047438030496	19,6 cm
	c26B Complete Cam 6MP, B016, Day	85258900	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	433 g	9,0 cm
			2,6 l
	Mx-c26B-6D036	4047438030502	19,6 cm
	c26B Complete Cam 6MP, B036, Day	85258900	15,0 cm
	IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	444 g	9,0 cm
			2,6 l
	Mx-c26B-6N	4047438030519	19,6 cm
	c26B Body 6MP (Night)	85258900	15,0 cm
	c26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	431 g	9,0 cm
			2,6 l
	Mx-c26B-6N016	4047438030526	19,6 cm
	c26B Complete Cam 6MP, B016, Night	85258900	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	433 g	9,0 cm
			2,6 l

**Mx-c26B-6N036****c26B Complete Cam 6MP, B036, Night**

IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030533	19,6 cm
85258900	15,0 cm
444 9	9,0 cm
	2,6 l

**Mx-c26B-AU-6D016****c26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030540	19,6 cm
85258900	15,0 cm
442 9	9,0 cm
	2,6 l

**Mx-c26B-AU-6D036****c26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030557	19,6 cm
85258900	15,0 cm
446 9	9,0 cm
	2,6 l

**Mx-c26B-AU-6N016****c26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030564	19,6 cm
85258900	15,0 cm
452 9	9,0 cm
	2,6 l

**Mx-c26B-AU-6N036****c26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030571	19,6 cm
85258900	15,0 cm
446 9	9,0 cm
	2,6 l

i26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-i26B-6D	4047438030816	19,6 cm
	i26B Body 6MP (Day)	85258900	14,8 cm
	i26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	420 g	9,0 cm
			2,6 l
	Mx-i26B-6D016	4047438030823	19,6 cm
	i26B Complete Cam 6MP, B016, Day	85258900	15,0 cm
	Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	423 g	9,0 cm
			2,6 l
	Mx-i26B-6D036	4047438030830	19,6 cm
	i26B Complete Cam 6MP, B036, Day	85258900	15,0 cm
	IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	440 g	9,0 cm
			2,6 l
	Mx-i26B-6N	4047438030847	19,6 cm
	i26B Body 6MP (Night)	85258900	14,8 cm
	i26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	420 g	9,0 cm
			2,6 l
	Mx-i26B-6N016	4047438030854	19,6 cm
	i26B Complete Cam 6MP, B016, Night	85258900	15,0 cm
	Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	423 g	9,0 cm
			2,6 l

**Mx-i26B-6N036****i26B Complete Cam 6MP, B036, Night**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030861 19,6 cm
85258900 15,0 cm
440 g 9,0 cm
2,6 l

**Mx-i26B-AU-6D016****i26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030878 19,6 cm
85258900 15,0 cm
429 g 9,0 cm
2,6 l

**Mx-i26B-AU-6D036****i26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030885 19,6 cm
85258900 15,0 cm
437 g 9,0 cm
2,6 l

**Mx-i26B-AU-6N016****i26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030892 19,6 cm
85258900 15,0 cm
429 g 9,0 cm
2,6 l

**Mx-i26B-AU-6N036****i26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030908 19,6 cm
85258900 15,0 cm
437 g 9,0 cm
2,6 l

p26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-p26B-6D	4047438031226	19,6 cm
	p26B Body 6MP, Day	85258900	18,0 cm
	p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	582 g	14,8 cm
			5,2 l
	Mx-p26B-6D016	4047438031233	19,6 cm
	p26B Complete Cam 6MP, B016, Day	85258900	18,0 cm
	Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	574 g	14,8 cm
			5,2 l
	Mx-p26B-6D036	4047438031240	19,6 cm
	p26B Complete Cam 6MP, B036, Day	85258900	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	596 g	14,8 cm
			5,2 l
	Mx-p26B-6D061	4047438031257	19,6 cm
	p26B Complete Cam 6MP, B061, Day	85258900	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	480 g	14,8 cm
			5,2 l
	Mx-p26B-6D079	4047438031264	19,6 cm
	p26B Complete Cam 6MP, B079, Day	85258900	18,0 cm
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	596 g	14,8 cm
			5,2 l

**Mx-p26B-6D119****p26B Complete Cam 6MP, B119, Day**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031271 19,6 cm
85258900 18,0 cm
480 9 14,8 cm
5,2 l

**Mx-p26B-6D237****p26B Complete Cam 6MP, B237, Day**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Distant Tele lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031288 19,6 cm
85258900 18,0 cm
480 9 14,8 cm
5,2 l

**Mx-p26B-6N****p26B Body 6MP, Night**

p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031295 19,6 cm
85258900 18,0 cm
582 9 14,8 cm
5,2 l

**Mx-p26B-6N016****p26B Complete Cam 6MP, B016, Night**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031301 19,6 cm
85258900 18,0 cm
574 9 14,8 cm
5,2 l

**Mx-p26B-6N036****p26B Complete Cam 6MP, B036, Night**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031318 19,6 cm
85258900 18,0 cm
480 9 14,8 cm
5,2 l

**Mx-p26B-AU-6D****p26B Body 6MP, Day, Audio Package**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031325 19,6 cm
85258900 18,0 cm
591 9 14,8 cm
5,2 l

**Mx-p26B-AU-6D016****p26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031332 19,6 cm
85258900 18,0 cm
480 9 14,8 cm
5,2 l

**Mx-p26B-AU-6D036****p26B Complete Cam 6MP, B036, Day, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031349 19,6 cm
85258900 18,0 cm
480 9 14,8 cm
5,2 l

**Mx-p26B-AU-6N****p26B Body 6MP, Night, Audio Package**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031356 19,6 cm
85258900 18,0 cm
480 9 14,8 cm
5,2 l

**Mx-p26B-AU-6N016****p26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031363 19,6 cm
85258900 18,0 cm
480 9 14,8 cm
5,2 l

**Mx-p26B-AU-6N036****p26B Complete Cam 6MP, B036, Night, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45°
• ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031370	19,6 cm
85258900	18,0 cm
480 9	14,8 cm
	5,2 l

v26B Indoor Dome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-v26B-6D	4047438031547 19,6 cm
	v26B Body 6MP, Day, White	85258900 18,0 cm
		726 g 14,8 cm
		5,2 l
v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white		
	Mx-v26B-6D-b	4047438031554 19,6 cm
	v26B Body 6MP, Day, Black	85258900 18,0 cm
		726 g 14,8 cm
		5,2 l
v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: black		
	Mx-v26B-6D036	4047438031561 19,6 cm
	v26B Complete Cam 6MP, B036, Day, White	85258900 18,0 cm
		737 g 14,8 cm
		5,2 l
IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white		
	Mx-v26B-6N	4047438031578 19,6 cm
	v26B Body 6MP, Night, White	85258900 18,0 cm
		726 g 14,8 cm
		5,2 l
v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white		

**Mx-v26B-6N-b****v26B Body 6MP, Night, Black**

v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: black

4047438031585	19,6 cm
85258900	18,0 cm
726 9	14,8 cm
	5,2 l

Professional Video Systems Thermal

BeyondHumanVision

MOBOTIX

M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16TB-EST079	4047438037433	29,6 cm
	M16B Thermographic Camera TR (EST), 50 mK, R079 (45°)	85258900	19,6 cm
	IP thermographic camera with EST079 thermal lens (for Elevated Skin Temperature Measurement), horizontal/vertical image angle 45°/35°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm
			10,4 l
	Mx-M16TB-EST119	4047438037440	29,6 cm
	M16B Thermographic Camera TR (EST), 50 mK, R119 (25°)	85258900	19,6 cm
	IP thermographic camera with EST119 thermal lens (for Elevated Skin Temperature Measurement), horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm
			10,4 l
	Mx-M16TB-EST237	4047438037457	29,6 cm
	M16B Thermographic Camera TR (EST), 50 mK, R237 (17°)	85258900	19,6 cm
	IP thermographic camera with EST237 thermal lens (for Elevated Skin Temperature Measurement), horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm
			10,4 l
	Mx-M16TB-R079	4047438030984	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R079 (45°)	90251900	19,6 cm
	IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm
			10,4 l

**Mx-M16TB-R119****M16B Thermographic Camera TR, 50 mK, R119 (25°)**

IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438030991	29,6 cm
90251900	19,6 cm
1.936 9	18,0 cm
	10,4 l

**Mx-M16TB-R237****M16B Thermographic Camera TR, 50 mK, R237 (17°)**

IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031004	29,6 cm
90251900	19,6 cm
1.942 9	18,0 cm
	10,4 l

**Mx-M16TB-R079-VDS****M16B Thermographic Camera TR, 50 mK, R079 (45°) - VDS**

VdS-Bundle • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041607	29,6 cm
90251900	26,8 cm
2.170 9	18,0 cm
	14,3 l

**Mx-M16TB-R119-VDS****M16B Thermographic Camera TR, 50 mK, R119 (25°) - VDS**

VdS Bundle • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041614	29,6 cm
90251900	26,8 cm
2.170 9	18,0 cm
	14,3 l

**Mx-M16TB-R237-VDS****M16B Thermographic Camera TR, 50 mK, R237 (17°) - VDS**

VdS Bundle • IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041621	29,6 cm
90251900	26,8 cm
2.170 9	18,0 cm
	14,3 l

**Mx-M16TB-T079****M16B Thermographic Camera 50 mK, T079 (45°)**

IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/35°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031011	29,6 cm
90251900	19,6 cm
2.460 9	18,0 cm
	10,4 l

**Mx-M16TB-T119****M16B Thermographic Camera 50 mK, T119 (25°)**

IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031028	29,6 cm
90251900	19,6 cm
2.460 9	18,0 cm
	10,4 l

**Mx-M16TB-T237****M16B Thermographic Camera 50 mK, T237 (17°)**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031035	29,6 cm
90251900	19,6 cm
1.946 9	18,0 cm
	10,4 l

M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16TB-R079-EN54	4047438043380	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R079 (45°) - EN54	90251900	19,6 cm
	EN54 Bundle • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.807 g	18,0 cm
		10,4 l	
	Mx-M16TB-R119-EN54	4047438043397	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R119 (25°) - EN54	90251900	19,6 cm
	EN54 Bundle • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.807 g	18,0 cm
		10,4 l	
	Mx-M16TB-R237-EN54	4047438043403	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R237 (17°) - EN54	90251900	19,6 cm
	EN54 Bundle • IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.807 g	18,0 cm
		10,4 l	
	Mx-M16TB-R500	4047438035514	29,6 cm
	M16B Thermographic Camera 35 mK, R500 (9.3°)	90251920	19,6 cm
	IP thermographic camera with R500 thermal lens, horizontal/vertical image angle 9.3°/7.1°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F): NETD typ. 35 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.946 g	18,0 cm
		10,4 l	

**Mx-M16TB-T500****M16B Thermographic Camera 50 mK, T500 (9.3°)**

IP thermographic camera with T500 thermal lens, horizontal/vertical image angle 9.3°/7.1°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438047500	29,6 cm
90251920	19,6 cm
1.946 g	18,0 cm
	10,4 l

Sensor Module Thermal for MOBOTIX 7

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-O-M73TB-336R100 Thermal module 336-R100 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate	4047438040198 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 Mx-O-M73TB-336R150 Thermal module 336-R150 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate	4047438040204 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 Mx-O-M73TB-336R280 Thermal module 336-R280 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate	4047438040211 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 Mx-O-M73TB-336R500 Thermal module 336-R500 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 9,3° x 7,1° • incl. M73 replacement front plate	4047438043557 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 Mx-O-M73TB-336T100 Thermal module 336-T100 with front plate for M73 (B) CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate	4047438040129 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l

**Mx-O-M73TB-336T150****Thermal module 336-T150 with front plate for M73 (B)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate

4047438040136	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-336T280****Thermal module 336-T280 with front plate for M73 (B)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate

4047438040143	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-336T500****Thermal module 336-T500 with front plate for M73 (B)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 9° x 7° • incl. M73 replacement front plate

4047438041287	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R050****Thermal module 640-R050 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate

4047438040228	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R080****Thermal module 640-R080 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate

4047438040235	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R100****Thermal module 640-R100 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate

4047438040242	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R150****Thermal module 640-R150 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate

4047438040259 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640R280****Thermal module 640-R280 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 18° x 14° • incl. M73 replacement front plate

4047438042598 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640T050****Thermal module 640-T050 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate

4047438040150 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640T080****Thermal module 640-T080 with front plate für M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate

4047438040167 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640T100****Thermal module 640-T100 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate

4047438040174 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640T150****Thermal module 640-T150 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate

4047438040181 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640T280****Thermal module 640-T280 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 18° x 14° • incl. M73 replacement front plate

4047438041294	19,6 cm
90275000	18,0 cm
450 9	14,8 cm
	5,2 l

**Mx-O-M7SA-320T040****Thermal Module ECO 320 - T040**

MOBOTIX 7 Thermal Module 320-T040 for M73/S74, CIF 320x240 • 9fps • 105° x 75°; 3,00mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040648	9,8 cm
90275000	7,5 cm
106 9	9,0 cm
	0,7 l

**Mx-O-M7SA-320T080****Thermal Module ECO 320 - T080**

MOBOTIX 7 Thermal Module 320-T080 for M73/S74, CIF 320x240 • 9fps • 56° x 42°; 3,00mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040655	9,8 cm
90275000	7,5 cm
106 9	9,0 cm
	0,7 l

**Mx-O-M7SB-336RP100****S7x PTMount Thermal 336-R100 (B model)**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable

4047438040051	19,6 cm
90021900	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-M7SB-336RP150****S7x PTMount Thermal 336-R150 (B model)**


CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable

4047438040068	19,6 cm
90021900	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-M7SB-336RP280****S7x PTMount Thermal 336-R280 (B model)**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable

4047438040075	19,6 cm
90021900	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-M7SB-336RS100****S7x Thermal Module 336-R100 (B model)**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35°

4047438039918	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336RS150****S7x Thermal module 336-R150 (B model)**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19°

4047438039925	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336RS280****S7x Thermal Module 336-R280 (B model)**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13°

4047438039932	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336TP100****S7x PTMount Thermal 336-T100 (B model)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable

4047438039987	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336TP150****S7x PTMount Thermal 336-T150 (B model)**


CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable

4047438039994	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336TP280****S7x PTMount Thermal 336-T280 (B model)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable

4047438040006	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336TS100****S7x Thermal Module 336-T100 (B model)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35°

4047438039840	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336TS150****S7x Thermal module 336-T150 (B model)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19°

4047438039857	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336TS280****S7x Thermal Module 336-T280 (B model)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13°

4047438039864	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RP050****S7x PTMount Thermal 640-R050 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° Equipped with a 2 meter connection cable

4047438040082	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RP080****S7x PTMount Thermal 640-R080 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° Equipped with a 2 meter connection cable

4047438040099	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RP100****S7x PTMount Thermal 640-R100 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° Equipped with a 2 meter connection cable

4047438040105	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RP150****S7x PTMount Thermal 640-R150 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable

4047438040112	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RS050****S7x Thermal Module 640-R050 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69°

4047438039949	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS080****S7x Thermal Module 640-R080 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56°

4047438039956	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS100****S7x Thermal Module 640-R100 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37°

4047438039963	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS150****S7x Thermal module 640-R150 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26°

4047438039970	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TP050****S7x PTMount Thermal 640-T050 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • Equipped with a 2 meter connection cable

4047438040013	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP080****S7x PTMount Thermal 640-T080 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • Equipped with a 2 meter connection cable

4047438040020	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP100****S7x PTMount Thermal 640-T100 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • Equipped with a 2 meter connection cable

4047438040037	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP150****S7x PTMount Thermal 640-T150 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable

4047438040044	19,6 cm
90021900	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TS050****S7x Thermal Module 640-T050 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69°

4047438039871	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS080****S7x Thermal Module 640-T080 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56°

4047438039888	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS100****S7x Thermal module 640-T100 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37°

4047438039895	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS150****S7x Thermal module 640-T150 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26°

4047438039901	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

M73A Thermal Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M73TA-B336R100-EN54	4047438043410 29,6 cm
	M73A Thermographic Camera TR(B), CIF, R100 (45°) - EN54	90251900 26,8 cm
		2.814 g 18,0 cm
		14,3 l
EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R100, Mx-F-MSA, Mx-O-M7SA-Blind		
	Mx-M73TA-B336R150-EN54	4047438043427 29,6 cm
	M73A Thermographic Camera TR(B), CIF, R150 (25°) - EN54	90251900 26,8 cm
		2.814 g 18,0 cm
		14,3 l
EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R150, Mx-F-MSA, Mx-O-M7SA-Blind		
	Mx-M73TA-B336R280-EN54	4047438043434 29,6 cm
	M73A Thermographic Camera TR(B), CIF, R280 (17°) - EN54	90251900 26,8 cm
		2.814 g 18,0 cm
		14,3 l
EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R280, Mx-F-MSA, Mx-O-M7SA-Blind		

**Mx-M73TA-B640R050-EN54****M73A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R050, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043441	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B640R080-EN54****M73A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R080, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043458	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B640R100-EN54****M73A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R100, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043465	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B640R150-EN54****M73A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R150, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043472	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

Sensor Modules Thermal For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-SMA-TS-R079	4047438030090	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TS-R119	4047438030106	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TS-R237	4047438030113	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TP-R079	4047438030120	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,8 cm
			5,2 l
	Mx-O-SMA-TP-R119	4047438030137	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,8 cm
			5,2 l

**Mx-O-SMA-TP-R237****PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438030144 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-R079-b****PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black**


PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030151 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-R119-b****PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030168 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-R237-b****PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030175 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TS-T079****Thermal Sensor Module For S16/S15, 50 mK, B079 (45°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029049 17,5 cm
90275000 14,0 cm
650 g 13,5 cm
3,3 l

**Mx-O-SMA-TS-T119****Thermal Sensor Module For S16/S15, 50 mK, B119 (25°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029056 17,5 cm
90275000 14,0 cm
650 g 13,5 cm
3,3 l

**Mx-O-SMA-TS-T237****Thermal Sensor Module For S16/S15, 50 mK, B237 (17°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9,8 ft, to be ordered individually)

4047438029063	17,5 cm
90275000	14,0 cm
650 9	13,5 cm
	3,3 l

**Mx-O-SMA-TP-T079****PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029070	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T119****PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029087	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T237****PTMount Thermal For S16/S15, 50 mK, B237 (17°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029094	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T079-b****PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030021	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T119-b****PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030038	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T237-b****PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black

4047438030045	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

S74 Thermal Bundle

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-S74TA-B336R100-EN54 S74A Thermographic Camera TR(B), CIF, R100 (45°) - EN54 EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN	4047438043489 90251900 3.520 g	40,8 cm 31,2 cm 20,2 cm 25,7 l
 Mx-S74TA-B336R150-EN54 S74A Thermographic Camera TR(B), CIF, R150 (25°) - EN54 EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN	4047438043496 90251900 3.520 g	40,8 cm 31,2 cm 20,2 cm 25,7 l
 Mx-S74TA-B336R280-EN54 S74A Thermographic Camera TR(B), CIF, R280 (17°) - EN54 EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP280, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN	4047438043502 90251900 3.520 g	40,8 cm 31,2 cm 20,2 cm 25,7 l

**Mx-S74TA-B640R050-EN54****S74A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP050, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043519 40,8 cm
90251900 31,2 cm
3.520 g 20,2 cm
25,7 l

**Mx-S74TA-B640R080-EN54****S74A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP080, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043526 40,8 cm
90251900 31,2 cm
3.520 g 20,2 cm
25,7 l

**Mx-S74TA-B640R100-EN54****S74A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043533 40,8 cm
90251900 31,2 cm
3.520 g 20,2 cm
25,7 l

**Mx-S74TA-B640R150-EN54****S74A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043540	40,8 cm
90251900	31,2 cm
3.520 9	20,2 cm
	25,7 l

p71A ECO Thermal Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-p71TA-320T040	4047438042499	19,6 cm
	p71 Thermal ECO 320 - T040	90251900	18,0 cm
	p71 Indoor camera with Thermal ECO module 320-T040. CIF 320x240 • 9fps • 105 x 75°; 5,23mr • NETD: 65mK (typ); < 100mK (max) • build in ambient temperature sensor • IR Range 7,8 to 14µm • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C - Built-in speaker and microphone • USB-C • 8GB memory card included	1.175 g	14,8 cm
			5,2 l
	Mx-p71TA-320T080	4047438042505	19,6 cm
	p71 Thermal ECO 320 - T080	90251900	18,0 cm
	p71 Indoor camera with Thermal ECO 320-T080. CIF 320x240 • 9fps • 56 x 42°; 3mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C - Built-in speaker and microphone • USB-C • 8GB memory card included	1.175 g	14,8 cm
			5,2 l

MOBOTIX MOVE Cameras

BeyondHumanVision

MOBOTIX

MOBOTIX MOVE Speed Dome Cameras

MOBOTIX MOVE Speed Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SD1A-230-LL	4047438040495	42,5 cm
	MOBOTIX MOVE SpeedDome SD-230-LL Low Light	85258900	26,2 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-230-LL • Weatherproof motor-driven ONVIF S / G Dome PTZ camera • Up to 30x optical zoom • Image sensor: 2MP SONY Low-Light Sensor (1945 x 1097), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 129 mm, viewing angle HxV: 62 ° - 2 ° x 47 ° -2 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • Anti-Vibration function • autom. Object Tracking • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30 B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE802.3at, max. 23.11 W, AC24V max. 24.20 W / 39.60 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • Warranty: 5 years	5.700 g	35,0 cm
			39,0 l
	Mx-SD1A-540-IR-VA	4047438045049	40,2 cm
	MOBOTIX MOVE SpeedDome SD-540-IR-VA (DNN Analytics)	85258900	25,0 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-540-IR-VA • Weatherproof motor-driven ONVIF S / G / T / M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 40x optical zoom • Image sensor: 5MP SONY STARVIS II IMX675 (2608 x 1964), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.95: 4.3 to 170 mm, viewing angle HxV: 62,6 ° - 1,9 ° x 48,8 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IR LEDs (working distance up to 300m) • IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 5MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 59.05 W / 87.12 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	5.950 g	37,0 cm
			37,2 l
	Mx-SD1A-831-LIR-VA	4047438045056	33,0 cm
	MOBOTIX MOVE SpeedDome SD-831-LIR-VA LIDAR (DNN)	85258900	33,0 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-831-LIR-VA • Weatherproof motor-driven ONVIF S / G / T / M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 31x optical zoom • Precise LiDAR Focusing System • Image sensor: 8MP SONY STARVIS II IMX678 (3856 x 2180) 4K, 1/1.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.35-F4.6: 6.9 to 214.6 mm, viewing angle HxV: 61.8 ° - 2.2 ° x 35.9 ° -1.3 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • IR LEDs (working distance up to 300m) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IR LEDs (working distance up to 200m) • IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 8MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	7.640 g	54,0 cm
			58,8 l

**Mx-SD2A-230-LL-FM-VA****MOBOTIX MOVE SpeedDome SD-230-LL-FM-VA Low Light**

MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-FM-VA • Weatherproof motor-driven ONVIF S / G / T/M Indoor Dome PTZ camera for ceiling flush mount • 10 Integrated Video Analytic Function incl. DNN Face- and Licens10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3 ° - 2.3 ° x 34.9 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE+ IEEE802.3at, max. 17.71 W, AC24V max. 17.10 W / 32.76 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years

4047438045032 31,0 cm
85258900 31,0 cm
3.970 9 38,0 cm
36,5 l

**Mx-SD2A-230-LL-VA****MOBOTIX MOVE SpeedDome SD-230-LL-VA Low Light (DNN)**

MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-VA • Weatherproof motor-driven ONVIF S / G / T/M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3 ° - 2.3 ° x 34.9 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Human, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE + IEEE802.3at, max. 25.5 W, AC24V max. 29.04 W / 53.24 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years

4047438045025 42,5 cm
85258900 26,2 cm
5.150 9 35,0 cm
39,0 l

**Mx-SD1A-330****MOBOTIX MOVE SpeedDome SD-330**

MOBOTIX MOVE SpeedDome Network Camera SD-330 • Weatherproof motor-driven ONVIF S / G Dome PTZ camera • Up to 30x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 129 mm, viewing angle HxV: 62 ° - 2 ° x 47 ° -2 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30 B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3at or DC 12V (2.12 A) or AC 24V; max 25.4 W • Warranty: 5 years

4047438031646 42,5 cm
85258900 26,2 cm
5.700 9 35,0 cm
39,0 l

**Mx-SD1A-340-IR****MOBOTIX MOVE SpeedDome SD-340-IR**

MOBOTIX MOVE SpeedDome Network Camera SD-340-IR • Weatherproof, motorized ONVIF S / G dome PTZ camera with built-in IR LEDs (up to 200m) for day and night use • Up to 40x optical zoom • Image sensor: 3MP (2065 x 1533), 1/2.8" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Motor-controlled Varifocal lens (F1.6: 4.3 to 170 mm, viewing angle HxV: 62 ° -2 ° x 49 ° -1 °) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66 • Ambient temperature -40 to 55°C, Humidity 10 to 90% • Video codecs: H.265, H.264, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 3MP @ 30B / s (H.265, H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: UPoE (Universal PoE) or DC 12V (3.25 A) or AC 24V; max 39 W • Warranty: 5 years

4047438031653 40,2 cm
85258900 25,0 cm
5.600 9 37,0 cm
37,2 l

MOBOTIX MOVE Vandal Dome Cameras

MOBOTIX MOVE Vandal Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VD1A-8-IR-VA	4047438040341	17,3 cm
	MOBOTIX MOVE VandalDome VD-8-IR-VA (DNN Analytics)	85258900	17,3 cm
	MOBOTIX MOVE Vandal Dome Network Camera VD-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max. 11.67 W, DC12V max. 12.14 W, AC24V max. 11.99 W / 20.02 VA • Optic hardened and "selfcleaning" Anti-Reflex coating by MOBOTIX ClearView • MTBF: 95.000h • Warranty: 5 years	1.081 g	16,6 cm 5,0 l
	Mx-VD2A-5-IR-VA	4047438040457	17,5 cm
	MOBOTIX MOVE VandalDome VD2-5-IR-VA (Video Analytics)	85258900	17,5 cm
	MOBOTIX MOVE Vandal Dome Network Camera VD2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 5MP H.264, H.265 30 fps • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	1.210 g	17,0 cm 5,2 l
	Mx-VD3A-2-IR-VA	4047438040433	17,5 cm
	MOBOTIX MOVE VandalDome VD3-2-IR-VA (Video Analytics)	85258900	17,5 cm
	MOBOTIX MOVE Vandal Dome Network Camera VD3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	1.210 g	17,0 cm 5,2 l
	Mx-VD1A-4-IR	4047438031639	17,5 cm
	MOBOTIX MOVE VandalDome VD-4-IR	85258900	17,5 cm
	MOBOTIX MOVE VandalDome Network Camera VD1A-4-IR • Weatherproof ONVIF S/G dome camera with integrated IR LEDs (up to 30 m) for day and night operation • Image sensor: 4MP (2688 x 1512), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.7: 3 to 9 mm, viewing angle HxV: 103°-35° x 53°-23°) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 65°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 5 years	1.050 g	17,0 cm 5,2 l

**Mx-VD1A-4-IR-D****MOBOTIX MOVE VandalDome VD-4-IR-D**

MOBOTIX MOVE VandalDome Network Camera VD-4-IR-D • Weatherproof ONVIF S/G dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Image sensor: 4MP (2688 x 1512), 1/3" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35 °-15 °, V: 20 °-9 °) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, H.265); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 5 years

4047438034371 17,5 cm
85258900 17,5 cm
1.010 9 17,0 cm
5,2 l

**Mx-VD2A-2-IR****MOBOTIX MOVE VandalDome VD2-2-IR**

MOBOTIX MOVE VandalDome Network Camera VD2-2-IR • Image sensor: 2MP (1920x1080), 1/3" Progressive CMOS • Weatherproof ONVIF S/G/T vandal dome camera with built-in IR LEDs (up to 40 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 91 °-34 °) • IP66 • IK10 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 320 dB) • Max. Frame rate: 2MP @ 60B / s (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af • Warranty: 5 years

4047438038959 17,5 cm
85258900 17,5 cm
1.010 9 17,0 cm
5,2 l

MOBOTIX MOVE Bullet Cameras


MOBOTIX MOVE Bullet Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-BC2A-2-IR	4047438038966	29,6 cm
	MOBOTIX MOVE Bullet Camera BC2-2-IR	85258900	20,0 cm
	MOBOTIX MOVE Bullet Network Camera BC2-2-IR • Image Resolution: 2MP (1920x1080), 1/2.7" Progressive CMOS • Weatherproof ONVIF S/G/T bullet camera with built-in IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 96.67° - 34.13° - V: 52.21° - 19.24°) • IP66 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 95% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af • MTBF: 95.000h • Warranty: 5 years	580 g	17,5 cm
			10,4 l
	Mx-VB1A-2-IR-ALPR	4047438044295	28,5 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-ALPR	85258900	19,6 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-ALPR (License Plate Recognition) • Integrated professional international Automatic License Plate Recognition for stopped and slow moving vehicles up to 18m distance • incl. MMC (Make, Model, Color Detection) • ALPR Activation License Key pre-installed • Max. Image Resolution: 2 MP / 1080p (Full-HD), 1/2.8" Progressive CMOS (SONY) • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 60m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Light-Sensitivity: Color: 0.02lx, B/W: 0.001lx, IR: 0lx • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°), Auto Iris with automatic adaptation to changing light situations • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 2 MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Bi-directional Audio (Line In/Out) • Alarm I/O • 64 GB SD-Karte pre-installed • Power supply: PoE IEEE802.3af, class 0, max 12.95 watt, DC12V, 15.59 watt, AC24V, max 13.31 watt, max 25.08 VA • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on), Rel. humidity 10 to 90% non-condensing • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	1.740 g	17,8 cm
			9,9 l
	Mx-VB1A-2-IR-D-ALPR	4047438044318	28,5 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-D-ALPR	85258900	19,6 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-D-ALPR (License Plate Recognition) • Integrated professional international Automatic License Plate Recognition for slow and fast moving vehicles up to 35m distance • incl. MMC (Make, Model, Color Detection) • ALPR Activation License Key pre-installed • Max. Image Resolution: 2 MP / 1080p (Full-HD), 1/2.8" Progressive CMOS (SONY) • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 60m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Light-Sensitivity: Color: 0.02lx, B/W: 0.001lx, IR: 0lx • Remote Zoom / Focus • Motor-controlled Zoom lens (F1.6-F2.4: 9 to 22 mm, viewing angle H: 36.1°-15.4°, V: 19.8° - 8.8°), Auto Iris with automatic adaptation to changing light situations • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 2 MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Bi-directional Audio (Line In/Out) • Alarm I/O • 64 GB SD-Karte pre-installed • Power supply: PoE IEEE802.3af, class 0, max 12.95 watt, DC12V, 15.59 watt, AC24V, max 13.31 watt, max 25.08 VA • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on), Rel. humidity 10 to 90% non-condensing • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	1.740 g	17,8 cm
			9,9 l

**Mx-VB1A-8-IR-VA****MOBOTIX MOVE VandalBullet VB-8-IR-VA (DNN Analytics)**


MOBOTIX MOVE Vandal Bullet Network Camera VB-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max 12.95 W, DC12V, 15.59 W, AC24V, max 13.31 W, max 25.08 VA • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040358 28,5 cm
85258900 19,6 cm
1.793 g 17,4 cm
9,7 l

**Mx-VB2A-5-IR-VA****MOBOTIX MOVE VandalBullet VB2-5-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Bullet Network Camera VB2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C (heater on), humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040464 29,6 cm
85258900 20,0 cm
1.710 g 17,5 cm
10,4 l

**Mx-VB3A-2-IR-VA****MOBOTIX MOVE VandalBullet VB3-2-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Bullet Network Camera VB3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP67, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040440 29,6 cm
85258900 20,0 cm
1.460 g 17,5 cm
10,4 l

**Mx-VB1A-4-IR****MOBOTIX MOVE VandalBullet VB1A-4-IR**

MOBOTIX MOVE VandalBullet Network Camera VB1A-4-IR • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 30m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 2.7 to 12 mm, viewing angle H: 99° - 31°, V: 53° - 18°) with "One Push" autofocus and P-Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 5 years

4047438034395 29,6 cm
85258900 20,0 cm
1.460 g 17,5 cm
10,4 l

**Mx-VB1A-4-IR-D****MOBOTIX MOVE VandalBullet VB1A-4-IR-D**

MOBOTIX MOVE Bullet Network Camera VB1A-4-IR-D • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 40m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35 °-15 °, V: 20 °-9 °) with Auto Iris with automatic adaptation to changing light situations • IP66, IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 5 years

4047438034401	29,6 cm
85258900	20,0 cm
1.460 9	17,5 cm
	10,4 l

**Mx-BC1A-4-IR-D****MOBOTIX MOVE BulletCamera BC-4-IR-D**

MOBOTIX MOVE Bullet Network Camera BC-4-IR-D • Image sensor: 4MP (2688x1512), 1/3" Progressive CMOS • Weatherproof ONVIF S / G bullet camera with built-in IR LEDs (up to 40m) for use with Day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6: 9 to 22 mm, viewing angle H: 35 °- 15 °, V: 20 °- 9 °) with Auto Iris with automatic adaptation to changing light situations • IP66 • Ambient temperature -30 to 60°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • WDR (120 dB) • Max. Frame rate: 4MP @ 30B / s (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af or DC 12V (2.12 A) or AC 24V; max 13.68 W • Warranty: 5 years

4047438034388	29,6 cm
85258900	20,0 cm
1.030 9	17,5 cm
	10,4 l

MOBOTIX MOVE Hemispheric Vandal Dome

MOBOTIX MOVE Hemispheric Vandal Dome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VH1A-12-IR-VA	4047438038317	17,3 cm
	MOBOTIX MOVE 12MP Vandal Hemispheric	85258900	17,3 cm
	MOBOTIX MOVE Vandal Hemispheric Network Camera Mx-VH1A-12-IR-VA • Image sensor: 12MP (4072 x 3046), 1/1.7" Progressive CMOS • Indoor • ONVIF S/G/T/M • Hemispheric camera with built-in IR LED illumination (up to 10 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • focal length 1.65 mm • IK10 • Ambient temperature -10 to 55°C (14° to 131°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Max. Frame rate: 12MP@20 fps (Backend dewarping) 8.9MP@27 fps (Edge dewarping) • Power supply: PoE IEEE 802.3af • Warranty: 5 years • MTBF: 95,000h	640 g	10,7 cm
			3,2 l

MOBOTIX MOVE Fixed Domes



Article No. / Name / Description

EAN / HS / weight dimen.

Mx-MD1A-5-IR

4047438042475 16,5 cm

MOBOTIX MOVE Indoor MicroDome Mx-MD-5-IR

85258900 16,5 cm

MOBOTIX MOVE Indoor MicroDome Network Camera Mx-MD-5-IR • Max. Image Resolution: 5M (2720x1976), 1/2.7" Progressive CMOS • ONVIF S/G/T dome camera with integrated IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F2.0: 2.8 mm), viewing angle H: 108.3°, V: - 76.5 °) • 3-axis lens adjustment • Indoor, IK8 • Ambient temperature -30 to 55°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max. 5.09 W • MTBF: 95.000h • Warranty: 5 years

450 g 13,5 cm
3,7 l

MOBOTIX MOVE Multi Sensor Cameras

MOBOTIX MOVE Multi Sensor Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VM1A-20-IR-VA	4047438045063	32,3 cm
	MOBOTIX MOVE Vandal Multisensor VM-20-IR-VA	85258900	30,5 cm
	MOBOTIX MOVE Vandal Multisensor Network Camera Mx-VM1A-20-IR-VA • Image sensor: 4x5MP (2608x1964), 1/2.8" Progressive CMOS IMX 675 SONY STARVIS II • Up to 3x optical zoom • ONVIF S/G/T/M • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Auto Object Tracking • Multisensor camera with built-in IR LED illumination (up to 30 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • FIPS140-2 level 3-compliant using TPM chipset • NEMA-4x compliant • M.2 SATA 3 SSD support • 2D & 3D Motion Compensated Noise Reduction (MCTF) • Motor-controlled Zoom lens (F1.6 x 4: 2,8mm to 8 mm, viewing angle HxV: 111,5° - 53,7° x 79° - 40,2°) with autofocus and P-Iris with automatic adaptation to changing light situations • IK10 / IP66 • Ambient temperature -40 to 60°C (22° to 122°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 9 Video-Streams simultaneously - 4x2 per sensor module + 1 quadview stream) • Wide Dynamic Range (130 dB) • Max. Frame rate: 5MP@30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE+ + IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA • Opt. Integrated Microphone & Loudspeaker (bi-directional communication) • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 95000h • Warranty: 5 years	3.740 g	15,6 cm
			15,4 l

Optics

BeyondHumanVision

MOBOTIX

Sensor Modules 4K for MOBOTIX 7

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-O-M7SA-12DN016 12MP Hemispheric Day & Night Sensor Module 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, white	4047438040631 90021900 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-M7SA-12DN016-b 12MP Hemispheric Day & Night Sensor Module black 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, black	4047438041379 90021900 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-M7SA-8D500 8° 4K Day Sensor mod. TELE M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438047265 90021900 210 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-M7SA-8DN040-b 120° 4K IR Cut Day & Night Sensor Module WIDE black M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041386 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-M7SA-8DN050-b 95° 4K IR Cut Day & Night Sensor Module WIDE black M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041393 90021900 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-O-M7SA-8DN080-b****60° 4K IR Cut Day & Night Sensor Module WIDE black**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041409	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN100-b****45° 4K IR Cut Day & Night Sensor Module STANDARD black**

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041416	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN150-b****30° 4K IR Cut Day & Night Sensor Module TELE black**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041423	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN280-b****15° 4K IR Cut Day & Night Sensor Module TELE black**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041430	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8L040****120° 4K LPF Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438040310	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8L500****8° 4K LPF Sensor mod. TELE**

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438044080	9,8 cm
90021900	7,5 cm
210 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N040-b****120° 4K Night Sensor Module WIDE black**

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041447	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N050-b****95° 4K Night Sensor Module WIDE black**

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041454	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N080-b****60° 4K Night Sensor Module WIDE black**

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041461	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N100-b****45° 4K Night Sensor Module STANDARD black**

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041478	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N150-b****30° 4K Night Sensor Module TELE black**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041485	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N280-b****15° 4K Night Sensor Module TELE black**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041492	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N500****8° 4K Night Sensor mod. TELE**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438047272	9,8 cm
90021900	7,5 cm
210 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN040****120° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034968	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN050****95° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034814	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN080****60° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035941	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN100****45° 4K IR Cut Day & Night Sensor Module STANDARD**

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034821	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN150****30° 4K IR Cut Day & Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035958	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN280****15° 4K IR Cut Day & Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034838	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8D040****120° 4K Day Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034944	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8D050****95° 4K Day Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034845	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8D080****60° 4K Day Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035989	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8D100****45° 4K Day Sensor Module STANDARD**

M73/S74 sensor module with premium standard-angle lens for day, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034852	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8D150****30° 4K Day Sensor Module TELE**

M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035996	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8D280****15° 4K Day Sensor Module TELE**

M73/S74 sensor module with premium tele lens for day, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034869	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N040****120° 4K Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034951	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N050****95° 4K Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034876	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N080****60° 4K Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035965	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N100****45° 4K Night Sensor Module STANDARD**

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034883	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N150****30° 4K Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035972	9,8 cm
90021900	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N280****15° 4K Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034890

9,8 cm

90021900

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8L150****30° 4K LPF Sensor Module TELE**

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037730

9,8 cm

90021900

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8L280****15° 4K LPF Sensor Module TELE**

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037723

9,8 cm

90021900

7,5 cm

140 g

9,0 cm

0,7 l

Sensor Modules 4MP Low Light for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-M7SA-4D045-f1.0	4047438044387	9,8 cm
	109° f/1,0 4MP Day Sensor module	90021900	7,5 cm
	M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 109° x 55°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4D050-f1.0	4047438044370	9,8 cm
	94° f/1,0 4MP Day Sensor module	90021900	7,5 cm
	M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 94°x49,5°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4D080-f1.0	4047438044363	9,8 cm
	57° f/1,0 4MP Day Sensor module	90021900	7,5 cm
	M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 57°x32°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4D115-f1.0	4047438044356	9,8 cm
	37° f/1,0 4MP Day Sensor module	90021900	7,5 cm
	M73/S74 sensor module with premium normal lens for day use, aperture: f/1.0, max. image angle (HxV): 37,5°x22°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4DN040	4047438037167	9,8 cm
	120° 4MP IR Cut Day & Night Ultra LowLight Sensor Module	90021900	7,5 cm
	M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120° x 60°, max. resolution: 4MP (2688x1512), IP66, white	140 g	9,0 cm
			0,7 l

**Mx-O-M7SA-4DN050****95° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP (2688x1512), IP66, white

4047438037174	9,8 cm
90021900	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN080****60° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP (2688x1512), IP66, white

4047438037181	9,8 cm
90021900	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN100****45° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP (2688x1512), IP66, white

4047438037198	9,8 cm
90021900	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN150****30° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP (2688x1512), IP66, white

4047438037204	9,8 cm
90021900	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN280****15° 4MP IR Cut Day & Night Low Light Sensor Module WIDE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP (2688x1512), IP66, white

4047438037211	9,8 cm
90021900	7,5 cm
140 9	9,0 cm
	0,7 l

Sensor Modules 6MP For S16A/S16B And

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-O-SMA-S-6D016 Sensor Module 6MP, B016 (Day), White Sensor module S16/M16 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029100 9,8 cm 90021900 7,5 cm 144 g 9,0 cm	0,7 l
 Mx-O-SMA-S-6D036 Sensor Module 6MP, B036 (Day), White Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029117 9,8 cm 90021900 7,5 cm 144 g 9,0 cm	0,7 l
 Mx-O-SMA-S-6D041 Sensor Module 6MP, B041 (Day), White Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029124 9,8 cm 90021900 7,5 cm 144 g 9,0 cm	0,7 l
 Mx-O-SMA-S-6D061 Sensor Module 6MP, B061 (Day), White Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029131 9,8 cm 90021900 7,5 cm 144 g 9,0 cm	0,7 l
 Mx-O-SMA-S-6D079 Sensor Module 6MP, B079 (Day), White Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029148 9,8 cm 90021900 7,5 cm 144 g 9,0 cm	0,7 l

**Mx-O-SMA-S-6D119****Sensor Module 6MP, B119 (Day), White**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

4047438029155	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D237****Sensor Module 6MP, B237 (Day), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

4047438029162	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D500****Sensor Module 6MP, B500 (Day), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

4047438029179	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6DCSV****Sensor Module 6MP, CSVario 4,5-10 mm (Day), White**

Sensor module S16/M16 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030052	10,5 cm
90021900	6,8 cm
190 G	10,5 cm
	0,7 l

**Mx-O-SMA-S-6DCS****Sensor Module 6MP, CS-Mount (Day), White**

Sensor module S16/M16 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030076	10,5 cm
90021900	6,8 cm
146 G	10,5 cm
	0,7 l

**Mx-O-SMA-S-6N016****Sensor Module 6MP, B016 (Night), White**

Sensor module S16/M16 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029186	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N036****Sensor Module 6MP, B036 (Night), White**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029193	9,8 cm
90021900	7,5 cm
170 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N041****Sensor Module 6MP, B041 (Night), White**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029209	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N061****Sensor Module 6MP, B061 (Night), White**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029216	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N079****Sensor Module 6MP, B079 (Night), White**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029223	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N119****Sensor Module 6MP, B119 (Night), White**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029230	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N237****Sensor Module 6MP, B237 (Night), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029247	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N500****Sensor Module 6MP, B500 (Night), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029254	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6NCSV****Sensor Module 6MP, CSVario 4,5-10 mm (Night), White**

Sensor module S16/M16 with CSVario Lens B045-100-CS (focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030069	10,5 cm
90021900	6,8 cm
190 G	10,5 cm
	0,7 l

**Mx-O-SMA-S-6NCS****Sensor Module 6MP, CS-Mount (Night), White**

Sensor module S16/M16 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030083	10,5 cm
90021900	6,8 cm
146 G	10,5 cm
	0,7 l

**Mx-O-SMA-S-6L016****Sensor Module 6MP, B016 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029261	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L036****Sensor Module 6MP, B036 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029278	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L041****Sensor Module 6MP, B041 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029285	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L061****Sensor Module 6MP, B061 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029292	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L079****Sensor Module 6MP, B079 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029308	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L119****Sensor Module 6MP, B119 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029315	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L237****Sensor Module 6MP, B237 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029322	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L500****Sensor Module 6MP, B500 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029339	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D016-b****Sensor Module 6MP, B016 (Day), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029346	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D036-b****Sensor Module 6MP, B036 (Day), Black**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029353	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D041-b****Sensor Module 6MP, B041 (Day), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029360	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D061-b****Sensor Module 6MP, B061 (Day), Black**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029377	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D079-b****Sensor Module 6MP, B079 (Day), Black**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029384	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D119-b****Sensor Module 6MP, B119 (Day), Black**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029391	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D237-b****Sensor Module 6MP, B237 (Day), Black**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029407	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D500-b****Sensor Module 6MP, B500 (Day), Black**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029414	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N016-b****Sensor Module 6MP, B016 (Night), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029421	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N036-b****Sensor Module 6MP, B036 (Night), Black**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029438	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N041-b****Sensor Module 6MP, B041 (Night), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029445	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N061-b****Sensor Module 6MP, B061 (Night), Black**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029452	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N079-b****Sensor Module 6MP, B079 (Night), Black**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029469	9,8 cm
90021900	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N119-b****Sensor Module 6MP, B119 (Night), Black**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029476	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N237-b****Sensor Module 6MP, B237 (Night), Black**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029483	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N500-b****Sensor Module 6MP, B500 (Night), Black**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029490	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L016-b****Sensor Module 6MP, B016 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029506	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L036-b****Sensor Module 6MP, B036 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029513	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L041-b****Sensor Module 6MP, B041 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029520	9,8 cm
90021900	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L061-b****Sensor Module 6MP, B061 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029537	9,8 cm
90021900	7,5 cm
144 9	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L079-b****Sensor Module 6MP, B079 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029544	9,8 cm
90021900	7,5 cm
144 9	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L119-b****Sensor Module 6MP, B119 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029551	9,8 cm
90021900	7,5 cm
144 9	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L237-b****Sensor Module 6MP, B237 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black


4047438029568	9,8 cm
90021900	7,5 cm
144 9	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L500-b****Sensor Module 6MP, B500 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029575	9,8 cm
90021900	7,5 cm
144 9	9,0 cm
	0,7 l

BlockFlexMounts 12MP for S7x



Article No. / Name / Description

EAN / HS / weight dimen.

MX-O-M7SA-B-12DN016

4047438047715 10,0 cm

BlockFlexMount 12MP IR Cut Day & Night Sensor Module,



90021900 7,5 cm


Suitable for: S74 • 12MP Sensor module with premium hemispheric lens and IR cut filter for day and night use, max. resolution: 4K UHD (2880x2880) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

120 g 9,0 cm

0,7 l


BlockFlexMounts 4K for S7x

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-O-M7SA-B-8DN040	4047438047722	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	90021900	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN050	4047438047739	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	90021900	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN080	4047438047746	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	90021900	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN100	4047438047753	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	90021900	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN150	4047438047760	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	90021900	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l

**MX-O-M7SA-B-8DN280****BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.**

Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8.5°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)



4047438047777	10,0 cm
90021900	7,5 cm
125 9	9,0 cm
	0,7 l

**MX-O-M7SA-B-8DN500****BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.**

Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 8°x4.5°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438047784	10,0 cm
90021900	7,5 cm
180 9	9,0 cm
	0,7 l

BlockFlexMounts 6MP For S16A/S16B

Article No. / Name / Description	EAN / HS / weight	dimen.
	4047438029797	9,8 cm
BlockFlexMount 6MP, Incl. Hemispheric B016 (Day) Suitable for: S16 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900	7,5 cm
	155 g	9,0 cm
		0,7 l
	4047438029803	9,8 cm
BlockFlexMount 6MP, Incl. B036 (Day) Suitable for: S16 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900	7,5 cm
	155 g	9,0 cm
		0,7 l
	4047438029810	10,0 cm
BlockFlexMount 6MP, Incl. B041 (Day) Suitable for: S16 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900	7,5 cm
	134 g	9,0 cm
		0,7 l
	4047438029827	10,0 cm
BlockFlexMount 6MP, Incl. B061 (Day) Suitable for: S16 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900	7,5 cm
	136 g	9,0 cm
		0,7 l
	4047438029834	10,0 cm
BlockFlexMount 6MP, Incl. B079 (Day) Suitable for: S16 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	90021900	7,5 cm
	134 g	9,0 cm
		0,7 l

**Mx-O-SMA-B-6D119****BlockFlexMount 6MP, Incl. B119 (Day)**

Suitable for: S16 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029841	10,0 cm
90021900	7,5 cm
130 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6D237****BlockFlexMount 6MP, Incl. B237 (Day)**


Suitable for: S16 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029858	10,0 cm
90021900	7,5 cm
134 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6D500****BlockFlexMount 6MP, incl. B500 (Day)**


Suitable for: S16 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029865	10,0 cm
90021900	7,5 cm
150 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6DCS****BlockFlexMount 6MP, For CS Mount Lens (Day)**

Suitable for: S16 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029766	9,8 cm
90021900	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N016****BlockFlexMount 6MP, Incl. Hemispheric B016 (Night)**

Suitable for: S16 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029872	9,8 cm
90021900	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N036****BlockFlexMount 6MP, Incl. B036 (Night)**

Suitable for: S16 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029889	9,8 cm
90021900	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N041****BlockFlexMount 6MP, Incl. B041 (Night)**


Suitable for: S16 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029896	9,8 cm
90021900	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N061****BlockFlexMount 6MP, Incl. B061 (Night)**

Suitable for: S16 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029902	9,8 cm
90021900	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N079****BlockFlexMount 6MP, Incl. B079 (Night)**

Suitable for: S16 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029919	10,0 cm
90021900	7,5 cm
134 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N119****BlockFlexMount 6MP, Incl. B119 (Night)**

Suitable for: S16 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029926	10,0 cm
90021900	7,5 cm
130 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N237****BlockFlexMount 6MP, Incl. B237 (Night)**


Suitable for: S16 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029933	10,0 cm
90021900	7,5 cm
134 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N500****BlockFlexMount 6MP, Incl. B500 (Night)**

Suitable for: S16 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029940	9,8 cm
90021900	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6NCS****BlockFlexMount 6MP, For CS Mount Lens (Night)**


Suitable for: S16 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029773	10,0 cm
90021900	7,5 cm
102 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L036****BlockFlexMount 6MP, Incl. B036 (Night LPF)**

Suitable for: S16 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029957	10,0 cm
90021900	7,5 cm
136 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L041****BlockFlexMount 6MP, Incl. B041 (Night LPF)**


Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029964	10,0 cm
90021900	7,5 cm
132 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L061****BlockFlexMount 6MP, Incl. B061 (Night LPF)**

Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029971	10,0 cm
90021900	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L079****BlockFlexMount 6MP, Incl. B079 (Night LPF)**

Suitable for: S16 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029988	10,0 cm
90021900	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L119****BlockFlexMount 6MP, Incl. B119 (Night LPF)**

Suitable for: S16 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029995	10,0 cm
90021900	7,5 cm
130 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L237****BlockFlexMount 6MP, Incl. B237 (Night LPF)**


Suitable for: S16 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030007	10,0 cm
90021900	7,5 cm
134 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L500****BlockFlexMount 6MP, Incl. B500 (Night LPF)**

Suitable for: S16 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030014	10,0 cm
90021900	7,5 cm
150 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6LCS****BlockFlexMount 6MP, For CS Mount Lens (Night LPF)**

Suitable for: S16 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029780	10,0 cm
90021900	7,5 cm
104 g	9,0 cm
	0,7 l

Sensor Modules 6MP For D16A/D16B

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-SDA-F-6D6N Sensor Bridge FIX For D16, 2x 6MP (Day & Night) Day & Night sensor bridge for D16 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)	4047438030182 19,6 cm 90021900 18,0 cm 346 g 14,8 cm 5,2 l
	Mx-O-SDA-P-6D6D Sensor Bridge PAN/180° For D16, 2x 6MP (Day) Panorama/180° sensor bridge for D16 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030199 19,6 cm 90021900 18,0 cm 346 g 14,8 cm 5,2 l
	Mx-O-SDA-P-6N6N Sensor Bridge PAN-N/180° for D16, 2x 6MP (Night) Panorama/180° sensor bridge for D16 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030205 19,6 cm 90021900 18,0 cm 344 g 14,8 cm 5,2 l
	Mx-O-SDA-S-6D036 Sensor Module D16 6MP, Incl. B036 (Day) Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029582 9,0 cm 90021900 7,5 cm 68 g 5,0 cm 0,3 l
	Mx-O-SDA-S-6D041 Sensor Module D16 6MP, Incl. B041 (Day) Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029599 9,0 cm 90021900 7,5 cm 66 g 5,0 cm 0,3 l

**Mx-O-SDA-S-6D061****Sensor Module D16 6MP, Incl. B061 (Day)**

Sensor module D16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029605	9,0 cm
90021900	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6D079****Sensor Module D16 6MP, Incl. B079 (Day)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029612	9,0 cm
90021900	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6D119****Sensor Module D16 6MP, Incl. B119 (Day)**

Sensor module D16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029629	9,0 cm
90021900	7,5 cm
64 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N036****Sensor Module D16 6MP, Incl. B036 (Night)**

Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029643	9,0 cm
90021900	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N041****Sensor Module D16 6MP, Incl. B041 (Night)**

Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029650	9,0 cm
90021900	7,5 cm
66 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N061****Sensor Module D16 6MP, Incl. B061 (Night)**

Sensor module D16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029667	9,0 cm
90021900	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N079****Sensor Module D16 6MP, Incl. B079 (Night)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029674	9,0 cm
90021900	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N119****Sensor Module D16 6MP, Incl. B119 (Night)**

Sensor module D16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029681	9,0 cm
90021900	7,5 cm
64 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6L036****Sensor Module D16 6MP, Incl. B036 (Night LPF)**

Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029704	7,5 cm
90021900	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L041****Sensor Module D16 6MP, Incl. B041 (Night LPF)**

Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029711	7,5 cm
90021900	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L061****Sensor Module D16 6MP, Incl. B061 (Night LPF)**

Sensor module D16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029728	7,5 cm
90021900	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L079****Sensor Module D16 6MP, Incl. B079 (Night LPF)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029735	7,5 cm
90021900	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L119****Sensor Module D16 6MP, Incl. B119 (Night LPF)**

Sensor module D16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029742	7,5 cm
90021900	4,9 cm
64 9	9,0 cm
	0,3 l

Camera Accessories

BeyondHumanVision

MOBOTIX

Camera Mounts (M7)

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-CM-M73	4047438039819	19,6 cm
	Ceiling Mount for M73 models	90079100	18,0 cm
	Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	631 g	14,8 cm
			5,2 l
	Mx-M-IC-DQ	4047438040761	39,5 cm
	In-Ceiling Set for MOBOTIX 7 Single Lens Models	90079100	29,6 cm
	In-Ceiling Set for MOBOTIX 7 Single Lens Models	665 g	9,0 cm
			10,5 l
	Mx-M-OW-DQ	4047438040662	29,6 cm
	On-Wall Set for MOBOTIX 7 Single Lens Models	90079100	19,6 cm
	On-Wall Set for MOBOTIX 7 Single Lens Models	410 g	9,0 cm
			5,2 l
	Mx-M-OW-DQ-10DEG	4047438043373	29,6 cm
	On-Wall Set 10° for MOBOTIX 7 Single Lens Models	90079100	19,6 cm
	On-Wall Set 10° inclined for MOBOTIX 7 Single Lens Models	500 g	9,0 cm
			5,2 l
	Mx-M-OW-M73	4047438039802	19,6 cm
	On-Wall Mount for M73 models	90079100	18,0 cm
	Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	502 g	14,8 cm
			5,2 l

**Mx-M-PM-M73****Pole mount for M73 models**

Suitable for: M73 Cameras • 2 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438035064	20,0 cm
90079100	18,2 cm
1.247 g	9,0 cm
	3,3 l

**Mx-M-WM-DQ****Wall Mount for MOBOTIX 7 Single Lens Models**

Wall Mount for MOBOTIX 7 Single Lens Models

4047438040778	29,6 cm
90079100	19,6 cm
835 g	18,0 cm
	10,4 l

**Mx-M-WPM-DQ****Wall & Pole/Corner Mount Set For D7x/Q7x**

Suitable for: D7x and Q7x • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (Mx-M-WM-DQ) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438041348	41,0 cm
90079100	31,0 cm
3.380 g	20,0 cm
	25,4 l

Mounts For S74

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-DLMA	4047438036887	19,6 cm
	DualMount S7x, white	90079100	15,0 cm
	For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white	450 g	9,0 cm
			2,6 l
	Mx-M-DLMA-b	4047438041553	19,6 cm
	DualMount S7x, black	90079100	15,0 cm
	For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	450 g	9,0 cm
			2,6 l
	Mx-M-PTMA	4047438036894	19,6 cm
	PTMount S7x, white	90079100	18,0 cm
	Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x and S16B • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white • Angled sensor cables are recommended (e.g. Mx-A-S7A-CBL01-AN)	620 g	14,8 cm
			5,2 l
	Mx-M-PTMA-b	4047438036900	19,6 cm
	PTMount S7x, black	90079100	18,0 cm
	Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	620 g	14,8 cm
			5,2 l
	Mx-M-PTMA-OW	4047438039826	9,8 cm
	On-Wall Kit for PTMount S7x, white	90079100	7,5 cm
	On-Wall Kit for PTMount S7x, white incl. Mounting parts	75 g	9,0 cm
			0,7 l

**Mx-M-PTMA-OW-b****On-Wall Kit for PTMount S7x, black**

On-Wall Kit for PTMount S7x, black incl. Mounting parts

4047438039833	9,8 cm
90079100	7,5 cm
75 g	9,0 cm
	0,7 l

**Mx-M-SLMA****SingleMount S7x, white**

For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x and S16B (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white

4047438036870	14,8 cm
90079100	9,8 cm
240 g	9,0 cm
	1,3 l

**Mx-M-SLMA-b****SingleMount S7x, black**

For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black

4047438037921	14,8 cm
90079100	9,8 cm
240 g	9,0 cm
	1,3 l

S7x Sensor Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-S7A-AUCBL05-AN	4047438040501	14,0 cm
	S74 audio cable 5m	85444210	3,5 cm
	Audio cable to connect a MOBOTIX 7 audio module Mx-F-AUDA to the IO board Mx-F-S7A-INT01 the S74, length 5m	155 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL01	4047438035583	14,0 cm
	Sensor Cable 1m for S7x straight-straight	85444210	3,5 cm
	Sensor cable straight-straight, lenght 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body	70 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL01-AN	4047438035897	14,0 cm
	Sensor cable 1m for S7x straight-angled	85444210	3,5 cm
	Sensor cable straight-angled, lenght 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts	70 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL02	4047438035590	14,0 cm
	Sensor Cable 2m for S7x straight-straight	85444210	3,5 cm
	Sensor cable straight-straight, lenght 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body	90 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL02-AN	4047438035903	14,0 cm
	Sensor cable 2m for S7x straight-angled	85444210	3,5 cm
	Sensor cable straight-angled, lenght 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts	90 g	15,0 cm
			0,7 l

**Mx-A-S7A-CBL03****Sensor Cable 3m for S7x straight-straight**

Sensor cable straight-straight, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body

4047438035606	14,0 cm
85444210	3,5 cm
110 g	15,0 cm
	0,7 l

**Mx-A-S7A-CBL03-AN****Sensor cable 3m for S7x straight-angled**


Sensor cable straight-angled, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts

4047438035910	14,0 cm
85444210	3,5 cm
110 g	15,0 cm
	0,7 l

**Mx-A-S7A-LCE-OF30****30m optical fibre cable for Long Cable Extender (A)**


MOBOTIX 30m optical fibre cable for Long Cable Extender Variante A

4047438040334	31,5 cm
85444210	31,5 cm
1.228 g	13,5 cm
	13,4 l

**Mx-CBL-MUC-AB-1****S74 Cable MiniUSB-C to USB-A 1m**


MiniUSB-C straight > USB-A straight • Length 1 m /3,3 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037129	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AB-5****S74 Cable MiniUSB-C to USB-A 5m**

MiniUSB-C straight > USB-A straight • Length 5 m /16,4 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037136	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-AN-AB-1****S7x Cable MiniUSB-C to USB-A angled-straight 1m**


MiniUSB-C angled > USB-A straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040556	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AN-AB-5****S7x Cable MiniUSB-C to USB-A angled-straight 5m**


MiniUSB-C angled > USB-A straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040563	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-AN-MU-1****S7x Cable MiniUSB-C to MiniUSB angled-straight 1m**

MiniUSB-C angled > MiniUSB straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040532	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AN-MU-5****S7x Cable MiniUSB-C to MiniUSB angled-straight 5m**

MiniUSB-C angled > MiniUSB straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040549	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-MU-1****S74 Cable MiniUSB-C to MiniUSB 1m**

MiniUSB-C straight > MiniUSB straight • Length 1 m /3,3 ft • For S74 • To connect RS232-IO-Box (MX-OPT-RS1-EXT)


4047438037143	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-MU-5****S74 Cable MiniUSB-C to MiniUSB 5m**

MiniUSB-C straight > MiniUSB straight • Length 5 m /16,4 ft • For S74 • To connect RS232-IO-Box (MX-OPT-RS1-EXT)

4047438037150	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

HD Premium Lenses

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-B036	4047438026536	9,0 cm
	Ultra Wide Lens B036, Focal Length: 3.6 mm	90021900	7,5 cm
	Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B041	4047438026543	9,0 cm
	Super Wide Lens B041, Focal Length: 4.1 mm	90021900	7,5 cm
	Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B061	4047438026550	9,0 cm
	Wide Lens B061, Focal Length: 6.1 mm	90021900	7,5 cm
	Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 60° x 45° (up to 5MP resolution) and 70.5° x 46° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B079	4047438026567	9,0 cm
	Standard Lens B079, Focal Length: 7.9 mm	90021900	7,5 cm
	Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)	34 g	5,0 cm
			0,3 l
	MX-B119	4047438026574	9,0 cm
	Tele Lens B119, Focal Length: 11.9 mm	90021900	7,5 cm
	Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 31° x 23° (up to 5MP resolution) and 36° x 24.5° (6MP resolution)	30 g	5,0 cm
			0,3 l

**MX-B237****lens for D1x/M2x/D2x (HS code 90021900)**

Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8
 • Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)

4047438026581	9,0 cm
90021900	7,5 cm
34 g	5,0 cm
	0,3 l

**MX-B500****Super Tele Lens B500, Focal Length: 50 mm**

Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5 •
 Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)

4047438026598	9,0 cm
90021900	7,5 cm
52 g	5,0 cm
	0,3 l

**MX-B045-100-CS****CSVario Lens For Cameras With CS-Mount**

CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm •
 Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical): 39°-89° x 29°-65°

4047438026604	9,0 cm
90021900	7,5 cm
66 g	5,0 cm
	0,3 l

**MX-SM-OPT-POL****Polarization Filter For Sensor Modules**

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

4047438019781	9,0 cm
90079100	7,5 cm
28 g	5,0 cm
	0,3 l

Domes & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-M24M-OPT-LCSK Replacement Lens Cover M2x, Standard Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)	4047438012980 90079100 32 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-M24M-OPT-LCSG Replacement Lens Cover M2x, With Glass Pane Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438012997 90079100 38 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-M24M-OPT-LCGL Replacement Lens Cover M2x, Extended Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438013000 90079100 44 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-OPT-DK-L11 Replacement Cover Hemispheric Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	4047438016469 90079100 24 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-D15-OPT-DCT Replacement Cover D1x/v2x, Standard Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)	4047438018227 90079100 54 g	19,6 cm 14,8 cm 9,0 cm 2,6 l

**MX-D15-OPT-DCS****Replacement Cover D1x/v2x, Tinted**

Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments

4047438018210	19,6 cm
90079100	14,8 cm
54 g	9,0 cm
	2,6 l

**MX-D15-DCT-XL****Replacement Cover D1x FIX/PAN, XL**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)

4047438027519	19,6 cm
90079100	18,0 cm
281 g	14,8 cm
	5,2 l

**MX-D15-DCS-XL****Replacement Cover D1x PAN/FIX, XL Tinted**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)

4047438027526	19,6 cm
90079100	18,0 cm
60 g	14,8 cm
	5,2 l

**MX-D24M-OPT-DCT****Replacement Cover D2x, Standard**

Suitable for: D2x • With sealing ring

4047438011419	19,6 cm
90079100	15,0 cm
150 g	9,0 cm
	2,6 l

**MX-D24M-OPT-DCS****Replacement Cover D2x, Tinted**

Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments

4047438011402	19,6 cm
90079100	15,0 cm
150 g	9,0 cm
	2,6 l

**MX-D15-Vandal-ESMA****Vandalism Set For D1x, Matt**

Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models

4047438018173	39,5 cm
90079100	29,6 cm
1.012 g	9,0 cm
	10,5 l

**MX-D15-DCT-V****Replacement Cover D1x/v2x, Vandalism**

Reinforced replacement cover (polycarbonate, 3 mm) for D1x and v25 Vandalism Sets • Suitable for: D1x and v2x • Not for D1x PAN/180° and FIX/Day&Night models (XL cover needed)

4047438027533	19,6 cm
90079100	18,0 cm
278 g	14,8 cm
	5,2 l

**MX-D24M-Vandal-ESMA****Vandalism Set For D2x, Matt**

Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)

4047438011143	30,5 cm
90079100	24,0 cm
672 g	12,0 cm
	8,8 l

**MX-D25-DCT-V****Replacement D2x, Vandalism**

Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring

4047438027700	19,6 cm
90079100	18,0 cm
60 g	14,8 cm
	5,2 l

**MX-Q24M-Vandal-ESMA****Vandalism Set For Q2x, Matt**

Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. safety screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available

4047438011273	29,6 cm
90079100	19,6 cm
590 g	9,0 cm
	5,2 l

**MX-MT-v25-V****Vandalism Set For v2x**

Suitable for: v2x without On-Wall Mounting Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027601	29,6 cm
90079100	19,6 cm
502 g	9,0 cm
	5,2 l

**MX-MT-v25-V-XL****Vandalism Set For v2x With On-Wall Mounting Set**

Suitable for: v2x with On-Wall Mounting Set with Audio • XL stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only with mounted On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027625	29,6 cm
90079100	19,6 cm
680 g	9,0 cm
	5,2 l

Mounts For S16A/S16B

Article No. / Name / Description	EAN / HS / weight	dimen.
 MX-FLEX-OPT-DM-PW DualMount S1x, White For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438017626 90079100 414 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 MX-FLEX-OPT-SM-PW SurroundMount S1x, White For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all 6MP Sensor modules (B016 to B500 and CS Mount) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438016407 90079100 392 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 MX-FLEX-OPT-DM-BL DualMount S1x, Black For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all screwable sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021869 90079100 414 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 MX-FLEX-OPT-SM-BL SurroundMount S1x, Black For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all screwable sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021845 90079100 392 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 MX-HALO-EXT-PW HaloMount S7x/S1x, White Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	4047438017664 90079100 175 g	13,5 cm 12,0 cm 4,5 cm 0,7 l

**MX-HALO-EXT-BL****HaloMount S7x/S1x, Black**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017671	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-EXT-CM****HaloMount S7x/S1x, Matt Chrome**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017633	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-EXT-CO****HaloMount S7x/S1x, Chrome**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017640	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-EXT-NG****HaloMount S7x/S1x, Brushed Nickel**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017657	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-SP-EXT-PW****SpeakerMount S1x, White**

Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • Impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included

4047438017688	13,5 cm
85182200	12,0 cm
273 g	4,5 cm
	0,7 l

**MX-HALO-SP-EXT-CM****SpeakerMount S1x, Matt Chrome**

Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • Impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included

4047438017695	13,5 cm
85182200	12,0 cm
273 g	4,5 cm
	0,7 l

**MX-S14-OPT-MK-CW****Extension Set Sensor Module, 40 mm and 15° wedges**


Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x and S7x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut

4047438016384	10,0 cm
90079100	7,5 cm
96 g	9,0 cm
	0,7 l

**MX-S14-OPT-MK-EX****Extension Sensor Module, 40 mm**

1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions

4047438016391	9,8 cm
90079100	7,5 cm
62 g	9,0 cm
	0,7 l


**MX-FLEX-OPT-AM-BL****AudioMount S26/S1xM, Self-Adhesive**

Suitable for: S26, S15M, S14M • Easy, quick and concealed mounting with adhesive foil (e.g. behind a stainless steel plate) • Speaker and microphone with camera connection cable included • Use of the camera as a door station by connecting an external doorbell (e.g., connected via MX-232-IO-Box)

4047438019873	24,0 cm
85299065	13,6 cm
386 g	5,3 cm
	1,7 l


Camera Mounts

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-OWA-AU	4047438030328	19,6 cm
	On-Wall Mounting Set With Audio For v26, White	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	510 g	14,8 cm
			5,2 l
	Mx-M-OWA-AU-b	4047438030335	19,6 cm
	On-Wall Mounting Set With Audio For v26, Black	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	510 g	14,8 cm
			5,2 l
	Mx-MT-OW2-AUD	4047438027632	19,6 cm
	On-Wall Mounting Set With Audio For v25, White	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	500 g	14,8 cm
			5,2 l
	MX-MT-OW2-AUD-b	4047438027670	19,6 cm
	On-Wall Mounting Set With Audio For v25, Black	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	500 g	14,8 cm
			5,2 l
	MX-MT-TUBE	4047438027557	29,6 cm
	MxTubeMount Ceiling Suspension System	90079100	19,6 cm
	For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color: white	870 g	9,0 cm
			5,2 l

**MX-MT-TUBE100****MxTube, 1 m**


Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium •
Outer diameter: 30 mm, wall thickness: 2 mm

4047438027687 106,0 cm
90079100 4,0 cm
700 g 4,0 cm
1,7 l

**MX-MT-TUBE200****MxTube, 2 m**

Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium •
Outer diameter: 30 mm, wall thickness: 2 mm

4047438027564 212,5 cm
90079100 4,0 cm
1.390 g 4,0 cm
3,4 l

**MX-OPT-UP1****Cavity Wall Installation Set i2x**

Cavity Wall Installation Set for the i2x • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations

4047438022118 14,8 cm
90079100 9,8 cm
158 g 9,0 cm
1,3 l

**MX-OPT-AP2****On-Wall Mounting Set for i2x**

Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white

4047438025898 14,8 cm
90079100 9,8 cm
136 g 9,0 cm
1,3 l

**MX-MT-OW-1****On-Wall Mounting Set for c2x/p2x**

Suitable for: c2x und p2x • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g., two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White

4047438027083 19,6 cm
90079100 18,0 cm
514 g 14,8 cm
5,2 l

**MX-MT-CM-1****Corner Mounting Set For c2x**

Suitable for: c2x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g., c2x with 103° lens B036) to capture an entire room • Color: White

4047438027076 29,6 cm
90079100 19,6 cm
448 g 9,0 cm
5,2 l

**MX-OPT-AP****On-Wall Mounting Set For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm

4047438011358	29,6 cm
90079100	19,6 cm
612 g	9,0 cm
	5,2 l

**MX-OPT-AP-10DEG****On-Wall Mounting Set For Q2x/D2x/ExtIO, 10°**

Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm

4047438010283	29,6 cm
90079100	19,6 cm
552 g	9,0 cm
	5,2 l

**MX-D15-OPT-WHMH-Set****Wall & Pole/Corner Mount Set For D1x**

Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438018159	41,0 cm
90079100	31,0 cm
6.280 g	39,0 cm
	49,6 l

**MX-OPT-WHMH-Set****Wall & Pole/Corner Mount Set For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438011396	41,0 cm
90079100	31,0 cm
3.380 g	20,0 cm
	25,4 l

**MX-WH-Dome****Wall Mount For D1x**


Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts

4047438002233	39,5 cm
90079100	29,6 cm
2.020 g	18,0 cm
	21,0 l

**MX-OPT-WH****Wall Mount For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts

4047438011372	29,6 cm
90079100	19,6 cm
886 g	18,0 cm
	10,4 l

**MX-MH-Dome-ESWS****Pole/Corner Mount For MX-WH-Dome**

Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002240	34,0 cm
90079100	18,5 cm
3.000 g	11,5 cm
	7,2 l

**MX-MH-SecureFlex-ESWS****Pole Mount For M1x/M2x**

Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002226	20,0 cm
90079100	15,2 cm
1.230 g	8,0 cm
	2,4 l

**MX-OPT-MH****Pole/Corner Mount For MX-OPT-WH**

Suitable for: D7x, Q7x, Q2x, D2x, ExtIO • Mount for fastening the wall mount Mx-M-WM-DQ and MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WHMH-Set) for the Q2x/D2x und ExtIO • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm • Wall mounts (Mx-M-WM-DQ or MX-OPT-WH) are not included in the scope of delivery and must be ordered separately

4047438011389	21,0 cm
90079100	20,0 cm
2.050 g	17,0 cm
	7,1 l

**MX-OPT-IC-ESMA****In-Ceiling Set For Q2x/D2x/ExtIO, Matt**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011433	29,6 cm
90079100	19,6 cm
724 g	9,0 cm
	5,2 l

**MX-OPT-IC-ESPO****In-Ceiling Set For Q2x/D2x/ExtIO, Polished**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011426	29,6 cm
90079100	19,6 cm
724 g	9,0 cm
	5,2 l

**MX-OPT-IC****In-Ceiling Set For Q2x/D2x/ExtIO, White**

Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011365	29,6 cm
90079100	19,6 cm
412 g	9,0 cm
	5,2 l



MX-DH-M24-SecureFlex
Ceiling Mount For M16/M26

Suitable for: M16, M26, M15, M25, M24 • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw, washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically • Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)

4047438015653	15,0 cm
90079100	9,5 cm
160 g	9,0 cm
	1,3 l



MX-OPT-TW-Demo-1
Demo Table/Wall Mount For Q2x/D2x

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055	14,8 cm
90079100	9,8 cm
170 g	9,0 cm
	1,3 l

MOBOTIX Cables

Article No. / Name / Description		EAN / HS / weight	dimen.
	MX-OPT-CBL-LAN-1-SP	4047438041591	23,5 cm
	Ethernet Patch Cable for MOBOTIX 7, 1 m	85444210	15,0 cm
	Ethernet Patch Cable for MOBOTIX systems • Lenght 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	40 g	2,0 cm
			0,7 l
	MX-OPT-CBL-LAN-10-SP	4047438041560	27,0 cm
	Ethernet Patch Cable for MOBOTIX 7, 10 m	85444210	17,0 cm
	Ethernet Patch Cable for MOBOTIX systems • Lenght 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	465 g	4,0 cm
			1,8 l
	MX-OPT-CBL-LAN-2-SP	4047438041584	23,5 cm
	Ethernet Patch Cable for MOBOTIX 7, 2 m	85444210	15,0 cm
	Ethernet Patch Cable for MOBOTIX systems • Lenght 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	65 g	2,0 cm
			0,7 l
	MX-OPT-CBL-LAN-5-SP	4047438041577	23,5 cm
	Ethernet Patch Cable for MOBOTIX 7, 5 m	85444210	15,0 cm
	Ethernet Patch Cable for MOBOTIX systems • Lenght 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	240 g	4,0 cm
			1,4 l
	MX-FLEX-OPT-CBL-015	4047438019941	9,8 cm
	Sensor Module Cable For M15/M16, 0.15 m	85444210	7,5 cm
	Lenght: 0.15 m/0,5 ft, to connect one sensor module (inside camera housing), angled plugs, only for M15/M16	16 g	9,0 cm
			0,7 l

**MX-FLEX-OPT-CBL-05****Sensor Cable For S1x, 0.5 m**

Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018890	10,0 cm
85444210	7,5 cm
66 g	9,0 cm
	0,7 l

**MX-FLEX-OPT-CBL-1****Sensor Cable For S1x, 1 m**

Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018883	10,0 cm
85444210	7,5 cm
80 g	9,0 cm
	0,7 l

**MX-FLEX-OPT-CBL-2****Sensor Cable For S1x, 2 m**

Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018876	10,0 cm
85444210	7,5 cm
116 g	9,0 cm
	0,7 l

**MX-FLEX-OPT-CBL-3****Sensor Cable For S1x (6MP/Thermal), 3 m**

Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S15/S16 camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules

4047438024303	10,0 cm
85444210	7,5 cm
144 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-AB-05****USB Device Cable For M/Q/T2x, 0.5 m**

MiniUSB angled > USB-A straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device

4047438016728	9,8 cm
85444210	7,5 cm
52 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-AB-2****USB Device Cable For M/Q/T2x, 2 m**

MiniUSB angled > USB-A straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB-Gerät

4047438016711	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-AB-5****USB Device Cable For M/Q/T2x, 5 m**

MiniUSB angled > USB-A straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device

4047438016704

9,8 cm

85444210

7,5 cm

194 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-EN-PG-05****ExtIO Cable For M/Q/T2x, 0,5 m**

MiniUSB angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO

4047438020947

9,8 cm

85444210

7,5 cm

52 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-EN-PG-2****ExtIO Cable For M/Q/T2x, 2 m**

MiniUSB angled > MiniUSB+ angled • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO

4047438020930

9,8 cm

85444210

7,5 cm

102 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-EN-PG-5****ExtIO Cable for M/Q/T2x, 5 m**

MiniUSB angled > MiniUSB+ angled • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO

4047438020923

9,8 cm

85444210

7,5 cm

194 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-AB-05****USB Device Cable For D25/D26, 0.5 m**

MiniUSB+ angled > USB-A straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect ext. USB device

4047438020916

9,8 cm

85444210

7,5 cm

52 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-AB-2****USB Device Cable For D25/D26, 2 m**

MiniUSB+ angled > USB-A straight • Length 2 m/6,6 ft • For D25/D26 • to connect ext. USB device

4047438020909

9,8 cm

85444210

7,5 cm

102 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-AB-5****USB Device Cable For D25/D26, 5 m**

MiniUSB+ angled > USB-A straight • Length 5 m/16,4 ft • For D25/D26 • To connect ext. USB device

4047438020893

9,8 cm

85444210

7,5 cm

194 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-EN-PG-05****ExtIO Cable For D25/D26, 0.5 m**

MiniUSB+ angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-ExtIO

4047438020886

9,8 cm

85444210

7,5 cm

52 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-EN-PG-2****ExtIO Cable For D25/D26, 2 m**

MiniUSB+ angled > MiniUSB+ angled • Length 2 m/6,6 ft • For D25/D26 • To connect MX-ExtIO

4047438020879

9,8 cm

85444210

7,5 cm

102 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-EN-PG-5****ExtIO Cable For D25/D26, 5 m**

MiniUSB+ angled > MiniUSB+ angled • Length 5 m/16,4 ft • For D25/D26 • To connect MX-ExtIO

4047438020862

9,8 cm

85444210

7,5 cm

194 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-STR-05****232-IO-Box Cable For D25/D26, 0.5 m**

MiniUSB+ angled > MiniUSB straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020855

9,8 cm

85444210

7,5 cm

52 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-STR-2****232-IO-Box Cable For D25/D26, 2 m**

MiniUSB+ angled > MiniUSB straight • Length 2 m/6,6 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020848

9,8 cm

85444210

7,5 cm

102 g

9,0 cm

0,7 l

**MX-CBL-MU-EN-PG-STR-5****232-IO-Box Cable For D25/D26, 5 m**

MiniUSB+ angled > MiniUSB straight • Length 5 m/16,4 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020831	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-STR-05****232-IO-Box Cable For M/Q/T2x, 0.5 m**

MiniUSB angled > MiniUSB straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016667	10,0 cm
85444210	7,5 cm
48 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-STR-2****232-IO-Box Cable For M/Q/T2x, 2 m**

MiniUSB angled > MiniUSB straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016650	10,0 cm
85444210	7,5 cm
94 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-STR-5****232-IO-Box Cable For M/Q/T2x, 5 m**

MiniUSB angled > MiniUSB straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016643	10,0 cm
85444210	7,5 cm
188 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-05****232-IO-Box Cable For D/S/V1x, 0.5 m**

MiniUSB straight > MiniUSB straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box

4047438016605	10,0 cm
85444210	7,5 cm
50 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-2****232-IO-Box Cable For D/S/V1x, 2 m**

MiniUSB straight > MiniUSB straight • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box

4047438016599	10,0 cm
85444210	7,5 cm
94 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-5****232-IO-Box Cable For D/S/V1x, 5 m**

MiniUSB straight > MiniUSB straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box

4047438016445	10,0 cm
85444210	7,5 cm
184 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-AB-05****USB Device Cable For D/S/V1x, 0.5 m**

MiniUSB straight > USB-A straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device

4047438016698	10,0 cm
85444210	7,5 cm
56 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-AB-2****USB Device Cable For D/S/V1x, 2 m**

MiniUSB straight > USB-A straight • Length 2 m/6,6 ft • D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device

4047438016681	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-AB-5****USB Device Cable For D/S/V1x, 5 m**

MiniUSB straight > USB-A straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device

4047438016674	10,0 cm
85444210	7,5 cm
196 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-EN-PG-05****ExtIO Cable For D/S/V1x, 0.5 m**

MiniUSB straight > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020978	9,8 cm
85444210	7,5 cm
52 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-EN-PG-2****ExtIO Cable For D/S/V1x, 2 m**

MiniUSB straight > MiniUSB+ angled • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020961	9,8 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-EN-PG-5****ExtIO Cable For D/S/V1x, 5 m**

MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020954	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-OPT-CBL-LAN-1****Ethernet Patch Cable, 1 m**

Ethernet Patch Cable for MOBOTIX systems • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012300	23,5 cm
85444210	15,0 cm
36 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-10****Ethernet Patch Cable, 10 m**

Ethernet Patch Cable for MOBOTIX systems • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012331	27,0 cm
85444210	17,0 cm
462 g	4,0 cm
	1,8 l

**MX-OPT-CBL-LAN-2****Ethernet Patch Cable, 2 m**

Ethernet Patch Cable for MOBOTIX systems • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012317	23,5 cm
85444210	15,0 cm
62 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-5****Ethernet Patch Cable, 5 m**

Ethernet Patch Cable for MOBOTIX systems • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012324	23,5 cm
85444210	15,0 cm
237 g	4,0 cm
	1,4 l

**MX-FLEX-IO-CBL-015****IO Connection Cable For M15/M16, 0.15 m**

Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15/M16 (inside camera housing)



4047438019958	13,5 cm
85444210	8,0 cm
10 g	2,0 cm
	0,2 l

**MX-CBL-NPA-BAT-2****NPA Battery Cable, 2 m**

NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft

4047438013949	10,0 cm
85444210	7,5 cm
68 9	9,0 cm
	0,7 l

Other Camera Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-SEC-SCREWS-SET Security Screw Set With Allen Bit For M73 Triple set of anti-theft screws (1 pcs M6x65, 4 pcs M6x16, 2 pcs M6x13) to securely attach the M73. Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)	4047438045209 90079100 68 g	9,0 cm 7,5 cm 4,6 cm 0,3 l
	Mx-O-M7SA-Blind Blind Module M73 For M73 • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.	4047438035415 90079100 50 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-OPT-Ring-L10-L12-BL Sealing Ring For Hemispheric Sensor Modules, Black Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black	4047438021241 90079100 16 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
	MX-OPT-Ring-L10-L12-PW Sealing Ring For Hemispheric Sensor Modules, White Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white	4047438021234 90079100 16 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
	MX-OPT-SEC-SCREWS-SET Security Screw Set With Allen Bit For M1x/M2x Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)	4047438021265 90079100 120 g	7,5 cm 4,9 cm 9,0 cm 0,3 l

**MX-SM-Blind-PW****Blind Module M1x**

For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.

4047438019965	9,0 cm
90079100	7,5 cm
46 9	5,0 cm
	0,3 l

MOBOTIX MOVE Accessories

MOBOTIX MOVE Accessories

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-A-SD-DBC-EC	4047438041508	26,0 cm
	Dome-Bubble EverClear (Clear) for MOBOTIX MOVE SD	90079100	25,5 cm
	Dome Bubble EverClear (Clear) for MOBOTIX MOVE PTZ SD-230/330	580 g	17,0 cm
			11,3 l
	Mx-A-SD-DBT-EC	4047438041515	26,0 cm
	Dome Bubble EverClear (Tinted) for MOBOTIX MOVE SD	90079100	25,5 cm
	Dome Bubble EverClear (Tinted) for MOBOTIX MOVE PTZ SD-230/330	580 g	17,0 cm
			11,3 l
	Mx-A-SD-DCS	4047438031776	26,0 cm
	Tinted Dome For MOBOTIX MOVE SD-330	90079100	25,5 cm
	Tinted replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330 • For particularly bright environments	300 g	17,0 cm
			11,3 l
	Mx-A-SD-DCT	4047438031783	26,0 cm
	Dome (Standard) For MOBOTIX MOVE SD-330	90079100	25,5 cm
	Standard replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330	300 g	17,0 cm
			11,3 l
	Mx-A-VB-FGK-EC	4047438041546	12,0 cm
	Frontglass Kit EverClear for MOBOTIX MOVE VandalBullet -	90079100	11,0 cm
	Frontglass Kit EverClear for MOBOTIX MOVE VB VandalBullet VB (model > Nov. 21)	33 g	3,0 cm
			0,4 l

**Mx-A-VD-DBC-EC****Dome Bubble EverClear (Clear) For MOBOTIX MOVE**

Dome Bubble EverClear (Clear) For MOBOTIX MOVE VD VandalDomes

4047438041522	17,0 cm
90079100	17,0 cm
240 g	13,0 cm
	3,8 l

**Mx-A-VD-DBT-EC****Dome -Bubble EverClear (Tinted) For MOBOTIX MOVE**

Dome Bubble EverClear (Tinted) For MOBOTIX MOVE VD VandalDomes

4047438041539	17,0 cm
90079100	17,0 cm
240 g	13,0 cm
	3,8 l

**Mx-A-VD-DCS****Tinted Dome For MOBOTIX MOVE VandalDome**

Tinted replacement dome for particularly bright environments • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031714	16,1 cm
90079100	16,1 cm
210 g	11,5 cm
	3,0 l

**Mx-A-VD-DCT****Dome (Standard) For MOBOTIX MOVE VandalDome**

VD Standard replacement dome • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031721	16,1 cm
90079100	16,1 cm
250 g	11,5 cm
	3,0 l

**Mx-A-VM-DBC****Dome-Bubble (Clear) for MOBOTIX MOVE Vandal**


VM Standard replacement dome • Suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047685	26,6 cm
90079100	25,0 cm
530 g	8,5 cm
	5,7 l

**Mx-A-VM-DBT****Dome-Bubble (Tinted) For MOBOTIX MOVE Vandal**


Tinted replacement dome for particularly bright environments • Suitable for MOBOTIX MOVE Vandal Multiisensor camera Mx-VM1A-20-IR-VA

4047438047692	26,6 cm
90079100	25,0 cm
530 g	8,5 cm
	5,7 l

**Mx-M-BC-P****Pole Mount For MOBOTIX MOVE BulletCamera**


BC Pole Mount suitable for all MOBOTIX MOVE BulletCameras (except Mx-BC1A-2-IR)

4047438031677	17,3 cm
90079100	17,3 cm
1.000 g	16,7 cm
	5,0 l

**Mx-M-BC-W****Wall Mount For MOBOTIX MOVE BulletCamera**


BC Wall Mount suitable for MOBOTIX MOVE BulletCamera (except Mx-BC1A-2-IR)

4047438031660	17,3 cm
90079100	17,3 cm
840 g	10,7 cm
	3,2 l

**Mx-M-NVR16-RM****19" Rack Mounting Brackets for MOVE NVR 16CH**


2x metal mounting brackets for installing MOBOTIX MOVE NVR 16CH in a 19" rack

4047438037075	14,5 cm
85299097	11,0 cm
447 g	6,0 cm
	1,0 l

**Mx-M-NVR8-RM****19" Rack Mounting Brackets for MOVE NVR 8CH**

2x metal mounting brackets for installing MOBOTIX MOVE NVR 8CH in a 19" rack

4047438037068	14,5 cm
85299097	11,0 cm
544 g	6,0 cm
	1,0 l

**Mx-M-SD-C****Corner Mount For MOBOTIX MOVE SD-330/SD-340-IR**

SD Corner Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031769	21,0 cm
90079100	12,5 cm
2.170 g	25,0 cm
	6,6 l

**Mx-M-SD-GN****MOBOTIX MOVE SD Parapet Mount**

MOBOTIX MOVE SD Parapet Mount(Gooseneck) with integrated junction Box for MOBOTIX MOVE SpeedDome Mx-SD1A-330 and Mx-SD1A-340-IR

4047438038997	90,0 cm
90079100	57,0 cm
14.800 g	20,0 cm
	102,6 l

**Mx-M-SD-P****Pole Mount For MOBOTIX MOVE SD-330/SD-340-IR**

SD Pole Mount suitable for MOBOTIX MOVE SpeedDome SD-330 und SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031752	31,0 cm
90079100	15,5 cm
1.580 g	26,0 cm
	12,5 l

**Mx-M-SD-PM****MOBOTIX MOVE SD Pendant Mount Kit**

MOBOTIX MOVE SD Pendant Mount Kit 25 cm incl. Base-Mount, 25 cm pendant pipe, installation material and safety wires 50cm & 1m. Max. extendable pendant mount lenght 1m by usage of additional pendant mount extension Mx-M-SD-PMEXT

4047438039000	64,0 cm
90079100	22,0 cm
2.295 g	22,0 cm
	31,0 l

**Mx-M-SD-PMEXT****MOBOTIX MOVE SD PM Extension**

MOBOTIX MOVE SD Pendant Mount 25cm extension for Mx-M-SD-PM

4047438039017	14,4 cm
90079100	14,5 cm
800 g	28,0 cm
	5,8 l

**Mx-M-SD-W****Wall Mount For MOBOTIX MOVE SD-330/SD-340-IR**

SD Wall Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)

4047438031745	21,6 cm
90079100	12,7 cm
840 g	14,8 cm
	4,1 l

**Mx-M-SD-WM****Wall Mount For MOBOTIX MOVE SpeedDome**


MOBOTIX MOVE SD Wall Mount supporting optional Junction Box Mx-M-SD-WMJB, suitable for MOBOTIX MOVE SpeedDome Mx-SD1A-330 and Mx-SD1A-340-IR

4047438038973	33,0 cm
90079100	15,0 cm
1.300 g	23,0 cm
	11,4 l

**Mx-M-SD-WMJB****MOBOTIX MOVE SD Junction Box**

MOBOTIX MOVE SD Wall Mount Junction Box for use with Wall Mount Mx-M-SD-WM

4047438038980	29,0 cm
90079100	32,0 cm
4.800 g	19,0 cm
	17,6 l

**Mx-M-VD-C****Corner Mount For MOBOTIX MOVE VandalDome**

VD Corner Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031738	21,0 cm
90079100	12,5 cm
2.170 g	25,0 cm
	6,6 l

**Mx-M-VD-IC****In-Ceiling Set For MOBOTIX MOVE VandalDome**

VD In-Ceiling Set suitable for all MOBOTIX MOVE VandalDome cameras

4047438031684	23,4 cm
90079100	23,4 cm
800 g	12,8 cm
	7,0 l

**Mx-M-VD-P****Pole Mount For MOBOTIX MOVE VandalDome**

VD-Pole Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031707	31,0 cm
90079100	15,5 cm
1.580 g	26,0 cm
	12,5 l

**Mx-M-VD-W****Wall Mount For MOBOTIX MOVE VandalDome**

VD Wall Mount Set (2-piece) suitable for all MOBOTIX MOVE VandalDome cameras

4047438031691	31,0 cm
90079100	22,0 cm
1.400 g	18,0 cm
	12,3 l

**Mx-M-VM-AP****Adapter Mounting Plate for MOBOTIX MOVE Vandal**

Adaptor Mounting Plate suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047678	36,4 cm
90079100	34,5 cm
1.950 g	12,8 cm
	16,1 l

**Mx-M-VM-IC****In-Ceiling Set For MOBOTIX MOVE Vandal Multisensor**

In-Ceiling Set suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047661	31,6 cm
90079100	34,5 cm
965 g	12,8 cm
	14,0 l

MOVE Other Accessories

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-ETP1A-2601-POW	4047438042581 19,4 cm
	Plug-type Power-supply for Mx-A-ETP1A-2601-SET	85365019 14,2 cm
	Refurbished Plug-type power supply for Mx-A-ETP1A-2601-SET • Output: 57V DC +/-3% / 1.2 A • Input: 90-260V AC (47-63Hz) • 68,4 Watt • Operating Temperature: 0-40 °C	490 g 4,0 cm
		1,1 l
	Mx-A-ETP1A-2601-SET	4047438041317 20,7 cm
	Media converter set Ethernet(PoE+) – Twisted-Pair	85299065 12,5 cm
	Mx-ETP1A-2601-SET Complete set consisting of two two-wire transmitting and receiving units for realising an Ethernet transmission path via Twisted Pair cable. • Transmission of Ethernet and PoE+ power supply via two-wire line according to IEEE1901. • Simple connection of 10/100 Mbps Ethernet end devices • Max. 95 Mbps transmission bandwidth, range up to 600m for data / 300m for PoE depending on the quality of the Twisted-Pair link • 128 bit AES network data encryption • Power supply 2-wire transmitter (Tx) and receiver (Rx) as well as end device via PoE+ network switch or external power supply 56VDC / 1.2A (not included!) • Connected end devices are supplied via PoE switch IEEE802.3af(PoE), IEEE802.3at (PoE+), UPoE up to 60W (requires ext. power supply unit). • Status LEDs (data, power supply, data link, PoE) • Integrated Overvoltage protection (IEC 61000-4-5 4kV(1.2 / 50us), 2kA(8 / 20us)) • Power Supply: TX: T-Linx or DC12V~57V, RX: PoE Switch or DC48V~57V • Operational temperature: -20 to 60 °C • Dimensions: 80.4(L) x 61.6(W) x 24(H)mm • Weight: RX/TX: 102g • Warranty: 2 years	368 g 7,0 cm
		1,8 l
	Mx-A-KBD1A-PTZ-JOG	4047438040754 42,5 cm
	MOBOTIX USB Keyboard with PTZ Joystick & Jog-Shuttle	85299065 27,0 cm
	USB control panel for operating MOBOTIX MxMC 2.6 and higher and MOBOTIX HUB incl. Control of software PTZ and motorized PTZ cameras and pan/tilt devices • Integrated 3-axis joystick • Integrated jog shuttle • 38 control keys with backlight predefined for MxMC functions or freely definable for MOBOTIX HUB • Integrated alarm buzzer • Suitable for operation as HID device on MOBOTIX VMS with Windows and MAC based operating systems via USB2.0 • Suitable for right- and left-handed users • Power supply: USB, max. 350 mA • Operating temperature: 0° - 45 °C (32 °F- 113 °F)	1.900 g 17,5 cm
		20,1 l


System Components

BeyondHumanVision

MOBOTIX

Functional Modules for MOBOTIX 7 Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-F-AUDA M73/S74 Audio Module equipped with microphone / Weatherproof audio module (IP66, -30 to 65 °C, IK07) with integrated microphone and speaker for connection to the MOBOTIX M73 camera, no camera removal required • In connection with the audio cable Mx-A-S7A-AUCBL05-AN and the IO plug-in board Mx-F-S7A-INT01, the audio module can also be operated at the S74 (compatible with S74 module mounts)	4047438034937 85299065 150 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-IRA-S M73/S74 IR Light Module for Standard Lens (45° - 60°) Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 45°-60° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses: up to 70 m	4047438034913 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-IRA-T M73/S74 IR Light Module for Tele Lens (15° - 30°) Infrared illuminator module for MOBOTIX M73/S74 cameras night sensor modules with 15°-30° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses up to 100 m	4047438034920 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-IRA-W M73/S74 IR Light Module for Wide Lens (95°) Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 95° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with W-IR illuminator: up to 40 m	4047438034906 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-MSA MOBOTIX 7 MultiSense Outdoor Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (max ±0.4°C / 0.72°F) and microphone • Camera connection and supply via MOBOTIX 7 sensor cable (up to 3m): power consumption approx. 100 mW • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Protection class IP66 • IK05 • Housing color: white	4047438035545 85299065 100 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-F-S7A-INT01****S74 IO Slide in Board**


S74 IO slide in board with 1x input / output, 1x line in / out and 1x mic in / speaker out functionality • Connection option for audio module Mx-F-AUDA with audio cable Mx-A-S7A-AUCBL05-AN

4047438035576	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-S7A-LCE****MOBOTIX 7 Long Cable Extender Kit (Type A)**


MOBOTIX 7 long cable extender kit - up to 30m extension between S74A and MOBOTIX 7 sensor module via LWL and power cable

4047438037877	19,6 cm
85299065	14,8 cm
448 9	9,0 cm
	2,6 l

**Mx-F-S7A-LSA****S74 network slide in board with LSA terminal**


S74 network slide in board with LSA terminal

4047438037051	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-S7A-RJ45****S74 Network slide in board with RJ45 socket**

S74 Network slide in board with RJ45 socket

4047438035569	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-S7A-RJ45-VDC****S74 RJ45 Network slide in board with 12/24 VDC Power**

S74 Network slide in board with RJ45 socket and 12/24V DC Power Supply

4047438039680	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-WLA-S****M73/S74 White Light for Standard lens 45-60°**

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 45-60° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses with illuminator: up to 60 m

4047438042529	9,8 cm
85395200	7,5 cm
145 9	9,0 cm
	0,7 l

**Mx-F-WLA-T****M73/S74 White Light for tele lens 15-30°**

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 15-30° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses with illuminator: up to 80 m



4047438042536	9,8 cm
85395200	7,5 cm
145 9	9,0 cm
	0,7 l


**Mx-F-WLA-W****M73/S74 White Light for Wide Lens 95°**

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 95° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with illuminator: up to 40 m

4047438042512	9,8 cm
85395200	7,5 cm
145 9	9,0 cm
	0,7 l


Interface Boxes

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-A-GPSA MX-GPS-Box Weatherproof GPS time base for MOBOTIX systems • GPS and Glonass support • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP66/IK08, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	4047438035507 85299065 120 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 MX-OPT-BPA1-EXT MX-BPA-BOX Power supply for several MxBus modules of one MxBus line • 2x2 connection terminals for MxBus • 2 connection terminals for external power supply from 12 to 48 V DC (2 terminals) • Max. output rating: 9 W • IP66/IK08, -30 bis 60 °C / -22 to 140 °F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438025881 85299065 120 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 MX-OPT-NPA1-EXT MX-NPA-Box Weatherproof PoE Injector (IEEE 802.3af) and network connector • Needs external power supply units and batteries from 12 to 57 V DC • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Important: only use with original MOBOTIX patch cables • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x	4047438015424 85043180 140 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
 MX-Overvoltage-Protection-Box-LSA Network Connector with Surge Protection, LSA Version Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438018470 85299065 146 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
 MX-Overvoltage-Protection-Box-RJ45 Network Connector with Surge Protection, RJ45 Version Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x	4047438018463 85299065 150 g	10,0 cm 7,5 cm 9,0 cm 0,7 l

**MX-OPT-Input1-EXT****MX-Input-Box**


Weatherproof connection of external sensors • Connection to camera using MxBus • 6 self-powered inputs for connection up to 6 external sensors • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x

4047438021227	10,0 cm
85299065	7,5 cm
148 g	9,0 cm
	0,7 l

**MX-OPT-Output1-EXT****MX-Output-Box**


Weatherproof connection of external devices and power relays • Connection to the camera via MxBus • Six self-powered outputs (12 V, each 10 mA) • Two isolated outputs (can be switched to "self-powered" using a jumper: 12 V, max. 50 mA) • Protection class IP66/IK07, -30 to 60 °C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x

4047438021944	10,5 cm
85299065	6,8 cm
120 g	10,5 cm
	0,7 l

**MX-OPT-RS1-EXT****MX-232-IO-Box**

Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

4047438015417	10,5 cm
85299065	6,8 cm
120 g	10,5 cm
	0,7 l

**MX-PROX-BOX****MX-Proximity-Box**

Weatherproof proximity sensor for MOBOTIX systems • Accurate detection of approaching objects based on radar microwave technology • Covered area (horizontal x vertical): 80° x 34° • Detection range: up to 8m/26 ft. (person), up to 20m/66 ft. (vehicle) • Camera connection and supply via MxBus • Protection class IP66/IK07, -20 to 60°C / -4 to 140°F • Box can also be mounted behind walls (e.g. wooden, plastic, glass or dry walls) • It is not possible to install the MX-Proximity-Box behind some materials since they absorb or reflect the radar waves (e.g., metal or metal-coated surfaces). Other materials are better suited since they absorb radar waves only slightly (e.g., uncoated glass, plastics, various wood-based materials, drywall).


4047438025935	10,5 cm
85299065	6,8 cm
165 g	10,5 cm
	0,7 l


**MX-OPT-DIGI-INT****MxDigitizer For S1x**

Interface box to connect one analog camera directly to a S1x Body as alternative image source (instead of one sensor module) • Up to two MxDigitizer boxes or two analog cameras can be connected to one S1x Body • Easy integration of analog cameras into the MOBOTIX IP video system incl. the support of MOBOTIX integrated image analysis tools (e.g. MxActivitySensor) • Box digitizes the analog signal input (NTSC/PAL) • Output format PAL: 704 x 525 pixels, up to 25 frames per second • Output format NTSC: 640 x 480 pixels, up to 30 frames per second • BNC connection of analog camera to MxDigitizer • Sensor cable connection of MxDigitizer to S1x Body (to be ordered separately, maximum length 3 m/9.8 ft) • Operating conditions: Indoors, 0 to 40°C (32 to 104°F) • Color: white

4047438028790	10,5 cm
85299065	6,8 cm
120 g	10,5 cm
	0,7 l

Functional Enhancement & IR Illuminators

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-ExtIO	4047438009850	29,6 cm
	ExtIO Extension Module For All MOBOTIX Cameras	85299065	19,6 cm
	ExtIO Weatherproof extension for all MOBOTIX cameras (except Basic models) • Power supply: PoE (Class 2, IEEE 802.3af) or USB (connection cable to be ordered individually) • Microphone/speaker • Line-in / Line-out • PIR sensor for motion detection • Temperature sensor • 2 buttons (e.g., lights, door bell) • 2 galvanically separated inputs • 2 galvanically separated outputs • Protection class IP65, -30 to 60° C / -22 to 140°F • Robust housing made of fiber-reinforced plastic PBT-GF30 • Mounting to a wall or ceiling, optionally with MOBOTIX mounting accessories (to be ordered individually) • Connecting via USB	744 g	9,0 cm
			5,2 l
	MX-MULTISENSE1-EXT	4047438028905	9,8 cm
	MxMultiSense Outdoor (HS code 85299065)	85299065	7,5 cm
	Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor ($\pm 0.3^{\circ}\text{C}$ / 0.18°F) and acoustic sensor (level of sound waves) • Camera connection and supply via MxBus: power consumption approx. 0.3 W, MxBus cable length up to 100 m / 330 ft. • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX mounts for sensor modules and standard mounts for recessed spotlights • Protection class IP66 • IK05 • Ambient temperature -20 to 60°C / -4 to 140°F • Housing color: white	110 g	9,0 cm
			0,7 l
	MX-OPT-IO3-INT	4047438025928	10,7 cm
	Extension Module For c25, i25, p25 And v25	85299065	5,2 cm
	Extension module for the indoor cameras x25 (to be mounted on the backside) • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window • contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x • isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA • per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l
	Mx-A-IOA-IC	4047438029032	10,7 cm
	Extension Module For All Indoor Cameras x26A/x26B	85299065	5,2 cm
	Expansion module for Indoor Cameras x26A/B, i26A/B, p26A/B and v26A/B (installed on the back) • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by the x26B Indoor Cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l
	Mx-A-SPA	4047438030229	30,5 cm
	MxSplitProtect Installation Box, IP66	85299065	24,0 cm
	Weatherproof installation box with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces (weatherproof): 1 LSA (with shield clip) for Ethernet 2 100Base-T, 2 MxRJ45 for Ethernet 100Base-T with PoE Mode A, 1 protective earth terminal • IP66 and IK08, ambient temperature: -30°C to 60°C (-22°F to 140°F) • Accessories (available separately): MxSplitProtectHR Hat Rail module (Mx-A-SPA-HR), cover with camera mount in three versions (Mx-A-SPCA-M/-H/-V), pole mount (MX-MH-SecureFlex-ESWS) • Housing color: white	1.184 g	16,0 cm
			11,7 l

**Mx-A-SPA-HR****MxSplitProtectHR Hat Rail Module**

Compatible with MxSplitProtect Installation Box (Mx-A-SPA): Hat rail module (for 35 mm DIN rails) with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces: 3x RJ45 for Ethernet 100Base-T, 1x protective earth terminal • Only use in indoor areas, ambient temperature: 0°C to 40°C (32°F to 104°F) • Accessories (available separately): MxSwitch (MX-SWITCH1) • Housing color: gray

4047438030236	10,0 cm
85299065	7,5 cm
130 g	9,0 cm
	0,7 l

**Mx-A-SPCA-M****MxSplitProtect Cover, M-Cameras**

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to install the standard VarioFlex wall mount of an M15/M16/M25/M26 camera directly to the cover • Color: white

4047438028820	19,6 cm
85299065	18,0 cm
514 g	14,8 cm
	5,2 l

**Mx-A-SPCA-H****MxSplitProtect Cover, Horizontal**


Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (vertically) install a Q2x (or D2x) camera with a 15° tilt angle without an additional mount directly to the cover • Color: white

4047438028837	19,6 cm
85299065	18,0 cm
570 g	14,8 cm
	5,2 l

**Mx-A-SPCA-V****MxSplitProtect Cover, Vertical**


Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (horizontally) install a Q2x/D2x camera without an additional mount directly to the cover • Color: white

4047438028844	19,6 cm
85299065	18,0 cm
482 g	14,8 cm
	5,2 l

**Mx-A-IRA-120****MxIRLight Infrared Illuminator (860 nm), 120°x120°**


Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030342	20,5 cm
85394900	17,5 cm
1.098 g	12,5 cm
	4,5 l

**Mx-A-IRA-90****MxIRLight Infrared Illuminator (860 nm), 90°x90°**

Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030359	20,5 cm
85394900	17,5 cm
1.112 g	12,5 cm
	4,5 l

**Mx-A-IRA-60****MxIRLight Infrared Illuminator (860 nm), 60°x60°**


Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030366	20,5 cm
85394900	17,5 cm
1.116 9	12,5 cm
	4,5 l

**Mx-A-IRA-45****MxIRLight Infrared Illuminator (860 nm), 45°x45°**


Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030373	20,5 cm
85394900	17,5 cm
1.124 9	12,5 cm
	4,5 l

**Mx-A-IRA-30****MxIRLight Infrared Illuminator (860 nm), 30°x30°**

Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030380	20,5 cm
85394900	17,5 cm
1.096 9	12,5 cm
	4,5 l

**Mx-A-IRA-15****MxIRLight Infrared Illuminator (860 nm), 15°x15°**

Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030397	20,5 cm
85394900	17,5 cm
1.090 9	12,5 cm
	4,5 l

**Mx-M-IRA-ML****MxIRLight Mounting Brackets For M1x**

Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030403	19,6 cm
85399010	5,5 cm
216 9	3,5 cm
	0,4 l

**Mx-M-IRA-M****MxIRLight Mounting Brackets For M2x**

Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030410	14,0 cm
85399010	5,5 cm
150 9	3,5 cm
	0,3 l

PoE Power Supply

Article No. / Name / Description	EAN / HS / weight	dimen.
	4047438047531	17,0 cm
	85043180	7,0 cm
	318 g	4,7 cm
		0,6 l
Mx-NPA-PoE1A-60W-BT PoE++ Power Network Injektor 60 Watt PoE++ 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • -10° to 40°C • @60W • -10° to 50°C, humidity 10 to 90% @30W • IEEE 802.3bt compliant • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation • Full Protection OVP, OCP • Additional required power cord C14-type not included • Warranty: 1 year		
	4047438039024	20,5 cm
	85043180	11,5 cm
	450 g	6,5 cm
		1,5 l
Mx-NPA-UPoE1A-60W UPoE Power Injector 60W UPoE (PoE++) 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • 14° to 113°F @60W • 14° to 131°F @30W • IEEE 802.3af compliant with 2-event classification • IEEE 802.3af backward compatible • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation		
	4047438028882	14,8 cm
	85176200	9,8 cm
	310 g	9,0 cm
		1,3 l
Mx-SWITCH1 MxSwitch For DIN Rail Mounting PoE+ Switch for the top-hat rail • 5x RJ45 port with 100 MBit/s (1x uplink, 4x PoE+ with max. 75 W) • Supply: 48 V DC, max. 75 W • Simplified cabling for door stations due to available connectivity for anti-theft protection, door opener and MxBus • MxBus, anti-theft protection, door and lock contact can be connected via separate wires of the ethernet cable		
	4047438012249	14,8 cm
	85043180	9,8 cm
	268 g	9,0 cm
		1,3 l
MX-NPA-PoE-EU-Set PoE Power Adapter Set, EU PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug		
	4047438012256	14,8 cm
	85043180	9,8 cm
	314 g	9,0 cm
		1,3 l
MX-NPA-PoE-INT-Set PoE Power Adapter Set, INT PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug		

**MX-NPA-PoE-RJ**
PoE Power Adapter

PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed



4047438013932	9,0 cm
85043180	7,5 cm
60 g	5,0 cm
	0,3 l

**MX-SNT-INT-PoE**
Universal Power Supply With 4 Power Plugs

For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F

4047438013925	9,8 cm
85043180	7,5 cm
160 g	9,0 cm
	0,7 l

MOBOTIX Storage & Recording Solutions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S-NVR1A-64-POE24	4047438040365	58,0 cm
	MOBOTIX MOVE NVR Network Video Recorder 64 Channels	85255000	58,0 cm
	MOBOTIX MOVE NVR Network Video Recorder for recording and Display up to 64 IP Cameras (Resolution up to 12MP) • 24 integrated PoE+ Ports for centralized powering of connected IP-Cameras • 8x 3.5" SATA3 lockable HDD cartridge-slots (Delivery without hard disks (not available via MOBOTIX) • Harddrives "Hot-Swappable" • RAID 0/1/5/10 Support for Data recovering in case of HDD Failure • Optional Failover-Server functionality withing MOVE NVR System • IP-Data-Throughput (Live & Recording): avg.: 480 Mbps, peak 2upt to 540 Mbps • Video-Codecs : H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support • 19"-Rack mount kit included. • Environmental Temperature 0 to 40°C • Power Supply: AC AC 100-240V, ATX 520W (53V/360W for PoE; 12V/160W for HDD/System) • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • Warranty: 2 Years (excl. HDD's)	12.510 g	25,0 cm
			84,1 l
	Mx-S-NAS2A-8	4047438034036	27,0 cm
	MOBOTIX NAS 2-Bay/8 Channels (NAS-251G)	84718000	20,2 cm
	MOBOTIX Network Attached Storage device with 2 bays and 8 ONVIF S channels • Max. Storage capacity net (with redundancy): 12 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	2.320 g	23,5 cm
			12,8 l
	Mx-S-NAS4A-16	4047438034043	30,5 cm
	MOBOTIX NAS 4-Bay/16 Channels (NAS-451G)	84718000	25,0 cm
	MOBOTIX Network Attached Storage device with 4 bays and 16 ONVIF S channels • Max. Storage capacity net (with redundancy): 36 TB • Delivery without hard disks (not available on MOBOTIX) • Incl. Power cable C13 with EU plug (cable with US / GB / AU plug available on request)	3.420 g	31,6 cm
			24,1 l
	Mx-S-NVR1A-8-POE	4047438036849	42,6 cm
	MOBOTIX MOVE NVR Network Video Recorder 8 Channels	85255000	37,9 cm
	MOBOTIX MOVE NVR Network Video Recorder with 8 integrated PoE IP-Camera Channels (12 IP-Cameras total support) • Max. Storage capacity net (internal & external): 20 TB (2x 3.5" SATA3) • Delivery without hard disks (not available via MOBOTIX) • IP-Data-Throughput (Live & Recording): 80 up to peak 120Mbps • Recording & Playback: H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support	4.200 g	11,0 cm
			17,8 l
	Mx-S-NVR1A-16-POE	4047438036856	49,5 cm
	MOBOTIX MOVE NVR Network Video Recorder 16 Channels	85255000	34,5 cm
	MOBOTIX MOVE NVR Network Video Recorder with 16 integrated PoE IP-Camera Channels (24 IP-Cameras total support) • Max. Storage capacity net: 28 TB (2x 3.5" SATA3) • Delivery without hard disks (not available via MOBOTIX) • IP-Data-Throughput (Live & Recording): 160 up to peak 240Mbps • Recording • Support of ONVIF S conformant 3rd Party cameras: H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support	8.500 g	18,1 cm
			30,9 l

MOBOTIX Cloud

BeyondHumanVision

MOBOTIX

MOBOTIX Cloud Bridge



Article No. / Name / Description

EAN / HS / weight dimen.

Mx-S-BRIDGEB-DT-20

4047438043588 29,6 cm

MOBOTIX CLOUD Bridge 304+ for up to 20 IP Cameras

85299065 19,6 cm

High-security connection box for the MOBOTIX CLOUD VMS • Locally connected to the Internet and up to 20 ONVIF IP cameras at 4MP resolution • Cybersecure connection to regionally available MOBOTIX CLOUD data centers • Secure end-to-end encryption of all data stored and transferred in the system • No data loss in case of up to 2-day Internet outage: Integrated hard disk as a memory buffer in case of interrupted connection to the cloud • No data loss due to Internet bandwidth fluctuations: Automatic data buffering in the BRIDGE • Ultra flexible cloud data storage with individually selectable retention period (max. 5 years) • Compact, robust metal housing with an extended temperature range and fanless device design for maximum reliability thanks to SSD memory • Dimensions (LxWxH): 127 x 127 x 45 mm (5" x 5" x 1.75") • Connections: AC power supply (adapter included), 2x ETH (1x for PoE switch for local cameras, 1x for internet router), monitor and keyboard (optional) • Integrated display for status display such as the IP

1.980 g 9,0 cm

5,2 l

MOBOTIX Cloud Subscriptions

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-CL-Sub-ANA-001-12	4047438042062	cm
	MOBOTIX CLOUD Yearly Analytics Subscription, Line Cross		cm
	Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross •	g	cm
	Cancellation possible at any time at the end of the subscription period.		l
	Mx-CL-Sub-ANA-001-36	4047438046701	cm
	MOBOTIX CLOUD 3 Yearly Analytics Subscription, Line Cross		cm
	3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross •	g	cm
	Cancellation possible at any time at the end of the subscription period.		l
	Mx-CL-Sub-ANA-001-60	4047438046718	cm
	MOBOTIX CLOUD 5 Yearly Analytics Subscription, Line Cross		cm
	5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross •	g	cm
	Cancellation possible at any time at the end of the subscription period.		l
	Mx-CL-Sub-ANA-002-12	4047438042079	cm
	MOBOTIX CLOUD Yearly Analytics Subscription, Counting		cm
	Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting •	g	cm
	Cancellation possible at any time at the end of the subscription period.		l
	Mx-CL-Sub-ANA-002-36	4047438046725	cm
	MOBOTIX CLOUD 3 Yearly Analytics Subscription, Counting		cm
	3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting •	g	cm
	Cancellation possible at any time at the end of the subscription period.		l

**Mx-CL-Sub-ANA-002-60**

4047438046732

cm

MOBOTIX CLOUD 5 Yearly Analytics Subscription, Counting

cm

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting •
Cancellation possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ANA-003-12**

4047438042086

cm

MOBOTIX CLOUD Yearly Analytics Subscription, Area

cm

Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion •
Cancellation possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ANA-003-36**

4047438046749

cm

MOBOTIX CLOUD 3 Yearly Analytics Subscription, Area

cm

3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion •
Cancellation possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ANA-003-60**

4047438046756

cm

MOBOTIX CLOUD 5 Yearly Analytics Subscription, Area

cm

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion •
Cancellation possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ANA-004-12**

4047438042093

cm

MOBOTIX CLOUD Yearly Analytics Subscription, Camera

cm

Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect
• Cancellation possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ANA-004-36**

4047438046763

cm

MOBOTIX CLOUD 3 Yearly Analytics Subscription, Camera

cm

3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper
Detect • Cancellation possible at any time at the end of the subscription period.

g

cm
l

**Mx-CL-Sub-ANA-004-60**

4047438046770

cm

MOBOTIX CLOUD 5 Yearly Analytics Subscription, Camera

cm

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-ANA-005-12**

4047438042109

cm

MOBOTIX CLOUD Yearly Analytics Subscription, Loitering

cm

Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-ANA-005-36**

4047438046787

cm

MOBOTIX CLOUD 3 Yearly Analytics Subscription, Loitering

cm

3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-ANA-005-60**

4047438046794

cm

MOBOTIX CLOUD 5 Yearly Analytics Subscription, Loitering

cm

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-ED001-1**

4047438048002

cm

1 Month MOBOTIX CLOUD Account Subscription, update to

cm

1 Month subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-ED001-12**

4047438048019

cm

MOBOTIX CLOUD Yearly Account Subscription, update to

cm

Yearly subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-ED001-36**

4047438048026

cm

3 Yearly MOBOTIX CLOUD Account Subscription, update to

3 Yearly subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-ED001-60**

4047438048033

cm

5 Yearly MOBOTIX CLOUD Account Subscription, update to

5 Yearly subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-ED002-1**

4047438048040

cm

1 Month MOBOTIX CLOUD Account Subscription, update to

1 Month subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month.

g

cm

cm
l**Mx-CL-Sub-ED002-12**

4047438048057

cm

MOBOTIX CLOUD Yearly Account Subscription, update to

Yearly subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-ED002-36**

4047438048064

cm

3 Yearly MOBOTIX CLOUD Account Subscription, update to

3 Yearly subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-ED002-60**

4047438048071

cm

5 Yearly MOBOTIX CLOUD Account Subscription, update to

5 Yearly subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD1-D1095-12**

4047438041744

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D1095-36**

4047438045667

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D1095-60**

4047438045674

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D14-12**

4047438041676

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D14-36**

4047438045520

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D14-60**

4047438045537

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD1-D180-12**

4047438041713

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D180-36**

4047438045605

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D180-60**

4047438045612

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D1825-12**

4047438041751

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D1825-36**

4047438045681

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D1825-60**

4047438045698

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD1-D30-12**

4047438041683

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D30-36**

4047438045544

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D30-60**

4047438045551

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D365-12**

4047438041720

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D365-36**

4047438045629

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D365-60**

4047438045636

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD1-D60-12**

4047438041690

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D60-36**

4047438045568

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D60-60**

4047438045575

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D7-12**

4047438041669

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D7-36**

4047438045506

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D7-60**

4047438045513

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD1-D730-12**

4047438041737

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D730-36**

4047438045643

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D730-60**

4047438045650

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D90-12**

4047438041706

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D90-36**

4047438045582

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD1-D90-60**

4047438045599

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD10-D1095-12**

4047438042390

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D1095-36**

4047438046664

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D1095-60**

4047438046671

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D14-12**

4047438042321

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/14

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D14-36**

4047438046527

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D14-60**

4047438046534

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD10-D180-12**

4047438042369

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D180-36**

4047438046602

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D180-60**

4047438046619

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-12**

4047438042406

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-36**

4047438046688

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-60**

4047438046695

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD10-D30-12**

4047438042338

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/30

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D30-36**

4047438046541

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D30-60**

4047438046558

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D365-12**

4047438042376

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D365-36**

4047438046626

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D365-60**

4047438046633

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD10-D60-12**

4047438042345

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/60

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D60-36**

4047438046565

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D60-60**

4047438046572

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D7-12**

4047438042314

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D7-36**

4047438046503

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD10-D7-60**

4047438046510

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD10-D730-12**

4047438042383

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD10-D730-36**

4047438046640

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD10-D730-60**

4047438046657

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD10-D90-12**

4047438042352

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/90

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD10-D90-36**

4047438046589

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD10-D90-60**

4047438046596

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD15-D1095-1**

4047438047128

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1095

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD15-D1095-12**

4047438047135

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/1095

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D1095-36**

4047438047142

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D1095-60**

4047438047159

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D14-1**

4047438046848

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/14

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D14-12**

4047438046855

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/14

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D14-36**

4047438046862

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D14-60**

4047438046879

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D180-1**

4047438047005

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/180

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D180-12**

4047438047012

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/180

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D180-36**

4047438047029

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D180-60**

4047438047036

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD15-D1825-1**

4047438047166

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1825

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD15-D1825-12**

4047438047173

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/1825

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D1825-36**

4047438047180

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D1825-60**

4047438047197

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D30-1**

4047438046886

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/30

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D30-12**

4047438046893

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/30

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D30-36**

4047438046909

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D30-60**

4047438046916

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-1**

4047438047043

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/365

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-12**

4047438047050

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/365

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-36**

4047438047067

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-60**

4047438047074

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD15-D60-1**

4047438046923

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/60

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D60-12**

4047438046930

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/60

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D60-36**

4047438046947

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D60-60**

4047438046954

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D7-1**

4047438046800

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/7

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D7-12**

4047438046817

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/7

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD15-D7-36**

4047438046824

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D7-60**

4047438046831

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-1**

4047438047081

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/730

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-12**

4047438047098

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/730

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-36**

4047438047104

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-60**

4047438047111

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD15-D90-1**

4047438046961

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/90

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D90-12**

4047438046978

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/90

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D90-36**

4047438046985

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D90-60**

4047438046992

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D1095-12**

4047438041843

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D1095-36**

4047438045865

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD2-D1095-60**

4047438045872

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D14-12**

4047438041775

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/14

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D14-36**

4047438045728

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D14-60**

4047438045735

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D180-12**

4047438041812

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D180-36**

4047438045803

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D180-60**

4047438045810

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D1825-12**

4047438041850

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD2-D1825-36**

4047438045889

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD2-D1825-60**

4047438045896

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD2-D30-12**

4047438041782

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/30

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD2-D30-36**

4047438045742

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD2-D30-60**

4047438045759

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D365-12**

4047438041829

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D365-36**

4047438045827

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D365-60**

4047438045834

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D60-12**

4047438041799

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/60

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D60-36**

4047438045766

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD2-D60-60**

4047438045773

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D7-12**

4047438041768

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D7-36**

4047438045704

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D7-60**

4047438045711

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D730-12**

4047438041836

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD2-D730-36**

4047438045841

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-HD2-D730-60**

4047438045858

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD2-D90-12**

4047438041805

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/90

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD2-D90-36**

4047438045780

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD2-D90-60**

4047438045797

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D1095-12**

4047438041942

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D1095-36**

4047438046060

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D1095-60**

4047438046077

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D14-12**

4047438041874

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D14-36**

4047438045926

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D14-60**

4047438045933

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D180-12**

4047438041911

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D180-36**

4047438046008

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D180-60**

4047438046015

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D1825-12**

4047438041959

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D1825-36**

4047438046084

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D1825-60**

4047438046091

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D30-12**

4047438041881

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D30-36**

4047438045940

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D30-60**

4047438045957

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D365-12**

4047438041928

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D365-36**

4047438046022

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D365-60**

4047438046039

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D60-12**

4047438041898

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D60-36**

4047438045964

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D60-60**

4047438045971

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D7-12**

4047438041867

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D7-36**

4047438045902

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/7 Days

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D7-60**

4047438045919

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/7 Days

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D730-12**

4047438041935

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D730-36**

4047438046046

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D730-60**

4047438046053

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD3-D90-12**

4047438041904

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D90-36**

4047438045988

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD3-D90-60**

4047438045995

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D1095-12**

4047438042192

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D1095-36**

4047438046268

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D1095-60**

4047438046275

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D14-12**

4047438042123

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D14-36**

4047438046121

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D14-60**

4047438046138

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D180-12**

4047438042161

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D180-36**

4047438046206

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D180-60**

4047438046213

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D1825-12**

4047438042208

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D1825-36**

4047438046282

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D1825-60**

4047438046299

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D30-12**

4047438042130

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D30-36**

4047438046145

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D30-60**

4047438046152

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D365-12**

4047438042178

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D365-36**

4047438046220

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D365-60**

4047438046237

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D60-12**

4047438042147

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D60-36**

4047438046169

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD4-D60-60**

4047438046176

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D7-12**

4047438042116

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D7-36**

4047438046107

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/7 Days

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D7-60**

4047438046114

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/7 Days

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D730-12**

4047438042185

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D730-36**

4047438046244

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D730-60**

4047438046251

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D90-12**

4047438042154

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D90-36**

4047438046183

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD4-D90-60**

4047438046190

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD5-D1095-12**

4047438042291

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD5-D1095-36**

4047438046466

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD5-D1095-60**

4047438046473

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD5-D14-12**

4047438042222

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D14-36**

4047438046329

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D14-60**

4047438046336

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D180-12**

4047438042260

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D180-36**

4047438046404

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D180-60**

4047438046411

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD5-D1825-12**

4047438042307

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D1825-36**

4047438046480

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D1825-60**

4047438046497

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D30-12**

4047438042239

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D30-36**

4047438046343

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D30-60**

4047438046350

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD5-D365-12**

4047438042277

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D365-36**

4047438046428

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D365-60**

4047438046435

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D60-12**

4047438042246

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D60-36**

4047438046367

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD5-D60-60**

4047438046374

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/60

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D7-12**

4047438042215

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/7 Days

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D7-36**

4047438046305

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/7 Days

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D7-60**

4047438046312

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/7 Days

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D730-12**

4047438042284

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/730

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D730-36**

4047438046442

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/730

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l

**Mx-CL-Sub-HD5-D730-60**

4047438046459

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/730

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D90-12**

4047438042253

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/90 Days

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D90-36**

4047438046381

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/90

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-HD5-D90-60**

4047438046398

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/90

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-M10-1**

4047438040327

cm

MOBOTIX CLOUD Camera license, only live stream, NO

cm

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm
l**Mx-CL-Sub-M10-12**

4047438042482

cm

MOBOTIX CLOUD Yearly Camera Subscription, only Live

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the year

g

cm
l

**Mx-CL-Sub-M10-36**

4047438045278

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, only Live

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the year

g

cm
l**Mx-CL-Sub-M10-60**

4047438045285

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, only Live

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the year

g

cm
l**Mx-CL-Sub-SD1-D1095-12**

4047438042048

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/1095

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-SD1-D1095-36**

4047438045469

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/1095

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-SD1-D1095-60**

4047438045476

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/1095

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-SD1-D14-12**

4047438041973

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/14 Days

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l

**Mx-CL-Sub-SD1-D14-36**

4047438045315

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D14-60**

4047438045322

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D180-12**

4047438042017

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/180 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D180-36**

4047438045407

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D180-60**

4047438045414

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D1825-12**

4047438042055

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D1825-36**

4047438045483

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D1825-60**

4047438045490

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D30-12**

4047438041980

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D30-36**

4047438045339

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D30-60**

4047438045346

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D365-12**

4047438042024

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/365 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D365-36**

4047438045421

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D365-60**

4047438045438

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D60-12**

4047438041997

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D60-36**

4047438045360

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D60-60**

4047438045377

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D7-12**

4047438041966

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SD1-D7-36**

4047438045292

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/7 Days

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SD1-D7-60**

4047438045308

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/7 Days

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SD1-D730-12**

4047438042031

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/730 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SD1-D730-36**

4047438045445

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SD1-D730-60**

4047438045452

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SD1-D90-12**

4047438042000

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-SD1-D90-36**

4047438045384

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SD1-D90-60**

4047438045391

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SP01-M30-1**

4047438047203

cm

MOBOTIX CLOUD Monthly SIP Audio-Support Subscription

Monthly Subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SP01-M30-12**

4047438047210

cm

MOBOTIX CLOUD Yearly SIP Audio-Support Subscription

Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SP01-M30-36**

4047438047227

cm

MOBOTIX CLOUD 3 Yearly SIP Audio-Support Subscription

3 Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-SP01-M30-60**

4047438047234

cm

MOBOTIX CLOUD 5 Yearly SIP Audio-Support Subscription

5 Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l

**Mx-CL-Sub-SD1-D7-1**

4047438036375

cm

MOBOTIX CLOUD Camera Subscription, VGA/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D14-1**

4047438036382

cm

MOBOTIX CLOUD Camera Subscription, VGA/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX Cloud access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D30-1**

4047438036399

cm

MOBOTIX CLOUD Camera Subscription, VGA/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D60-1**

4047438036405

cm

MOBOTIX CLOUD Camera Subscription, VGA/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D90-1**

4047438036412

cm

MOBOTIX CLOUD Camera Subscription, VGA/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D180-1**

4047438036429

cm

MOBOTIX CLOUD Camera Subscription, VGA/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-SD1-D365-1**

4047438036436

cm

MOBOTIX CLOUD Camera Subscription, VGA/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-SD1-D730-1**

4047438036443

cm

MOBOTIX CLOUD Camera Subscription, VGA/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-SD1-D1095-1**

4047438036450

cm

MOBOTIX CLOUD Camera Subscription, VGA/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-SD1-D1825-1**

4047438036467

cm

MOBOTIX CLOUD Camera Subscription, VGA/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D7-1**

4047438036023

cm

MOBOTIX CLOUD Camera Subscription, 720p/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D14-1**

4047438036030

cm

MOBOTIX CLOUD Camera Subscription, 720p/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D30-1**

4047438036047

cm

MOBOTIX CLOUD Camera Subscription, 720p/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D60-1**

4047438036054

cm

MOBOTIX CLOUD Camera Subscription, 720p/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D90-1**

4047438036061

cm

MOBOTIX CLOUD Camera Subscription, 720p/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D180-1**

4047438036078

cm

MOBOTIX CLOUD Camera Subscription, 720p/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D365-1**

4047438036085

cm

MOBOTIX CLOUD Camera Subscription, 720p/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D730-1**

4047438036092

cm

MOBOTIX CLOUD Camera Subscription, 720p/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D1095-1**

4047438036108

cm

MOBOTIX CLOUD Camera Subscription, 720p/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD1-D1825-1**

4047438036115

cm

MOBOTIX CLOUD Camera Subscription, 720p/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D7-1**

4047438036122

cm

MOBOTIX CLOUD Camera Subscription, 1080p/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D14-1**

4047438036139

cm

MOBOTIX CLOUD Camera Subscription, 1080p/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D30-1**

4047438036146

cm

MOBOTIX CLOUD Camera Subscription, 1080p/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D60-1**

4047438036153

cm

MOBOTIX CLOUD Camera Subscription, 1080p/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD2-D90-1**

4047438036160

cm

MOBOTIX CLOUD Camera Subscription, 1080p/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D180-1**

4047438036177

cm

MOBOTIX CLOUD Camera Subscription, 1080p/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D365-1**

4047438036184

cm

MOBOTIX CLOUD Camera Subscription, 1080p/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D730-1**

4047438036191

cm

MOBOTIX CLOUD Camera Subscription, 1080p/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D1095-1**

4047438036207

cm

MOBOTIX CLOUD Camera Subscription, 1080p/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D1825-1**

4047438036214

cm

MOBOTIX CLOUD Camera Subscription, 1080p/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD3-D7-1**

4047438036221

cm

MOBOTIX CLOUD Camera Subscription, 3MP/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D14-1**

4047438036238

cm

MOBOTIX CLOUD Camera Subscription, 3MP/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D30-1**

4047438036245

cm

MOBOTIX CLOUD Camera Subscription, 3MP/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D60-1**

4047438036252

cm

MOBOTIX CLOUD Camera Subscription, 3MP/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D90-1**

4047438036269

cm

MOBOTIX CLOUD Camera Subscription, 3MP/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D180-1**

4047438036276

cm

MOBOTIX CLOUD Camera Subscription, 3MP/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD3-D365-1**

4047438036283

cm

MOBOTIX CLOUD Camera Subscription, 3MP/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD3-D730-1**

4047438036290

cm

MOBOTIX CLOUD Camera Subscription, 3MP/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX Cloud access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD3-D1095-1**

4047438036306

cm

MOBOTIX CLOUD Camera Subscription, 3MP/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD3-D1825-1**

4047438036313

cm

MOBOTIX CLOUD Camera Subscription, 3MP/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD4-D7-1**

4047438036481

cm

MOBOTIX CLOUD Camera Subscription, 4MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD4-D14-1**

4047438036498

cm

MOBOTIX CLOUD Camera Subscription, 4MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD4-D30-1**

4047438036504

cm

MOBOTIX CLOUD Camera Subscription, 4MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D60-1**

4047438036511

cm

MOBOTIX CLOUD Camera Subscription, 4MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D90-1**

4047438036528

cm

MOBOTIX CLOUD Camera Subscription, 4MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D180-1**

4047438036535

cm

MOBOTIX CLOUD Camera Subscription, 4MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D365-1**

4047438036542

cm

MOBOTIX CLOUD Camera Subscription, 4MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D730-1**

4047438036559

cm

MOBOTIX CLOUD Camera Subscription, 4MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD4-D1095-1**

4047438036566

cm

MOBOTIX CLOUD Camera Subscription, 4MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D1825-1**

4047438036573

cm

MOBOTIX CLOUD Camera Subscription, 4MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D7-1**

4047438036580

cm

MOBOTIX CLOUD Camera Subscription, 5MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D14-1**

4047438036597

cm

MOBOTIX CLOUD Camera Subscription, 5MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D30-1**

4047438036603

cm

MOBOTIX CLOUD Camera Subscription, 5MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D60-1**

4047438036610

cm

MOBOTIX CLOUD Camera Subscription, 5MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD5-D90-1**

4047438036627

cm

MOBOTIX CLOUD Camera Subscription, 5MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D180-1**

4047438036634

cm

MOBOTIX CLOUD Camera Subscription, 5MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D365-1**

4047438036641

cm

MOBOTIX CLOUD Camera Subscription, 5MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D730-1**

4047438036658

cm

MOBOTIX CLOUD Camera Subscription, 5MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D1095-1**

4047438036665

cm

MOBOTIX CLOUD Camera Subscription, 5MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D1825-1**

4047438036672

cm

MOBOTIX CLOUD Camera Subscription, 5MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD10-D7-1**

4047438036689

cm

MOBOTIX CLOUD Camera Subscription, 10MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D14-1**

4047438036696

cm

MOBOTIX CLOUD Camera Subscription, 10MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D30-1**

4047438036702

cm

MOBOTIX CLOUD Camera Subscription, 10MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D60-1**

4047438036719

cm

MOBOTIX CLOUD Camera Subscription, 10MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D90-1**

4047438036726

cm

MOBOTIX CLOUD Camera Subscription, 10MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D180-1**

4047438036733

cm

MOBOTIX CLOUD Camera Subscription, 10MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD10-D365-1**

4047438036740

cm

MOBOTIX CLOUD Camera Subscription, 10MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D730-1**

4047438036757

cm

MOBOTIX CLOUD Camera Subscription, 10MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D1095-1**

4047438036764

cm

MOBOTIX CLOUD Camera Subscription, 10MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-1**

4047438036771

cm

MOBOTIX CLOUD Camera Subscription, 10MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-ANA-001-1**

4047438036320

cm

MOBOTIX CLOUD Analytics Subscription, Line Cross

Monthly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-ANA-002-1**

4047438036337

cm

MOBOTIX CLOUD Analytics Subscription, Counting

Monthly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-ANA-003-1****MOBOTIX CLOUD Analytics Subscription, Area Intrusion**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion •
Cancellation of subscription possible at any time at the end of the month

4047438036344

g

cm

cm

cm
l**Mx-CL-Sub-ANA-004-1****MOBOTIX CLOUD Analytics Subscription, Camera Tamper**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper
Detect • Cancellation of subscription possible at any time at the end of the month

4047438036351

g

cm

cm

cm
l**Mx-CL-Sub-ANA-005-1****MOBOTIX CLOUD Analytics Subscription, Loitering**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Loitering •
Cancellation of subscription possible at any time at the end of the month

4047438036368

g

cm

cm

cm
l

Access Control

BeyondHumanVision

MOBOTIX

T26B Camera Module

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-T26B-6D016 T26 CamCore, 6MP, B016, Day, White Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	4047438032025 19,6 cm 85258900 14,8 cm 400 g 9,0 cm 2,6 l
	Mx-T26B-6N016 T26 CamCore, 6MP, B016, Night, White Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	4047438032032 19,6 cm 85258900 14,8 cm 400 g 9,0 cm 2,6 l
	Mx-T26B-6D016-b T26 CamCore, 6MP, B016, Day, Black Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	4047438032049 19,6 cm 85258900 14,8 cm 400 g 9,0 cm 2,6 l
	Mx-T26B-6N016-b T26 CamCore, 6MP B016, Night, Black Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	4047438032056 19,6 cm 85258900 14,8 cm 400 g 9,0 cm 2,6 l
	Mx-T26B-6D016-s T26 CamCore, 6MP, B016, Day, Silver Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	4047438032063 19,6 cm 85258900 14,8 cm 400 g 9,0 cm 2,6 l

**Mx-T26B-6N016-s****T26 CamCore, 6MP, B016, Night, Silver**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver

4047438032070	19,6 cm
85258900	14,8 cm
400 g	9,0 cm
	2,6 l

**Mx-T26B-6D016-d****T26 CamCore, 6MP, B016, Day, Dark Gray**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray

4047438032087	19,6 cm
85258900	14,8 cm
400 g	9,0 cm
	2,6 l

**Mx-T26B-6N016-d****T26 CamCore, 6MP, B016, Night, Dark Gray**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray

4047438032094	19,6 cm
85258900	14,8 cm
400 g	9,0 cm
	2,6 l

KeypadRFID Module

Article No. / Name / Description

EAN / HS / weight dimen.



Mx-A-KEYC

Keypad With RFID Technology For T26, White

Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White

4047438034135 19,6 cm
85371091 15,0 cm
330 g 9,0 cm
2,6 l




Mx-A-KEYC-b

Keypad With RFID Technology For T26, Black

Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

4047438034128 19,6 cm
85371091 15,0 cm
330 g 9,0 cm
2,6 l



Mx-A-KEYC-d

Keypad With RFID Technology For T26, Dark Gray

Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray

4047438034111 19,6 cm
85371091 15,0 cm
330 g 9,0 cm
2,6 l



Mx-A-KEYC-s

Keypad With RFID Technology For T26, Silver

Keypad access module for MOBOTIX T26 IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

4047438034104 19,6 cm
85371091 15,0 cm
330 g 9,0 cm
2,6 l

BellRFID Module

Article No. / Name / Description

EAN / HS / weight dimen.



Mx-A-BELLC

BellRFID Base Module For T26, White

BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White

4047438034067 19,6 cm
85299065 15,0 cm
350 g 9,0 cm
2,6 l



Mx-A-BELLC-b

BellRFID Base Module For T26, Black

BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

4047438034074 19,6 cm
85299065 15,0 cm
350 g 9,0 cm
2,6 l



Mx-A-BELLC-d

BellRFID Base Module For T26, Dark Gray

BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray

4047438034081 19,6 cm
85299065 15,0 cm
350 g 9,0 cm
2,6 l



Mx-A-BELLC-s

BellRFID Base Module For T26, Silver

BellRFID access module for MOBOTIX T26 IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

4047438034098 19,6 cm
85299065 15,0 cm
350 g 9,0 cm
2,6 l



MX-Bell1-Button-F1

BellRFID Bell Button Set F1

1 big key with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label

4047438017190 10,3 cm
85299065 1,7 cm
94 g 10,3 cm
0,2 l

**MX-Bell1-Button-F2****BellRFID Bell Button Set F2**

2 medium-sized keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label

4047438017176 10,3 cm
85299065 1,7 cm
94 9 10,3 cm
0,2 l

**MX-Bell1-Button-F3****BellRFID Bell Button Set F3**

1 medium-sized and 2 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label

4047438017527 10,3 cm
85299065 1,7 cm
94 9 10,3 cm
0,2 l

**MX-Bell1-Button-F4****BellRFID Bell Button Set F4**

4 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label

4047438017183 10,3 cm
85299065 1,7 cm
94 9 10,3 cm
0,2 l

**MX-Bell1-Button-05****BellRFID Bell Button Set 05**

5 small keys (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label

4047438017534 10,3 cm
85299065 1,7 cm
94 9 10,3 cm
0,2 l

**MX-Bell1-Button-XL1****BellRFID Bell Button Set XL1**

1 big XL key (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label

4047438017169 10,3 cm
85299065 1,7 cm
94 9 10,3 cm
0,2 l

Info Module

Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-Info1-EXT-PW Info Module With LEDs, White Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	4047438014991 19,6 cm 85414900 15,0 cm 282 g 9,0 cm 2,6 l
	MX-Info1-EXT-SV Info Module With LEDs, Silver Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	4047438015035 19,6 cm 85414900 15,0 cm 282 g 9,0 cm 2,6 l
	MX-Info1-EXT-DG Info Module With LEDs, Dark Gray Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	4047438015028 19,6 cm 85414900 15,0 cm 282 g 9,0 cm 2,6 l
	MX-Info1-EXT-BL Info Module With LEDs, Black Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	4047438015011 19,6 cm 85414900 15,0 cm 282 g 9,0 cm 2,6 l

MX-DoorMaster

Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-Door2-INT-ON-PW	4047438021876 14,8 cm
	DoorMaster For On-Wall Mounting	85363010 9,8 cm
		412 g 9,0 cm
		1,3 l
Security Door Opener with integrated access code memory for on-wall mounting • Complete set including DoorMaster module, on-wall housing, three device frames, neutral housing covering, battery pack and mounting parts • Suitable for: IP Video Door Station with T2x and S1x as door camera • Built-in backup power supply (battery) for access modules • Doorbell • Direct connection and power supply for electric Door Opener und door sensors • Interface und power supply: MxBus • Two status LEDs, two function buttons, integrated • Speaker (doorbell) • Two galvanically separated inputs (AC/DC, selfpowered • up to 48 V) • Isolated relay output (AC/DC, 24 V/1 A) or port for standard door openers (6 to 12 V AC) • Outlet for MOBOTIX anti theft protection (12 V DC) • Protection class: IP20 • Ambient temperature: -5 to 40 °C / 23 to 104 °F • Color: white		
	MX-Door2-INT-PW	4047438019934 14,8 cm
	DoorMaster For In-Wall Mounting	85363010 9,8 cm
		322 g 9,0 cm
		1,3 l
Security door opener with internal access code memory: A MOBOTIX door station may be coupled with the MOBOTIX MX-DoorMaster, making it impossible to open the door by forcibly removing the system and bypassing the connecting cable • 2nd product generation, suitable for: IP video door stations with an T2x and S1x as door camera • Integrated (rechargeable) battery power supply for access modules • Security door opener/bell with access code storage (protected against manipulation) • Connection for door opener, door sensor and door lock sensor • Interface and power supply: MxBus (max. 50 m distance to door station) • User interfaces: 2 status LEDs, 2 function buttons, integrated speaker (doorbell) • Inputs: 2 galvanically separated inputs with shared ground connection (AC/DC, self-powered up to 48 V) • Outputs: 1 isolated relay output (AC/DC, 24 V/1 A) or 1 connector for standard door opener (6 to 12 V AC), 1 output for MOBOTIX theft protection (12 V DC) • Protection class: IP20 (DIN EN 60529) • Operating temperature: -5 to 40°C / 23 to 104°F (DIN EN 50155) • Switch time: max. 5 s		


Access Control Accessories


	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-FrogDisplay	4047438041324	14,0 cm
	frogblue Display Indoor Station	85285291	13,0 cm
	frogblue Display for MOBOTIX Doorstation T26	220 g	6,0 cm
			1,1 l

Building Automation Accessories

Article No. / Name / Description	EAN / HS / weight	dimen.
 MX-AdminCard1 Admin RFID Transponder Card (Red) For system configuration IP Video Door Station via KeypadRFID and BellRFID • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	4047438015288 85235200 2 g	8,5 cm 5,5 cm 0,1 cm 0,0 l
 MX-UserCard1 User RFID Transponder Card (Blue) For keyless entry via with KeypadRFID or BellRFID (IP video door station) • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	4047438015295 85235200 2 g	8,5 cm 5,5 cm 0,1 cm 0,0 l
 MX-OPT-IO1 Extended Terminal Board (IO Module) Suitable for: T2x, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).	4047438013307 85299065 86 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 MX-OPT-IO2 Ethernet Terminal Board Suitable for: T2x • The Ethernet terminal board is used to connect the door station for the versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module	4047438014786 85299065 60 g	9,8 cm 7,5 cm 9,0 cm 0,7 l


Frames & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-OPT-Box-1-EXT-IN-US	4047438034463	14,5 cm
	Single In-Wall-Housing (USA version)	90079100	13,5 cm
	Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	186 g	3,5 cm
			0,7 l
	Mx-OPT-Box-2-EXT-IN-US	4047438034470	23,5 cm
	Double In-Wall-Housing (USA version)	90079100	13,5 cm
	Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	270 g	3,5 cm
			1,1 l
	Mx-OPT-Box-3-EXT-IN-US	4047438034487	33,5 cm
	Triple In-Wall-Housing (USA version)	90079100	13,5 cm
	Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	362 g	3,5 cm
			1,6 l
	MX-OPT-Frame-1-EXT-PW	4047438014892	13,5 cm
	Single Frame, White	90079100	14,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White	268 g	5,5 cm
			1,1 l
	MX-OPT-Frame-1-EXT-SV	4047438014939	13,5 cm
	Single Frame, Silver	90079100	14,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver	268 g	5,5 cm
			1,1 l

**MX-OPT-Frame-1-EXT-DG****Single Frame, Dark Gray**

Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection •
Includes special key for module unlocking, housing gasket and installation material •
Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Dark Gray

4047438014922	13,5 cm
90079100	14,5 cm
268 g	5,5 cm
	1,1 l

**MX-OPT-Frame-1-EXT-BL****Single Frame, Black**

Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection •
Includes special key for module unlocking, housing gasket and installation material •
Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Black

4047438014915	13,5 cm
90079100	14,5 cm
268 g	5,5 cm
	1,1 l

**MX-OPT-Box-1-EXT-ON-PW****Single On-Wall-Housing, White**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White

4047438015202	14,5 cm
90079100	13,5 cm
286 g	3,5 cm
	0,7 l

**MX-OPT-Box-1-EXT-ON-SV****Single On-Wall-Housing, Silver**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver

4047438015240	14,5 cm
90079100	13,5 cm
286 g	3,5 cm
	0,7 l

**MX-OPT-Box-1-EXT-ON-DG****Single On-Wall-Housing, Dark Gray**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Dark Gray

4047438015233	14,5 cm
90079100	13,5 cm
286 g	5,0 cm
	1,0 l

**MX-OPT-Box-1-EXT-ON-BL****Single On-Wall-Housing, Black**


Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Black

4047438015226	14,5 cm
90079100	13,5 cm
286 g	3,5 cm
	0,7 l

**MX-OPT-Box-1-EXT-IN****Single In-Wall-Housing**


Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

4047438015271	14,5 cm
90079100	13,5 cm
186 g	3,5 cm
	0,7 l

**MX-OPT-Frame-2-EXT-PW****Double Frame, White**


Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White

4047438014847	23,5 cm
90079100	13,5 cm
333 g	3,5 cm
	1,1 l

**MX-OPT-Frame-2-EXT-SV****Double Frame, Silver**


Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver

4047438014885	23,5 cm
90079100	13,5 cm
333 g	3,5 cm
	1,1 l

**MX-OPT-Frame-2-EXT-DG****Double Frame, Dark Gray**

Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray

4047438014878	23,5 cm
90079100	13,5 cm
333 g	5,0 cm
	1,6 l

**MX-OPT-Frame-2-EXT-BL****Double Frame, Black**

Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black

4047438014861	23,5 cm
90079100	13,5 cm
333 g	3,5 cm
	1,1 l

**MX-OPT-Box-2-EXT-ON-PW****Double On-Wall-Housing, White**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White

4047438015158	23,5 cm
90079100	13,5 cm
430 g	3,5 cm
	1,1 l

**MX-OPT-Box-2-EXT-ON-SV****Double On-Wall-Housing, Silver**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver

4047438015196	23,5 cm
90079100	13,5 cm
430 g	3,5 cm
	1,1 l

**MX-OPT-Box-2-EXT-ON-DG****Double On-Wall-Housing, Dark Gray**


Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray

4047438015189	23,5 cm
90079100	13,5 cm
430 g	3,0 cm
	1,0 l

**MX-OPT-Box-2-EXT-ON-BL****Double On-Wall-Housing, Black**


Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black

4047438015172	23,5 cm
90079100	13,5 cm
430 g	3,5 cm
	1,1 l

**MX-OPT-Box-2-EXT-IN****Double In-Wall-Housing**


Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

4047438015264	23,5 cm
90079100	13,5 cm
270 g	3,5 cm
	1,1 l

**MX-OPT-Frame-3-EXT-PW****Triple Frame, White**


Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: White

4047438014793	33,5 cm
90079100	13,5 cm
426 g	5,5 cm
	2,5 l

**MX-OPT-Frame-3-EXT-SV****Triple Frame, Silver**

Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Silver

4047438014830	33,5 cm
90079100	13,5 cm
426 g	5,5 cm
	2,5 l

**MX-OPT-Frame-3-EXT-DG****Triple Frame, Dark Gray**

Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Dark Gray

4047438014823	33,5 cm
90079100	13,5 cm
426 g	5,0 cm
	2,3 l

**MX-OPT-Frame-3-EXT-BL****Triple Frame, Black**

Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Black

4047438014816	33,5 cm
90079100	13,5 cm
426 g	5,5 cm
	2,5 l

**MX-OPT-Box-3-EXT-ON-PW****Triple On-Wall-Housing, White**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White

4047438015103	33,5 cm
90079100	13,5 cm
574 g	3,5 cm
	1,6 l

**MX-OPT-Box-3-EXT-ON-SV****Triple On-Wall-Housing, Silver**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver

4047438015141	33,5 cm
90079100	13,5 cm
574 g	3,5 cm
	1,6 l

**MX-OPT-Box-3-EXT-ON-DG****Triple On-Wall-Housing, Dark Gray**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray

4047438015134	33,5 cm
90079100	13,5 cm
574 g	3,0 cm
	1,4 l

**MX-OPT-Box-3-EXT-ON-BL****Triple On-Wall-Housing, Black**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black

4047438015127	33,5 cm
90079100	13,5 cm
574 g	3,5 cm
	1,6 l

**MX-OPT-Box-3-EXT-IN****Triple In-Wall-Housing**


Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

4047438015257	33,5 cm
90079100	13,5 cm
362 g	3,5 cm
	1,6 l

**MX-OPT-FlatMount-EXT-PW****FlatMount Frame, white**


For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white

4047438019811	14,7 cm
90079100	13,7 cm
190 g	5,5 cm
	1,1 l

**MX-OPT-FlatMount-EXT-BL****FlatMount Frame, black**

For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: black

4047438019835	14,7 cm
90079100	13,7 cm
190 g	5,5 cm
	1,1 l

**MX-OPT-FlatMount-Box-EXT-IN****FlatMount Frame In-Wall Housing**

In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm

4047438019866	13,8 cm
90079100	6,5 cm
130 g	13,8 cm
	1,2 l

Software & Services

BeyondHumanVision

MOBOTIX

MOBOTIX HUB Video Management System

MOBOTIX HUB

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-HUB-L1-BAS	4047438039208	cm
	L1 Base License (8 Device Licenses incl) MOBOTIX HUB L1 is available as a free version. The license includes the basic license and device license with the support of up to eight cameras	g	cm l
	Mx-HUB-L2-BAS	4047438038584	cm
	MOBOTIX HUB L2 Base License (BL) MOBOTIX HUB L2 for smaller companies with one location manages up to 48 surveillance cameras	g	cm l
	Mx-HUB-L2-DEV	4047438038591	cm
	MOBOTIX HUB L2 Device License (DL) Device licenses for MOBOTIX HUB L2. Up to 48 device licenses can be linked to the HUB L2	g	cm l
	Mx-HUB-L2-1MDEV	4047438039215	cm
	1 Month Advanced Services for MOBOTIX HUB L2 Device 1 month MOBOTIX HUB L2 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L2 Advanced Service for 1, 2, 3 and 5 years.	g	cm l
	Mx-HUB-L2-1YDEV	4047438038607	cm
	One year MOBOTIX HUB Advanced Services for L2 Device 1 Year MOBOTIX HUB L2 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.	g	cm l

**Mx-HUB-L2-2YDEV**

4047438038614

cm

Two years MOBOTIX HUB Advanced Services for L2 Device

2 Year MOBOTIX HUB L2 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L2-3YDEV**

4047438038621

cm

Three years MOBOTIX HUB Advanced Services for L2 Device

3 Year MOBOTIX HUB L2 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L2-5YDEV**

4047438038638

cm

Five years MOBOTIX HUB Advanced Services for L2 Device

5 Year MOBOTIX HUB L2 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L2-3YOPT-DEV**

4047438039031

cm

Three years opt-in MOBOTIX HUB Advanced Services for L2

The MOBOTIX HUB Advanced Service Opt-In for HUB L2 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L2 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

l

**Mx-HUB-L2-UP-BASWO**

4047438039277

cm

Version Upgrade HUB L2 BL w/o ASP

Software update for MOBOTIX HUB L2 base licenses that are not in possession of an Advanced Service Product.

g

cm

l

**Mx-HUB-L2-UP-DEVWO**

4047438039284

cm

Version Upgrade HUB L2 DL w/o ASP

Software update for MOBOTIX HUB L2 device licenses that are not in possession of an Advanced Service Product.

g

cm

l

**Mx-HUB-L3-BAS**

4047438038645

cm

MOBOTIX HUB L3 Base License (BL)

MOBOTIX HUB L3 is the solution for medium-sized companies. The number of cameras is unlimited and can be distributed across multiple locations.

g

cm

l

**Mx-HUB-L3-DEV**

4047438038652

cm

MOBOTIX HUB L3 Device License (DL)

Device licenses for MOBOTIX HUB L3. Unlimited number of devices can be integrated into one L3 installation.

g

cm

cm

l

**Mx-HUB-L3-1MDEV**

4047438039222

cm

1 Month Advanced Services for MOBOTIX HUB L3 Device

1 month MOBOTIX HUB L3 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L3 Advanced Service for 1, 2, 3 and 5 years.

g

cm

cm

l

**Mx-HUB-L3-1YDEV**

4047438038669

cm

One year MOBOTIX HUB Advanced Services for L3 Device

1 Year MOBOTIX HUB L3 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm

l

**Mx-HUB-L3-2YDEV**

4047438038676

cm

Two years MOBOTIX HUB Advanced Services for L3 Device

2 Year MOBOTIX HUB L3 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm

l

**Mx-HUB-L3-3YDEV**

4047438038683

cm

Three years MOBOTIX HUB Advanced Services for L3 Device

3 Year MOBOTIX HUB L3 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm

l

**Mx-HUB-L3-5YDEV**

4047438038690

cm

Five years MOBOTIX HUB Advanced Services for L3 Device

cm

5 Year MOBOTIX HUB L3 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm
l**Mx-HUB-L3-3YOPT-DEV**

4047438039048

cm

Three years opt-in MOBOTIX HUB Advanced Services for L3

cm

The MOBOTIX HUB Advanced Service Opt-In for HUB L3 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L3 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm
l**Mx-HUB-TRAD-BAS-L2-L3-W**

4047438039369

cm

Trade-in BL L2->L3 w/ ASP

cm

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).

g

cm
l**Mx-HUB-TRAD-DEV-L2-L3-W**

4047438039376

cm

Trade-in DL L2->L3 w/ ASP

cm

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).

g

cm
l**Mx-HUB-TRAD-BAS-L2-L3-WO**

4047438039383

cm

Trade-in BL L2->L3 w/o ASP

cm

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).

g

cm
l**Mx-HUB-TRAD-DEV-L2-L3-WO**

4047438039390

cm

Trade-in DL L2->L3 w/o ASP

cm

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).

g

cm
l

**Mx-HUB-L3-UP-BASWO**

4047438039291

cm

Version Upgrade HUB L3 BL w/o ASP

Software update for MOBOTIX HUB L3 base licenses that are not in possession of an Advanced Service Product.

g

cm

cm
l**Mx-HUB-L3-UP-DEVWO**

4047438039307

cm

Version Upgrade HUB L3 DL w/o ASP

Software update for MOBOTIX HUB L3 device licenses that are not in possession of an Advanced Service Product.

g

cm

cm
l**Mx-HUB-L4-BAS**

4047438038706

cm

MOBOTIX HUB L4 Base License (BL)

MOBOTIX HUB L4 is made for medium and large installations. In addition to the features of MOBOTIX HUB L3, L4 provides access to failover recording servers in case of server failure. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.

g

cm

cm
l**Mx-HUB-L4-DEV**

4047438038713

cm

MOBOTIX HUB L4 Device License (DL)

Device licenses for MOBOTIX HUB L4. Unlimited number of devices can be integrated into one L4 installation. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.

g

cm

cm
l**Mx-HUB-L4-1MBAS**

4047438039239

cm

1 Month Advanced Services for MOBOTIX HUB L4 Base

1 month MOBOTIX HUB L4 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.

g

cm

cm
l**Mx-HUB-L4-1YBAS**

4047438038720

cm

One year MOBOTIX HUB Advanced Services for L4 Base

1 year MOBOTIX HUB L4 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l

**Mx-HUB-L4-2YBAS**

4047438038737

cm

Two years MOBOTIX HUB Advanced Services for L4 Base

2 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L4-3YBAS**

4047438038744

cm

Three years MOBOTIX HUB Advanced Services for L4 Base

3 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L4-5YBAS**

4047438038751

cm

Five years MOBOTIX HUB Advanced Services for L4 Base

5-year MOBOTIX HUB L4 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L4-3YOPT-BAS**

4047438039055

cm

Three years opt-in MOBOTIX HUB Advanced Services for L4

The MOBOTIX HUB Advanced Service Opt-In for HUB L4 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

l

**Mx-HUB-L4-1MDEV**

4047438039246

cm

1 Month Advanced Services for MOBOTIX HUB L4 Device

1 month MOBOTIX HUB L4 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.

g

cm

l

**Mx-HUB-L4-1YDEV**

4047438038768

cm

One year MOBOTIX HUB Advanced Services for L4 Device

1 year MOBOTIX HUB L4 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

l

**Mx-HUB-L4-2YDEV**

4047438038775

cm

Two years MOBOTIX HUB Advanced Services for L4 Device

2 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L4-3YDEV**

4047438038782

cm

Three years MOBOTIX HUB Advanced Services for L4 Device

3 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L4-5YDEV**

4047438038799

cm

Five years MOBOTIX HUB Advanced Services for L4 Device

5-year MOBOTIX HUB L4 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L4-3YOPT-DEV**

4047438039062

cm

Three years opt-in MOBOTIX HUB Advanced Services for L4

The MOBOTIX HUB Advanced Service Opt-In for HUB L4 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

l

**Mx-HUB-TRAD-BAS-L2-L4-W**

4047438039406

cm

Trade-in BL L2->L4 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-DEV-L2-L4-W**

4047438039413

cm

Trade-in DL L2->L4 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-BAS-L2-L4-WO**

4047438039420

cm

Trade-in BL L2->L4 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-DEV-L2-L4-WO**

4047438039437

cm

Trade-in DL L2->L4 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L3-L4-W**

4047438039444

cm

Trade-in BL L3->L4 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L3-L4-W**

4047438039451

cm

Trade-in DL L3->L4 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L3-L4-WO**

4047438039468

cm

Trade-in BL L3->L4 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L3-L4-WO**

4047438039475

cm

Trade-in BL L3->L4 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-L4-UP-BASWO**

4047438039314

cm

Version Upgrade HUB L4 BL w/o ASP

Software update for MOBOTIX HUB L4 base licenses that are not in possession of an Advanced Service Product.

g

cm

l

**Mx-HUB-L4-UP-DEVWO**

4047438039321

cm

Version Upgrade HUB L4 DL w/o ASP

Software update for MOBOTIX HUB L4 device licenses that are not in possession of an Advanced Service Product.

g

cm

cm

l

**Mx-HUB-L5-BAS**

4047438038805

cm

MOBOTIX HUB L5 Base License (BL)

MOBOTIX HUB L5 is the video management platform for large and extremely security-oriented applications. In addition to centralized management of all servers, cameras and users across multiple sites, L5 also includes control for a professional video wall as standard. The use of MOBOTIX HUB L5 requires an Advanced Service (base + devices) of at least one year.

g

cm

cm

l

**Mx-HUB-L5-DEV**

4047438038812

cm

MOBOTIX HUB L5 Device License (DL)

Device licenses for MOBOTIX HUB L5. Unlimited number of devices can be integrated into one L5 installation.

g

cm

cm

l

**Mx-HUB-L5-INTCON**

4047438038829

cm

MOBOTIX HUB Interconnect Device License (DL)

Interconnect licenses for MOBOTIX HUB L5. Unlimited number of Interconnect licenses can be used into one L5 installation.

g

cm

cm

l

**Mx-HUB-L5-1MBAS**

4047438039253

cm

1 Month Advanced Services for MOBOTIX HUB L5 Base

1 month MOBOTIX HUB L5 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.

g

cm

cm

l

**Mx-HUB-L5-1YBAS**

4047438038836

cm

One year MOBOTIX HUB Advanced Services for L5 Base

1 year MOBOTIX HUB L5 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L5-2YBAS**

4047438038843

cm

Two years MOBOTIX HUB Advanced Services for L5 Base

2 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L5-3YBAS**

4047438038850

cm

Three years MOBOTIX HUB Advanced Services for L5 Base

3 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L5-5YBAS**

4047438038867

cm

Five years MOBOTIX HUB Advanced Services for L5 Base

5-year MOBOTIX HUB L5 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

l

**Mx-HUB-L5-3YOPT-BAS**

4047438039079

cm

Three years opt-in MOBOTIX HUB Advanced Services for L5

The MOBOTIX HUB Advanced Service Opt-In for HUB L5 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

l

**Mx-HUB-L5-1MDEV**

4047438039260

cm

1 Month Advanced Services for MOBOTIX HUB L5 Device

1 month MOBOTIX HUB L5 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.

g

cm

l

**Mx-HUB-L5-1YDEV**

4047438038874

cm

One year MOBOTIX HUB Advanced Services for L5 Device

1 year MOBOTIX HUB L5 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

l

**Mx-HUB-L5-2YDEV**

4047438038881

cm

Two years MOBOTIX HUB Advanced Services for L5 Device

2 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

l

**Mx-HUB-L5-3YDEV**

4047438038898

cm

Three years MOBOTIX HUB Advanced Services for L5 Device

3 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

l

**Mx-HUB-L5-5YDEV**

4047438038904

cm

Five years MOBOTIX HUB Advanced Services for L5 Device

5-year MOBOTIX HUB L5 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

l

**Mx-HUB-L5-3YOPT-DEV**

4047438039086

cm

Three years opt-in MOBOTIX HUB Advanced Services for L5

The MOBOTIX HUB Advanced Service Opt-In for HUB L5 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

l

**Mx-HUB-TRAD-BAS-L2-L5-W**

4047438039482

cm

Trade-in BL L2->L5 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-DEV-L2-L5-W**

4047438039499

cm

Trade-in DL L2->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-BAS-L2-L5-WO**

4047438039505

cm

Trade-in BL L2->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L2-L5-WO**

4047438039512

cm

Trade-in DL L2->L5 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L3-L5-W**

4047438039529

cm

Trade-in BL L3->L5 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L3-L5-W**

4047438039536

cm

Trade-in DL L3->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L3-L5-WO**

4047438039543

cm

Trade-in BL L3->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L3-L5-WO**

4047438039550

cm

Trade-in DL L3->L5 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which not are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-BAS-L4-L5-W**

4047438039567

cm

Trade-in BL L4->L5 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L4-L5-W**

4047438039574

cm

Trade-in DL L4->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L4-L5-WO**

4047438039581

cm

Trade-in BL L4->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L4-L5-WO**

4047438039598

cm

Trade-in DL L4->L5 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which not are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-L5-UP-BASWO**

4047438039338

cm

Version Upgrade HUB L5 BL w/o ASP

Software update for MOBOTIX HUB L5 base licenses that are not in possession of an Advanced Service Product

g

cm

cm

l

**Mx-HUB-L5-UP-DEVWO**

4047438039345

cm

Version Upgrade HUB L5 DL w/o ASP

Software update for MOBOTIX HUB L5 device licenses that are not in possession of an Advanced Service Product

g

cm

cm
l**Mx-HUB-L5-UP-INTWO**

4047438039352


cm

Version Upgrade HUB L5 Intercon. DL w/o ASP

Software update for MOBOTIX HUB L5 interconnect licenses that are not in possession of an Advanced Service Product

g

cm

cm
l**Mx-HUB-ACC-WALL**

4047438039116


cm

MOBOTIX HUB Video Wall Base License (BL)

MOBOTIX HUB Video Wall is an advanced add-on video wall product that improves response time by displaying all the video data in your installation and giving a complete overview of large surveillance centers.

g

cm

cm
l**Mx-HUB-ACC-WALL-UP**

4047438039604


cm

Version Upgrade HUB Video Wall BL w/o ASP

Software update for MOBOTIX HUB Video Wall license that are not in possession of an Advanced Service Product

g

cm

cm
l**Mx-HUB-ACS-BASE**

4047438039178


cm

MOBOTIX HUB Access Base License (BL)

MOBOTIX HUB Access is an Add-on product that video enables physical security through integration of access control and intrusion systems

g

cm

cm
l**Mx-HUB-ACS-BASE-UP**

4047438039611

cm


Version Upgrade HUB Access BL w/o ASP

Software update for MOBOTIX HUB Access Basic license, which are not in possession of an Advanced Service product.

g

cm


cm
l

**Mx-HUB-ACS-DOOR****MOBOTIX HUB Access Door License (DL)**

Device license for MOBOTIX HUB Access.

4047438039185


g

cm
cm
cm
l**Mx-HUB-ACS-DOOR-UP****Version Upgrade HUB Access DL w/o ASP**

Software Update for MOBOTIX HUB Access Devices License, which are not in possession of an Advanced Service Product.

4047438039628


g

cm
cm
cm
l**Mx-HUB-XP-TRA-BAS****Xprotect Transaction Base License Server incl. 1 Connection**

XProtect Transact Base Server incl. 1 Connection License. XProtect Transact video enables different types of transaction-based processes. Combining transaction data from point of sales systems, scanners, cash point machines, or similar systems with corresponding video, XProtect Transact enables real-time monitoring, exception handling and documentation of transactions.

4047438039154


g

cm
cm
cm
l**Mx-HUB-XP-TRA-BAS-UP****Version Upgrade Xprotect Transaction BL w/o ASP**

Software Update for XProtect Transaction Base License, which are not in possession of an Advanced Service Product.

4047438039635


g

cm
cm
cm
l**Mx-HUB-XP-TRA-CON****Xprotect Transaction Connection License**

Connection licence for Xprotect Transact.

4047438039161

g

cm
cm
cm
l**Mx-HUB-XP-TRA-CON-UP****Version Upgrade Xprotect Transaction CL w/o ASP**

Software update for XProtect Transaction Connection license, which are not in possession of an Advanced Service Product

4047438039642

g

cm
cm
cm
l

**Mx-HUB-XP-LPR-BAS**

4047438039123

cm

Xprotect LPR Base License incl. 5 Country Modules

XProtect LPR Base License, incl. 5 Country Modules. XProtect LPR is license plate recognition (LPR) software that detects license plate information from any vehicle around the world and links the license plate number with video.

g

cm

l

**Mx-HUB-XP-LPR-BAS-UP**

4047438039659

cm

Version Upgrade Xprotect LPR BL w/o ASP

Software update for XProtect LPR Basic license, which are not in possession of an Advanced Service Product.

g

cm

cm

l

**Mx-HUB-XP-LPR-DEV**

4047438039130

cm

XProtect LPR Device License (DL)

Device licence for Xprotect LPR.

g

cm

cm

l

**Mx-HUB-XP-LPR-DEV-UP**

4047438039666

cm

Version Upgrade Xprotect LPR DL w/o ASP

Software update for XProtect LPR devices license, which are not in possession of an Advanced Service Product.

g

cm

cm

l

**Mx-HUB-XP-LPR-CTY**

4047438039147

cm

Xprotect LPR Country Modul

Country modul for Xprotect LPR.

g

cm

cm

l

**Mx-HUB-XP-LPR-CTY-UP**

4047438039673

cm

Version Upgrade Xprotect LPR CM w/o ASP

Software update for XProtect LPR Country Module not in possession of an Advanced Service Product.

g

cm

cm

l

MxManagementCenter and Additional Licences

ONVIF-compliant Video Managemnt System

MxManagementCenter (MxMC) is a powerful, intuitive video management system for Windows and macOS systems. MxMC can be utilized for projects and security installations of all sizes and with any number of cameras or storage media. It was designed to be user-friendly, high-performing and secure.

Please follow this link for further license-related informations: <https://www.mobotix.com/de/support/download-center/software-downloads/lizenz-portal>

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-SW-MC-ADCON-VM	4047438035071	0,0 cm
	MxMC Advanced Config License for virtual machines (VM)		0,0 cm
	Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required) • released for virtual machines (VM)	0 g	0,0 cm
			0,0 l
	Mx-SW-MC	4047438034456	0,0 cm
	MxManagementCenter VMS For Windows/macOS		0,0 cm
	Free-of-charge MOBOTIX video management software MxManagementCenter (MxMC) • Certified ONVIF conformity (Profile S) • Versions 2.2 for Windows (Windows 8 or later) or macOS (10.12 or higher) • Language packs: English, German, French, Spanish, Italian, Russian, Turkish, Portuguese, Japanese • System requirements: 2 GHz processor (min.), at least 2 GB RAM, video card with support for OpenGL V2.1 • Download free of charge: www.mobotix.com > Support > Download Center > Software Downloads > Cameras > MxManagementCenter	0 g	0,0 cm
			0,0 l
	Mx-SW-MC-ADCON	4047438034197	0,0 cm
	MxMC Advanced Config License		0,0 cm
	Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	0 g	0,0 cm
			0,0 l
	Mx-SW-MC-STARTER	4047438034142	0,0 cm
	MxMC Integration Starter License		0,0 cm
	MOBOTIX license for the general use of H.264 with a MxMC workstation (as of MxMC 2.0) for live images, playback and/or export • Unlimited number of users per workstation • No time limit for use • One additional video channel for a third-party ONVIF-S camera included • Download via external license portal (access data required)	0 g	0,0 cm
			0,0 l
	Mx-SW-MC-CHAN	4047438034159	0,0 cm
	MxMC Integration Channel License		0,0 cm
	MOBOTIX license for using an additional video channel from an external ONVIF S compliant IP camera with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	0 g	0,0 cm
			0,0 l

**Mx-SW-MC-SDATA**

4047438034449

0,0 cm

MxMC Smart Data License


MOBOTIX license for connecting an external data source (Smart Data Source) to a MxMC workstation (as of MxMC 2.1) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

0 9

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-POS**

4047438031615

0,0 cm

MxMC POS Single Cash Point License

MOBOTIX license for connecting a cash register to a MxMC workstation (as of MxMC 1.7) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

0 9

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-AS-1**

4047438034166

0,0 cm

MxMC Advanced Service License, 1 Year

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 1 year/12 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0 9

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-AS-2**

4047438034173

0,0 cm

MxMC Advanced Service License, 2 Years

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 2 years/24 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0 9

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-AS-5**

4047438034180

0,0 cm

MxMC Advanced Service License, 5 Years

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 5 years/60 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0 9

0,0 cm

0,0 cm

0,0 l

Certified Apps for MOBOTIX 7

Certified Apps for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-APP-AI-B-FIR	4047438035279	cm
	Bundle of A.I. Tech Fire & Smoke Apps		cm
	Bundle of A.I. Tech Fire & Smoke Apps: AI-FIRE + AI-SMOKE	g	cm
			l
	Mx-APP-AI-B-RET	4047438035262	cm
	Bundle of A.I. Tech Retail Apps		cm
	Bundle of A.I. Tech Retail Apps: AI-PEOPLE, AI-HEAT, AI-OCCUPANCY, AI-OVEROCCUPANCY, AI-CROWD and AI-OVERCROWD	g	cm
			l
	Mx-APP-AI-B-SEC	4047438035248	cm
	Bundle of A.I. Tech Security Apps		cm
	Bundle of A.I. Tech Security Apps: AI-INTRUSION-PRO + AI-LOITERING + AI-LOST	g	cm
			l
	Mx-APP-AI-B-TRA	4047438035255	cm
	Bundle of A.I. Tech Traffic Apps		cm
	Bundle of A.I. Tech Traffic Apps: AI-ROAD3D and AI-INCIDENT	g	cm
			l
	Mx-APP-AI-BIO	4047438035132	cm
	AI-Bio Certified App		cm
	Biometric analysis of gender, age and length of stay of customers/visitors as a basis for customer and stock management in the retail sector.	g	cm
			l

**Mx-APP-AI-CRO**

4047438035118


cm

AI-Crowd Certified App

Appraises the number of people in busy areas, recognizes queue situations, among other things.

g

cm

cm
l**Mx-APP-AI-CRO-D**

4047438037334

cm

AI-Crowd Deep Certified App

Estimation of number of people within a monitored area (indoor / outdoor) • Identification of overcrowded areas based on a defined threshold • Real-time monitoring of Social Distance • MOBOTIX events via MxMessageSystem • Statistical analysis via embedded Dashboard • Research via MxMC Smart Data Interface

g

cm

cm
l**Mx-APP-AI-CROP**

4047438037341

cm

AI-Crowd Plus Certified App

A.I. Tech Crowd / Overcrowd bundle including the following features: • Estimation of number of people within a monitored area (indoor / outdoor) • Identification of overcrowded areas based on a defined threshold • MOBOTIX events via MxMessageSystem • Statistical analysis via embedded Dashboard • Research via MxMC Smart Data Interface

g

cm

cm
l**Mx-APP-AI-FD-D**

4047438037327

cm

AI-Facedetect Deep Certified App

A.I. Tech Face Detection App including the following features: • Detection of faces within the live stream • People counting based on face detection • Detection of persons wearing masks / not wearing masks (e.g. mouth-nose-protection) • MOBOTIX events via MxMessageSystem • Statistical analysis via embedded Dashboard • Research via MxMC Smart Data Interface

g

cm

cm
l**Mx-APP-AI-FIRE**

4047438035187

cm

AI-Fire Certified App

Early detection of flames indoors and outdoors (e.g., vehicles, containers). No thermal sensor required.

g

cm

cm
l**Mx-APP-AI-HEA**

4047438035293

cm

AI-Heat Certified App

Classifies most visited areas (hot spots) and the less crowded ones (dead areas) depending on the time spent by people inside.

g

cm

cm
l

**Mx-APP-AI-INC**

4047438035224

cm

AI-Incident Certified App

Traffic monitoring: Presence of pedestrians, vehicles stopping, queues or vehicles in the wrong direction.

g

cm

l

**Mx-APP-AI-INTP**

4047438035156

cm

AI-Intrusion-PRO Certified App

Shows intruders crossing a sequence of virtual lines. Setting multiple lines increases the reliability of anti-intrusion systems.

g

cm

cm

l

**Mx-APP-AI-LOI**

4047438035170

cm

AI-Loitering Certified App

Detects suspicious behaviour of people who stay in certain areas for a longer period of time.

g

cm

cm

l

**Mx-APP-AI-LOS**

4047438035163

cm

AI-Lost Certified App

Detects stray luggage and other objects (e.g. garbage) as well as the removal of objects (e.g. paintings in museums).

g

cm

cm

l

**Mx-APP-AI-OCC**

4047438035095

cm

AI-Occupancy Certified App

Detects „Hot Spots“ and „Dead Areas“ in defined areas.

g

cm

cm

l

**Mx-APP-AI-OVER**

4047438035125

cm

AI-Overcrowd Certified App

Identifies crowded areas based on user-defined thresholds (number of people).

g

cm

cm

l

**Mx-APP-AI-OVERO****AI-Overoccupancy Certified App**

Identifies the occupancy rate in defined areas and detects overoccupied zones.

4047438035101

g

cm

cm

cm

l

**Mx-APP-AI-PAR-D****AI-Parking Certified App**

Classification of vehicles. Detects whether and how many parking spaces are free or occupied.

4047438035231

g

cm

cm

cm

l

**Mx-APP-AI-PEO****AI-People Certified App**

Counts people crossing a virtual line (e.g. door/corridor) in a certain direction.

4047438035088

g

cm

cm

cm

l

**Mx-APP-AI-ROA3****AI-Road3D Certified App**

Traffic monitoring: Detection, tracking and counting of vehicles (behavior, traffic density, type [trucks, cars, cycles]). Identifies vehicles that are too fast.

4047438035217

g

cm

cm

cm

l

**Mx-APP-AI-SMO****AI-Smoke Certified App**

Smoke detection inside and outside. No thermal sensor required.

4047438035194

g

cm

cm

cm

l

**Mx-APP-AI-SPI****AI-Spill Certified App**

Detects situations when people fall and remain on the ground.

4047438035200

g

cm

cm

cm

l

**Mx-APP-FF-LPR-AM**

4047438037822

cm


FF Group License Plate Recognition App Region Americas

FF Group License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • Recognition of latin characters optimized for American license plates • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem

g

cm

l

**Mx-APP-FF-LPR-EUCA**

4047438036474

cm

FF Group License Plate Recognition App Region EUCA

FF Group License Plate Recognition App including the following features: License plate recognition of one- and two-line license plates • Recognition log • MOBOTIX events via MxMessageSystem • Country coverage: ALB, AUT, BEL, BIH, BGR, HRV, CYP, CZE, DNK, EST, FIN, FRA, DEU, GRC, HUN, ISL, ITA, IRL, ISR, LVA, LTU, LUX, MKD, MLT, MNE, NLD, NOR, POL, PRT, ROU, SRB, SVK, SVN, ESP, SWE, CHE, TUR, GBR, VAT, ARM, AZE, BLR, GEO, KAZ, KGZ, MDA, RUS, TJK, TKM, UKR, UZB, AUS, NZL

g

cm

cm

l

**Mx-APP-FF-LPR-ME**

4047438040686

cm

FF Group License Plate Recognition App Region Middle East

FF Group License Plate Recognition App including the following features: • Recognition of one- and two-line license plates • simultaneous recognition on one or more image sensors • Recognition of Latin and Arabic characters • Multiple license plate lists for individual actions (e.g. access granted, alarm, etc.) • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface • meta data transfer through generic transmission protocols

g

cm

cm

l

**Mx-APP-FF-MMCR-EUCA**

4047438037839

cm

FF Group App License Plate, Make, Model and Color

FF Group MMCR App including the following features: • Recognition of one- and two-line license plates • Recognition of Latin and Hebrew characters • Additional recognition of vehicle brand, model, color and type • Multifactor events (e.g. license plate and vehicle brand match) • Recognition protocol (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem

g

cm

cm

l

**Mx-APP-IRIS-ANO**

4047438045230

cm

Irisity Iris Anonymization App

Irisity Iris Anonymization App including the following features: • patented dynamic pixelation of people in the camera's field of view • designed to address GDPR and privacy regulations • Configurable option to force switch to black/white image to ensure maximum privacy • applicable in indoor and outdoor camera operation • pixelation of persons from a minimum height of 20 pixels

g

cm

cm

l

**Mx-APP-IRIS-C-INT**

4047438040693

cm

Irisity Iris Core Intrusion App

Irisity Iris Core Intrusion App including the following features: • Detects the intrusion of objects of interest into user-defined detection zones / areas • Designed for reliable detection of people and vehicles covering only small portions of the field of view • Reduction of false alarms to a minimum by filtering out non-critical motion (e.g. trees, clouds, etc.) • simultaneous detection on one or more image sensors • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB

g

cm

cm

l

**Mx-APP-MX-ARA**

4047438044998

cm

MOBOTIX Advanced Radiometry App

MOBOTIX Advanced Radiometry App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON

g

cm

cm
l**Mx-APP-MX-BAR**

4047438044981


cm

MOBOTIX Barcode Reader App

MOBOTIX Barcode Reader App including the following features: • Reader supports more than 40 common 1D, 2D and Stacked barcode types (e.g. QR Code, Data Matrix Code, Dot Code, etc.) • Optimized for difficult barcode reads (e.g. damaged, faded or distorted barcodes, barcodes on difficult surfaces, DPM codes) • Quick reading of one or multiple barcodes in motion • Definition of up to 20 detection areas within the camera's field of view • MOBOTIX events via MxMessageSystem • reporting of barcode reads via generic XML, JSON and MODBUS/TCP

g

cm

cm
l**Mx-APP-MX-COR**

4047438042567

cm

MOBOTIX Color Recognition App

MOBOTIX Color Recognition including the following features: • Detection of user-specified color values within customized detection areas • Definition of up to 20 detection areas within the camera's field of view • Supports the recognition of all RGB color values • Set sensitivity, required percentage within the defined detection area and duration of the associated condition • MOBOTIX events via MxMessageSystem

g

cm

cm
l**Mx-APP-MX-THD**

4047438045087

cm

MOBOTIX Thermal Heat Detection App

MOBOTIX Thermal Heat Detection App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (according to CNPP France 19005 certification) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • the MOBOTIX Thermal Heat Detection App is required in any case to fulfill the requirements for CNPP France 19005 certification (Thermal Camera Heat Detection Systems)

g

cm

cm
l**Mx-APP-MX-TVA**

4047438045216

cm

MOBOTIX Thermal Validation App

MOBOTIX Thermal Validation App including the following features: • App optimizes MOBOTIX Thermal Radiometry cameras for use in the fields of waste management and logistics • Enables filtering of vehicles (e.g. construction vehicles und forklifts) as a non-critical source of high temperatures (e.g. by measuring hot body parts such as the exhaust or engine cover) • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON / XML via HTTP(S)

g

cm

cm
l

**Mx-APP-VIS-FR-1**

4047438035286


cm

Visage Technologies Face Recognition. 1 Year license

cm

Facial recognition by means of deposited image data. With 97% accuracy for access control applications. 1 year license.

g

cm
l**Mx-APP-VIS-FR-2**

4047438035309

cm

Visage Technologies Face Recognition. 2 Years license

cm

Facial recognition by means of deposited image data. With 97% accuracy for access control applications. 2 year license.

g

cm
l**Mx-APP-VX-ADR**

4047438037815

cm

Vaxtor App License Plate and Dangerous Goods Recognition

cm

Vaxtor App for License Plate and Dangerous Goods Recognition including the following features: • License plate recognition of one- and two-line license plates • read conventional and dangerous good plates simultaneously • support of latin, hebrew and arabic characters for global application • recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and trigger mode for LPR/ADR

g

cm
l**Mx-APP-VX-AIN**

4047438040518

cm

Vaxtor Aircraft Identification Number Recognition App

cm

Vaxtor Aircraft Identification Number Recognition App including the following features: • Recognition of ICAO- and FAA-issued identification numbers • Operations up to a speed of 50 km/h • Real-time results: Aircraft ID, Aircraft Type, Country, etc. • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.)

g

cm
l**Mx-APP-VX-CON**

4047438037938

cm

Vaxtor App for Cargo Container Code Recognition

cm

Vaxtor App for Container Code Recognition including the following features: • Recognition of cargo container codes according to ISO 6346 • Real time results: • Container Code • Property Code • Owner • Container Type • Container Dimensions • Control Digit • Control Digit Validation • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm
l**Mx-APP-VX-GEN**

4047438042543

cm

Vaxtor Generic Optical Character Recognition App

cm

Vaxtor Generic Optical Character Recognition App including the following features: • generic optical character recognition to read any combination of uppercase Latin characters and/or numbers • reads characters arranged in up to three lines • user-defined specification of the required code format • recognition log • MOBOTIX events via MxMessageSystem • numerous integration options for further processing of the generated metadata (generic as well as native reporting interfaces) • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm
l

**Mx-APP-VX-LPR**

4047438037358

cm


Vaxtor License Plate Recognition App

Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • Recognition log • MOBOTIX events via MxMessageSystem • Global country coverage

g

cm

l

**Mx-APP-VX-LPR-M**

4047438040402

cm

Vaxtor License Plate Recognition App (multi-lens)

Vaxtor License Plate Recognition App (multi-lens application) including the following features: • License plate recognition of one- and two-line license plates • simultaneous recognition on one or more image sensors • monitoring the dwell time of license plates in the detection area • support of latin, hebrew and arabic characters for global application • Recognition log • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm

cm

l

**Mx-APP-VX-MMC**

4047438038324

cm

Vaxtor License Plate Recognition App incl. Vehicle Make,

Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • support of latin, hebrew and arabic characters for global application • Additional recognition of vehicle make, model, color and class • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm

cm

l

**Mx-APP-VX-UIC**

4047438040266

cm

Vaxtor App for UIC Railway Code Recognition

Vaxtor App for UIC Railway Code Recognition including the following features: • Recognition of the International Union of Railways Wagon and Coach numbers (UIC Codes) • Real time results: UIC Code, Country Code, Vehicle Type, Control Digit, Direction of travel • Stop / Go and slow speed (<10 km/h) applications (depending on installation and module selection) • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm

cm

l

**Mx-APP-VX-USD**

4047438041638

cm

Vaxtor USDOT Number Recognition App

Vaxtor USDOT Number Recognition App including the following features: • Recognition of USDOT identification numbers • Operations up to a vehicle speed of 50 km/h • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled operation mode



g





cm

cm

l

Desktop Apps

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SW-MC-QNAP QNAP QVR Pro license for activation of MxMC Playback Enables MxMC playback support in the QVR Pro recording software on a QNAP NAS with QTS operating system. • Supports MxMC playback from ONVIF cameras such as the MOVE camera series. • Optimal combination on a QNAP NAS • IOT cameras store independently on the NAS via file sharing (SMB) and record the integrated MOVE or ONVIF cameras in parallel with the QVR Pro Recording Software. The output is done with the MxMC. • The license is activated on the QNAP NAS via the QNAP License Manager. • License is not transferable • one license per QNAP NAS with QVR Pro is required! • For camera recordings, QNAP requires additional camera channel licenses per channel, which must be obtained from QNAP!	4047438047791 g	cm cm cm l
	Mx-SW-XPro-CLOUD-Bas MOBOTIX HUB Plug In - MOBOTIX CLOUD Base License for Activates the MOBOTIX CLOUD support in Milestone XProtect • Main application features in the Smart Client are • Integrating cloud cameras in the desk client layout • Additional CLOUD tab in the application • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License	4047438047876 g	cm cm cm l
	Mx-SW-XPro-CLOUD-Dev MOBOTIX HUB Plug In - MOBOTIX CLOUD Device License for Activates another camera in the MOBOTIX CLOUD support in Milestone XProtect • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX CLOUD Base license • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License	4047438048125 g	cm cm cm l
	Mx-SW-XPro-Config MOBOTIX HUB Plug In - MOBOTIX camera Configuration for Activates the configuration settings for MOBOTIX cameras in Milestone XProtect - Management Client offers camera specific configuration tabs for P3/P6/P7 and MOVE cameras - License is activated via the MOBOTIX License Portal. - License is non-transferable - One license per Milestone • Activates the function for all MOBOTIX cameras registered in the system.	4047438047890 g	cm cm cm l
	Mx-SW-XPro-ForSe MOBOTIX HUB Plug In - ForensicSearch for Milestone Activates the MOBOTIX ForensicSearch filters in Milestone XProtect Smart Client and supports the MOBOTIX event and app meta data for the forensic search - Intelligent search filter reduces the search in the playback to the essential - Search filter for camera apps as well as for MOBOTIX events - Support for camera models P6 / P7 and MOVE LPR models - License is activated via the MOBOTIX License Portal. - License is not transferable - One license per Milestone XProtect VMS is required. - Activates the function for all MOBOTIX cameras registered in the system.	4047438047913 g	cm cm cm l

	Mx-SW-XPro-SYNC-DB-Bas	4047438047852	cm
	MOBOTIX HUB Plug In - MOBOTIX SYNC Base License for	g	cm l
Activates the MOBOTIX SYNC Dashboard in Milestone XProtect Smart Client • Main applications are - Display of statistical values in diagrams • Display of lists of detected number plates • Support for MOBOTIX SYNC and Helix Vaxtor • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone XProtect VMS is required. • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence			
	Mx-SW-XPro-SYNC-DB-Dev	4047438048101	cm
	MOBOTIX HUB Plug In - MOBOTIX SYNC Device License for	g	cm l
Activates another MOBOTIX SYNC Grafana Dashboard in the Milestone XProtect Smart Client. • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX SYNC Base license • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence			
	Mx-SW-XPro-Th-DB-Bas	4047438047838	cm
	MOBOTIX HUB Plug In - ThermalDashboard Base License for	g	cm l
Activates the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Main applications are • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent licence			
	Mx-SW-XPro-Th-DB-Dev	4047438048088	cm
	MOBOTIX HUB Plug In - ThermalDashboard Device License	g	cm l
Activates another camera in the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent licence			
	Mx-SYNC-S-BAS	4047438047548	cm
	MOBOTIX SYNC Server	g	cm l
Store metadata and attached images generated by MOBOTIX Certified Apps (e.g. Vaxtor ALPR / OCR Apps) or other compatible data sources • 4 camera device licenses included • additional camera device licenses via additional license on demand • Monitor incoming license plates / metadata (e.g. plate reads) in real time • Search and filter existing license plates / metadata based on content such as Plate, Country, Camera, Zone, Make, Model, Color, Direction, etc. • Download and export customized license plate lists and search results • Management of cameras includes: • camera zones • manage and synchronize denied & granted license plate list • assign actuators (incl. camera I/Os) • manage data retention policies separately for images and metadata • supports GDPR measures with dedicated reports and data deletion • granular user and group permissions • login management including LDAP integration • audit trail of all interactions on the system including actions made by cameras • Send notifications (e.g. via E-Mail) • SYNC server license with runtime of 3 years after activation			

**Mx-SYNC-S-DEV**

4047438047562

cm

MOBOTIX SYNC Camera Device License

1 camera device license per additional camera device • Enables adding camera devices to the server/client on demand • *4 camera device licenses included in the server base license

g

cm

cm
l**Mx-SYNC-S-CLI**

4047438047579

cm

MOBOTIX SYNC Client

Redundant operation and data storage for applications with discontinuous connection to the server (e.g. mobile applications) • active server connection enables continuous data synchronization

g

cm

cm
l**Mx-SYNC-P-GRA**

4047438047593

cm

MOBOTIX SYNC Grafana Plug-In

Visualization and consolidation of incoming metadata in customized dashboards including: • statistic insights • data queries • annotations • create and manage alerts / post-actions • exports

g

cm

cm
l

Warranty Extensions

Warranty Extensions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-WE-DTVS-1 1 Year Warranty Extension For Dual Thermal Systems S74 5+1 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031974	cm
		g	cm l
	Mx-WE-DTVS-2 2 Years Warranty Extension For Dual Thermal Systems S74 5+2 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031981	cm
		g	cm l
	Mx-WE-DTVS-3 3 Years Warranty Extension For Dual Thermal Systems S74 5+3 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031998	cm
		g	cm l
	Mx-WE-IVS-1 1 Year Warranty Extension For Indoor Video Systems 5+1 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031820	cm
		g	cm l
	Mx-WE-IVS-2 2 Years Warranty Extension For Indoor Video Systems 5+2 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031837	cm
		g	cm l

**Mx-WE-IVS-3****3 Years Warranty Extension For Indoor Video Systems**

5+3 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031844

cm

g

cm

l

**Mx-WE-OVS-1****1 Year Warranty Extension For Outdoor Video Systems**

5+1 Year Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031875

cm

g

cm

cm

l

**Mx-WE-OVS-2****2 Years Warranty Extension For Outdoor Video Systems**

5+2 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031882

cm

g

cm

cm

l

**Mx-WE-OVS-3****3 Years Warranty Extension For Outdoor Video Systems**

5+3 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031899

cm

g

cm

cm

l

**Mx-WE-STVS-1****1 Year Warranty Extension For Single Thermal Systems**

5+1 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031929

cm

g

cm

cm

l

**Mx-WE-STVS-2****2 Years Warranty Extension For Single Thermal Systems**

5+2 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031936

cm

g

cm

cm

l

**Mx-WE-STVS-3****3 Years Warranty Extension For Single Thermal Systems**

5+3 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031943

cm

cm

g

cm

l

Firmware for MOBOTIX IoT Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-FW-VDS-UP	4047438041652	cm
	M16TB Firmware for VDS-compliant fire monitoring		cm
	Firmware for upgrading an M16TB Thermal TR camera including specific accessories to a VdS-approved fire protection solution • For use in environments with increased fire risk, e.g. waste management • Detects critical temperatures • Measuring range between 50 °C and 200°C • Measuring distance 40 m (M16TB-R079), 50 m (M16TB - R119), 60m (M16TB-R237) • Alarm triggered when exceeding a threshold value • Price on request	g	cm l