



Find out more at www.mobotix.com




## MOBOTIX MOVE Vandal Multisensor PTZ Combo 20MP

# Compact, versatile and accurate down to the last detail

Based on the 360-degree omnidirectional view of the multisensors, the **AI-assisted motion and object detection** seamlessly relays the event to the PTZ unit. Thanks to **auto-tracking**, the PTZ camera keeps a constant eye on the object and captures any activity reliably and automatically. Of course, as the operator, you can also pan and zoom to a desired position yourself to get a more accurate picture.

The **pre-installed AI-based video analytics** (intrusion, wrong direction, crossing lines, loitering) **work license-free on all four directional sensors simultaneously**, enabling reliable video surveillance 24/7.

#### The perfect all-in-one video solution for larger surveillance areas



#### Many strengths compactly combined in one camera

- Multi-directional 4 x 5 MP (fixed)
- Calibration-free multisensor unit
- Automatic object tracking (PTZ)
- PTZ 2MP Optical Zoom (x21)
- Pan/Tilt speed up to 500 deg/s

- Integrated IT security TPM chipset (certified to FIPS 140-2 Level 3)
- Intelligent video motion detection
- NDAA compliant
- IP66 / IP67 / IK 10/ NEMA 4X



### **MOBOTIX MOVE Vandal Multisensor PTZ Combo 20MP – Technical Details**

MOBOTIX MOVE Vandalism Multisensor PTZ Combo Network Camera Mx-VMSD1A-2021-VA - Image sensor Multi: 4x5MP (2560x1920), 1/2.7" Progressive CMOS - Image sensor PTZ: 2MP (1920x1080), 1/2.8" Progressive CMOS - ONVIF S/G/T/M - Pre-installed AI-VMD DNN based video motion detection - Automatic object tracking with PTZ unit - Automatic switching from color to B/W image (mechanical IR cut filter) - FIPS140-2 Level 3 certified IT security TPM chipset - Intelligent encoding "Smart Low Bitrate Control" - Multisensor: 4x fixed focal length lens 3.2mm (Viewing Angle HxV: 97 °x 71 °) - PTZ: 21x Motorized Zoom/Focus Lens 4.0mm - 84.6mm with Autofocus and P-Iris (Viewing Angle HxV: 3. 7° - 77° x 2.2° -44°) - IK10 / IP66/ IP67 - NDAA Compliant - NEMA-4x Compliant - Ambient Temperature -40 to 55°C (-4° to 131°F), Humidity 10 to 100% -Video Codecs: H.264, H.265, MJPEG - Wide Dynamic Range up to 108dB for multisensor / 144 dB for PTZ unit - 1 Micro SD/SDHC/SDXC Card support each up to 512 GB (multisensor/ PTZ) - Max. Frame rate multisensor: 5MP@15 fps H.264, MJPEG: 1080p @ 15 fps - Max. Frame rate PTZ: 2MP@60 fps H.264, MJPEG: 1080p @ 60 fps - Power supply: PoE++ IEEE802.3bt, max. 35.6 W, DC54V max. 35.6 W - Audio Line In/Out - MTBF: 95000h - Warranty: 5 yrs.



Find out more now: 360° all-round view + PTZ in one camera

MOBOTIX AG • Kaiserstrasse • 67722 Langmeil • Germany +49 (0) 6302 9816-103 • sales@mobotix.com • www.mobotix.com

MOBOTIX is a registered trademark of MOBOTIX AG in the European Union, the USA, and other countries. This may only be transferred to trade or commercial partners. Subject to change. MOBOTIX does not assume any liability for technical errors, printing errors or omissions. All rights reserved. © MOBOTIX AG 2023 (DE\_10/23)

