

Product Overview

13.03.2025 English EUR



BeyondHumanVision

MOBOTIX




All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group
MOBOTIX • 13.03.2025 • MOBOTIX accepts no liability arising from printing errors, mistakes and changes. • Revision 11.03.2025

Video Systems IoT Outdoor

BeyondHumanVision

MOBOTIX

M ONE M1A Single IP Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-ONE-M1A-S-8DN040</p> <p>M ONE with 4K DN040 (Day/Night), 120°x60°</p> <p>M ONE Single IP camera equipped with one premium wide-angle lens B040 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438048446</p> <p>85258900</p> <p>1.500 g</p>	<p>29,6 cm</p> <p>19,6 cm</p> <p>18,0 cm</p> <p>10,4 l</p>
 <p>Mx-ONE-M1A-S-8DN050</p> <p>M ONE with 4K DN050 (Day/Night), 95°x50°</p> <p>M ONE Single IP camera equipped with one premium wide-angle lens B050 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438048453</p> <p>85258900</p> <p>1.500 g</p>	<p>29,6 cm</p> <p>19,6 cm</p> <p>18,0 cm</p> <p>10,4 l</p>
 <p>Mx-ONE-M1A-S-8DN080</p> <p>M ONE with 4K DN080 (Day/Night), 60°x33°</p> <p>M ONE Single IP camera equipped with one premium wide-angle lens B080 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438048460</p> <p>85258900</p> <p>1.500 g</p>	<p>29,6 cm</p> <p>19,6 cm</p> <p>18,0 cm</p> <p>10,4 l</p>

**Mx-ONE-M1A-S-8DN100****M ONE with 4K DN100 (Day/Night), 45°x25°**

M ONE Single IP camera equipped with one premium normal lens B100 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048477 29,6 cm
85258900 19,6 cm
1.500 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DN150****M ONE with 4K DN150 (Day/Night), 30°x17°**

M ONE Single IP camera equipped with one premium tele lens B150 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048484 29,6 cm
85258900 19,6 cm
1.500 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DN280****M ONE with 4K DN280 (Day/Night), 15°x8,5°**

M ONE Single IP camera equipped with one premium tele lens B280 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048491 29,6 cm
85258900 19,6 cm
1.500 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DNTELE****M ONE with 4K DN Tele Varifocal (Day/Night), 42° - 15°**

M ONE Single IP camera equipped with one premium motorized tele varifocal lens and IR cut filter for day and night use, aperture: f/1,7, image angle H: 42°-15°, V:22,8° -8,4° • focal length: 11-29 mm • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048422 29,6 cm
85258900 19,6 cm
1.550 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DNWIDE****M ONE with 4K DN Wide Varifocal (Day/Night), 112° - 47,5°**

M ONE Single IP camera equipped with one premium motorized wide varifocal lens and IR cut filter for day and night use, aperture: f/1.3, image angle H: 112°-47,5°, V:58°-26,6° • focal length: 4.3-9.3 mm • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048439 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N040****M ONE with 4K Night sensor, 120°x60°**

M ONE Single IP camera equipped with one premium wide-angle lens B040 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 120°x60° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048521 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N050****M ONE with 4K Night sensor, 95°x50°**

M ONE Single IP camera equipped with one premium wide-angle lens B050 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 95°x50° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048538 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N080****M ONE with 4K Night sensor, 60°x33°**

M ONE Single IP camera equipped with one premium wide-angle lens B080 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 60°x33° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048545 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N100****M ONE with 4K Night sensor, 45°x25°**

M ONE Single IP camera equipped with one premium normal lens B100 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 45°x25° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x Audio Out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048552	29,6 cm
85258900	19,6 cm
1.500 9	18,0 cm
	10,4 l

**Mx-ONE-M1A-S-8N150****M ONE with 4K Night sensor, 30°x17°**

M ONE Single IP camera equipped with one premium tele lens B150 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 30°x17° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x mic In, 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: Aluminium, PBT -30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048569	29,6 cm
85258900	19,6 cm
1.500 9	18,0 cm
	10,4 l

**Mx-ONE-M1A-S-8N280****M ONE with 4K Night sensor, 15°x8,5°**


M ONE Single IP camera equipped with one premium tele lens B280 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048576	29,6 cm
85258900	19,6 cm
1.500 9	18,0 cm
	10,4 l






M73A

MOBOTIX 7 Solution Platform

Weatherproof (IP66) Fixed Network Camera (Body) in two color variants, modular design with separately orderable optical 4K UHD image sensor modules (optimized for day, night or day & night use) and separately orderable function modules for easy insertion in the front panel (3 module openings, can be assigned as required), module connection via MOBOTIX sensor cables pre-positioned in the camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-M73A-LSA</p> <p>M73 Body with LSA Connector Box (white)</p> <p>M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA terminal for weatherproof network connection via laying cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	4047438036825	29,6 cm
	85258900	26,8 cm
	2.500 g	18,0 cm
		14,3 l
 <p>Mx-M73A-RJ45</p> <p>M73 Body with RJ45 Connector Box (white)</p> <p>M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	4047438034982	29,6 cm
	85258900	26,8 cm
	2.500 g	18,0 cm
		14,3 l

D71A Dome Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-D71A-4DN050</p> <p>D71 Complete Camera 4MP Ultra LowLight DN050 (Day)</p> <p>D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included</p>	<p>4047438039741 19,6 cm</p> <p>85258900 18,0 cm</p> <p>1.180 g 14,8 cm</p> <p>5,2 l</p>	
 <p>Mx-D71A-4DN080</p> <p>D71 Complete Camera 4MP Ultra LowLight DN080 (Day)</p> <p>D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included</p>	<p>4047438039758 19,6 cm</p> <p>85258900 18,0 cm</p> <p>1.180 g 14,8 cm</p> <p>5,2 l</p>	
 <p>Mx-D71A-4DN100</p> <p>D71 Complete Camera 4MP Ultra LowLight DN100 (Day)</p> <p>D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included</p>	<p>4047438039765 19,6 cm</p> <p>85258900 18,0 cm</p> <p>1.180 g 14,8 cm</p> <p>5,2 l</p>	
 <p>Mx-D71A-4DN150</p> <p>D71 Complete Camera 4MP Ultra LowLight DN150 (Day)</p> <p>D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included</p>	<p>4047438039772 19,6 cm</p> <p>85258900 18,0 cm</p> <p>1.180 g 14,8 cm</p> <p>5,2 l</p>	
 <p>Mx-D71A-4DN280</p> <p>D71 Complete Camera 4MP Ultra LowLight DN280 (Day)</p> <p>D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included</p>	<p>4047438039789 19,6 cm</p> <p>85258900 18,0 cm</p> <p>1.180 g 14,8 cm</p> <p>5,2 l</p>	

**Mx-D71A-8DN050****D71 Complete Camera 4K DN050 (Day(Night), 95°x50°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039697	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

**Mx-D71A-8DN080****D71 Complete Camera 4K DN080 (Day(Night), 60°x33°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039703	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

**Mx-D71A-8DN100****D71 Complete Camera 4K DN100 (Day(Night), 45°x25°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039710	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

**Mx-D71A-8DN150****D71 Complete Camera 4K DN150 (Day(Night), 30°x17°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039727	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l


**Mx-D71A-8DN280****D71 Complete Camera 4K DN280 (Day(Night), 15°x8,5°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039734	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

M16B AllroundDual Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16B	4047438030915	29,6 cm
	M16B Body, For M16 Sensor Modules (Day/Night)	85258900	19,6 cm
	<p>M16 camera module for connecting one or two M16/M15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)</p>	1.764 g	18,0 cm
			10,4 l

Q71A Hemispheric Camera



Article No. / Name / Description

EAN / HS / weight dimen.

Mx-Q71A-12DN016

4047438039796

19,6 cm

Q71 Complete Camera 12MP, DN016 (Day/Night), 360°

85258900

18,0 cm

Q71 camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 • 12MP image sensor • 4K effective resolution: 2880x2880 (hemispheric original image) • Max. Frame rate (4K): 20 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR and white light LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • IP66 • IK10 except on the lens • Operating temperature range: -40 to +65 °C • Built-in speaker and microphone - Line In & Out - Input & Output • USB-C • 8GB memory card included


1.050 g

14,8 cm

5,2 l

D16B DualDome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-D16B	4047438030588 39,5 cm
	D16B Body, For D16B/D15 Sensor Modules (Day/Night)	85258900 29,6 cm
	IP camera module for connecting one or two D16/D15 sensor modules or a D16/D15 lens bridge FIX/PAN (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module/bridge): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 31° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Incl. 1x standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.277 g 9,0 cm
		10,5 l

S74A

Article No. / Name / Description

EAN / HS / weight dimen.

**Mx-S74A**

4047438035552 29,6 cm

S74 Body for 4 Sensor- and Functional Modules

85258900 19,6 cm

1.400 g 9,0 cm

5,2 l

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 or 1x LSA board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

**Mx-S74A-LSA**

4047438047814 29,6 cm

S74 Body for 4 Sensor- and Functional Modules with LSA

85258900 19,6 cm

1.525 g 9,0 cm

5,2 l

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

**Mx-S74A-RJ45**

4047438047807 29,6 cm

S74 Body for 4 Sensor- and Functional Modules with RJ45

85258900 19,6 cm

1.520 g 9,0 cm

5,2 l

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

**Mx-S74A-SET****S74 Set with 2x 12DN016 sensor modules**

S74A IP camera (set) incl. built-in AudioI/O and RJ45 plug-in board + 2x 3m sensor cable (Mx-A-S7A-CBL03) + 2x 12DN016 sensor module (12MP, Day/Night, Hemispheric, white, Mx-O-M7SA-12DN016) • for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board (with 12/24 VDC Power Supply) for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047999	29,6 cm
85258900	19,6 cm
1.980 9	18,0 cm
	10,4 l


**Mx-S74A-VDC****S74 Body for 4 Sensor- and Functional Modules with RJ45**

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board (with 12/24 VDC Power Supply) for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047821	29,6 cm
85258900	19,6 cm
1.510 9	9,0 cm
	5,2 l



S16B DualFlex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S16B	4047438031400 19,6 cm
	S16B Body, For S16B/S15 Sensor Modules	85258900 14,8 cm
	S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP66/IK06, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio (I/O); RS232 via MX Interface Box	660 g 9,0 cm
		2,6 l



M26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M26B-6D	4047438031042 29,6 cm
	M26B Body 6MP (Day)	85258900 19,6 cm
	IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.337 g 18,0 cm
		10,4 l
	Mx-M26B-6N	4047438031134 29,6 cm
	M26B Body 6MP (Night)	85258900 19,6 cm
	IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	1.344 g 18,0 cm
		10,4 l


D26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-D26B-6D	4047438030670 19,6 cm
	D26B Body 6MP (Day)	85258900 18,0 cm
		799 g 14,8 cm
		5,2 l
	Mx-D26B-6N	4047438030748 19,6 cm
	D26B Body 6MP (Night)	85258900 18,0 cm
		799 g 14,8 cm
		5,2 l

Q26B Hemispheric Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.



Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-Q26B-6D016	4047438031387 29,6 cm
	Q26B Complete Cam 6MP, B016 (Day)	85258900 19,6 cm
		853 g 9,0 cm
		5,2 l
Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)		

Video Systems IoT Indoor

BeyondHumanVision

MOBOTIX

c71A Indoor Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-c71A-8DN016	4047438041027	19,6 cm
	c71 Indoor Complete Camera 4k, DN016 (Day/Night)	85258900	18,0 cm
	c71 Indoor camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 • 4k image sensor • 4MP effective resolution: 2160x2160 (hemispheric original image) • Max. Frame rate (4MP): 30 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	1.040 g	14,8 cm
			5,2 l
	Mx-c71A-NurseAssist	4047438048293	19,6 cm
	MOBOTIX c71 NurseAssist powered by Kepler Vision	85258900	18,0 cm
	MOBOTIX c71 NurseAssist powered by Kepler Vision Technologies including the following features: • monitoring of the well-being of patients in private rooms, corridors and common areas of Healthcare facilities • minimization of reaction times due to decentralized state-of-the-art fall detection • prevention of accidents through: person down, person in bed and person out of bed event • simple and decent installation • GDPR compliant operation through event-controlled obscuring of live and recorded images	1.040 g	14,8 cm
			5,2 l

p71A Indoor Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-p71A-4DN040</p> <p>p71 Indoor Complete Camera 4MP Ultra LowLight DN040</p> <p>p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	<p>4047438041164</p> <p>85258900</p> <p>1.175 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
 <p>Mx-p71A-4DN050</p> <p>p71 Indoor Complete Camera 4MP Ultra LowLight DN050</p> <p>p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	<p>4047438041171</p> <p>85258900</p> <p>1.175 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
 <p>Mx-p71A-4DN080</p> <p>p71 Indoor Complete Camera 4MP Ultra LowLight DN080</p> <p>p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	<p>4047438041188</p> <p>85258900</p> <p>1.175 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
 <p>Mx-p71A-4DN100</p> <p>p71 Indoor Complete Camera 4MP Ultra LowLight DN100</p> <p>p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	<p>4047438041195</p> <p>85258900</p> <p>1.175 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
 <p>Mx-p71A-4DN150</p> <p>p71 Indoor Complete Camera 4MP Ultra LowLight DN150</p> <p>p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	<p>4047438041201</p> <p>85258900</p> <p>1.175 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>

**Mx-p71A-4DN280****p71 Indoor Complete Camera 4MP Ultra LowLight DN280**

p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041218	19,6 cm
85258900	18,0 cm
1.175 9	14,8 cm
	5,2 l

**Mx-p71A-8DN040****p71 Indoor Complete Camera 4K DN040 (Day/Night), 120°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041041	19,6 cm
85258900	18,0 cm
815 9	14,8 cm
	5,2 l

**Mx-p71A-8DN050****p71 Indoor Complete Camera 4K DN050 (Day/Night), 95°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041058	19,6 cm
85258900	18,0 cm
1.175 9	14,8 cm
	5,2 l

**Mx-p71A-8DN080****p71 Indoor Complete Camera 4K DN080 (Day(Night), 60°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041065	19,6 cm
85258900	18,0 cm
1.175 9	14,8 cm
	5,2 l

**Mx-p71A-8DN100****p71 Indoor Complete Camera 4K DN100 (Day(Night), 45°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041072	19,6 cm
85258900	18,0 cm
1.175 9	14,8 cm
	5,2 l

**Mx-p71A-8DN150****p71 Indoor Complete Camera 4K DN150 (Day(Night), 30°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty






4047438041089	19,6 cm
85258900	18,0 cm
1.175 9	14,8 cm
	5,2 l

**Mx-p71A-8DN280****p71 Indoor Complete Camera 4K DN280 (Day(Night), 15°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041096	19,6 cm
85258900	18,0 cm
1.175 9	14,8 cm
	5,2 l

v71A Indoor Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-v71A-4DN050</p> <p>v71 Indoor Complete Camera 4MP Ultra LowLight DN050 -</p> <p>v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	4047438040921 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 <p>Mx-v71A-4DN080</p> <p>v71 Indoor Complete Camera 4MP Ultra LowLight DN080 -</p> <p>v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	4047438040938 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 <p>Mx-v71A-4DN100</p> <p>v71 Indoor Complete Camera 4MP Ultra LowLight DN100 -</p> <p>v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	4047438040945 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 <p>Mx-v71A-4DN150</p> <p>v71 Indoor Complete Camera 4MP Ultra LowLight DN150 -</p> <p>v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	4047438040952 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 <p>Mx-v71A-4DN280</p> <p>v71 Indoor Complete Camera 4MP Ultra LowLight DN280 -</p> <p>v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty</p>	4047438040969 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

**Mx-v71A-8DN050****v71 Indoor Complete Camera 4K DN050 - 95°x50°**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040822 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

**Mx-v71A-8DN080****v71 Indoor Complete Camera 4K DN080 - 60°x33° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040839 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

**Mx-v71A-8DN100****v71 Indoor Complete Camera 4K DN100 - 45°x25° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040846 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

**Mx-v71A-8DN150****v71 Indoor Complete Camera 4K DN150 - 30°x17° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040853 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l





**Mx-v71A-8DN280****v71 Indoor Complete Camera 4K DN280 - 15°x8,5° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040860 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l





c26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-c26B-6D016	4047438030496	19,6 cm
	c26B Complete Cam 6MP, B016, Day	85258900	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	433 g	9,0 cm
		2,6 l	
	Mx-c26B-6N016	4047438030526	19,6 cm
	c26B Complete Cam 6MP, B016, Night	85258900	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	433 g	9,0 cm
		2,6 l	
	Mx-c26B-AU-6D016	4047438030540	19,6 cm
	c26B Complete Cam 6MP, B016, Day, Audio Package	85258900	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	442 g	9,0 cm
		2,6 l	
	Mx-c26B-AU-6N016	4047438030564	19,6 cm
	c26B Complete Cam 6MP, B016, Night, Audio Package	85258900	15,0 cm
	Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	452 g	9,0 cm
		2,6 l	



p26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-p26B-6D</p> <p>p26B Body 6MP, Day</p> <p>p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031226</p> <p>85258900</p> <p>582 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
 <p>Mx-p26B-6N</p> <p>p26B Body 6MP, Night</p> <p>p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031295</p> <p>85258900</p> <p>582 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
 <p>Mx-p26B-AU-6D</p> <p>p26B Body 6MP, Day, Audio Package</p> <p>p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031325</p> <p>85258900</p> <p>591 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
 <p>Mx-p26B-AU-6N</p> <p>p26B Body 6MP, Night, Audio Package</p> <p>p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white</p>	<p>4047438031356</p> <p>85258900</p> <p>480 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>

v26B Indoor Dome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-v26B-6D	4047438031547 19,6 cm
	v26B Body 6MP, Day, White	85258900 18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white	726 g 14,8 cm
		5,2 l
	Mx-v26B-6N	4047438031578 19,6 cm
	v26B Body 6MP, Night, White	85258900 18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white	726 g 14,8 cm
		5,2 l

Video Systems IoT Thermal

BeyondHumanVision

MOBOTIX

M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16TB-R079	4047438030984	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R079 (45°)	90251900	19,6 cm
	IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm
			10,4 l
	Mx-M16TB-R090	4047438036795	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R090 (35°)	90251900	19,6 cm
	IP thermographic camera TR with Germanium Lens: B090 equivalent, horizontal/vertical image angle 35°/27° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.480 g	18,0 cm
			10,4 l
	Mx-M16TB-R119	4047438030991	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R119 (25°)	90251900	19,6 cm
	IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.936 g	18,0 cm
			10,4 l
	Mx-M16TB-R237	4047438031004	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R237 (17°)	90251900	19,6 cm
	IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.942 g	18,0 cm
			10,4 l

**Mx-M16TB-T079****M16B Thermographic Camera 50 mK, T079 (45°)**

IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/35°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031011 29,6 cm
90251900 19,6 cm
2.460 9 18,0 cm
10,4 l

**Mx-M16TB-T119****M16B Thermographic Camera 50 mK, T119 (25°)**

IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031028 29,6 cm
90251900 19,6 cm
2.460 9 18,0 cm
10,4 l

**Mx-M16TB-T237****M16B Thermographic Camera 50 mK, T237 (17°)**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031035 29,6 cm
90251900 19,6 cm
1.946 9 18,0 cm
10,4 l

**Mx-M16TB-R079-VDS****M16B Thermographic Camera TR, 50 mK, R079 (45°) - VDS**

VdS-Bundle • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041607 29,6 cm
90251900 26,8 cm
2.170 9 18,0 cm
14,3 l

**Mx-M16TB-R119-VDS****M16B Thermographic Camera TR, 50 mK, R119 (25°) - VDS**

VdS Bundle • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041614 29,6 cm
90251900 26,8 cm
2.170 9 18,0 cm
14,3 l

**Mx-M16TB-R237-VDS****M16B Thermographic Camera TR, 50 mK, R237 (17°) - VDS**

VdS Bundle • IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041621 29,6 cm
90251900 26,8 cm
2.170 9 18,0 cm
14,3 l

**Mx-M16TB-R079-EN54-V2****M16B Thermographic Camera TR, 50 mK, R079 (45°) - EN54**

EN54 V2 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438048330 29,6 cm
90251900 26,8 cm
2.170 9 18,0 cm
14,3 l

**Mx-M16TB-R119-EN54-V2****M16B Thermographic Camera TR, 50 mK, R119 (25°) - EN54**

EN54 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438048347 29,6 cm
90251900 26,8 cm
2.170 9 18,0 cm
14,3 l

**Mx-M16TB-R237-EN54-V2****M16B Thermographic Camera TR, 50 mK, R237 (17°) - EN54**

EN54 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box

- IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438048354	29,6 cm
90251900	26,8 cm
2.170 g	18,0 cm
	14,3 l

M73A Thermal Camera

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-M73TA-B336R100-EN54-V2</p> <p>M73A Thermographic Camera TR(B), CIF, R100 (45°) - EN54</p> <p>EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R100, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA</p>	4047438049849	41,0 cm
	90251900	31,0 cm
	3.550 g	20,0 cm
		25,4 l
 <p>Mx-M73TA-B336R150-EN54-V2</p> <p>M73A Thermographic Camera TR(B), CIF, R150 (25°) - EN54</p> <p>EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R150, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA</p>	4047438049856	41,0 cm
	90251900	31,0 cm
	3.550 g	20,0 cm
		25,4 l
 <p>Mx-M73TA-B336R280-EN54-V2</p> <p>M73A Thermographic Camera TR(B), CIF, R280 (17°) - EN54</p> <p>EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R280, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA</p>	4047438049863	41,0 cm
	90251900	31,0 cm
	3.550 g	20,0 cm
		25,4 l

**Mx-M73TA-B640R050-EN54-V2****M73A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R050, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438049870	41,0 cm
90251900	31,0 cm
3.550 g	20,0 cm
	25,4 l

**Mx-M73TA-B640R080-EN54-V2****M73A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R080, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438049887	41,0 cm
90251900	31,0 cm
3.550 g	20,0 cm
	25,4 l

**Mx-M73TA-B640R100-EN54-V2****M73A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R100, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438049894	41,0 cm
90251900	31,0 cm
3.550 g	20,0 cm
	25,4 l

**Mx-M73TA-B640R150-EN54-V2****M73A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**

EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R150, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438049900	41,0 cm
90251900	31,0 cm
3.550 9	20,0 cm
	25,4 l

**Mx-M73TA-B336R100-EN54****M73A Thermographic Camera TR(B), CIF, R100 (45°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R100, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043410	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B336R150-EN54****M73A Thermographic Camera TR(B), CIF, R150 (25°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R150, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043427	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B336R280-EN54****M73A Thermographic Camera TR(B), CIF, R280 (17°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R280, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043434	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B640R050-EN54****M73A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R050, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043441	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B640R080-EN54****M73A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R080, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043458	29,6 cm
90251900	26,8 cm
2.814 9	18,0 cm
	14,3 l

**Mx-M73TA-B640R100-EN54****M73A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R100, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043465 29,6 cm
90251900 26,8 cm
2.814 9 18,0 cm
14,3 l

**Mx-M73TA-B640R150-EN54****M73A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R150, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043472 29,6 cm
90251900 26,8 cm
2.814 9 18,0 cm
14,3 l

**Mx-M73TA-IRIS-INT-T040****MOBOTIX M73TA T040 Irisity Intrusion Bundle**

MOBOTIX M73TA Irisity Intrusion Bundle, consisting of: M73 Body with RJ45 connection box (Mx-M73A-RJ45), 105° Thermal Module ECO 320 - T140 (Mx-O-M7SA-320T140), 120° 4K IR-Cut Day & Night Sensor Module WIDE (Mx-O-M7SA-8DN040), IR Light Module for Wide Lens (Mx-F-IRA-S) and pre-installed Irisity Iris Core Intrusion App (Mx-APP-IRIS-C-INT)

4047438050517 29,6 cm
90251900 26,8 cm
2.800 9 18,0 cm
14,3 l

**Mx-M73TA-IRIS-INT-T080****MOBOTIX M73TA T080 Irisity Intrusion Bundle**

MOBOTIX M73TA Irisity Intrusion Bundle, consisting of: M73 Body with RJ45 connection box (Mx-M73A-RJ45), 56° Thermal Module ECO 320 - T080 (Mx-O-M7SA-320T080), 60° 4K IR-Cut Day & Night Sensor Module WIDE (Mx-O-M7SA-8DN080), IR Light Module for Wide Lens (Mx-F-IRA-S) and pre-installed Irisity Iris Core Intrusion App (Mx-APP-IRIS-C-INT)

4047438050500 29,6 cm
90251900 26,8 cm
2.800 9 18,0 cm
14,3 l

**Mx-M73TA-IRIS-INT-T150****MOBOTIX M73TA T150 Irisity Intrusion Bundle**

MOBOTIX M73TA Irisity Intrusion Bundle, consisting of: M73 Body with RJ45 connection box (Mx-M73A-RJ45), 24° Thermal Module ECO 320 - T150 (Mx-O-M7SA-320T150), 30° 4K IR-Cut Day & Night Sensor Module TELE (Mx-O-M7SA-8DN150), IR Light Module for Tele Lens (Mx-F-IRA-T) and pre-installed Irisity Iris Core Intrusion App (Mx-APP-IRIS-C-INT)


4047438049436 29,6 cm

90251900 26,8 cm

2.800 g 18,0 cm

14,3 l

S74 Thermal Bundle

Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S74TA-B336R100-EN54-V2	4047438049917 41,0 cm
	S74A Thermographic Camera TR(B), CIF, R100 (45°) - EN54	90251900 31,0 cm
	EN54 V2 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN, Mx-F-4IOA, Mx-F-NPAA	3.880 g 20,0 cm
		25,4 l
	Mx-S74TA-B336R150-EN54-V2	4047438049924 41,0 cm
	S74A Thermographic Camera TR(B), CIF, R150 (25°) - EN54	90251900 31,0 cm
	EN54 V2 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN, Mx-F-4IOA, Mx-F-NPAA	3.880 g 20,0 cm
		25,4 l
	Mx-S74TA-B336R280-EN54-V2	4047438049931 41,0 cm
	S74A Thermographic Camera TR(B), CIF, R280 (17°) - EN54	90251900 31,0 cm
	EN54 V2 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP280, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN, Mx-F-4IOA, Mx-F-NPAA	3.880 g 20,0 cm
		25,4 l

**Mx-S74TA-B640R050-EN54-V2****S74A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 V2 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP050, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN, Mx-F-4IOA, Mx-F-NPAA

4047438049948 41,0 cm
90251900 31,0 cm
3.880 9 20,0 cm
25,4 l

**Mx-S74TA-B640R080-EN54-V2****S74A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 V2 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP080, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN, Mx-F-4IOA, Mx-F-NPAA

4047438049955 41,0 cm
90251900 31,0 cm
3.880 9 20,0 cm
25,4 l

**Mx-S74TA-B640R100-EN54-V2****S74A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 V2 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN, Mx-F-4IOA, Mx-F-NPAA

4047438049962 41,0 cm
90251900 31,0 cm
3.880 9 20,0 cm
25,4 l

**Mx-S74TA-B640R150-EN54-V2****S74A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**

EN54 V2 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN, Mx-F-4IOA, Mx-F-NPAA

4047438049979	41,0 cm
90251900	31,0 cm
3.880 g	20,0 cm
	25,4 l

**Mx-S74TA-B336R100-EN54****S74A Thermographic Camera TR(B), CIF, R100 (45°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043489	40,8 cm
90251900	31,2 cm
3.520 g	20,2 cm
	25,7 l

**Mx-S74TA-B336R150-EN54****S74A Thermographic Camera TR(B), CIF, R150 (25°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043496	40,8 cm
90251900	31,2 cm
3.520 g	20,2 cm
	25,7 l

**Mx-S74TA-B336R280-EN54****S74A Thermographic Camera TR(B), CIF, R280 (17°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP280, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043502	40,8 cm
90251900	31,2 cm
3.520 g	20,2 cm
	25,7 l

**Mx-S74TA-B640R050-EN54****S74A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP050, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043519	40,8 cm
90251900	31,2 cm
3.520 g	20,2 cm
	25,7 l

**Mx-S74TA-B640R080-EN54****S74A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP080, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043526	40,8 cm
90251900	31,2 cm
3.520 g	20,2 cm
	25,7 l

**Mx-S74TA-B640R100-EN54****S74A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN



4047438043533	40,8 cm
90251900	31,2 cm
3.520 9	20,2 cm
	25,7 l

**Mx-S74TA-B640R150-EN54****S74A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**






EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043540	40,8 cm
90251900	31,2 cm
3.520 9	20,2 cm
	25,7 l

p71A ECO Thermal Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-p71TA-320T040	4047438042499	19,6 cm
	p71 Thermal ECO 320 - T040	90251900	18,0 cm
	p71 Indoor camera with Thermal ECO module 320-T040. CIF 320x240 • 9fps • 105 x 75°; 5,23mr • NETD: 65mK (typ); < 100mK (max) • build in ambient temperature sensor • IR Range 7,8 to 14µm • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C - Built-in speaker and microphone • USB-C • 8GB memory card included	1.175 g	14,8 cm
			5,2 l
	Mx-p71TA-320T080	4047438042505	19,6 cm
	p71 Thermal ECO 320 - T080	90251900	18,0 cm
	p71 Indoor camera with Thermal ECO 320-T080. CIF 320x240 • 9fps • 56 x 42°; 3mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C - Built-in speaker and microphone • USB-C • 8GB memory card included	1.175 g	14,8 cm
			5,2 l

Sensor Module Thermal for MOBOTIX 7

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-O-M73TB-336R100 Thermal module 336-R100 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate</p>	4047438040198 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 <p>Mx-O-M73TB-336R150 Thermal module 336-R150 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate</p>	4047438040204 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 <p>Mx-O-M73TB-336R280 Thermal module 336-R280 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate</p>	4047438040211 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 <p>Mx-O-M73TB-336T100 Thermal module 336-T100 with front plate for M73 (B) CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate</p>	4047438040129 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
 <p>Mx-O-M73TB-336T150 Thermal module 336-T150 with front plate for M73 (B) CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate</p>	4047438040136 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l

**Mx-O-M73TB-336T280****Thermal module 336-T280 with front plate for M73 (B)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate

4047438040143 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640R050****Thermal module 640-R050 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate

4047438040228 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640R080****Thermal module 640-R080 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate

4047438040235 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640R100****Thermal module 640-R100 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate

4047438040242 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640R150****Thermal module 640-R150 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate

4047438040259 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640T050****Thermal module 640-T050 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate

4047438040150 19,6 cm
 90275000 18,0 cm
 450 g 14,8 cm
 5,2 l

**Mx-O-M73TB-640T080****Thermal module 640-T080 with front plate für M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate

4047438040167	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640T100****Thermal module 640-T100 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate

4047438040174	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640T150****Thermal module 640-T150 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate

4047438040181	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73SA-320T040****Thermal Module ECO 320 - T040 (105° x 75°)**

MOBOTIX 7 Thermal Module 320-T040 for M73/S74, CIF 320x240 • 9fps • 105° x 75°; 5,23mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040648	9,8 cm
90275000	7,5 cm
106 g	9,0 cm
	0,7 l

**Mx-O-M73SA-320T080****Thermal Module ECO 320 - T080 (56° x 42°)**

MOBOTIX 7 Thermal Module 320-T080 for M73/S74, CIF 320x240 • 9fps • 56° x 42°; 3,00mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040655	9,8 cm
90275000	7,5 cm
106 g	9,0 cm
	0,7 l

**Mx-O-M73SA-320T150****Thermal module ECO 320 - T150 (24° x 18°)**

MOBOTIX 7 Thermal Module 320-T150 for M73/S74, CIF 320x240 • 9fps • 24° x 18°; 1.32 mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438045193	9,8 cm
90275000	7,5 cm
106 g	9,0 cm
	0,7 l

**Mx-O-M7SB-336RP100****S7x PTMount Thermal 336-R100 (B model) 45° x 35°**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable

4047438040051	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336RP150****S7x PTMount Thermal 336-R150 (B model) 25° x 19°**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable

4047438040068	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336RP280****S7x PTMount Thermal 336-R280 (B model) 17° x 13°**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable

4047438040075	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336RS100****S7x Thermal Module 336-R100 (B model) 45° x 35°**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35°

4047438039918	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336RS150****S7x Thermal module 336-R150 (B model) 25° x 19°**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19°

4047438039925	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336RS280****S7x Thermal Module 336-R280 (B model) 17° x 13°**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13°

4047438039932	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336TP100****S7x PTMount Thermal 336-T100 (B model) 45° x 35°**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable

4047438039987	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336TP150****S7x PTMount Thermal 336-T150 (B model) 25° x 19°**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable

4047438039994	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336TP280****S7x PTMount Thermal 336-T280 (B model) 17° x 13°**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable

4047438040006	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336TS100****S7x Thermal Module 336-T100 (B model) 45° x 35°**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35°

4047438039840	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336TS150****S7x Thermal module 336-T150 (B model) 25° x 19°**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19°

4047438039857	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-336TS280****S7x Thermal Module 336-T280 (B model) 17° x 13°**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13°

4047438039864	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RP050****S7x PTMount Thermal 640-R050 (B model) 90° x 69°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • Equipped with a 2 meter connection cable

4047438040082	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RP080****S7x PTMount Thermal 640-R080 (B model) 69° x 56°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • Equipped with a 2 meter connection cable

4047438040099	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RP100****S7x PTMount Thermal 640-R100 (B model) 45° x 37°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • Equipped with a 2 meter connection cable

4047438040105	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RP150****S7x PTMount Thermal 640-R150 (B model) 30° x 26°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable

4047438040112	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RS050****S7x Thermal Module 640-R050 (B model) 90° x 69°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69°

4047438039949	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS080****S7x Thermal Module 640-R080 (B model) 69° x 56°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56°

4047438039956	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS100****S7x Thermal Module 640-R100 (B model) 45° x 37°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37°

4047438039963	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS150****S7x Thermal module 640-R150 (B model) 30° x 26°**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26°

4047438039970	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TP050****S7x PTMount Thermal 640-T050 (B model) 90° x 69°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • Equipped with a 2 meter connection cable

4047438040013	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP080****S7x PTMount Thermal 640-T080 (B model) 69° x 56°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • Equipped with a 2 meter connection cable

4047438040020	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP100****S7x PTMount Thermal 640-T100 (B model) 45° x 37°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • Equipped with a 2 meter connection cable

4047438040037	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP150****S7x PTMount Thermal 640-T150 (B model) 30° x 26°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable

4047438040044	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TS050****S7x Thermal Module 640-T050 (B model) 90° x 69°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69°

4047438039871	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS080****S7x Thermal Module 640-T080 (B model) 69° x 56°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56°

4047438039888	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS100****S7x Thermal module 640-T100 (B model) 45° x 37°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37°

4047438039895	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS150****S7x Thermal module 640-T150 (B model) 30° x 26°**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26°

4047438039901	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

Sensor Modules Thermal For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-SMA-TS-R090	4047438048408	17,5 cm
	Thermal Sensor Module TR for S16/S15, 50 mK, B090 (35°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B090 equivalent, horizontal/vertical image angle 35°/27° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TS-R079	4047438030090	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TS-R119	4047438030106	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TS-R237	4047438030113	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm
			3,3 l
	Mx-O-SMA-TP-R079	4047438030120	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,8 cm
			5,2 l

**Mx-O-SMA-TP-R119****PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438030137 19,6 cm
90275000 18,0 cm
890 9 14,8 cm
5,2 l

**Mx-O-SMA-TP-R237****PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438030144 19,6 cm
90275000 18,0 cm
890 9 14,8 cm
5,2 l

**Mx-O-SMA-TP-R079-b****PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030151 19,6 cm
90275000 18,0 cm
890 9 14,8 cm
5,2 l

**Mx-O-SMA-TP-R119-b****PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030168 19,6 cm
90275000 18,0 cm
890 9 14,8 cm
5,2 l

**Mx-O-SMA-TP-R237-b****PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030175 19,6 cm
90275000 18,0 cm
890 9 14,8 cm
5,2 l

**Mx-O-SMA-TS-T079****Thermal Sensor Module For S16/S15, 50 mK, B079 (45°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029049 17,5 cm
90275000 14,0 cm
650 9 13,5 cm
3,3 l

**Mx-O-SMA-TS-T119****Thermal Sensor Module For S16/S15, 50 mK, B119 (25°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029056 17,5 cm
90275000 14,0 cm
650 g 13,5 cm
3,3 l

**Mx-O-SMA-TS-T237****Thermal Sensor Module For S16/S15, 50 mK, B237 (17°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029063 17,5 cm
90275000 14,0 cm
650 g 13,5 cm
3,3 l

**Mx-O-SMA-TP-T079****PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029070 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-T119****PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029087 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-T237****PTMount Thermal For S16/S15, 50 mK, B237 (17°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029094 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-T079-b****PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030021 19,6 cm
90275000 18,0 cm
890 g 14,8 cm
5,2 l

**Mx-O-SMA-TP-T119-b****PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030038	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T237-b****PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black

4047438030045	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l




Video Systems MOVE

BeyondHumanVision

MOBOTIX

MOBOTIX MOVE Speed Dome Cameras

MOBOTIX MOVE Speed Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SD1A-540-IR-VA	4047438045049	40,2 cm
	MOBOTIX MOVE SpeedDome SD-540-IR-VA (DNN Analytics)	85258900	25,0 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-540-IR-VA • Weatherproof motor-driven ONVIF S / G / T / M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 40x optical zoom • Image sensor: 5MP SONY STARVIS II IMX675 (2608 x 1964), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.95: 4.3 to 170 mm, viewing angle HxV: 62,6 ° - 1,9 ° x 48,8 ° - 1,4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IR LEDs (working distance up to 300m) • IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 5MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 59.05 W / 87.12 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	5.950 g	37,0 cm
			37,2 l
	Mx-SD1A-831-LIR-VA	4047438045056	33,0 cm
	MOBOTIX MOVE SpeedDome SD-831-LIR-VA LIDAR (DNN	85258900	33,0 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-831-LIR-VA • Weatherproof motor-driven ONVIF S / G / T / M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 31x optical zoom • Precise LiDAR Focusing System • Image sensor: 8MP SONY STARVIS II IMX678 (3856 x 2180) 4K, 1/1.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.35-F4.6: 6.9 to 214.6 mm, viewing angle HxV: 61.8 ° - 2.2 ° x 35.9 ° - 1.3 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IR LEDs (working distance up to 300 m) • IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 8MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	7.640 g	54,0 cm
			58,8 l
	Mx-SD2A-230-LL-FM-VA	4047438045032	31,0 cm
	MOBOTIX MOVE SpeedDome SD-230-LL-FM-VA Low Light	85258900	31,0 cm
	MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-FM-VA • Weatherproof motor-driven ONVIF S / G / T / M Indoor Dome PTZ camera for ceiling flush mount • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3 ° - 2.3 ° x 34.9 ° - 1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE+ IEEE802.3at, max. 17.71 W, AC24V max. 17.10 W / 32.76 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h	3.970 g	38,0 cm
			36,5 l





**Mx-SD2A-230-LL-VA****MOBOTIX MOVE SpeedDome SD-230-LL-VA Low Light (DNN**

MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-VA • Weatherproof motor-driven ONVIF S / G / T / M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3 ° - 2.3 ° x 34.9 ° - 1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Human, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE + IEEE802.3at, max. 25.5 W, AC24V max. 29.04 W / 53.24 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h

4047438045025	42,5 cm
85258900	26,2 cm
5.150 9	35,0 cm
	39,0 l

MOBOTIX MOVE Vandal Dome Cameras

MOBOTIX MOVE Vandal Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VT1A-2-IR	4047438048200	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-2-IR	85258900	16,5 cm
	MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-2-IR • Max. Image Resolution: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F1.6: 2.8 mm), viewing angle H: 105°, V: 56° • 3-axis adjustment(Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 2MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	950 g	15,4 cm 4,2 l
	Mx-VT1A-203-IR	4047438048262	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-203-IR	85258900	16,5 cm
	MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-203-IR • Max. Image Resolution: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Motor-controlled varifocal lens (F1.4-2.8: 2.7 to 13.5 mm, viewing angle H: 111°-34°, V: 61°-19°) • 3-axis adjustment (Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 2MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	980 g	15,4 cm 4,2 l
	Mx-VT1A-5-IR	4047438048255	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-5-IR	85258900	16,5 cm
	MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-5-IR • Max. Image Resolution: 5MP (2592x1944), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F1.6: 2.8 mm), viewing angle H: 97°, V: 70.5° • 3-axis adjustment(Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	950 g	15,4 cm 4,2 l
	Mx-VT1A-503-IR	4047438048279	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-503-IR	85258900	16,5 cm
	MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-503-IR • Max. Image Resolution: 5MP (2592x1944), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Motor-controlled varifocal lens (F1.4-2.8: 2.7 to 13.5 mm, viewing angle H: 103°-31°, V: 76°-23.5°) • 3-axis adjustment(Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	980 g	15,4 cm 4,2 l

**Mx-VD1A-8-IR-VA****MOBOTIX MOVE VandalDome VD-8-IR-VA (DNN Analytics)**

MOBOTIX MOVE Vandal Dome Network Camera VD-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max. 11.67 W, DC12V max. 12.14 W, AC24V max. 11.99 W / 20.02 VA • Optic hardened and "selfcleaning" Anti-Reflex coating by MOBOTIX ClearView • MTBF: 95.000h • Warranty: 5 years

4047438040341 17,3 cm
85258900 17,3 cm
1.081 9 16,6 cm
5,0 l

**Mx-VD2A-5-IR-VA****MOBOTIX MOVE VandalDome VD2-5-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Dome Network Camera VD2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 5MP H.264, H.265 30 fps • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040457 17,5 cm
85258900 17,5 cm
1.210 9 17,0 cm
5,2 l

**Mx-VD3A-2-IR-VA****MOBOTIX MOVE VandalDome VD3-2-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Dome Network Camera VD3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040433 17,5 cm
85258900 17,5 cm
1.210 9 17,0 cm
5,2 l



**Mx-VD2A-2-IR****MOBOTIX MOVE VandalDome VD2-2-IR**

MOBOTIX MOVE VandalDome Network Camera VD2-2-IR • Image sensor: 2MP (1920x1080), 1/3" Progressive CMOS • Weatherproof ONVIF S/G/T vandal dome camera with built-in IR LEDs (up to 40 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 91°-34°) • IP66 • IK10 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 130 dB) • Max. Frame rate: 2MP @ 60B / s (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af • Warranty: 5 years

4047438038959 17,5 cm
85258900 17,5 cm
1.010 9 17,0 cm
5,2 l

MOBOTIX MOVE Bullet Cameras


MOBOTIX MOVE Bullet Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-BC2A-2-IR	4047438038966	29,6 cm
	MOBOTIX MOVE BulletCamera BC2-2-IR	85258900	20,0 cm
	MOBOTIX MOVE Bullet Network Camera BC2-2-IR • Image Resolution: 2MP (1920x1080), 1/2.7" Progressive CMOS • Weatherproof ONVIF S/G/T bullet camera with built-in IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 96.67° - 34.13° - V: 52.21° - 19.24°) • IP66 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 95% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af • MTBF: 95.000h • Warranty: 5 years	580 g	17,5 cm
			10,4 l
	Mx-VB1A-2-IR-ALPR	4047438044295	28,5 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-	85258900	19,6 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-ALPR (License Plate Recognition) • Integrated professional international Automatic License Plate Recognition for stopped and slow moving vehicles up to 18m distance • incl. MMC (Make, Model, Color Detection) • ALPR Activation License Key pre-installed • Max. Image Resolution: 2 MP / 1080p (Full-HD), 1/2.8" Progressive CMOS (SONY) • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 60m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Light-Sensitivity: Color: 0.02lx, B/W: 0.001lx, IR: 0lx • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°), Auto Iris with automatic adaptation to changing light situations • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 2 MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Bi-directional Audio (Line In/Out) • Alarm I/O • 64 GB SD-Karte pre-installed • Power supply: PoE IEEE802.3af, class 0, max 12.95 watt, DC12V, 15.59 watt, AC24V, max 13.31 watt, max 25.08 VA • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on), Rel. humidity 10 to 90% non-condensing • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	1.740 g	17,8 cm
			9,9 l
	Mx-VB1A-2-IR-D-ALPR	4047438044318	28,5 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-	85258900	19,6 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-D-ALPR (License Plate Recognition) • Integrated professional international Automatic License Plate Recognition for slow and fast moving vehicles up to 35m distance • incl. MMC (Make, Model, Color Detection) • ALPR Activation License Key pre-installed • Max. Image Resolution: 2 MP / 1080p (Full-HD), 1/2.8" Progressive CMOS (SONY) • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 60m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Light-Sensitivity: Color: 0.02lx, B/W: 0.001lx, IR: 0lx • Remote Zoom / Focus • Motor-controlled Zoom lens (F1.6-F2.4: 9 to 22 mm, viewing angle H: 36.1°-15.4°, V: 19.8° -8.8°), Auto Iris with automatic adaptation to changing light situations • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 2 MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Bi-directional Audio (Line In/Out) • Alarm I/O • 64 GB SD-Karte pre-installed • Power supply: PoE IEEE802.3af, class 0, max 12.95 watt, DC12V, 15.59 watt, AC24V, max 13.31 watt, max 25.08 VA • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on), Rel. humidity 10 to 90% non-condensing • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	1.740 g	17,8 cm
			9,9 l

**Mx-VB1A-8-IR-VA****MOBOTIX MOVE VandalBullet VB-8-IR-VA (DNN Analytics)**


MOBOTIX MOVE Vandal Bullet Network Camera VB-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max 12.95 W, DC12V, 15.59 W, AC24V, max 13.31 W, max 25.08 VA • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040358 28,5 cm
85258900 19,6 cm
1.793 9 17,4 cm
9,7 l

**Mx-VB2A-5-IR-VA****MOBOTIX MOVE VandalBullet VB2-5-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Bullet Network Camera VB2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C (heater on), humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040464 29,6 cm
85258900 20,0 cm
1.710 9 17,5 cm
10,4 l


**Mx-VB3A-2-IR-VA****MOBOTIX MOVE VandalBullet VB3-2-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Bullet Network Camera VB3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP67, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years


4047438040440 29,6 cm
85258900 20,0 cm
1.460 9 17,5 cm
10,4 l

MOBOTIX MOVE Hemispheric Vandal Dome

MOBOTIX MOVE Hemispheric Vandal Dome Camera



	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VH1A-12-IR-VA	4047438038317	17,3 cm
	MOBOTIX MOVE 12MP Vandal Hemispheric	85258900	17,3 cm
	MOBOTIX MOVE Vandal Hemispheric Network Camera Mx-VH1A-12-IR-VA • Image sensor: 12MP (4072 x 3046), 1/1.7" Progressive CMOS • Indoor • ONVIF S/G/T/M • Hemispheric camera with built-in IR LED illumination (up to 10 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • focal length 1.65 mm • IK10 • Ambient temperature -10 to 55°C (14° to 131°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Max. Frame rate: 12MP@20 fps (Backend dewarping) 8.9MP@27 fps (Edge dewarping) • Power supply: PoE IEEE 802.3af • Warranty: 5 years • MTBF: 95,000h	640 g	10,7 cm
			3,2 l

MOBOTIX MOVE Fixed Domes

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-MD1A-5-IR	4047438042475	16,5 cm
	MOBOTIX MOVE Indoor MicroDome Mx-MD-5-IR	85258900	16,5 cm
	MOBOTIX MOVE Indoor MicroDome Network Camera Mx-MD-5-IR • Max. Image Resolution: 5M (2720x1976), 1/2.7" Progressive CMOS • ONVIF S/G/T dome camera with integrated IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F2.0: 2.8 mm), viewing angle H: 108.3°, V: - 76.5 °) • 3-axis lens adjustment • Indoor, IK8 • Ambient temperature -30 to 55°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max. 5.09 W • MTBF: 95.000h • Warranty: 5 years	450 g	13,5 cm
			3,7 l

MOBOTIX MOVE Multi Sensor Cameras

MOBOTIX MOVE Multi Sensor Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VM1A-20-IR-VA	4047438045063	32,3 cm
	MOBOTIX MOVE Vandal Multisensor VM-20-IR-VA	85258900	30,5 cm
	<p>MOBOTIX MOVE Vandal Multisensor Network Camera Mx-VM1A-20-IR-VA • Image sensor: 4x5MP (2608x1964), 1/2.8" Progressive CMOS IMX 675 SONY STARVIS II • Up to 3x optical zoom • ONVIF S/G/T/M • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Auto Object Tracking • Multisensor camera with built-in IR LED illumination (up to 30 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • FIPS140-2 level 2-compliant IT-Secure TPM chipset • NEMA-4x compliant • M.2 SATA 3 SSD support • 2D & 3D Motion Compensated Noise Reduction (MCTF) • Motor-controlled Zoom lens (F1.6 x 4: 2,8mm to 8 mm, viewing angle HxV: 111,5° - 53,7° x 79° - 40,2°) with autofocus and P-Iris with automatic adaptation to changing light situations • IK10 / IP66 • Ambient temperature -40 to 60°C (22° to 122°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 9 Video-Streams simultaneously - 4x2 per sensor module + 1 quadview stream) • Wide Dynamic Range (130 dB) • Max. Frame rate: 5MP@30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA • Opt. Integrated Microphone & Loudspeaker (bi-directional communication) • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 95000h • Warranty: 5 years</p>	3.740 g	15,6 cm
			15,4 l
	Mx-VMSD1A-2021-VA	4047438047524	34,0 cm
	MOBOTIX MOVE Vandal Multisensor PTZ Combo VMSD-2021-	85258900	28,7 cm
	<p>MOBOTIX MOVE Vandal Multisensor PTZ Combo Network Camera Mx-VMSD1A-2021-VA • Image sensor Multi: 4x5MP (2560x1920), 1/2.7" Progressive CMOS • Image sensor PTZ: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M • Pre-Installed AI-VMD DNN based Video-Motion Detection • Auto Object Tracking by PTZ-Unit • Automatic changeover from color to B / W image (mechanical IR cut filter) • FIPS140-2 level 3 certified IT-Security TPM chipset • Intelligent Encoding, "Smart Low Bitrate Control" • Multisensor: 4x Fixed Focal Lens 3.2mm (viewing angle HxV: 97° x 71°) • PTZ: 21x Motorized Zoom / Focus Lens 4.0 - 84.6mm with Autofokus & P-Iris (Viewing angle HxV: 3.7° - 77° x 2.2° - 44°) • IK10 / IP66 / IP67 • NNDA conformant • NEMA-4x conformant • Ambient temperature -40 to 55°C (-4° to 131°F), humidity 10 to 100% • Video codecs: H.264, H.265, MJPEG • Wide Dynamic Range up to 108 dB for Multisensor / 144 dB for PTZ-Unit • 1 Micro SD/SDHC/SDXC Card support up to 512 GB on each Multisensor/ PTZ • Max. Frame rate Multisensor: 5MP@15 fps H.264, MJPEG: 1080p @ 15 fps, max. Frame rate PTZ: 2MP@60 fps H.264, MJPEG: 1080p @ 60 fps • Power supply: PoE++ IEEE802.3bt, DC 54 V max. 35.6 W • Audio Line In/Out • MTBF: 95000h</p>	4.950 g	34,5 cm
			33,7 l

Optics

BeyondHumanVision

MOBOTIX

Sensor Modules 4K for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-M7SA-12DN016 12MP Hemispheric Day & Night Sensor Module 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, white	4047438040631 85299096 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-12DN016-b 12MP Hemispheric Day & Night Sensor Module black 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, black	4047438041379 85299096 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-8D500 8° 4K Day Sensor mod. TELE M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438047265 85299096 210 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-8DN040-b 120° 4K IR Cut Day & Night Sensor Module WIDE black M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041386 85299096 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-8DN050-b 95° 4K IR Cut Day & Night Sensor Module WIDE black M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041393 85299096 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



Mx-O-M7SA-8DN080-b
60° 4K IR Cut Day & Night Sensor Module WIDE black
 M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041409	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8DN100-b
45° 4K IR Cut Day & Night Sensor Module STANDARD black
 M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041416	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8DN150-b
30° 4K IR Cut Day & Night Sensor Module TELE black
 M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041423	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8DN280-b
15° 4K IR Cut Day & Night Sensor Module TELE black
 M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041430	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8L040
120° 4K LPF Sensor Module WIDE
 M73/S74 sensor module with premium wide-angle lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 120° x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438040310	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8L500
8° 4K LPF Sensor mod. TELE
 M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438044080	9,8 cm
85299096	7,5 cm
210 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N040-b**
120° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041447	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N050-b**
95° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041454	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N080-b**
60° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041461	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N100-b**
45° 4K Night Sensor Module STANDARD black

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041478	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N150-b**
30° 4K Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041485	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N280-b**
15° 4K Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041492	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N500****8° 4K Night Sensor mod. TELE**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438047272

9,8 cm

85299096

7,5 cm

210 g

9,0 cm

0,7 l

**Mx-O-M7SA-8DN040****120° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034968

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8DN050****95° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034814

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8DN080****60° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035941

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8DN100****45° 4K IR Cut Day & Night Sensor Module STANDARD**

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034821

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8DN150****30° 4K IR Cut Day & Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035958

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8DN280****15° 4K IR Cut Day & Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034838

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8D040****120° 4K Day Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034944

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8D050****95° 4K Day Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034845

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8D080****60° 4K Day Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035989

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8D100****45° 4K Day Sensor Module STANDARD**

M73/S74 sensor module with premium standard-angle lens for day, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034852

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8D150****30° 4K Day Sensor Module TELE**

M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035996

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8D280****15° 4K Day Sensor Module TELE**

M73/S74 sensor module with premium tele lens for day, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034869	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N040****120° 4K Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034951	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N050****95° 4K Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034876	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N080****60° 4K Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035965	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N100****45° 4K Night Sensor Module STANDARD**

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034883	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N150****30° 4K Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035972	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8N280****15° 4K Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034890

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8L150****30° 4K LPF Sensor Module TELE**

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037730

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

**Mx-O-M7SA-8L280****15° 4K LPF Sensor Module TELE**

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037723

9,8 cm

85299096

7,5 cm

140 g

9,0 cm

0,7 l

Sensor Modules 4MP Low Light for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-M7SA-4D045-f1.0	4047438044387	9,8 cm
	109° f/1,0 4MP Day Sensor module	85299096	7,5 cm
	M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 109° x 55°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4D050-f1.0	4047438044370	9,8 cm
	94° f/1,0 4MP Day Sensor module	85299096	7,5 cm
	M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 94°x49,5°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4D080-f1.0	4047438044363	9,8 cm
	57° f/1,0 4MP Day Sensor module	85299096	7,5 cm
	M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 57°x32°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4D115-f1.0	4047438044356	9,8 cm
	37° f/1,0 4MP Day Sensor module	85299096	7,5 cm
	M73/S74 sensor module with premium normal lens for day use, aperture: f/1.0, max. image angle (HxV): 37,5°x22°, max. resolution: 4MP (2688x1512), IP66, white	160 g	9,0 cm
			0,7 l
	Mx-O-M7SA-4DN040	4047438037167	9,8 cm
	120° 4MP IR Cut Day & Night Ultra LowLight Sensor Module	85299096	7,5 cm
	M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120° x 60°, max. resolution: 4MP (2688x1512), IP66, white	140 g	9,0 cm
			0,7 l

**Mx-O-M7SA-4DN050****95° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP (2688x1512), IP66, white

4047438037174	9,8 cm
85299096	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN080****60° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP (2688x1512), IP66, white

4047438037181	9,8 cm
85299096	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN100****45° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP (2688x1512), IP66, white

4047438037198	9,8 cm
85299096	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN150****30° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP (2688x1512), IP66, white






4047438037204	9,8 cm
85299096	7,5 cm
140 9	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN280****15° 4MP IR Cut Day & Night Low Light Sensor Module TELE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP (2688x1512), IP66, white

4047438037211	9,8 cm
85299096	7,5 cm
140 9	9,0 cm
	0,7 l

Sensor Modules 6MP For S16A/S16B And

Article No. / Name / Description	EAN / HS / weight	dimen.
 Mx-O-SMA-S-6D016 Sensor Module 6MP, B016 (Day), White Sensor module S16/M16 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029100 85299096 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-SMA-S-6D036 Sensor Module 6MP, B036 (Day), White Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029117 85299096 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-SMA-S-6D041 Sensor Module 6MP, B041 (Day), White Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029124 85299096 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-SMA-S-6D079 Sensor Module 6MP, B079 (Day), White Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029148 85299096 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
 Mx-O-SMA-S-6D237 Sensor Module 6MP, B237 (Day), White Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029162 85299096 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-O-SMA-S-6D500****Sensor Module 6MP, B500 (Day), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

4047438029179

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6N016****Sensor Module 6MP, B016 (Night), White**

Sensor module S16/M16 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029186

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6N036****Sensor Module 6MP, B036 (Night), White**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029193

9,8 cm

85299096

7,5 cm

170 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6N041****Sensor Module 6MP, B041 (Night), White**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029209

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6N079****Sensor Module 6MP, B079 (Night), White**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029223

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6N237****Sensor Module 6MP, B237 (Night), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029247

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6N500****Sensor Module 6MP, B500 (Night), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029254

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6L237****Sensor Module 6MP, B237 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029322

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6L500****Sensor Module 6MP, B500 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029339

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6D016-b****Sensor Module 6MP, B016 (Day), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029346

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6D041-b****Sensor Module 6MP, B041 (Day), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029360

9,8 cm

85299096

7,5 cm

144 g

9,0 cm

0,7 l

**Mx-O-SMA-S-6N016-b****Sensor Module 6MP, B016 (Night), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029421

9,8 cm

85299096

7,5 cm

144 g

9,0 cm


0,7 l

**Mx-O-SMA-S-6N041-b****Sensor Module 6MP, B041 (Night), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029445	9,8 cm
85299096	7,5 cm
144 9	9,0 cm
	0,7 l

BlockFlexMounts 12MP for S7x



Article No. / Name / Description

EAN / HS / weight dimen.

MX-O-M7SA-B-12DN016

4047438047715 10,0 cm

BlockFlexMount 12MP IR Cut Day & Night Sensor Module,

85299096 7,5 cm

Suitable for: S74 • 12MP Sensor module with premium hemispheric lens and IR cut filter for day and night use, max. resolution: 4K UHD (2880x2880) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

120 g 9,0 cm

0,7 l

BlockFlexMounts 4K for S7x

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-O-M7SA-B-8DN040	4047438047722	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	85299096	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN050	4047438047739	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	85299096	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN080	4047438047746	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	85299096	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN100	4047438047753	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	85299096	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l
	MX-O-M7SA-B-8DN150	4047438047760	10,0 cm
	BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.	85299096	7,5 cm
	Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	125 g	9,0 cm
			0,7 l



MX-O-M7SA-B-8DN280

BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.

Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8.5°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438047777	10,0 cm
85299096	7,5 cm
125 9	9,0 cm
	0,7 l



MX-O-M7SA-B-8DN500

BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.

Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 8°x4.5°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438047784	10,0 cm
85299096	7,5 cm
180 9	9,0 cm
	0,7 l

Sensor Modules 6MP For D16A/D16B

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-O-SDA-F-6D6N	4047438030182	19,6 cm
	Sensor Bridge FIX For D16, 2x 6MP (Day & Night)	85299096	18,0 cm
	Day & Night sensor bridge for D16 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)	346 g	14,8 cm
			5,2 l
	Mx-O-SDA-P-6D6D	4047438030199	19,6 cm
	Sensor Bridge PAN/180° For D16, 2x 6MP (Day)	85299096	18,0 cm
	Panorama/180° sensor bridge for D16 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	346 g	14,8 cm
			5,2 l
	Mx-O-SDA-P-6N6N	4047438030205	19,6 cm
	Sensor Bridge PAN-N/180° for D16, 2x 6MP (Night)	85299096	18,0 cm
	Panorama/180° sensor bridge for D16 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	344 g	14,8 cm
			5,2 l
	Mx-O-SDA-S-6D036	4047438029582	9,0 cm
	Sensor Module D16 6MP, Incl. B036 (Day)	85299096	7,5 cm
	Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	68 g	5,0 cm
			0,3 l
	Mx-O-SDA-S-6D041	4047438029599	9,0 cm
	Sensor Module D16 6MP, Incl. B041 (Day)	85299096	7,5 cm
	Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	66 g	5,0 cm
			0,3 l

**Mx-O-SDA-S-6D079****Sensor Module D16 6MP, Incl. B079 (Day)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029612	9,0 cm
85299096	7,5 cm
68 9	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N036****Sensor Module D16 6MP, Incl. B036 (Night)**

Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029643	9,0 cm
85299096	7,5 cm
68 9	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N041****Sensor Module D16 6MP, Incl. B041 (Night)**

Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029650	9,0 cm
85299096	7,5 cm
66 9	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N079****Sensor Module D16 6MP, Incl. B079 (Night)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029674	9,0 cm
85299096	7,5 cm
68 9	5,0 cm
	0,3 l

Camera Accessories

BeyondHumanVision

MOBOTIX

Camera Mounts (M7)

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-CM-M73	4047438039819	19,6 cm
	Ceiling Mount for M73 models	90079100	18,0 cm
	Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	631 g	14,8 cm
			5,2 l
	Mx-M-IC-DQ	4047438040761	39,5 cm
	In-Ceiling Set for MOBOTIX 7 Single Lens Models	90079100	29,6 cm
	In-Ceiling Set for MOBOTIX 7 Single Lens Models	665 g	9,0 cm
			10,5 l
	Mx-M-OW-DQ	4047438040662	29,6 cm
	On-Wall Set for MOBOTIX 7 Single Lens Models	90079100	19,6 cm
	On-Wall Set for MOBOTIX 7 Single Lens Models	410 g	9,0 cm
			5,2 l
	Mx-M-OW-DQ-10DEG	4047438043373	29,6 cm
	On-Wall Set 10° for MOBOTIX 7 Single Lens Models	90079100	19,6 cm
	On-Wall Set 10° inclined for MOBOTIX 7 Single Lens Models	500 g	9,0 cm
			5,2 l
	Mx-M-OW-M73	4047438039802	19,6 cm
	On-Wall Mount for M73 models	90079100	18,0 cm
	Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	502 g	14,8 cm
			5,2 l

**Mx-M-PM-M73****Pole mount for M73 models**

Suitable for: M73 Cameras • 2 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438035064	20,0 cm
90079100	18,2 cm
1.247 g	9,0 cm
	3,3 l

**Mx-M-WM-DQ****Wall Mount for MOBOTIX 7 Single Lens Models**

Wall Mount for MOBOTIX 7 Single Lens Models




4047438040778	29,6 cm
90079100	19,6 cm
835 g	18,0 cm
	10,4 l

**Mx-M-WPM-DQ****Wall & Pole/Corner Mount Set For D7x/Q7x**

Suitable for: D7x and Q7x • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (Mx-M-WM-DQ) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438041348	41,0 cm
90079100	31,0 cm
3.380 g	20,0 cm
	25,4 l

Mounts For S74

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-M-DLMA DualMount S7x, white For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white</p>	4047438036887 90079100 450 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p>Mx-M-DLMA-b DualMount S7x, black For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black</p>	4047438041553 90079100 450 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
 <p>Mx-M-PTMA PTMount S7x, white Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x and S16B • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white • Angled sensor cables are recommended (e.g. Mx-A-S7A-CBL01-AN)</p>	4047438036894 90079100 620 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 <p>Mx-M-PTMA-b PTMount S7x, black Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black</p>	4047438036900 90079100 620 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 <p>Mx-M-PTMA-OW On-Wall Kit for PTMount S7x, white On-Wall Kit for PTMount S7x, white incl. Mounting parts</p>	4047438039826 90079100 75 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-M-PTMA-OW-b****On-Wall Kit for PTMount S7x, black**

On-Wall Kit for PTMount S7x, black incl. Mounting parts

4047438039833	9,8 cm
90079100	7,5 cm
75 g	9,0 cm
	0,7 l

**Mx-M-SLMA****SingleMount S7x, white**

For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x and S16B (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white

4047438036870	14,8 cm
90079100	9,8 cm
240 g	9,0 cm
	1,3 l

**Mx-M-SLMA-b****SingleMount S7x, black**

For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black

4047438037921	14,8 cm
90079100	9,8 cm
240 g	9,0 cm
	1,3 l

S7x Sensor Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-S7A-AUCBL05-AN	4047438040501	14,0 cm
	S74 audio cable 5m	85444210	3,5 cm
	Audio cable to connect a MOBOTIX 7 audio module Mx-F-AUDA to the IO board Mx-F-S7A-INT01 the S74, length 5m	155 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL01	4047438035583	14,0 cm
	Sensor Cable 1m for S7x straight-straight	85444210	3,5 cm
	Sensor cable straight-straight, lenght 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body	70 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL01-AN	4047438035897	14,0 cm
	Sensor cable 1m for S7x straight-angled	85444210	3,5 cm
	Sensor cable straight-angled, lenght 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts	70 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL02	4047438035590	14,0 cm
	Sensor Cable 2m for S7x straight-straight	85444210	3,5 cm
	Sensor cable straight-straight, lenght 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body	90 g	15,0 cm
			0,7 l
	Mx-A-S7A-CBL02-AN	4047438035903	14,0 cm
	Sensor cable 2m for S7x straight-angled	85444210	3,5 cm
	Sensor cable straight-angled, lenght 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts	90 g	15,0 cm
			0,7 l

**Mx-A-S7A-CBL03****Sensor Cable 3m for S7x straight-straight**


Sensor cable straight-straight, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body

4047438035606	14,0 cm
85444210	3,5 cm
110 g	15,0 cm
	0,7 l

**Mx-A-S7A-CBL03-AN****Sensor cable 3m for S7x straight-angled**


Sensor cable straight-angled, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts

4047438035910	14,0 cm
85444210	3,5 cm
110 g	15,0 cm
	0,7 l

**Mx-CBL-MUC-AB-1****S74 Cable MiniUSB-C to USB-A 1m**

MiniUSB-C straight > USB-A straight • Length 1 m /3,3 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037129	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AB-5****S74 Cable MiniUSB-C to USB-A 5m**


MiniUSB-C straight > USB-A straight • Length 5 m /16,4 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037136	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-AN-AB-1****S7x Cable MiniUSB-C to USB-A angled-straight 1m**

MiniUSB-C angled > USB-A straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040556	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AN-AB-5****S7x Cable MiniUSB-C to USB-A angled-straight 5m**

MiniUSB-C angled > USB-A straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040563	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-AN-MU-1****S7x Cable MiniUSB-C to MiniUSB angled-straight 1m**

MiniUSB-C angled > MiniUSB straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040532	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AN-MU-5****S7x Cable MiniUSB-C to MiniUSB angled-straight 5m**

MiniUSB-C angled > MiniUSB straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)


4047438040549	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-MU-5****S74 Cable MiniUSB-C to MiniUSB 5m**





MiniUSB-C straight > MiniUSB straight • Length 5 m /16,4 ft • For S74 • To connect RS232-IO-Box (MX-OPT-RS1-EXT)

4047438037150	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

Camera Mounts ONE

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-CM-M1	4047438048415	15,0 cm
	Ceiling Mount for M1 ONE Cameras	90079100	9,5 cm
	Suitable for: M1 ONE Cameras • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw, washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically •	160 g	9,0 cm
	Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)		1,3 l

HD Premium Lenses

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-B036	4047438026536	9,0 cm
	Ultra Wide Lens B036, Focal Length: 3.6 mm	90021100	7,5 cm
	Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)	34 g	5,0 cm 0,3 l
	MX-B041	4047438026543	9,0 cm
	Super Wide Lens B041, Focal Length: 4.1 mm	90021100	7,5 cm
	Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)	34 g	5,0 cm 0,3 l
	MX-B079	4047438026567	9,0 cm
	Standard Lens B079, Focal Length: 7.9 mm	90021100	7,5 cm
	Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)	34 g	5,0 cm 0,3 l
	MX-B237	4047438026581	9,0 cm
	lens for D1x/M2x/D2x (HS code 90021900)	90021100	7,5 cm
	Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)	34 g	5,0 cm 0,3 l
	MX-B500	4047438026598	9,0 cm
	Super Tele Lens B500, Focal Length: 50 mm	90021100	7,5 cm
	Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5 • Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)	52 g	5,0 cm 0,3 l



MX-SM-OPT-POL

Polarization Filter For Sensor Modules

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

4047438019781	9,0 cm
90079100	7,5 cm
28 9	5,0 cm
	0,3 l

Domes & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-M24M-OPT-LCSK	4047438012980	9,0 cm
	Replacement Lens Cover M2x, Standard	90079100	7,5 cm
	Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)	32 g	5,0 cm
			0,3 l
	MX-M24M-OPT-LCSG	4047438012997	9,0 cm
	Replacement Lens Cover M2x, With Glass Pane	90079100	7,5 cm
	Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	38 g	5,0 cm
			0,3 l
	MX-M24M-OPT-LCGL	4047438013000	9,0 cm
	Replacement Lens Cover M2x, Extended	90079100	7,5 cm
	Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	44 g	5,0 cm
			0,3 l
	MX-OPT-DK-L11	4047438016469	9,0 cm
	Replacement Cover Hemispheric	90079100	7,5 cm
	Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	24 g	5,0 cm
			0,3 l
	MX-D15-OPT-DCT	4047438018227	19,6 cm
	Replacement Cover D1x/v2x, Standard	90079100	14,8 cm
	Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)	54 g	9,0 cm
			2,6 l

**MX-D15-OPT-DCS****Replacement Cover D1x/v2x, Tinted**

Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments

4047438018210	19,6 cm
90079100	14,8 cm
54 g	9,0 cm
	2,6 l

**MX-D15-DCT-XL****Replacement Cover D1x FIX/PAN, XL**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)

4047438027519	19,6 cm
90079100	18,0 cm
281 g	14,8 cm
	5,2 l

**MX-D15-DCS-XL****Replacement Cover D1x PAN/FIX, XL Tinted**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)

4047438027526	19,6 cm
90079100	18,0 cm
60 g	14,8 cm
	5,2 l

**MX-D24M-OPT-DCT****Replacement Cover D2x, Standard**

Suitable for: D2x • With sealing ring



4047438011419	19,6 cm
90079100	15,0 cm
150 g	9,0 cm
	2,6 l

**MX-D24M-OPT-DCS****Replacement Cover D2x, Tinted**






Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments


4047438011402	19,6 cm
90079100	15,0 cm
150 g	9,0 cm
	2,6 l

Mounts For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-S14-OPT-MK-CW	4047438016384	10,0 cm
	Extension Set Sensor Module, 40 mm and 15° wedges	90079100	7,5 cm
	Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x and S7x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut	96 g	9,0 cm
			0,7 l
	MX-S14-OPT-MK-EX	4047438016391	9,8 cm
	Extension Sensor Module, 40 mm	90079100	7,5 cm
	1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions	62 g	9,0 cm
			0,7 l


Camera Mounts

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-M-OWA-AU	4047438030328	19,6 cm
	On-Wall Mounting Set With Audio For v26, White	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	510 g	14,8 cm
			5,2 l
	Mx-M-OWA-AU-b	4047438030335	19,6 cm
	On-Wall Mounting Set With Audio For v26, Black	90079100	18,0 cm
	On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	510 g	14,8 cm
			5,2 l
	MX-MT-OW2-AUD	4047438027632	19,6 cm
	On-Wall Mounting Set With Audio For v25, White	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	500 g	14,8 cm
			5,2 l
	MX-MT-OW2-AUD-b	4047438027670	19,6 cm
	On-Wall Mounting Set With Audio For v25, Black	90079100	18,0 cm
	Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	500 g	14,8 cm
			5,2 l
	MX-MT-TUBE	4047438027557	29,6 cm
	MxTubeMount Ceiling Suspension System	90079100	19,6 cm
	For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color: white	870 g	9,0 cm
			5,2 l

**MX-MT-TUBE100****MxTube, 1 m**

Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium •
Outer diameter: 30 mm, wall thickness: 2 mm

4047438027687 106,0 cm
90079100 4,0 cm
700 9 4,0 cm
1,7 l

**MX-MT-TUBE200****MxTube, 2 m**

Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium •
Outer diameter: 30 mm, wall thickness: 2 mm

4047438027564 212,5 cm
90079100 4,0 cm
1.390 9 4,0 cm
3,4 l

**MX-OPT-AP****On-Wall Mounting Set For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts •
Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x
37 mm

4047438011358 29,6 cm
90079100 19,6 cm
612 9 9,0 cm
5,2 l

**MX-OPT-AP-10DEG****On-Wall Mounting Set For Q2x/D2x/ExtIO, 10°**

Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts •
Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating
additional modules • Dimensions: 165 mm x 37 mm

4047438010283 29,6 cm
90079100 19,6 cm
552 9 9,0 cm
5,2 l

**MX-D15-OPT-WHMH-Set****Wall & Pole/Corner Mount Set For D1x**

Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and
wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides
of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm
stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced
plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g.,
interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl.
mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438018159 41,0 cm
90079100 31,0 cm
6.280 9 39,0 cm
49,6 l

**MX-OPT-WHMH-Set****Wall & Pole/Corner Mount Set For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and
wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm
stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced
plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g.,
interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters
of 60 to 180 mm

4047438011396 41,0 cm
90079100 31,0 cm
3.380 9 20,0 cm
25,4 l

**MX-WH-Dome****Wall Mount For D1x**


Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts

4047438002233	39,5 cm
90079100	29,6 cm
2.020 g	18,0 cm
	21,0 l

**MX-OPT-WH****Wall Mount For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts

4047438011372	29,6 cm
90079100	19,6 cm
886 g	18,0 cm
	10,4 l

**MX-MH-Dome-ESWS****Pole/Corner Mount For MX-WH-Dome**

Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002240	34,0 cm
90079100	18,5 cm
3.000 g	11,5 cm
	7,2 l

**MX-MH-SecureFlex-ESWS****Pole Mount For M1x/M2x**

Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002226	20,0 cm
90079100	15,2 cm
1.230 g	8,0 cm
	2,4 l

**MX-OPT-MH****Pole/Corner Mount For MX-OPT-WH**

Suitable for: D7x, Q7x, Q2x, D2x, ExtIO • Mount for fastening the wall mount Mx-M-WM-DQ and MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WMH-Set) for the Q2x/D2x und ExtIO • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm • Wall mounts (Mx-M-WM-DQ or MX-OPT-WH) are not included in the scope of delivery and must be ordered separately

4047438011389	21,0 cm
90079100	20,0 cm
2.050 g	17,0 cm
	7,1 l

**MX-OPT-IC-ESMA****In-Ceiling Set For Q2x/D2x/ExtIO, Matt**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011433	29,6 cm
90079100	19,6 cm
724 g	9,0 cm
	5,2 l

**MX-OPT-IC-ESPO****In-Ceiling Set For Q2x/D2x/ExtIO, Polished**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011426	29,6 cm
90079100	19,6 cm
724 9	9,0 cm
	5,2 l

**MX-OPT-IC****In-Ceiling Set For Q2x/D2x/ExtIO, White**

Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011365	29,6 cm
90079100	19,6 cm
412 9	9,0 cm
	5,2 l

**MX-DH-M24-SecureFlex****Ceiling Mount For M16/M26**

Suitable for: M16, M26, M15, M25, M24 • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw, washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically • Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)

4047438015653	15,0 cm
90079100	9,5 cm
160 9	9,0 cm
	1,3 l

**MX-OPT-TW-Demo-1****Demo Table/Wall Mount For Q2x/D2x**

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055	14,8 cm
90079100	9,8 cm
170 9	9,0 cm
	1,3 l

MOBOTIX Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-OPT-CBL-LAN-1-SP	4047438041591	23,5 cm
	Ethernet Patch Cable for MOBOTIX M73, 1 m	85444210	15,0 cm
	Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	40 g	2,0 cm
			0,7 l
	MX-OPT-CBL-LAN-10-SP	4047438041560	27,0 cm
	Ethernet Patch Cable for MOBOTIX M73, 10 m	85444210	17,0 cm
	Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	465 g	4,0 cm
			1,8 l
	MX-OPT-CBL-LAN-2-SP	4047438041584	23,5 cm
	Ethernet Patch Cable for MOBOTIX M73, 2 m	85444210	15,0 cm
	Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	65 g	2,0 cm
			0,7 l
	MX-OPT-CBL-LAN-5-SP	4047438041577	23,5 cm
	Ethernet Patch Cable for MOBOTIX M73, 5 m	85444210	15,0 cm
	Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	240 g	4,0 cm
			1,4 l
	MX-FLEX-OPT-CBL-015	4047438019941	9,8 cm
	Sensor Module Cable For M15/M16, 0.15 m	85444210	7,5 cm
	Lenght: 0.15 m/0,5 ft, to connect one sensor module (inside camera housing), angled plugs, only for M15/M16	16 g	9,0 cm
			0,7 l

**MX-FLEX-OPT-CBL-05****Sensor Cable For S1x, 0.5 m**

Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018890	10,0 cm
85444210	7,5 cm
66 g	9,0 cm
	0,7 l

**MX-FLEX-OPT-CBL-1****Sensor Cable For S1x, 1 m**

Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018883	10,0 cm
85444210	7,5 cm
80 g	9,0 cm
	0,7 l

**MX-FLEX-OPT-CBL-2****Sensor Cable For S1x, 2 m**

Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018876	10,0 cm
85444210	7,5 cm
116 g	9,0 cm
	0,7 l

**MX-FLEX-OPT-CBL-3****Sensor Cable For S1x (6MP/Thermal), 3 m**

Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S15/S16 camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules

4047438024303	10,0 cm
85444210	7,5 cm
144 g	9,0 cm
	0,7 l

**MX-OPT-CBL-LAN-1****Ethernet Patch Cable, 1 m**

Ethernet Patch Cable for MOBOTIX systems (except M73) • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012300	23,5 cm
85444210	15,0 cm
36 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-10****Ethernet Patch Cable, 10 m**

Ethernet Patch Cable for MOBOTIX systems (except M73) • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012331	27,0 cm
85444210	17,0 cm
462 g	4,0 cm
	1,8 l

**MX-OPT-CBL-LAN-2****Ethernet Patch Cable, 2 m**

Ethernet Patch Cable for MOBOTIX systems (except M73) • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012317	23,5 cm
85444210	15,0 cm
62 9	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-5****Ethernet Patch Cable, 5 m**

Ethernet Patch Cable for MOBOTIX systems (except M73) • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012324	23,5 cm
85444210	15,0 cm
237 9	4,0 cm
	1,4 l

**MX-FLEX-IO-CBL-015****IO Connection Cable For M15/M16, 0.15 m**

Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15/M16 (inside camera housing)






4047438019958	13,5 cm
85444210	8,0 cm
10 9	2,0 cm
	0,2 l

**MX-CBL-NPA-BAT-2****NPA Battery Cable, 2 m**

NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft

4047438013949	10,0 cm
85444210	7,5 cm
68 9	9,0 cm
	0,7 l

Other Camera Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-SEC-SCREWS-SET Security Screw Set With Allen Bit For M73 Triple set of anti-theft screws (1 pcs M6x65, 4 pcs M6x16, 2 pcs M6x13) to securely attach the M73. Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)	4047438045209 90079100 68 g	9,0 cm 7,5 cm 4,6 cm 0,3 l
	Mx-O-M7SA-Blind Blind Module M73 For M73 • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.	4047438035415 90079100 50 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-OPT-Ring-L10-L12-BL Sealing Ring For Hemispheric Sensor Modules, Black Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black	4047438021241 90079100 16 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
	MX-OPT-Ring-L10-L12-PW Sealing Ring For Hemispheric Sensor Modules, White Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white	4047438021234 90079100 16 g	7,5 cm 4,9 cm 9,0 cm 0,3 l
	MX-OPT-SEC-SCREWS-SET Security Screw Set With Allen Bit For M1x/M2x Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)	4047438021265 90079100 120 g	7,5 cm 4,9 cm 9,0 cm 0,3 l






**MX-SM-Blind-PW****Blind Module M1x**

For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.

4047438019965	9,0 cm
90079100	7,5 cm
46 9	5,0 cm
	0,3 l

MOBOTIX MOVE Accessories

MOBOTIX MOVE Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-SD-DBC-EC	4047438041508	26,0 cm
	Dome-Bubble EverClear (Clear) for MOBOTIX MOVE SD	90079100	25,5 cm
	Dome Bubble EverClear (Clear) for MOBOTIX MOVE PTZ SD-230/330	580 g	17,0 cm
			11,3 l
	Mx-A-SD-DBT-EC	4047438041515	26,0 cm
	Dome Bubble EverClear (Tinted) for MOBOTIX MOVE SD	90079100	25,5 cm
	Dome Bubble EverClear (Tinted) for MOBOTIX MOVE PTZ SD-230/330	580 g	17,0 cm
			11,3 l
	Mx-A-SD-DCS	4047438031776	26,0 cm
	Tinted Dome For MOBOTIX MOVE SD-330	90079100	25,5 cm
	Tinted replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330 • For particularly bright environments	300 g	17,0 cm
			11,3 l
	Mx-A-SD-DCT	4047438031783	26,0 cm
	Dome (Standard) For MOBOTIX MOVE SD-330	90079100	25,5 cm
	Standard replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330	300 g	17,0 cm
			11,3 l
	Mx-A-VB-FGK-EC	4047438041546	12,0 cm
	Frontglass Kit EverClear for MOBOTIX MOVE VandalBullet -	90079100	11,0 cm
	Frontglass Kit EverClear for MOBOTIX MOVE VB VandalBullet VB (model > Nov. 21)	33 g	3,0 cm
			0,4 l

**Mx-A-VD-DBC-EC****Dome Bubble EverClear (Clear) For MOBOTIX MOVE**

Dome Bubble EverClear (Clear) For MOBOTIX MOVE VD VandalDomes

4047438041522	17,0 cm
90079100	17,0 cm
240 g	13,0 cm
	3,8 l

**Mx-A-VD-DBT-EC****Dome -Bubble EverClear (Tinted) For MOBOTIX MOVE**

Dome Bubble EverClear (Tinted) For MOBOTIX MOVE VD VandalDomes

4047438041539	17,0 cm
90079100	17,0 cm
240 g	13,0 cm
	3,8 l

**Mx-A-VD-DCS****Tinted Dome For MOBOTIX MOVE VandalDome**

Tinted replacement dome for particularly bright environments • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031714	16,1 cm
90079100	16,1 cm
210 g	11,5 cm
	3,0 l

**Mx-A-VD-DCT****Dome (Standard) For MOBOTIX MOVE VandalDome**


VD Standard replacement dome • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031721	16,1 cm
90079100	16,1 cm
250 g	11,5 cm
	3,0 l

**Mx-A-VM-DBC****Dome-Bubble (Clear) for MOBOTIX MOVE Vandal**


VM Standard replacement dome • Suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047685	26,6 cm
90079100	25,0 cm
530 g	8,5 cm
	5,7 l

**Mx-A-VM-DBT****Dome-Bubble (Tinted) For MOBOTIX MOVE Vandal**


Tinted replacement dome for particularly bright environments • Suitable for MOBOTIX MOVE Vandal Multiisensor camera Mx-VM1A-20-IR-VA

4047438047692	26,6 cm
90079100	25,0 cm
530 g	8,5 cm
	5,7 l

**Mx-M-BC-P****Pole Mount For MOBOTIX MOVE BulletCamera**


BC Pole Mount suitable for all MOBOTIX MOVE BulletCameras (except Mx-BC1A-2-IR)

4047438031677	17,3 cm
90079100	17,3 cm
1.000 g	16,7 cm
	5,0 l

**Mx-M-BC-W****Wall Mount For MOBOTIX MOVE BulletCamera**


BC Wall Mount suitable for MOBOTIX MOVE BulletCamera (except Mx-BC1A-2-IR)

4047438031660	17,3 cm
90079100	17,3 cm
840 g	10,7 cm
	3,2 l

**Mx-M-NVR16-RM****19" Rack Mounting Brackets for MOVE NVR 16CH**


2x metal mounting brackets for installing MOBOTIX MOVE NVR 16CH in a 19" rack

4047438037075	14,5 cm
85299096	11,0 cm
447 g	6,0 cm
	1,0 l

**Mx-M-NVR8-RM****19" Rack Mounting Brackets for MOVE NVR 8CH**

2x metal mounting brackets for installing MOBOTIX MOVE NVR 8CH in a 19" rack

4047438037068	14,5 cm
85299096	11,0 cm
544 g	6,0 cm
	1,0 l

**Mx-M-SD-C****Corner Mount For MOBOTIX MOVE SpeedDomes**

SD Corner Mount suitable for MOBOTIX MOVE SpeedDomes • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031769	21,0 cm
90079100	12,5 cm
2.170 g	25,0 cm
	6,6 l

**Mx-M-SD-GN****MOBOTIX MOVE SD Parapet Mount**

MOBOTIX MOVE SD Parapet Mount(Gooseneck) with integrated junction Box for MOBOTIX MOVE SpeedDomes

4047438038997	90,0 cm
90079100	57,0 cm
14.800 g	20,0 cm
	102,6 l

**Mx-M-SD-P****Pole Mount For MOBOTIX MOVE Speeddomes**

SD Pole Mount suitable for MOBOTIX MOVE SpeedDomes • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031752	31,0 cm
90079100	15,5 cm
1.580 g	26,0 cm
	12,5 l

**Mx-M-SD-PM****MOBOTIX MOVE SpeedDomes Pendant Mount Kit**

MOBOTIX MOVE SD Pendant Mount Kit 25 cm incl. Base-Mount for MOBOTIX MOVE SpeedDomes, 25 cm pendant pipe, installation material and safety wires 50cm & 1m. Max. extendable pendant mount lenght 1m by usage of additional pendant mount extension Mx-M-SD-PMEXT

4047438039000	64,0 cm
90079100	22,0 cm
2.295 g	22,0 cm
	31,0 l

**Mx-M-SD-PMEXT****MOBOTIX MOVE SD PM Extension**

MOBOTIX MOVE SD Pendant Mount 25cm extension for Mx-M-SD-PM

4047438039017	14,4 cm
90079100	14,5 cm
800 g	28,0 cm
	5,8 l

**Mx-M-SD-W****Wall Mount For MOBOTIX MOVE Speeddomes**

SD Wall Mount suitable for MOBOTIX MOVE SpeedDomes • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)

4047438031745	21,6 cm
90079100	12,7 cm
840 g	14,8 cm
	4,1 l

**Mx-M-SD-WL****Wall Mount long for MOBOTIX MOVE Speeddomes and**

Wall Mount long for MOBOTIX MOVE Speeddomes SD and Multisensor VMxx • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)

4047438048194	34,8 cm
90079100	10,4 cm
1.500 g	13,8 cm
	5,0 l

**Mx-M-SD-WM****Wall Mount for MOBOTIX MOVE SpeedDome**


MOBOTIX MOVE SD Wall Mount supporting optional Junction Box Mx-M-SD-WMJB, suitable for MOBOTIX MOVE SpeedDomes

4047438038973	33,0 cm
90079100	15,0 cm
1.300 g	23,0 cm
	11,4 l

**Mx-M-SD-WMJB****MOBOTIX MOVE SD Junction Box**

MOBOTIX MOVE SD Wall Mount Junction Box for use with Wall Mount Mx-M-SD-WM

4047438038980	29,0 cm
90079100	32,0 cm
4.800 g	19,0 cm
	17,6 l

**Mx-M-VD-C****Corner Mount For MOBOTIX MOVE VandalDome**

VD Corner Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031738	21,0 cm
90079100	12,5 cm
2.170 g	25,0 cm
	6,6 l

**Mx-M-VD-IC****In-Ceiling Set For MOBOTIX MOVE VandalDome**

VD In-Ceiling Set suitable for all MOBOTIX MOVE VandalDome cameras

4047438031684	23,4 cm
90079100	23,4 cm
800 g	12,8 cm
	7,0 l

**Mx-M-VD-P****Pole Mount For MOBOTIX MOVE VandalDome**

VD-Pole Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031707	31,0 cm
90079100	15,5 cm
1.580 g	26,0 cm
	12,5 l

**Mx-M-VD-W****Wall Mount For MOBOTIX MOVE VandalDome**

VD Wall Mount Set (2-piece) suitable for all MOBOTIX MOVE VandalDome cameras

4047438031691	31,0 cm
90079100	22,0 cm
1.400 g	18,0 cm
	12,3 l

**Mx-M-VM-AP****Adapter Mounting Plate for MOBOTIX MOVE Vandal**

Adaptor Mounting Plate suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047678	36,4 cm
90079100	34,5 cm
1.950 g	12,8 cm
	16,1 l

**Mx-M-VM-IC****In-Ceiling Set For MOBOTIX MOVE Vandal Multisensor**

In-Ceiling Set suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047661	31,6 cm
90079100	34,5 cm
965 g	12,8 cm
	14,0 l

**Mx-M-VMSD-AP****Adapter Mounting-Plate for MOBOTIX MOVE Vandal**

VMSD Adaptor Mounting -Plate suitable for MOBOTIX MOVE Vandal Multisensor PTZ Combo camera Mx-VMSD1A-2021-VA

4047438047517	32,2 cm
90079100	32,2 cm
1.570 g	11,9 cm
	12,3 l

**Mx-M-VMSD-IC****In-Ceiling Set For MOBOTIX MOVE Vandal Multisensor PTZ**

VMSD In-Ceiling Set suitable for MOBOTIX MOVE Vandal Multisensor PTZ Combo camera Mx-VMSD1A-2021-VA

4047438047708	40,9 cm
90079100	38,9 cm
3.500 g	22,6 cm
	36,0 l

**Mx-M-VT-AP****Adapter Mounting-Plate for MOBOTIX MOVE Vandal Turret**


Adapter Mounting Plate suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT-5-IR, VT-203-IR, VT-503-IR

4047438049009	16,2 cm
90079100	17,2 cm
600 g	14,3 cm
	4,0 l

**Mx-M-VT-JB****Junction Box for MOBOTIX MOVE Vandal Turret Camera**

Junction Box suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT-5-IR, VT-203-IR, VT-503-IR

4047438049016	17,3 cm
90079100	17,1 cm
950 g	13,4 cm
	4,0 l

**Mx-M-VT-WM****Wall Mount for MOBOTIX MOVE Vandal Turret Camera**

Wall Mount suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT-5-IR, VT-203-IR, VT-503-IR

4047438048996	22,6 cm
90079100	10,3 cm
600 g	15,5 cm
	3,6 l

MOVE Other Accessories






Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-ETP1A-2601-POW	4047438042581 19,4 cm
	Plug-type Power-supply for Mx-A-ETP1A-2601-SET	85365019 14,2 cm
	Plug-type power supply for Mx-A-ETP1A-2601-SET • Output: 57V DC +/-3% / 1.2 A •	490 g 4,0 cm
	Input: 90-260V AC (47-63Hz) • 68,4 Watt • Operating Temperature: 0-40 °C	1,1 l
	Mx-A-ETP1A-2601-SET	4047438041317 20,7 cm
	Media converter set Ethernet(PoE+) – Twisted-Pair	85299030 12,5 cm
	Mx-ETP1A-2601-SET Complete set consisting of two two-wire transmitting and receiving units for realising an Ethernet transmission path via Twisted Pair cable. • Transmission of Ethernet and PoE+ power supply via two-wire line according to IEEE1901. • Simple connection of 10/100 Mbps Ethernet end devices • Max. 95 Mbps transmission bandwidth, range up to 600m for data / 300m for PoE depending on the quality of the Twisted-Pair link • 128 bit AES network data encryption • Power supply 2-wire transmitter (Tx) and receiver (Rx) as well as end device via PoE+ network switch or external power supply 56VDC / 1.2A (not included!) • Connected end devices are supplied via PoE switch IEEE802.3af(PoE), IEEE802.3at (PoE+), UPoE up to 60W (requires ext. power supply unit). • Status LEDs (data, power supply, data link, PoE) • Integrated Overvoltage protection (IEC 61000-4-5 4kV(1.2 / 50us), 2kA(8 / 20us)) • Power Supply: TX: T-Linx or DC12V~57V, RX: PoE Switch or DC48V~57V • Operational temperature: -20 to 60 °C • Dimensions: 80.4(L) x 61.6(W) x 24(H)mm • Weight: RX/TX: 102g • Warranty: 2 years	368 g 7,0 cm
		1,8 l
	Mx-A-KBD1A-PTZ-JOG	4047438040754 42,5 cm
	MOBOTIX USB Keyboard with PTZ Joystick & Jog-Shuttle	85299030 27,0 cm
	USB control panel for operating MOBOTIX MxMC 2.6 and higher and MOBOTIX HUB incl. Control of software PTZ and motorized PTZ cameras and pan/tilt devices • Integrated 3-axis joystick • Integrated jog shuttle • 38 control keys with backlight predefined for MxMC functions or freely definable for MOBOTIX HUB • Integrated alarm buzzer • Suitable for operation as HID device on MOBOTIX VMS with Windows and MAC based operating systems via USB2.0 • Suitable for right- and left-handed users • Power supply: USB, max. 350 mA • Operating temperature: 0° - 45 °C (32 °F- 113 °F)	1.900 g 17,5 cm
		20,1 l


System Components

BeyondHumanVision

MOBOTIX


Functional Modules for MOBOTIX 7 Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-F-AUDA M73/S74 Audio Module equipped with microphone / Weatherproof audio module (IP66, -30 to 65 °C, IK07) with integrated microphone and speaker for connection to the MOBOTIX M73 camera, no camera removal required • In connection with the audio cable Mx-A-S7A-AUCBL05-AN and the IO plug-in board Mx-F-S7A-INT01, the audio module can also be operated at the S74 (compatible with S74 module mounts)	4047438034937 85299030 150 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-IRA-S M73/S74 IR Light Module for Standard Lens (45° - 60°) Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 45°-60° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses: up to 70 m	4047438034913 85299030 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-IRA-T M73/S74 IR Light Module for Tele Lens (15° - 30°) Infrared illuminator module for MOBOTIX M73/S74 cameras night sensor modules with 15°-30° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses up to 100 m	4047438034920 85299030 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-IRA-W M73/S74 IR Light Module for Wide Lens (95°) Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 95° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with W-IR illuminator: up to 40 m	4047438034906 85299030 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-F-MSA MOBOTIX 7 MultiSense Outdoor Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (max ±0.4°C / 0.72°F) and microphone • Camera connection and supply via MOBOTIX 7 sensor cable (up to 3m): power consumption approx. 100 mW • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Protection class IP66 • IK05 • Housing color: white	4047438035545 85299030 100 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-F-S7A-INT01****S74 IO Slide in Board**


S74 IO slide in board with 1x input / output, 1x line in / out and 1x mic in / speaker out functionality • Connection option for audio module Mx-F-AUDA with audio cable Mx-A-S7A-AUCBL05-AN

4047438035576	14,8 cm
85299030	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-S7A-LSA****S74 network slide in board with LSA terminal**


S74 network slide in board with LSA terminal

4047438037051	14,8 cm
85299030	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-S7A-RJ45****S74 Network slide in board with RJ45 socket**

S74 Network slide in board with RJ45 socket

4047438035569	14,8 cm
85299030	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-S7A-RJ45-VDC****S74 RJ45 Network slide in board with 12/24 VDC Power**

S74 Network slide in board with RJ45 socket and 12/24V DC Power Supply

4047438039680	14,8 cm
85299030	9,8 cm
110 9	9,0 cm
	1,3 l

**Mx-F-WLA-S****M73/S74 White Light for Standard lens 45-60°**

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 45-60° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses with illuminator: up to 60 m

4047438042529	9,8 cm
85395200	7,5 cm
145 9	9,0 cm
	0,7 l

**Mx-F-WLA-T****M73/S74 White Light for tele lens 15-30°**

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 15-30° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses with illuminator: up to 80 m

4047438042536	9,8 cm
85395200	7,5 cm
145 9	9,0 cm
	0,7 l

**Mx-F-WLA-W****M73/S74 White Light for Wide Lens 95°**

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 95° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with illuminator: up to 40 m






4047438042512 9,8 cm

85395200 7,5 cm






145 g 9,0 cm


0,7 l

Interface Boxes

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-F-4IOA Input/Output Box for MOBOTIX 7 and MOBOTIX ONE Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB-C • 4 galvanically isolated inputs, 4 relay output • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F</p>	4047438048309 85299030 130 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
 <p>Mx-F-GPSA GPS Box for MOBOTIX 7 and ONE Weatherproof GPS time base for MOBOTIX 7 and ONE cameras • GPS and Glonass support • Connects via USB-C • Protection class IP66/IK08, -30 to 60°C / -22 to +140°F</p>	4047438048316 85299030 120 g	10,5 cm 6,8 cm 10,5 cm 0,7 l
 <p>Mx-F-NPAA POE Power Adapter for MOBOTIX cameras Weatherproof PoE Injector and network connector • Needs external power supply units and batteries from 12 to 24V DC • Protection class IP66/IK08, -30 to 50°C / -22 to 122°F • Important: only use with original MOBOTIX patch cables</p>	4047438048323 85299030 140 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
 <p>MX-Overvoltage-Protection-Box-LSA Network Connector with Surge Protection, LSA Version Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x</p>	4047438018470 85299030 146 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
 <p>MX-Overvoltage-Protection-Box-RJ45 Network Connector with Surge Protection, RJ45 Version Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x</p>	4047438018463 85299030 150 g	10,0 cm 7,5 cm 9,0 cm 0,7 l

Functional Enhancement & IR Illuminators

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-OPT-IO3-INT	4047438025928	10,7 cm
	Extension Module For c25, i25, p25 And v25	85299030	5,2 cm
	Extension module for the indoor cameras x25 (to be mounted on the backside) • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window • contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x • isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA • per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l
	Mx-A-IOA-IC	4047438029032	10,7 cm
	Extension Module For All Indoor Cameras x26A/x26B	85299030	5,2 cm
	Expansion module for Indoor Cameras c26A/B, i26A/B, p26A/B and v26A/B (installed on the back) • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by the x26B Indoor Cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W	45 g	8,7 cm
			0,5 l
	Mx-A-IRA-120	4047438030342	20,5 cm
	MxIRLight Infrared Illuminator (860 nm), 120°x120°	85394900	17,5 cm
	Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	1.098 g	12,5 cm
			4,5 l
	Mx-A-IRA-90	4047438030359	20,5 cm
	MxIRLight Infrared Illuminator (860 nm), 90°x90°	85394900	17,5 cm
	Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	1.112 g	12,5 cm
			4,5 l
	Mx-A-IRA-60	4047438030366	20,5 cm
	MxIRLight Infrared Illuminator (860 nm), 60°x60°	85394900	17,5 cm
	Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	1.116 g	12,5 cm
			4,5 l

**Mx-A-IRA-45****MxIRLight Infrared Illuminator (860 nm), 45°x45°**


Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030373	20,5 cm
85394900	17,5 cm
1.124 9	12,5 cm
	4,5 l

**Mx-A-IRA-30****MxIRLight Infrared Illuminator (860 nm), 30°x30°**

Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030380	20,5 cm
85394900	17,5 cm
1.096 9	12,5 cm
	4,5 l

**Mx-A-IRA-15****MxIRLight Infrared Illuminator (860 nm), 15°x15°**

Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030397	20,5 cm
85394900	17,5 cm
1.090 9	12,5 cm
	4,5 l

**Mx-M-IRA-ML****MxIRLight Mounting Brackets For M1x**

Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030403	19,6 cm
85399010	5,5 cm
216 9	3,5 cm
	0,4 l

**Mx-M-IRA-M****MxIRLight Mounting Brackets For M2x**

Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030410	14,0 cm
85399010	5,5 cm
150 9	3,5 cm
	0,3 l

PoE Power Supply




Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-NPA-PoE1A-60W-BT PoE++ Power Network Injektor 60 Watt PoE++ 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • -10° to 40°C • @60W • -10° to 50°C, humidity 10 to 90% @30W • IEEE 802.3bt compliant • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation • Full Protection OVP, OCP • Additional required power cord C14-type not included • Warranty: 1 year</p>	4047438047531 85043180 318 g	17,0 cm 7,0 cm 4,7 cm 0,6 l
 <p>Mx-NPA-UPoE1A-60W UPoE Power Injector 60W UPoE (PoE++) 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • 14° to 113°F @60W • 14° to 131°F @30W • IEEE 802.3at compliant with 2-event classification • IEEE 802.3af backward compatible • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation</p>	4047438039024 85043180 450 g	20,5 cm 11,5 cm 6,5 cm 1,5 l
 <p>Mx-NPA-PoE-EU-Set PoE Power Adapter Set, EU PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug</p>	4047438012249 85043180 268 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
 <p>Mx-NPA-PoE-INT-Set PoE Power Adapter Set, INT PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug</p>	4047438012256 85043180 314 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
 <p>Mx-NPA-PoE-RJ PoE Power Adapter PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed</p>	4047438013932 85043180 60 g	9,0 cm 7,5 cm 5,0 cm 0,3 l

**MX-SNT-INT-PoE****Universal Power Supply With 4 Power Plugs**

For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F

4047438013925	9,8 cm
85043180	7,5 cm
160 g	9,0 cm
	0,7 l

MOBOTIX Storage & Recording Solutions

Article No. / Name / Description	EAN / HS / weight	dimen.
 <p>Mx-S-NVR1A-64-POE24</p> <p>MOBOTIX MOVE NVR Network Video Recorder 64 Channels</p> <p>MOBOTIX MOVE NVR Network Video Recorder for recording and Display up to 64 IP Cameras (Resolution up to 12MP) • 24 integrated PoE+ Ports for centralized powering of connected IP-Cameras • 8x 3.5" SATA3 lockable HDD cartridge-slots (Delivery without hard disks (not available via MOBOTIX) • Harddrives "Hot-Swappable" • RAID 0/1/5/10 Support for Data recovering in case of HDD Failure • Optional Failover-Server functionality withing MOVE NVR System • IP-Data-Throughput (Live & Recording): avg.: 480 Mbps, peak 2up to 540 Mbps • Video-Codecs : H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support • 19"-Rack mount kit included. • Environmental Temperature 0 to 40°C • Power Supply: AC AC 100~240V, ATX 520W (53V/360W for PoE; 12V/160W for HDD/System) • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • Warranty: 5 Years (excl. HDD's)</p>	4047438040365	58,0 cm
	85219000	58,0 cm
	12.510 g	25,0 cm
		84,1 l
 <p>Mx-S-NVR1B-16-POE</p> <p>MOBOTIX MOVE NVR Network Video Recorder 16 Channels</p> <p>MOBOTIX MOVE NVR Network Video Recorder with 16 integrated PoE IP camera channels (support of up to 24 IP cameras in total) • 8GB RAM integrated • Max. Storage capacity net: 28 TB (2x 3.5" SATA3) • Supplied without hard disks (not available via MOBOTIX) • IP data throughput (live & recording): max. 240 Mbps • Recording compression: H.264 / H.265 • Supports ONVIF S compliant third-party cameras • APP remote access (IOS / Android), live, playback • CMS (Central Monitoring Software) Remote Zugriff • Integrierated in MOBOTIX HUB VMS • iSCSI NAS storage support • Incl. power connection cable with EU plug (cable with US/GB/AU plug available on request) • Warranty: 5 Years (excl. HDD's)</p>	4047438047623	49,5 cm
	85219000	34,5 cm
	8.500 g	18,1 cm
		30,9 l
 <p>Mx-S-NVR1B-8-POE</p> <p>MOBOTIX MOVE NVR Network Video Recorder 8 Channels</p> <p>MOBOTIX MOVE NVR Network Video Recorder with 8 integrated PoE IP camera channels (support of up to 12 IP cameras in total) • 4GB RAM integrated • Max. Storage capacity net: 20 TB (2x 3.5" SATA3) Supplied without hard disks (not available via MOBOTIX) • IP data throughput (live & recording): max. 160 Mbps • Recording & playback: H.264 / H.265 • Supports ONVIF S compliant third-party cameras • APP remote access (IOS / Android), live, playback • CMS (Central Monitoring Software) Remote Zugriff • Integrierated in MOBOTIX HUB VMS • iSCSI NAS storage support • Incl. power connection cable with EU plug (cable with US/GB/AU plug available on request) • Warranty: 5 Years (excl. HDD's)</p>	4047438047616	42,6 cm
	85219000	37,9 cm
	4.200 g	11,0 cm
		17,8 l

MOBOTIX Cloud

BeyondHumanVision

MOBOTIX

MOBOTIX Cloud Bridge



Article No. / Name / Description

EAN / HS / weight dimen.

Mx-S-BRIDGEB-DT-20

4047438043588 29,6 cm

MOBOTIX CLOUD Bridge 304+ for up to 20 IP Cameras






85299030 19,6 cm

High-security connection box for the MOBOTIX CLOUD VMS • Locally connected to the Internet and up to 20 ONVIF IP cameras at 4MP resolution • Cybersecure connection to regionally available MOBOTIX CLOUD data centers • Secure end-to-end encryption of all data stored and transferred in the system • No data loss in case of up to 2-day Internet outage: Integrated hard disk as a memory buffer in case of interrupted connection to the cloud • No data loss due to Internet bandwidth fluctuations: Automatic data buffering in the BRIDGE • Ultra flexible cloud data storage with individually selectable retention period (max. 5 years) • Compact, robust metal housing with an extended temperature range and fanless device design for maximum reliability thanks to SSD memory • Dimensions (LxWxH): 127 x 127 x 45 mm (5" x 5" x 1.75") • Connections: AC power supply (adapter included), 2x ETH (1x for PoE switch for local cameras, 1x for internet router), monitor and keyboard (optional) • Integrated display for status display such as the IP

1.980 g 9,0 cm

5,2 l

MOBOTIX Cloud Subscriptions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-CL-Sub-ANA-001-12 MOBOTIX CLOUD Yearly Analytics Subscription, Line Cross	4047438042062	cm
	Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.	g	cm l
	Mx-CL-Sub-ANA-001-36 MOBOTIX CLOUD 3 Yearly Analytics Subscription, Line Cross	4047438046701	cm
	3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.	g	cm l
	Mx-CL-Sub-ANA-001-60 MOBOTIX CLOUD 5 Yearly Analytics Subscription, Line Cross	4047438046718	cm
	5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.	g	cm l
	Mx-CL-Sub-ANA-002-12 MOBOTIX CLOUD Yearly Analytics Subscription, Counting	4047438042079	cm
	Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.	g	cm l
	Mx-CL-Sub-ANA-002-36 MOBOTIX CLOUD 3 Yearly Analytics Subscription, Counting	4047438046725	cm
	3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.	g	cm l

**Mx-CL-Sub-ANA-002-60****MOBOTIX CLOUD 5 Yearly Analytics Subscription, Counting**

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438046732

cm

g

cm

l

**Mx-CL-Sub-ANA-003-12****MOBOTIX CLOUD Yearly Analytics Subscription, Area**

Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438042086

cm

g

cm

cm

l

**Mx-CL-Sub-ANA-003-36****MOBOTIX CLOUD 3 Yearly Analytics Subscription, Area**

3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438046749

cm

g

cm

cm

l

**Mx-CL-Sub-ANA-003-60****MOBOTIX CLOUD 5 Yearly Analytics Subscription, Area**

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438046756

cm

g

cm

cm

l

**Mx-CL-Sub-ANA-004-12****MOBOTIX CLOUD Yearly Analytics Subscription, Camera**

Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438042093

cm

g

cm

cm

l

**Mx-CL-Sub-ANA-004-36****MOBOTIX CLOUD 3 Yearly Analytics Subscription, Camera**

3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438046763

cm

g

cm

cm

l

**Mx-CL-Sub-ANA-004-60**

4047438046770

cm

MOBOTIX CLOUD 5Y Analytics Subscription, Camera Tamper

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-ANA-005-12**

4047438042109

cm

MOBOTIX CLOUD Yearly Analytics Subscription, Loitering

Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-ANA-005-36**

4047438046787

cm

MOBOTIX CLOUD 3 Yearly Analytics Subscription, Loitering

3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-ANA-005-36**

4047438046794

cm

MOBOTIX CLOUD 5 Yearly Analytics Subscription, Loitering

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-ED001-1**

4047438048002

cm

1 Month MOBOTIX CLOUD Subscription, update to

1 Month subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-ED001-12**

4047438048019

cm

MOBOTIX CLOUD Yearly Subscription, update to

Yearly subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-ED001-36**

4047438048026

cm

3 Years MOBOTIX CLOUD Subscription, update to

cm

3 Years subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ED001-60**

4047438048033

cm

5 Years MOBOTIX CLOUD Subscription, update to

cm

5 Years subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ED002-1**

4047438048040

cm

1 Month MOBOTIX CLOUD Subscription, update to

cm

1 Month subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month.

g

cm
l**Mx-CL-Sub-ED002-12**

4047438048057

cm

MOBOTIX CLOUD Yearly Subscription, update to Enterprise

cm

Yearly subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ED002-36**

4047438048064

cm

3 Years MOBOTIX CLOUD Subscription, update to Enterprise

cm

3 Years subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l**Mx-CL-Sub-ED002-60**

4047438048071

cm

5 Years MOBOTIX CLOUD Subscription, update to Enterprise

cm

5 Years subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
l

**Mx-CL-Sub-HD1-D1095-12**

4047438041744

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D1095-36**

4047438045667

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D1095-60**

4047438045674

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D14-12**

4047438041676

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D14-36**

4047438045520

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D14-60**

4047438045537

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD1-D180-12**

4047438041713

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD1-D180-36**

4047438045605

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD1-D180-60**

4047438045612

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD1-D1825-12**

4047438041751

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD1-D1825-36**

4047438045681

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD1-D1825-60**

4047438045698

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l

**Mx-CL-Sub-HD1-D30-12**

4047438041683

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D30-36**

4047438045544

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D30-60**

4047438045551

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D365-12**

4047438041720

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D365-36**

4047438045629

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D365-60**

4047438045636

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD1-D60-12**

4047438041690


cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D60-36**

4047438045568

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D60-60**

4047438045575

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D7-12**

4047438041669

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D7-36**

4047438045506

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD1-D7-60**

4047438045513

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD1-D730-12**

4047438041737

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD1-D730-36**

4047438045643

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD1-D730-60**

4047438045650

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD1-D90-12**

4047438041706

cm

MOBOTIX CLOUD Yearly Camera Subscription, 720p/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD1-D90-36**

4047438045582

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD1-D90-60**

4047438045599

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D1095-12**

4047438042390

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D1095-36**

4047438046664

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D1095-60**

4047438046671

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D14-12**

4047438042321

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/14

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D14-36**

4047438046527

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D14-60**

4047438046534

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD10-D180-12**

4047438042369

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D180-36**

4047438046602

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D180-60**

4047438046619

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-12**

4047438042406

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-36**

4047438046688

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-60**

4047438046695

cm


MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD10-D30-12**

4047438042338

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/30

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD10-D30-36**

4047438046541

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D30-60**

4047438046558

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D365-12**

4047438042376

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D365-36**

4047438046626

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D365-60**

4047438046633

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D60-12**

4047438042345

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/60

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D60-36**

4047438046565

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D60-60**

4047438046572

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D7-12**

4047438042314

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D7-36**

4047438046503

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD10-D7-60**

4047438046510

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD10-D730-12**

4047438042383

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD10-D730-36**

4047438046640

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D730-60**

4047438046657

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D90-12**

4047438042352

cm

MOBOTIX CLOUD Yearly Camera Subscription, 10MP/90

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D90-36**

4047438046589

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD10-D90-60**

4047438046596

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD15-D1095-1**

4047438047128

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1095

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-HD15-D1095-12**

4047438047135

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/1095

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD15-D1095-36**

4047438047142

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD15-D1095-60**

4047438047159

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD15-D14-1**

4047438046848

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/14

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-HD15-D14-12**

4047438046855

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/14

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD15-D14-36**

4047438046862

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD15-D14-60**

4047438046879

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD15-D180-1**

4047438047005

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/180

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm
cm
l**Mx-CL-Sub-HD15-D180-12**

4047438047012

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/180

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD15-D180-36**

4047438047029

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-HD15-D180-60**

4047438047036

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l

**Mx-CL-Sub-HD15-D1825-1**

4047438047166

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1825

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D1825-12**

4047438047173

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/1825

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D1825-36**

4047438047180

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D1825-60**

4047438047197

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D30-1**

4047438046886

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/30

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D30-12**

4047438046893

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/30

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD15-D30-36**

4047438046909

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D30-60**

4047438046916

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-1**

4047438047043

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/365

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-12**

4047438047050

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/365

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-36**

4047438047067

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D365-60**

4047438047074

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD15-D60-1**

4047438046923

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/60

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D60-12**

4047438046930

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/60

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D60-36**

4047438046947

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D60-60**

4047438046954

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D7-1**

4047438046800

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/7

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D7-12**

4047438046817

cm


MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/7

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD15-D7-36**

4047438046824

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D7-60**

4047438046831

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-1**

4047438047081

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/730

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-12**

4047438047098

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/730

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-36**

4047438047104


cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D730-60**

4047438047111

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD15-D90-1**

4047438046961

cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/90

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-HD15-D90-12**

4047438046978

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/90

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D90-36**

4047438046985

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD15-D90-60**

4047438046992

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D1095-12**

4047438041843

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D1095-36**

4047438045865

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD2-D1095-60**

4047438045872

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D14-12**

4047438041775

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/14

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D14-36**

4047438045728

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D14-60**

4047438045735

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D180-12**

4047438041812

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D180-36**

4047438045803

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD2-D180-60**

4047438045810

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/180

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD2-D1825-12**

4047438041850

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/1825

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD2-D1825-36**

4047438045889

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/1825

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD2-D1825-60**

4047438045896

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/1825

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD2-D30-12**

4047438041782

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/30

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD2-D30-36**

4047438045742

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/30

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l

**Mx-CL-Sub-HD2-D30-60**

4047438045759


cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D365-12**

4047438041829

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D365-36**

4047438045827

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D365-60**

4047438045834

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D60-12**

4047438041799

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/60

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D60-36**

4047438045766

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD2-D60-60**

4047438045773

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D7-12**

4047438041768

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D7-36**

4047438045704

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/7

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D7-60**

4047438045711

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/7

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D730-12**

4047438041836

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D730-36**

4047438045841

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD2-D730-60**

4047438045858

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D90-12**

4047438041805

cm

MOBOTIX CLOUD Yearly Camera Subscription, 1080p/90

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D90-36**

4047438045780

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD2-D90-60**

4047438045797

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D1095-12**

4047438041942

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D1095-36**

4047438046060

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD3-D1095-60**

4047438046077

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D14-12**

4047438041874

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D14-36**

4047438045926

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D14-60**

4047438045933

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D180-12**

4047438041911

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D180-36**

4047438046008

cm


MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD3-D180-60**

4047438046015

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D1825-12**

4047438041959

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D1825-36**

4047438046084

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D1825-60**

4047438046091

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D30-12**

4047438041881

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D30-36**

4047438045940

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD3-D30-60**

4047438045957

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D365-12**

4047438041928

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D365-36**

4047438046022

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D365-60**

4047438046039

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D60-12**

4047438041898

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D60-36**

4047438045964

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D60-60**

4047438045971

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD3-D7-12**

4047438041867

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D7-36**

4047438045902

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/7 Days

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D7-60**

4047438045919

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/7 Days

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D730-12**

4047438041935

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D730-36**

4047438046046

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD3-D730-60**

4047438046053

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D90-12**

4047438041904

cm

MOBOTIX CLOUD Yearly Camera Subscription, 3MP/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D90-36**

4047438045988

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD3-D90-60**

4047438045995

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD4-D1095-12**

4047438042192

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD4-D1095-36**

4047438046268

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD4-D1095-60**

4047438046275

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD4-D14-12**

4047438042123

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D14-36**

4047438046121

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D14-60**

4047438046138

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D180-12**

4047438042161

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D180-36**

4047438046206

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D180-60**

4047438046213

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD4-D1825-12**

4047438042208

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D1825-36**

4047438046282

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D1825-60**

4047438046299

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D30-12**

4047438042130

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D30-36**

4047438046145

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D30-60**

4047438046152

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD4-D365-12**

4047438042178

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D365-36**

4047438046220

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D365-60**

4047438046237

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D60-12**

4047438042147

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D60-36**

4047438046169

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D60-60**

4047438046176

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD4-D7-12**

4047438042116

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D7-36**

4047438046107

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/7 Days

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D7-60**

4047438046114

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/7 Days

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D730-12**

4047438042185

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/730

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D730-36**

4047438046244

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD4-D730-60**

4047438046251

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD4-D90-12**

4047438042154

cm

MOBOTIX CLOUD Yearly Camera Subscription, 4MP/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD4-D90-36**

4047438046183

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD4-D90-60**

4047438046190

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D1095-12**

4047438042291

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D1095-36**

4047438046466

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD5-D1095-60**

4047438046473

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D14-12**

4047438042222

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D14-36**

4047438046329

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D14-60**

4047438046336

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D180-12**

4047438042260

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/180

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D180-36**

4047438046404

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD5-D180-60**

4047438046411

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/180

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D1825-12**

4047438042307

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D1825-36**

4047438046480

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D1825-60**

4047438046497

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D30-12**

4047438042239

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D30-36**

4047438046343

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-HD5-D30-60**

4047438046350

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-HD5-D365-12**

4047438042277

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/365

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD5-D365-36**

4047438046428

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD5-D365-60**

4047438046435

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD5-D60-12**

4047438042246

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/60 Days


Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD5-D60-36**

4047438046367

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-HD5-D60-60**

4047438046374


cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/60

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD5-D7-12**

4047438042215

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/7 Days

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD5-D7-36**

4047438046305

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/7 Days

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD5-D7-60**

4047438046312

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/7 Days

cm

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD5-D730-12**

4047438042284

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/730

cm

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l**Mx-CL-Sub-HD5-D730-36**

4047438046442

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/730

cm

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
l

**Mx-CL-Sub-HD5-D730-60**

4047438046459

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D90-12**

4047438042253

cm

MOBOTIX CLOUD Yearly Camera Subscription, 5MP/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D90-36**

4047438046381

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-HD5-D90-60**

4047438046398

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-M10-1**

4047438040327

cm

MOBOTIX CLOUD Camera license, only live stream, NO

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-M10-12**

4047438042482

cm

MOBOTIX CLOUD 1Y Camera Subscription, only Live, NO

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the year • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-M10-36****MOBOTIX CLOUD 3Y Camera Subscription, only Live, NO**

3 Years subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the year • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438045278

cm

g

cm

l

**Mx-CL-Sub-M10-60****MOBOTIX CLOUD 5Y Camera Subscription, only Live, NO**

5 Years subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the year • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438045285

cm

g

cm

cm

l

**Mx-CL-Sub-PR1-D180-1****MOBOTIX CLOUD monthly Camera Subscription, for preview**

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438049146

cm

g

cm

cm

l

**Mx-CL-Sub-PR1-D180-12****MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview**

1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438049153

cm

g

cm

cm

l

**Mx-CL-Sub-PR1-D180-36****MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview**

3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438049160

cm

g

cm

cm

l

**Mx-CL-Sub-PR1-D180-60****MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview**

5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

4047438049177

cm

g

cm

cm

l

**Mx-CL-Sub-PR1-D30-1**

4047438049023

cm

MOBOTIX CLOUD monthly Camera Subscription for preview

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-PR1-D30-12**

4047438049030

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview

1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-PR1-D30-36**

4047438049047

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview

3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-PR1-D30-60**

4047438049054

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview

5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-PR1-D365-1**

4047438049184

cm

MOBOTIX CLOUD monthly Camera Subscription,for preview

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-PR1-D365-12**

4047438049191

cm


MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview

1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-PR1-D365-36**

4047438049207


cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview

3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-PR1-D365-60**

4047438049214

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview

5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-PR1-D60-1**

4047438049061

cm

MOBOTIX CLOUD monthly Camera Subscription,for preview

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-PR1-D60-12**

4047438049078

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview

1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-PR1-D60-36**

4047438049085

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview

3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-PR1-D60-60**

4047438049092

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview

5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-PR1-D730-1**

4047438049221

cm

MOBOTIX CLOUD monthly Camera Subscription,for preview

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-PR1-D730-12**

4047438049238

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview

1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-PR1-D730-36**

4047438049245

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview

3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-PR1-D730-60**

4047438049252

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview

5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-PR1-D90-1**

4047438049108

cm

MOBOTIX CLOUD monthly Camera Subscription,for preview

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm
l**Mx-CL-Sub-PR1-D90-12**

4047438049115

cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview

1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l

**Mx-CL-Sub-PR1-D90-36**

4047438049122

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview

3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-PR1-D90-60**

4047438049139

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview

5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-SD1-D1095-12**

4047438042048

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/1095

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-SD1-D1095-36**

4047438045469

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/1095

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-SD1-D1095-60**

4047438045476

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/1095

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l**Mx-CL-Sub-SD1-D14-12**

4047438041973

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/14 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm
cm
l

**Mx-CL-Sub-SD1-D14-36**

4047438045315

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-SD1-D14-60**

4047438045322

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D180-12**

4047438042017

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/180 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D180-36**

4047438045407

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D180-60**

4047438045414

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/180


5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D1825-12**

4047438042055

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/1825

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D1825-36**

4047438045483

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/1825

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-SD1-D1825-60**

4047438045490

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/1825

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D30-12**

4047438041980

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/30 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D30-36**

4047438045339

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/30

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D30-60**

4047438045346

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/30

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D365-12**

4047438042024

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/365 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D365-36**

4047438045421

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/365

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-SD1-D365-60**

4047438045438

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/365

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D60-12**

4047438041997

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/60 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D60-36**

4047438045360

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/60

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D60-60**

4047438045377

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/60

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D7-12**

4047438041966

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/7 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D7-36**

4047438045292

cm

MOBOTIX CLOUD 3 Years Camera Subscription, VGA/7 Days

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

l

**Mx-CL-Sub-SD1-D7-60**

4047438045308

cm

MOBOTIX CLOUD 5 Years Camera Subscription, VGA/7 Days

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D730-12**

4047438042031

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/730 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D730-36**

4047438045445

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/730

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D730-60**

4047438045452

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/730

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D90-12**

4047438042000

cm

MOBOTIX CLOUD Yearly Camera Subscription, VGA/90 Days

Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm

l

**Mx-CL-Sub-SD1-D90-36**

4047438045384

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-SD1-D90-60**

4047438045391

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period. • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing.

g

cm

cm
l**Mx-CL-Sub-SP01-M30-1**

4047438047203

cm

MOBOTIX CLOUD Monthly SIP Audio-Support Subscription

Monthly Subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period

g

cm

cm
l**Mx-CL-Sub-SP01-M30-12**

4047438047210

cm

MOBOTIX CLOUD Yearly SIP Audio-Support Subscription

Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing

g

cm

cm
l**Mx-CL-Sub-SP01-M30-36**

4047438047227

cm

MOBOTIX CLOUD 3 Yearly SIP Audio-Support Subscription

3 Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing

g

cm

cm
l**Mx-CL-Sub-SP01-M30-60**

4047438047234

cm


MOBOTIX CLOUD 5 Yearly SIP Audio-Support Subscription

5 Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period • Mixed billing not possible! • All devices in the sub-account must be switched to annual billing

g

cm

cm
l

**Mx-CL-Sub-SD1-D7-1**

4047438036375

cm

MOBOTIX CLOUD Camera Subscription, VGA/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D14-1**

4047438036382

cm

MOBOTIX CLOUD Camera Subscription, VGA/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX Cloud access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D30-1**

4047438036399

cm

MOBOTIX CLOUD Camera Subscription, VGA/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D60-1**

4047438036405

cm

MOBOTIX CLOUD Camera Subscription, VGA/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D90-1**

4047438036412

cm

MOBOTIX CLOUD Camera Subscription, VGA/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-SD1-D180-1**

4047438036429

cm

MOBOTIX CLOUD Camera Subscription, VGA/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-SD1-D365-1**

4047438036436

cm

MOBOTIX CLOUD Camera Subscription, VGA/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-SD1-D730-1**

4047438036443

cm

MOBOTIX CLOUD Camera Subscription, VGA/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-SD1-D1095-1**

4047438036450

cm

MOBOTIX CLOUD Camera Subscription, VGA/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-SD1-D1825-1**

4047438036467

cm

MOBOTIX CLOUD Camera Subscription, VGA/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D7-1**

4047438036023

cm

MOBOTIX CLOUD Camera Subscription, 720p/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D14-1**

4047438036030

cm

MOBOTIX CLOUD Camera Subscription, 720p/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D30-1**

4047438036047

cm

MOBOTIX CLOUD Camera Subscription, 720p/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D60-1**

4047438036054

cm

MOBOTIX CLOUD Camera Subscription, 720p/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D90-1**

4047438036061

cm

MOBOTIX CLOUD Camera Subscription, 720p/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D180-1**

4047438036078

cm

MOBOTIX CLOUD Camera Subscription, 720p/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D365-1**

4047438036085

cm

MOBOTIX CLOUD Camera Subscription, 720p/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D730-1**

4047438036092

cm

MOBOTIX CLOUD Camera Subscription, 720p/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD1-D1095-1**

4047438036108

cm

MOBOTIX CLOUD Camera Subscription, 720p/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

l

**Mx-CL-Sub-HD1-D1825-1**

4047438036115

cm

MOBOTIX CLOUD Camera Subscription, 720p/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD2-D7-1**

4047438036122

cm

MOBOTIX CLOUD Camera Subscription, 1080p/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD2-D14-1**

4047438036139

cm

MOBOTIX CLOUD Camera Subscription, 1080p/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD2-D30-1**

4047438036146

cm

MOBOTIX CLOUD Camera Subscription, 1080p/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD2-D60-1**

4047438036153

cm

MOBOTIX CLOUD Camera Subscription, 1080p/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm

l

**Mx-CL-Sub-HD2-D90-1**

4047438036160

cm

MOBOTIX CLOUD Camera Subscription, 1080p/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D180-1**

4047438036177

cm

MOBOTIX CLOUD Camera Subscription, 1080p/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D365-1**

4047438036184

cm

MOBOTIX CLOUD Camera Subscription, 1080p/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D730-1**

4047438036191

cm

MOBOTIX CLOUD Camera Subscription, 1080p/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D1095-1**

4047438036207

cm

MOBOTIX CLOUD Camera Subscription, 1080p/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD2-D1825-1**

4047438036214

cm

MOBOTIX CLOUD Camera Subscription, 1080p/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD3-D7-1**

4047438036221

cm

MOBOTIX CLOUD Camera Subscription, 3MP/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D14-1**

4047438036238

cm

MOBOTIX CLOUD Camera Subscription, 3MP/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D30-1**

4047438036245

cm

MOBOTIX CLOUD Camera Subscription, 3MP/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D60-1**

4047438036252

cm

MOBOTIX CLOUD Camera Subscription, 3MP/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D90-1**

4047438036269

cm

MOBOTIX CLOUD Camera Subscription, 3MP/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D180-1**

4047438036276

cm

MOBOTIX CLOUD Camera Subscription, 3MP/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD3-D365-1**

4047438036283

cm

MOBOTIX CLOUD Camera Subscription, 3MP/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D730-1**

4047438036290

cm

MOBOTIX CLOUD Camera Subscription, 3MP/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX Cloud access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D1095-1**

4047438036306

cm

MOBOTIX CLOUD Camera Subscription, 3MP/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD3-D1825-1**

4047438036313

cm

MOBOTIX CLOUD Camera Subscription, 3MP/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D7-1**

4047438036481

cm

MOBOTIX CLOUD Camera Subscription, 4MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D14-1**

4047438036498

cm

MOBOTIX CLOUD Camera Subscription, 4MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD4-D30-1**

4047438036504

cm

MOBOTIX CLOUD Camera Subscription, 4MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D60-1**

4047438036511

cm

MOBOTIX CLOUD Camera Subscription, 4MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D90-1**

4047438036528

cm

MOBOTIX CLOUD Camera Subscription, 4MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D180-1**

4047438036535

cm

MOBOTIX CLOUD Camera Subscription, 4MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D365-1**

4047438036542

cm

MOBOTIX CLOUD Camera Subscription, 4MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D730-1**

4047438036559

cm


MOBOTIX CLOUD Camera Subscription, 4MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD4-D1095-1**

4047438036566

cm

MOBOTIX CLOUD Camera Subscription, 4MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD4-D1825-1**

4047438036573

cm

MOBOTIX CLOUD Camera Subscription, 4MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D7-1**

4047438036580

cm

MOBOTIX CLOUD Camera Subscription, 5MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D14-1**

4047438036597

cm

MOBOTIX CLOUD Camera Subscription, 5MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D30-1**

4047438036603

cm

MOBOTIX CLOUD Camera Subscription, 5MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D60-1**

4047438036610

cm

MOBOTIX CLOUD Camera Subscription, 5MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD5-D90-1**

4047438036627

cm

MOBOTIX CLOUD Camera Subscription, 5MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D180-1**

4047438036634

cm

MOBOTIX CLOUD Camera Subscription, 5MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D365-1**

4047438036641

cm

MOBOTIX CLOUD Camera Subscription, 5MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D730-1**

4047438036658

cm

MOBOTIX CLOUD Camera Subscription, 5MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D1095-1**

4047438036665

cm

MOBOTIX CLOUD Camera Subscription, 5MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD5-D1825-1**

4047438036672

cm

MOBOTIX CLOUD Camera Subscription, 5MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD10-D7-1**

4047438036689

cm

MOBOTIX CLOUD Camera Subscription, 10MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D14-1**

4047438036696

cm

MOBOTIX CLOUD Camera Subscription, 10MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D30-1**

4047438036702

cm

MOBOTIX CLOUD Camera Subscription, 10MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D60-1**

4047438036719

cm

MOBOTIX CLOUD Camera Subscription, 10MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D90-1**

4047438036726

cm

MOBOTIX CLOUD Camera Subscription, 10MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D180-1**

4047438036733

cm

MOBOTIX CLOUD Camera Subscription, 10MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-HD10-D365-1**

4047438036740

cm

MOBOTIX CLOUD Camera Subscription, 10MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D730-1**

4047438036757

cm

MOBOTIX CLOUD Camera Subscription, 10MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D1095-1**

4047438036764

cm

MOBOTIX CLOUD Camera Subscription, 10MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-HD10-D1825-1**

4047438036771

cm

MOBOTIX CLOUD Camera Subscription, 10MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-ANA-001-1**

4047438036320

cm

MOBOTIX CLOUD Analytics Subscription, Line Cross

Monthly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation of subscription possible at any time at the end of the month

g

cm

cm
l**Mx-CL-Sub-ANA-002-1**

4047438036337

cm

MOBOTIX CLOUD Analytics Subscription, Counting

Monthly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation of subscription possible at any time at the end of the month

g

cm

cm
l

**Mx-CL-Sub-ANA-003-1****MOBOTIX CLOUD Analytics Subscription, Area Intrusion**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion •
Cancellation of subscription possible at any time at the end of the month

4047438036344

cm

g

cm

cm
l**Mx-CL-Sub-ANA-004-1****MOBOTIX CLOUD Analytics Subscription, Camera Tamper**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper
Detect • Cancellation of subscription possible at any time at the end of the month

4047438036351

cm

g

cm

cm
l**Mx-CL-Sub-ANA-005-1****MOBOTIX CLOUD Analytics Subscription, Loitering**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Loitering •
Cancellation of subscription possible at any time at the end of the month

4047438036368

cm

g

cm

cm
l

Software & Services

BeyondHumanVision

MOBOTIX

MOBOTIX HUB Video Management System

MOBOTIX HUB

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-HUB-MgmtSrvFailover MOBOTIX HUB Management Server Failover - Redundancy Enables support for a failover server in the MOBOTIX HUB for the HUB Management Server • It provides HUB users with an always available high availability cluster with real • time replication and failover • It is a complete solution that protects the management server (and the event, log and SQL servers if they are installed on the same physical server) from hardware, software and human errors • Its efficient design and easy configuration give you the ability to seamlessly and automatically switch to a reliable backup management server if the primary server fails. • Its efficient design and simple configuration give you the ability to seamlessly and automatically switch to a reliable backup management server if the primary server fails. It offers real-time synchronous file replication, automatic application failover and automatic fallback after a server failure • Licence is issued via MOBOTIX Sales • Licence is non-transferable • One licence per MOBOTIX HUB VMS is required. • Usable from MOBOTIX HUB L4 • Only 1 server pair per location is supported	4047438049580	cm
		g	cm l
	Mx-HUB-TRAD-MgmtSrvFailover-W MOBOTIX HUB Management Server Failover - Trade-in SL w/ Product Upgrade of the MOBOTIX HUB Management Server Failover license, which are in possession of an Advanced Service Product (ASP). • Usable from MOBOTIX HUB L4 • Only 1 server pair per location is supported	4047438049597	cm
		g	cm l
	Mx-HUB-TRAD-MgmtSrvFailover-WO MOBOTIX HUB Management Server Failover - Trade-in SL Product Upgrade of the MOBOTIX HUB Management Server Failover license, which are NOT in possession of an Advanced Service Product (ASP). • Usable from MOBOTIX HUB L4 • Only 1 server pair per location is supported	4047438049603	cm
		g	cm l
	Mx-SW-HUB-SuspectTrack Milestone Suspect Tracking Plug In - Virtual Patrol Support Activates the Milestone Suspect Tracking plugin in the MOBOTIX HUB from our technology partner Milestone • Suspect Tracking offers a user-friendly way to track objects of interest between the cameras in the MOBOTIX HUB Desk Client or simply move around the camera area in a logical way • Suspect Tracking supports all integrated cameras in the MOBOTIX HUB , Independent of the manufacturer • Main application areas are: Virtual patrol for the user • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • Usable from MOBOTIX HUB L2 • Independent of the number of integrated cameras • Permanent licence	4047438049474	cm
		g	cm l
	Mx-HUB-L1-BAS L1 Base License (8 Device Licenses incl) MOBOTIX HUB L1 is available as a free version. The license includes the basic license and device license with the support of up to eight cameras	4047438039208	cm
		g	cm l

**Mx-HUB-L2-BAS****MOBOTIX HUB L2 Base License (BL)**

MOBOTIX HUB L2 for smaller companies with one location manages up to 48 surveillance cameras

4047438038584

cm

cm

g

cm

l

**Mx-HUB-L2-DEV****MOBOTIX HUB L2 Device License (DL)**

Device licenses for MOBOTIX HUB L2. Up to 48 device licenses can be linked to the HUB L2

4047438038591

cm

cm

g

cm

l

**Mx-HUB-L2-1MDEV****1 Month Advanced Services for MOBOTIX HUB L2 Device**

1 month MOBOTIX HUB L2 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L2 Advanced Service for 1, 2, 3 and 5 years.

4047438039215

cm

cm

g

cm

l

**Mx-HUB-L2-1YDEV****One year MOBOTIX HUB Advanced Services for L2 Device**

1 Year MOBOTIX HUB L2 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038607

cm

cm

g

cm

l

**Mx-HUB-L2-2YDEV****Two years MOBOTIX HUB Advanced Services for L2 Device**

2 Year MOBOTIX HUB L2 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038614

cm

cm

g

cm

l

**Mx-HUB-L2-3YDEV****Three years MOBOTIX HUB Advanced Services for L2 Device**

3 Year MOBOTIX HUB L2 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038621

cm

cm

g

cm

l

**Mx-HUB-L2-5YDEV**

4047438038638

cm

Five years MOBOTIX HUB Advanced Services for L2 Device

cm

5 Year MOBOTIX HUB L2 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm
l**Mx-HUB-L2-3YOPT-DEV**

4047438039031

cm

Three years opt-in MOBOTIX HUB Advanced Services for L2

cm

The MOBOTIX HUB Advanced Service Opt-In for HUB L2 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L2 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm
l**Mx-HUB-L2-UP-BASWO**

4047438039277

cm

Version Upgrade HUB L2 BL w/o ASP

cm

Software update for MOBOTIX HUB L2 base licenses that are not in possession of an Advanced Service Product.

g

cm
l**Mx-HUB-L2-UP-DEVWO**

4047438039284

cm

Version Upgrade HUB L2 DL w/o ASP

cm

Software update for MOBOTIX HUB L2 device licenses that are not in possession of an Advanced Service Product.

g

cm
l**Mx-HUB-L3-BAS**

4047438038645

cm

MOBOTIX HUB L3 Base License (BL)

cm

MOBOTIX HUB L3 is the solution for medium-sized companies. The number of cameras is unlimited and can be distributed across multiple locations.

g

cm
l**Mx-HUB-L3-DEV**

4047438038652

cm

MOBOTIX HUB L3 Device License (DL)

cm

Device licenses for MOBOTIX HUB L3. Unlimited number of devices can be integrated into one L3 installation.

g

cm
l

**Mx-HUB-L3-1MDEV**

4047438039222

cm

1 Month Advanced Services for MOBOTIX HUB L3 Device

1 month MOBOTIX HUB L3 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L3 Advanced Service for 1, 2, 3 and 5 years.

g

cm

cm
l**Mx-HUB-L3-1YDEV**

4047438038669

cm

One year MOBOTIX HUB Advanced Services for L3 Device

1 Year MOBOTIX HUB L3 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L3-2YDEV**

4047438038676

cm

Two years MOBOTIX HUB Advanced Services for L3 Device

2 Year MOBOTIX HUB L3 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L3-3YDEV**

4047438038683

cm

Three years MOBOTIX HUB Advanced Services for L3 Device

3 Year MOBOTIX HUB L3 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L3-5YDEV**

4047438038690

cm

Five years MOBOTIX HUB Advanced Services for L3 Device

5 Year MOBOTIX HUB L3 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L3-3YOPT-DEV**

4047438039048

cm

Three years opt-in MOBOTIX HUB Advanced Services for L3

The MOBOTIX HUB Advanced Service Opt-In for HUB L3 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L3 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

cm
l

**Mx-HUB-TRAD-BAS-L2-L3-W**

4047438039369

cm

Trade-in BL L2->L3 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-DEV-L2-L3-W**

4047438039376

cm

Trade-in DL L2->L3 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L2-L3-WO**

4047438039383

cm

Trade-in BL L2->L3 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L2-L3-WO**

4047438039390

cm

Trade-in DL L2->L3 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-L3-UP-BASWO**

4047438039291

cm

Version Upgrade HUB L3 BL w/o ASP

Software update for MOBOTIX HUB L3 base licenses that are not in possession of an Advanced Service Product.

g

cm

cm

l

**Mx-HUB-L3-UP-DEVWO**

4047438039307

cm

Version Upgrade HUB L3 DL w/o ASP

Software update for MOBOTIX HUB L3 device licenses that are not in possession of an Advanced Service Product.

g

cm

cm

l

**Mx-HUB-L4-BAS**

4047438038706

cm

MOBOTIX HUB L4 Base License (BL)

MOBOTIX HUB L4 is made for medium and large installations. In addition to the features of MOBOTIX HUB L3, L4 provides access to failover recording servers in case of server failure. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.

g

cm

cm
l**Mx-HUB-L4-DEV**

4047438038713

cm

MOBOTIX HUB L4 Device License (DL)

Device licenses for MOBOTIX HUB L4. Unlimited number of devices can be integrated into one L4 installation. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.

g

cm

cm
l**Mx-HUB-L4-1MBAS**

4047438039239

cm

1 Month Advanced Services for MOBOTIX HUB L4 Base

1 month MOBOTIX HUB L4 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.

g

cm

cm
l**Mx-HUB-L4-1YBAS**

4047438038720

cm

One year MOBOTIX HUB Advanced Services for L4 Base

1 year MOBOTIX HUB L4 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L4-2YBAS**

4047438038737

cm

Two years MOBOTIX HUB Advanced Services for L4 Base

2 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L4-3YBAS**

4047438038744

cm

Three years MOBOTIX HUB Advanced Services for L4 Base

3 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l

**Mx-HUB-L4-5YBAS****Five years MOBOTIX HUB Advanced Services for L4 Base**

5-year MOBOTIX HUB L4 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038751

cm

g

cm

l

**Mx-HUB-L4-3YOPT-BAS****Three years opt-in MOBOTIX HUB Advanced Services for L4**

The MOBOTIX HUB Advanced Service Opt-In for HUB L4 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

4047438039055

cm

g

cm

cm

l

**Mx-HUB-L4-1MDEV****1 Month Advanced Services for MOBOTIX HUB L4 Device**

1 month MOBOTIX HUB L4 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.

4047438039246

cm

g

cm

cm

l

**Mx-HUB-L4-1YDEV****One year MOBOTIX HUB Advanced Services for L4 Device**

1 year MOBOTIX HUB L4 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

4047438038768

cm

g

cm

cm

l

**Mx-HUB-L4-2YDEV****Two years MOBOTIX HUB Advanced Services for L4 Device**

2 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038775

cm

g

cm

cm

l

**Mx-HUB-L4-3YDEV****Three years MOBOTIX HUB Advanced Services for L4 Device**

3 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038782

cm

g

cm

cm

l

**Mx-HUB-L4-5YDEV**

4047438038799

cm

Five years MOBOTIX HUB Advanced Services for L4 Device

5-year MOBOTIX HUB L4 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L4-3YOPT-DEV**

4047438039062

cm

Three years opt-in MOBOTIX HUB Advanced Services for L4

The MOBOTIX HUB Advanced Service Opt-In for HUB L4 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

cm
l**Mx-HUB-TRAD-BAS-L2-L4-W**

4047438039406

cm

Trade-in BL L2->L4 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-DEV-L2-L4-W**

4047438039413

cm

Trade-in DL L2->L4 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-BAS-L2-L4-WO**

4047438039420

cm

Trade-in BL L2->L4 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-DEV-L2-L4-WO**

4047438039437

cm

Trade-in DL L2->L4 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm
l

**Mx-HUB-TRAD-BAS-L3-L4-W**

4047438039444

cm

Trade-in BL L3->L4 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-DEV-L3-L4-W**

4047438039451

cm

Trade-in DL L3->L4 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L3-L4-WO**

4047438039468

cm

Trade-in BL L3->L4 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L3-L4-WO**

4047438039475

cm

Trade-in DL L3->L4 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-L4-UP-BASWO**

4047438039314

cm

Version Upgrade HUB L4 BL w/o ASP

Software update for MOBOTIX HUB L4 base licenses that are not in possession of an Advanced Service Product.

g

cm

cm

l

**Mx-HUB-L4-UP-DEVWO**

4047438039321

cm

Version Upgrade HUB L4 DL w/o ASP

Software update for MOBOTIX HUB L4 device licenses that are not in possession of an Advanced Service Product.

g

cm

cm

l

**Mx-HUB-L5-BAS**

4047438038805

cm

MOBOTIX HUB L5 Base License (BL)

MOBOTIX HUB L5 is the video management platform for large and extremely security-oriented applications. In addition to centralized management of all servers, cameras and users across multiple sites, L5 also includes control for a professional video wall as standard. The use of MOBOTIX HUB L5 requires an Advanced Service (base + devices) of at least one year.

g

cm

l

**Mx-HUB-L5-DEV**

4047438038812

cm

MOBOTIX HUB L5 Device License (DL)

Device licenses for MOBOTIX HUB L5. Unlimited number of devices can be integrated into one L5 installation.

g

cm

cm

l

**Mx-HUB-L5-INTCON**

4047438038829

cm

MOBOTIX HUB Interconnect Device License (DL)

Interconnect licenses for MOBOTIX HUB L5. Unlimited number of Interconnect licenses can be used into one L5 installation.

g

cm

cm

l

**Mx-HUB-L5-1MBAS**

4047438039253

cm

1 Month Advanced Services for MOBOTIX HUB L5 Base

1 month MOBOTIX HUB L5 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.

g

cm

cm

l

**Mx-HUB-L5-1YBAS**

4047438038836

cm

One year MOBOTIX HUB Advanced Services for L5 Base

1 year MOBOTIX HUB L5 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm

l

**Mx-HUB-L5-2YBAS**

4047438038843

cm

Two years MOBOTIX HUB Advanced Services for L5 Base

2 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm

l

**Mx-HUB-L5-3YBAS**

4047438038850

cm

Three years MOBOTIX HUB Advanced Services for L5 Base

3 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L5-5YBAS**

4047438038867

cm

Five years MOBOTIX HUB Advanced Services for L5 Base

5-year MOBOTIX HUB L5 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

g

cm

cm
l**Mx-HUB-L5-3YOPT-BAS**

4047438039079

cm

Three years opt-in MOBOTIX HUB Advanced Services for L5

The MOBOTIX HUB Advanced Service Opt-In for HUB L5 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

cm
l**Mx-HUB-L5-1MDEV**

4047438039260

cm

1 Month Advanced Services for MOBOTIX HUB L5 Device

1 month MOBOTIX HUB L5 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.

g

cm

cm
l**Mx-HUB-L5-1YDEV**

4047438038874

cm

One year MOBOTIX HUB Advanced Services for L5 Device

1 year MOBOTIX HUB L5 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

cm
l**Mx-HUB-L5-2YDEV**

4047438038881

cm

Two years MOBOTIX HUB Advanced Services for L5 Device

2 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

cm
l

**Mx-HUB-L5-3YDEV**

4047438038898

cm

Three years MOBOTIX HUB Advanced Services for L5 Device

3 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

l

**Mx-HUB-L5-5YDEV**

4047438038904

cm

Five years MOBOTIX HUB Advanced Services for L5 Device

5-year MOBOTIX HUB L5 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

g

cm

l

**Mx-HUB-L5-3YOPT-DEV**

4047438039086

cm

Three years opt-in MOBOTIX HUB Advanced Services for L5

The MOBOTIX HUB Advanced Service Opt-In for HUB L5 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

g

cm

l

**Mx-HUB-TRAD-BAS-L2-L5-W**

4047438039482

cm

Trade-in BL L2->L5 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-DEV-L2-L5-W**

4047438039499

cm

Trade-in DL L2->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-BAS-L2-L5-WO**

4047438039505

cm

Trade-in BL L2->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-DEV-L2-L5-WO**

4047438039512

cm

Trade-in DL L2->L5 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which not are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-BAS-L3-L5-W**

4047438039529

cm

Trade-in BL L3->L5 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L3-L5-W**

4047438039536

cm

Trade-in DL L3->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L3-L5-WO**

4047438039543

cm

Trade-in BL L3->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L3-L5-WO**

4047438039550

cm

Trade-in DL L3->L5 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which not are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-BAS-L4-L5-W**

4047438039567

cm

Trade-in BL L4->L5 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L4-L5-W**

4047438039574

cm

Trade-in DL L4->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

l

**Mx-HUB-TRAD-BAS-L4-L5-WO**

4047438039581

cm

Trade-in BL L4->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-TRAD-DEV-L4-L5-WO**

4047438039598

cm

Trade-in DL L4->L5 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm

l

**Mx-HUB-L5-UP-BASWO**

4047438039338

cm

Version Upgrade HUB L5 BL w/o ASP

Software update for MOBOTIX HUB L5 base licenses that are not in possession of an Advanced Service Product

g

cm

cm

l

**Mx-HUB-L5-UP-DEVWO**

4047438039345

cm

Version Upgrade HUB L5 DL w/o ASP

Software update for MOBOTIX HUB L5 device licenses that are not in possession of an Advanced Service Product

g

cm

cm

l

**Mx-HUB-L5-UP-INTWO**

4047438039352

cm

Version Upgrade HUB L5 Intercon. DL w/o ASP


Software update for MOBOTIX HUB L5 interconnect licenses that are not in possession of an Advanced Service Product

g

cm

cm

l

**Mx-HUB-ACC-WALL**

4047438039116

cm


MOBOTIX HUB Video Wall Base License (BL)

MOBOTIX HUB Video Wall is an advanced add-on video wall product that improves response time by displaying all the video data in your installation and giving a complete overview of large surveillance centers.

g

cm

l

**Mx-HUB-ACC-WALL-UP**

4047438039604

cm


Version Upgrade HUB Video Wall BL w/o ASP

Software update for MOBOTIX HUB Video Wall license that are not in possession of an Advanced Service Product

g

cm

l

**Mx-HUB-ACS-BASE**

4047438039178

cm


MOBOTIX HUB Access Base License (BL)

MOBOTIX HUB Access is an Add-on product that video enables physical security through integration of access control and intrusion systems

g

cm

l

**Mx-HUB-ACS-BASE-UP**

4047438039611

cm


Version Upgrade HUB Access BL w/o ASP

Software update for MOBOTIX HUB Access Basic license, which are not in possession of an Advanced Service product.

g

cm

l

**Mx-HUB-ACS-DOOR**

4047438039185

cm


MOBOTIX HUB Access Door License (DL)

Device license for MOBOTIX HUB Access.

g

cm

l

**Mx-HUB-ACS-DOOR-UP**

4047438039628

cm


Version Upgrade HUB Access DL w/o ASP

Software Update for MOBOTIX HUB Access Devices License, which are not in possession of an Advanced Service Product.

g

cm

l

**Mx-HUB-XP-TRA-BAS**

4047438039154

cm


Xprotect Transaction Base License Server incl. 1 Connection

XProtect Transact Base Server incl. 1 Connection License. XProtect Transact video enables different types of transaction-based processes. Combining transaction data from point of sales systems, scanners, cash point machines, or similar systems with corresponding video, XProtect Transact enables real-time monitoring, exception handling and documentation of transactions.

g

cm

l

**Mx-HUB-XP-TRA-BAS-UP**

4047438039635

cm


Version Upgrade Xprotect Transaction BL w/o ASP

Software Update for XProtect Transaction Base License, which are not in possession of an Advanced Service Product.

g

cm

l

**Mx-HUB-XP-TRA-CON**

4047438039161

cm


Xprotect Transaction Connection License

Connection licence for Xprotect Transact.

g

cm

l

**Mx-HUB-XP-TRA-CON-UP**

4047438039642

cm

Version Upgrade Xprotect Transaction CL w/o ASP

Software update for XProtect Transaction Connection license, which are not in possession of an Advanced Service Product

g

cm

l

**Mx-HUB-XP-LPR-BAS**

4047438039123

cm

Xprotect LPR Base License incl. 5 Country Modules

XProtect LPR Base License, incl. 5 Country Modules. XProtect LPR is license plate recognition (LPR) software that detects license plate information from any vehicle around the world and links the license plate number with video.

g

cm

l

**Mx-HUB-XP-LPR-BAS-UP**

4047438039659

cm

Version Upgrade Xprotect LPR BL w/o ASP

Software update for XProtect LPR Basic license, which are not in possession of an Advanced Service Product.

g

cm

l

**Mx-HUB-XP-LPR-DEV****XProtect LPR Device License (DL)**

Device licence for Xprotect LPR.

4047438039130

cm

g

cm

l

**Mx-HUB-XP-LPR-DEV-UP****Version Upgrade Xprotect LPR DL w/o ASP**

Software update for XProtect LPR devices license, which are not in possession of an Advanced Service Product.

4047438039666

cm

g

cm

cm

l

**Mx-HUB-XP-LPR-CTY****Xprotect LPR Country Modul**

Country modul for Xprotect LPR.

4047438039147

cm

g

cm

cm

l

**Mx-HUB-XP-LPR-CTY-UP****Version Upgrade Xprotect LPR CM w/o ASP**

Software update for XProtect LPR Country Module not in possession of an Advanced Service Product.

4047438039673

cm

g

cm

cm

l

MxManagementCenter and Additional Licences

ONVIF-compliant Video Managemnt System

MxManagementCenter (MxMC) is a powerful, intuitive video management system for Windows and macOS systems. MxMC can be utilized for projects and security installations of all sizes and with any number of cameras or storage media. It was designed to be user-friendly, high-performing and secure.

Please follow this link for further license-related informations: <https://www.mobotix.com/de/support/download-center/software-downloads/lizenz-portal>

Article No. / Name / Description		EAN / HS / weight	dimen.
	Mx-SW-MC-ADCON-VM	4047438035071	0,0 cm
	MxMC Advanced Config License for virtual machines (VM)		0,0 cm
	Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required) • released for virtual machines (VM)	0 g	0,0 cm
			0,0 l
	Mx-SW-MC	4047438034456	0,0 cm
	MxManagementCenter VMS For Windows/macOS		0,0 cm
	Free-of-charge MOBOTIX video management software MxManagementCenter (MxMC) • Certified ONVIF conformity (Profile S) • Language packs: English, German, French, Spanish, Italian, Russian, Turkish, Portuguese, Japanese • System requirements: 2 GHz processor (min.), at least 2 GB RAM, video card with support for OpenGL V2.1 • Download free of charge: www.mobotix.com > Services > Download Center > Software Downloads > MxManagementCenter	0 g	0,0 cm
			0,0 l
	Mx-SW-MC-ADCON	4047438034197	0,0 cm
	MxMC Advanced Config License		0,0 cm
	Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	0 g	0,0 cm
			0,0 l
	Mx-SW-MC-STARTER	4047438034142	0,0 cm
	MxMC Integration Starter License		0,0 cm
	MOBOTIX license for the general use of H.264 with a MxMC workstation (as of MxMC 2.0) for live images, playback and/or export • Unlimited number of users per workstation • No time limit for use • One additional video channel for a third-party ONVIF-S camera included • Download via external license portal (access data required)	0 g	0,0 cm
			0,0 l
	Mx-SW-MC-CHAN	4047438034159	0,0 cm
	MxMC Integration Channel License		0,0 cm
	MOBOTIX license for using an additional video channel from an external ONVIF S compliant IP camera with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	0 g	0,0 cm
			0,0 l

**Mx-SW-MC-SDATA**

4047438034449

0,0 cm

MxMC Smart Data License

MOBOTIX license for connecting an external data source (Smart Data Source) to a MxMC workstation (as of MxMC 2.1) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

0 g

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-POS**

4047438031615

0,0 cm

MxMC POS Single Cash Point License

MOBOTIX license for connecting a cash register to a MxMC workstation (as of MxMC 1.7) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

0 g

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-AS-1**

4047438034166

0,0 cm

MxMC Advanced Service License, 1 Year

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 1 year/12 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0 g

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-AS-2**

4047438034173

0,0 cm

MxMC Advanced Service License, 2 Years

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 2 years/24 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0 g

0,0 cm

0,0 cm

0,0 l

**Mx-SW-MC-AS-5**

4047438034180

0,0 cm

MxMC Advanced Service License, 5 Years

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 5 years/60 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0 g


0,0 cm

0,0 cm

0,0 l

Certified Apps for MOBOTIX 7


Certified Apps for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-APP-KEP-NUA-EXT	4047438049412	cm
	Plug-in license to extend the functionality of c71		cm
	Plug-In license to extend the NurseAssist status and alarm notifications with the following functions: <ul style="list-style-type: none"> • Person sits on the edge of the bed • Person has left the room • Person has entered the room • Person has entered the bathroom / is in the bathroom • Bed is not recognized / is not present • Distinction between person lying and sitting on the floor IMPORTANT: Requires MOBOTIX c71 NurseAssist Smart Sensor or licensed Kepler NurseAssist Certified App	g	cm l

Certified Apps for MOBOTIX 7

Certified Apps for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-APP-IRIS-ANO Irisity Iris Anonymization App Irisity Iris Anonymization App including the following features: • patented dynamic pixelation of people in the camera's field of view • designed to address GDPR and privacy regulations • Configurable option to force switch to black/white image to ensure maximum privacy • applicable in indoor and outdoor camera operation • pixelation of persons from a minimum height of 20 pixels	4047438045230	cm
		g	cm l
	Mx-APP-IRIS-C-INT Irisity Iris Core Intrusion App Irisity Iris Core Intrusion App including the following features: • Detects the intrusion of objects of interest into user-defined detection zones / areas • Designed for reliable detection of people and vehicles covering only small portions of the field of view • Reduction of false alarms to a minimum by filtering out non-critical motion (e.g. trees, clouds, etc.) • simultaneous detection on one or more image sensors • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB	4047438040693	cm
		g	cm l
	Mx-APP-MX-ARA MOBOTIX Advanced Radiometry App MOBOTIX Advanced Radiometry App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON	4047438044998	cm
		g	cm l
	Mx-APP-MX-BAR MOBOTIX Barcode Reader App MOBOTIX Barcode Reader App including the following features: • Reader supports more than 40 common 1D, 2D and Stacked barcode types (e.g. QR Code, Data Matrix Code, Dot Code, etc.) • Optimized for difficult barcode reads (e.g. damaged, faded or distorted barcodes, barcodes on difficult surfaces, DPM codes) • Quick reading of one or multiple barcodes in motion • Definition of up to 20 detection areas within the camera's field of view • MOBOTIX events via MxMessageSystem • reporting of barcode reads via generic XML, JSON and MODBUS/TCP	4047438044981	cm
		g	cm l
	Mx-APP-MX-COR MOBOTIX Color Recognition App MOBOTIX Color Recognition including the following features: • Detection of user-specified color values within customized detection areas • Definition of up to 20 detection areas within the camera's field of view • Supports the recognition of all RGB color values • Set sensitivity, required percentage within the defined detection area and duration of the associated condition • MOBOTIX events via MxMessageSystem	4047438042567	cm
		g	cm l

**Mx-APP-MX-THD**

4047438045087


cm

MOBOTIX Thermal Heat Detection App

cm

MOBOTIX Thermal Heat Detection App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (according to CNPP France 19005 certification) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • the MOBOTIX Thermal Heat Detection App is required in any case to fulfill the requirements for CNPP France 19005 certification (Thermal Camera Heat Detection Systems)

g

cm
l**Mx-APP-MX-TVA**

4047438045216


cm

MOBOTIX Thermal Validation App

cm

MOBOTIX Thermal Validation App including the following features: • App optimizes MOBOTIX Thermal Radiometry cameras for use in the fields of waste management and logistics • Enables filtering of vehicles (e.g. construction vehicles and forklifts) as a non-critical source of high temperatures (e.g. by measuring hot body parts such as the exhaust or engine cover) • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON / XML via HTTP(S)

g

cm
l**Mx-APP-VX-ADR**

4047438037815

cm

Vaxtor App License Plate and Dangerous Goods Recognition

cm

Vaxtor App for License Plate and Dangerous Goods Recognition including the following features: • License plate recognition of one- and two-line license plates • read conventional and dangerous good plates simultaneously • support of latin, hebrew and arabic characters for global application • recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and trigger mode for LPR/ADR

g

cm
l**Mx-APP-VX-AIN**

4047438040518

cm

Vaxtor Aircraft Identification Number Recognition App

cm

Vaxtor Aircraft Identification Number Recognition App including the following features: • Recognition of ICAO- and FAA-issued identification numbers • Operations up to a speed of 50 km/h • Real-time results: Aircraft ID, Aircraft Type, Country, etc. • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.)

g

cm
l**Mx-APP-VX-CON**

4047438037938

cm

Vaxtor App for Cargo Container Code Recognition

cm

Vaxtor App for Container Code Recognition including the following features: • Recognition of cargo container codes according to ISO 6346 • Real time results: • Container Code • Property Code • Owner • Container Type • Container Dimensions • Control Digit • Control Digit Validation • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm
l

**Mx-APP-VX-GEN**

4047438042543

cm


Vaxtor Generic Optical Character Recognition App

Vaxtor Generic Optical Character Recognition App including the following features: • generic optical character recognition to read any combination of uppercase Latin characters and/or numbers • reads characters arranged in up to three lines • user-defined specification of the required code format • recognition log • MOBOTIX events via MxMessageSystem • numerous integration options for further processing of the generated metadata (generic as well as native reporting interfaces) • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm

l

**Mx-APP-VX-LPR**

4047438037358

cm

Vaxtor License Plate Recognition App


Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • Recognition log • MOBOTIX events via MxMessageSystem • Global country coverage

g

cm

cm

l

**Mx-APP-VX-LPR-M**

4047438040402

cm

Vaxtor License Plate Recognition App (multi-lens

Vaxtor License Plate Recognition App (multi-lens application) for S74 with two optical sensor modules including the following features: • License plate recognition of one- and two-line license plates • simultaneous recognition on both image sensors • monitoring the dwell time of license plates in the detection area • support of latin, hebrew and arabic characters for global application • Recognition log • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm

cm

l

**Mx-APP-VX-MMC**

4047438038324

cm

Vaxtor License Plate Recognition App incl. Vehicle Make,

Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • support of latin, hebrew and arabic characters for global application • Additional recognition of vehicle make, model, color and class • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm

cm

l

**Mx-APP-VX-UIC**

4047438040266

cm

Vaxtor App for UIC Railway Code Recognition

Vaxtor App for UIC Railway Code Recognition including the following features: • Recognition of the International Union of Railways Wagon and Coach numbers (UIC Codes) • Real time results: UIC Code, Country Code, Vehicle Type, Control Digit, Direction of travel • Stop / Go and slow speed (<10 km/h) applications (depending on installation and module selection) • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

g

cm

cm

l

**Mx-APP-VX-USD**

4047438041638

cm

Vaxtor USDOT Number Recognition App

Vaxtor USDOT Number Recognition App including the following features: • Recognition of USDOT identification numbers • Operations up to a vehicle speed of 50 km/h • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled operation mode

g

cm


cm

l

Desktop Apps

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SW-MC-QNAP	4047438047791	cm
	QNAP QVR Pro license for activation of MxMC Playback		cm
	Enables MxMC playback support in the QVR Pro recording software on a QNAP NAS with QTS operating system. • Supports MxMC playback from ONVIF cameras such as the MOVE camera series. • Optimal combination on a QNAP NAS • IOT cameras store independently on the NAS via file sharing (SMB) and record the integrated MOVE or ONVIF cameras in parallel with the QVR Pro Recording Software. The output is done with the MxMC. • The license is activated on the QNAP NAS via the QNAP License Manager. • License is not transferable • one license per QNAP NAS with QVR Pro is required! • For camera recordings, QNAP requires additional camera channel licenses per channel, which must be obtained from QNAP!	g	cm
			l
	Mx-SW-MC-Th-DB-Bas	4047438048217	cm
	MOBOTIX MxMC Feature - ThermalDashboard Base License		cm
	Activates the MOBOTIX Thermal Dashboard in the MxMC and supports the MOBOTIX Thermal Camera functions • Main applications are: • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MxMC is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX MxMC Device license per camera - Permanent license	g	cm
			l
	Mx-SW-MC-Th-DB-Dev	4047438048224	cm
	MOBOTIX MxMC Feature - ThermalDashboard Device		cm
	Activates another camera in the MOBOTIX Thermal Dashboard in the MxMC and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MxMC is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license	g	cm
			l
	Mx-SW-XPro-CLOUD-Bas	4047438047876	cm
	MOBOTIX HUB Plug In - MOBOTIX CLOUD Base License for		cm
	Activates the MOBOTIX CLOUD support in Milestone XProtect • Main application features in the Smart Client are • Integrating cloud cameras in the desk client layout • Additional CLOUD tab in the application • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License	g	cm
			l
	Mx-SW-XPro-CLOUD-Dev	4047438048125	cm
	MOBOTIX HUB Plug In - MOBOTIX CLOUD Device License for		cm
	Activates another camera in the MOBOTIX CLOUD support in Milestone XProtect • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX CLOUD Base license • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License	g	cm
			l

	Mx-SW-XPro-Config MOBOTIX HUB Plug In - MOBOTIX camera Configuration for Activates the configuration settings for MOBOTIX cameras in Milestone XProtect - Management Client offers camera specific configuration tabs for P3/P6/P7 and MOVE cameras - License is activated via the MOBOTIX License Portal. - License is non-transferable - One license per Milestone - Activates the function for all MOBOTIX cameras registered in the system.	4047438047890	cm
		g	cm
			l
	Mx-SW-XPro-ForSe MOBOTIX HUB Plug In - ForensicSearch for Milestone Activates the MOBOTIX ForensicSearch filters in Milestone XProtect Smart Client and supports the MOBOTIX event and app meta data for the forensic search - Intelligent search filter reduces the search in the playback to the essential - Search filter for camera apps as well as for MOBOTIX events - Support for camera models P6 / P7 and MOVE LPR models - License is activated via the MOBOTIX License Portal. - License is not transferable - One license per Milestone XProtect VMS is required. - Activates the function for all MOBOTIX cameras registered in the system.	4047438047913	cm
		g	cm
			l
	Mx-SW-XPro-Nurse-DB-Bas MOBOTIX HUB Plug In - NurseAssist Dashboard Base License Activates the MOBOTIX NurseAssist Dashboard in Milestone XProtect and supports the MOBOTIX C71 NurseAssist Camera functions • Main applications are • Live monitoring of patient conditions such as fall detection in a dashboard as a status tableau • Patient information • Virtual Patrol • Live image activation with intercom support • Slider too blurred the live image • Activity Log Book • Activity report for statistical analysis • Supports MOBOTIX C71 NurseAssist Kameras • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, Status Tableau from 4 NurseAssist cameras can be integrated in the layout • Additional NurseAssist cameras require one MOBOTIX Device license per camera - Permanent license	4047438049306	cm
		g	cm
			l
	Mx-SW-XPro-Nurse-DB-Dev MOBOTIX HUB Plug In - NurseAssist Dashboard Device Activates an additional camera for the MOBOTIX NurseAssist Dashboard in Milestone XProtect • Supports MOBOTIX C71 NurseAssist camera functions • Main application areas are • Live monitoring of patient conditions such as Fall detection in a dashboard as a status tableau • Patient information • Virtual tour • Live image activation with intercom support • Slider for live image blurring • Activity log book • Activity report for statistical evaluation • Supports MOBOTIX C71 NurseAssist cameras • Licence is activated via the MOBOTIX licence portal. • Licence is not transferable • One licence per NurseAssist camera required. • Requires a MOBOTIX NurseAssist Dashboard Base licence • With a MOBOTIX NurseAssist Dashboard Base licence, 4 NurseAssist cameras can be integrated in the Status Tableau • Additional NurseAssist cameras require a MOBOTIX Device licence per camera • Permanent licence	4047438049320	cm
		g	cm
			l
	Mx-SW-XPro-SYNC-DB-Bas MOBOTIX HUB Plug In - MOBOTIX SYNC Base License for Activates the MOBOTIX SYNC Dashboard in Milestone XProtect Smart Client • Main applications are - Display of statistical values in diagrams • Display of lists of detected number plates • Support for MOBOTIX SYNC and Helix Vaxtor • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone XProtect VMS is required. • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence	4047438047852	cm
		g	cm
			l

**Mx-SW-XPro-SYNC-DB-Dev**

4047438048101


cm

MOBOTIX HUB Plug In - MOBOTIX SYNC Device License for

Activates another MOBOTIX SYNC Grafana Dashboard in the Milestone XProtect Smart Client. • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX SYNC Base license • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence

g

cm

cm
l**Mx-SW-XPro-Th-DB-Bas**

4047438047838


cm

MOBOTIX HUB Plug In - ThermalDashboard Base License for

Activates the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Main applications are • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent licence

g

cm

cm
l**Mx-SW-XPro-Th-DB-Dev**

4047438048088


cm

MOBOTIX HUB Plug In - ThermalDashboard Device License

Activates another camera in the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent licence

g

cm

cm
l**Mx-SYNC-P-TM**

4047438049542


cm

MOBOTIX SYNC Traffic Management Plug-In

Extends the MOBOTIX SYNC Server functionality with the following features: • average speed at which vehicles went through a zone • calculate the dwell time for vehicles in a zone • both calculated based on records of entry/exit cameras

g

cm

cm
l**Mx-SYNC-P-YM**

4047438049504

cm

MOBOTIX SYNC Yard Management Plug-In

Extends the MOBOTIX SYNC Server functionality with the following features: • extended functions for access control • records of person categories, persons, and assigned authorizations • anti-passback • real-time attendance report • analysis on common routes and vehicle traceability (via REST API)

g

cm

cm
l

**Mx-SYNC-S-BAS**

4047438047548

cm

MOBOTIX SYNC Server

Store metadata and attached images generated by MOBOTIX Certified Apps (e.g. Vaxtor ALPR / OCR Apps) or other compatible data sources • 4 camera device licenses included • additional camera device licenses via additional license on demand • Monitor incoming license plates / metadata (e.g. plate reads) in real time • Search and filter existing license plates / metadata based on content such as Plate, Country, Camera, Zone, Make, Model, Color, Direction, etc. • Download and export customized license plate lists and search results • Management of cameras includes: • camera zones • manage and synchronize denied & granted license plate list • assign actuators (incl. camera I/Os) • manage data retention policies separately for images and metadata • supports GDPR measures with dedicated reports and data deletion • granular user and group permissions • login management including LDAP integration • audit trail of all interactions on the system including actions made by cameras • Send notifications (e.g. via E-Mail) • SYNC server license with runtime of 3 years after activation

g

cm

cm
l**Mx-SYNC-S-DEV**

4047438047562

cm

MOBOTIX SYNC Camera Device License

1 camera device license per additional camera device • Enables adding camera devices to the server/client on demand • *4 camera device licenses included in the server base license

g

cm

cm
l**Mx-SYNC-S-CLI**

4047438047579

cm

MOBOTIX SYNC Client

Redundant operation and data storage for applications with discontinuous connection to the server (e.g. mobile applications) • active server connection enables continuous data synchronization

g

cm

cm
l**Mx-SYNC-P-GRA**

4047438047593

cm

MOBOTIX SYNC Grafana Plug-In

Visualization and consolidation of incoming metadata in customized dashboards including: • statistic insights • data queries • annotations • create and manage alerts / post-actions • exports

g

cm

cm
l

Warranty Extensions

Warranty Extensions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-WE-DTVS-1	4047438031974	cm
	1 Year Warranty Extension For Dual Thermal Systems S74 5+1 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	g	cm l
	Mx-WE-DTVS-2	4047438031981	cm
	2 Years Warranty Extension For Dual Thermal Systems S74 5+2 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	g	cm l
	Mx-WE-DTVS-3	4047438031998	cm
	3 Years Warranty Extension For Dual Thermal Systems S74 5+3 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	g	cm l
	Mx-WE-IVS-1	4047438031820	cm
	1 Year Warranty Extension For Indoor Video Systems 5+1 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	g	cm l
	Mx-WE-IVS-2	4047438031837	cm
	2 Years Warranty Extension For Indoor Video Systems 5+2 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	g	cm l

**Mx-WE-IVS-3****3 Years Warranty Extension For Indoor Video Systems**

5+3 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031844

cm

g

cm

l

**Mx-WE-OVS-1****1 Year Warranty Extension For Outdoor Video Systems**

5+1 Year Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031875

cm

g

cm

cm

l

**Mx-WE-OVS-2****2 Years Warranty Extension For Outdoor Video Systems**

5+2 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031882

cm

g

cm

cm

l

**Mx-WE-OVS-3****3 Years Warranty Extension For Outdoor Video Systems**

5+3 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031899

cm

g

cm

cm

l

**Mx-WE-STVS-1****1 Year Warranty Extension For Single Thermal Systems**

5+1 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031929

cm

g

cm

cm

l

**Mx-WE-STVS-2****2 Years Warranty Extension For Single Thermal Systems**

5+2 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031936

cm

g

cm

cm

l

**Mx-WE-STVS-3****3 Years Warranty Extension For Single Thermal Systems**

5+3 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031943

cm

cm

g

cm

l

Other

BeyondHumanVision

MOBOTIX

Training Courses

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SE-Advanced MOBOTIX Seminar Advanced Course 1 (IoT) - 1 day training Classroom Training • This one-day seminar covers the in-depth configuration of a MOBOTIX camera system and advanced features of the MxManagementCenter video management software • In this comprehensive hands-on training, you will learn how to optimize settings and manage demanding IP video projects • Includes "Video Security Professional" certificate.	4047438049689 g	cm cm cm l
	Mx-SE-GDPR-DE MOBOTIX Seminar Datenschutz Video - ONLY in German Classroom Training - Datenschutz Video • ONLY available in German language	4047438049757 g	cm cm cm l
	Mx-SE-Grund-Video-DE MOBOTIX Seminar Videosicherheitstechnik - ONLY in Grundkurs Videosicherheitstechnik • ONLY available in German language	4047438049696 g	cm cm cm l
	Mx-SE-HTTP-API MOBOTIX Seminar HTTP API & MxMessageSystem - 1 day Classroom Training • This one-day seminar focuses on the use of the HTTP API and the MxMessageSystem via network and MxBus • Connection of the MOBOTIX 7 apps to the event logic of the IoT system • incl. "Integration Professional" certificate.	4047438049672 g	cm cm cm l
	Mx-SE-HUB-S-D MOBOTIX Hub Sales & Design Seminar – 1 day online Online training - This online training provides participants with the knowledge and skills they need to design MOBOTIX Hub video management systems. The aim is to effectively support customers' surveillance requirements and optimize the overall profitability of the video surveillance system - Prerequisite basic video security technology course - Includes "MOBOTIX Hub Sales & Design Specialist" certificate	4047438049719 g	cm cm cm l

	Mx-SE-HUB-Tec-DE	4047438049740	cm
	MOBOTIX Seminar HUB Technical Specialist L1 - ONLY in Onlinetraining HUB Technical Specialist L1 • ONLY available in German language	g	cm l
	Mx-SE-HUB-Tec1-EN	4047438049726	cm
	MOBOTIX Seminar HUB Technical Specialist L1 - 2 days Online Training - This two day online training consists of a series of hands-on exercises in which participants practice configuring a MOBOTIX Hub video management system. Step-by-step instructions and a professional trainer will guide participants in configuring systems according to sample specifications.ü Prerequisite Basic Video Security Technology Course and MOBOTIX Sales & Design • Incl. "MOBOTIX Hub Technical Specialist L1" certificate.	g	cm l
	Mx-SE-HUB-Tec2-EN	4047438049733	cm
	MOBOTIX Seminar HUB Technical Specialist L2 - 2 days Online Training - This two day online training consists of a series of hands-on exercises in which participants practice configuring a MOBOTIX Hub video management system. Step-by-step instructions and a professional trainer will guide participants in configuring systems according to sample specifications.ü Prerequisite Basic Video Security Technology Course and MOBOTIX Sales & Design and HUB Technical Specialist L1 • Incl. "MOBOTIX Hub Technical Specialist L2" certificate.	g	cm l
	Mx-SE-MOVE-Expert	4047438049702	cm
	MOBOTIX Seminar MOVE System Expert - Online training Online training - This training is offered in two parts. First, participants work through an intensive system workshop on eCampus. The workshop is divided into several lessons, which are completed within a week at your own pace. Following this, further live training sessions are offered online, in which specific topics are discussed. There is also the opportunity to ask current questions and receive the latest updates. - Incl. "MOBOTIX MOVE System Specialist" certificate	g	cm l
	Mx-SE-Smart-Auto	4047438049641	cm
	MOBOTIX Seminar Smart Automation Workshop Classroom Training - In the seminar "Smart Automation Workshop" you will learn • Concept and development of MQTT • MQTT Broker and first client accesses • Camera as MQTT client and switching of MQTT actuators • The app service for MOBOTIX IoT cameras - Configuration and use of individual camera apps • Incl. certificate "Smart Automation Professional"	g	cm l
	Mx-SE-Thermal	4047438049665	cm
	MOBOTIX Seminar Thermal - 1 day training course Classroom Training • In the "Thermal imaging technology" seminar, you will learn about the MOBOTIX thermal imaging camera product portfolio. It also covers the basics of thermal cameras and sample applications. Each participant can deepen their knowledge in practical exercises with a thermal imaging camera. • incl. certificate "MOBOTIX certified installer of thermal imaging systems".	g	cm l

**Mx-SE-VDS-EN54****MOBOTIX Seminar VDS & EN54 - 1 day classroom training**

Classroom Training - In the seminar "VdS&EN54" you will learn about the EN54-certified thermal system from MOBOTIX for early fire detection • Details about the necessary requirements to couple the MOBOTIX thermal camera with a fire alarm system • Prerequisite "Basic Course Video Security Technology" and "Advanced Course 1 Video Security Technology" • Incl. certificate "MOBOTIX certified installer of VdS-compliant early fire detection systems"

4047438049658

cm

cm


g

cm

l

Professional Services

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Password-Reset-Software</p> <p>Professional Services Password Reset Software</p> <p>This password reset is an encrypted, time limited (will expire after 30 days) software file, specific for the factory IP of the camera directly on-site at your customers location.</p>	<p>4047438035392</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>PS-Field-Service-Day</p> <p>Professional Services Field Engineering & On-Site Support,</p> <p>Available for MOBOTIX systems of any size and for all MOBOTIX hardware and software products; fixed price flat rate for one working day. • Field Engineering: System configuration, commissioning and user training directly on site. Complete configuration and customization. • On-site Support: One working day for on-site support and troubleshooting directly at the project site. Professional health and storage check, troubleshooting through reconfiguration and re-configuration, on-site user training.</p>	<p>4047438035347</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>PS-Field-Service-Day-100</p> <p>Professional Services Onsite Field Engineering / Project</p> <p>Onsite Field Engineering / Project Commissioning for projects of over 100+ MOBOTIX cameras (excludes travel costs)</p>	<p>4047438048149</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>PS-Field-Service-Half-Day</p> <p>Professional Services Field Engineering & On-Site Support,</p> <p>Available for MOBOTIX systems of any size and for all MOBOTIX hardware and software products; fixed price flat rate for half a working day. • Field Engineering: System configuration, commissioning and user training directly on site. Complete configuration and customization. • On-site Support: One working day for on-site support and troubleshooting directly at the project site. Professional health and storage check, troubleshooting through reconfiguration and re-configuration, on-site user training.</p>	<p>4047438035354</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>PS-PreConfig-9plus1free</p> <p>Professional Services Every 10th Pre-Configuration per PO</p> <p>Every 10th Pre-Configuration per PO is free (Buy 9 get 1 Free)</p>	<p>4047438048163</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>

**PS-PreConfig-IoT****Professional Services Pre-Configuration per IoT-Camera**

Pre-Configuration of all MOBOTIX IoT Cameras incl. Function Guarantee direct from production


4047438035316

cm

g

cm

l

**PS-PreConfig-IoT-Doorstation****Professional Services Pre-Configuration per Doorstation**

Pre-Configuration of all MOBOTIX DoorStations incl. Function Guarantee direct from production

4047438035323


cm

g

cm

cm

l

**PS-PreConfig-MxMove****Professional Services Pre-Configuration per MOVE-Camera**

Pre-Configuration of all MOBOTIX MOVE Cameras incl. Function Guarantee direct from production

4047438035330

cm

g

cm

cm

l

**PS-Remote-Service-Half-Hour****Professional Services Remote Support Half-Hourly Rate**

Half Hour professional troubleshooting, rectification and system optimization via secure IP remote connection by MOBOTIX specialists

4047438035385

cm

g

cm

cm

l

**PS-Remote-Service-Hour****Professional Services Remote Support Hourly Rate**

One Hour professional troubleshooting, rectification and system optimization via secure IP remote connection by MOBOTIX specialists

4047438035378

cm

g

cm

cm

l

**PS-Remote-Support-Opt****Professional Services Remote Support System Optimization**

Remote Support System Optimization • 1 hr Remote Support free for every 20 Pre-Configurations per PO

4047438048156

cm

g

cm

cm

l

**PS-Travelcost**

4047438035361

cm

Professional Services Travel & Accommodation Costs

cm

Costs for travel expenses of the MOBOTIX specialist. Maximum 2000€.

g

cm

l

**PS-Travelcost-plus**

4047438048170

cm

Professional Services Increased Travel & Accommodation

cm

Increase the maximum chargeable for travel costs to €3000

g

cm

l