

Technical Specifications

Vaxtor Container Code Recognition App

Recognition of cargo container codes according to ISO 6346

Based on deep learning processes the certified Vaxtor Container Code Recognition App recognizes container codes and delivers realtime results about the container owner, type dimensions and much more. The app is able to detect container codes within 900 ms and an extremely high hit probability of over 99 percent. Via blocking or permission lists, authorized, or containers with unauthorized content can be defined specifically. Possible areas of use for the application are harbor & airport logistics, container inventory & surveillance, border control, access control or logistic management.

- Recognition of cargo container codes according to ISO 6346 standard
- with over 99% accuracy optimally suited for detection and logging of container codes on entry, between zones, during processes or exit
- Two lists for individual actions (e.g. access granted/denied, alarm, etc.)
- Integrated Smart Data Interface for data retrieval with MxManagementCenter from version 2.4.3.





Technical Specifications

Product Information

Product Name	Vaxtor Container Code Recognition App
Order Code	Mx-APP-VX-CON
Supported MOBOTIX Cameras	Mx-M73A, Mx-S74A

Minimum Camera Firmware v7.1.3.x

MxManagementCenter	min. MxMC v2.4.3
Integration	■ Configuration: Advanced Config license required
	■ Event Search: Smart Data Interface license included

Product Features

App Features	Recognition of cargo container codes according to ISO 6346
	Real time results:
	■ Container Code
	Owner and corresponding origin
	■ Container Type
	Container Dimensions
	Control Digit
	■ Control Digit Validation
	■ Recognition log (Smart Data / Event Search via MxManagementCenter)
	■ MOBOTIX events via MxMessageSystem
	■ Two lists for individual actions (e.g. access granted/denied, alarm, etc.)
	■ Free flow and Signaled mode
Maximum number of recog- 1	

Maximum number of recognition areas

Ilition aleas		
Maximum number of enrolled license plates	1000 per list	
Meta Data / Statistic formats	JSON	

Trial License	30-day trial license pre-installed	
MxMessageSystem sup- ported	Yes	
Integration Interfaces	■ MxMC Smart Data	
	■ IP Notification	
	■ Milestone X-Protect	
	■ MOBOTIX SYNC	
	generic 3rd party integration via XML	
	compare supported camera's interfaces	
MOBOTIX Events	Yes	
ONVIF Events	Yes (Generic Message event)	

Supported Container Codes

Supported Container Codes Container code specification according to ISO 6346

Scene Requirements

Character Height	20px - 50px
Maximum Vertical Angle	30°
Maximum Horizontal Angle	< 25°
Maximum Tilt Angle	< 25°

Technical App Specifications

Synchronous / Asyn- chronous App	asynchronous
Simultaneous execution of other apps	No
Accuracy	min. 99% (considering scene requirements)
Processed frame rate	typ. 10 fps
Detection time	typ. 900 ms per Container

