



# Technical Specifications

## MOBOTIX S74 Long Cable Extender

**More range. More possibilities. More efficiency.**

One camera - up to four modules - and you can move each module up to 34 m away from the camera housing. That's flexibility, redefined! So you could even monitor the ground and top floors of the Leaning Tower of Pisa with a single camera. Or line up all the spaghetti from one package. That's the distance you can cover with the MOBOTIX S74 Long Cable Extender.

- Modules can be placed up to 34 meters away from the camera housing.
- Image data transmitted between the two LCE connection boxes with up to 30 m of fiber-optic cable.
- Suitable for all S74 sensor modules (4K, 4MP Ultra LowLight, Thermal B-Series will be supported with a later camera firmware release from late Q1/22 onwards) and for the MultiSense module and IR modules.
- 30fps@4K (WDR off), 15fps@4K (WDR on).



BeyondHumanVision

**MOBOTIX**

Document ID: Mx\_TS\_Mx-F-S7A-LCE\_V1.11\_EN

V1.11, 6/24/2026, Order Code: Mx-F-S7A-LCE

# Technical Specifications

## Type

## Mx-F-S7A-LCE

Connectors (per LCE Box)

1 MOBOTIX 7 sensor module connector (USB-C)

1 Optical interface:

Cable quality OM2 or better

Fibre 50/125  $\mu\text{m}$

Receptacle LC - LC

Transmission type Simplex

1 Electrical interface:

Power and electrical interface 6x2 for I2C (SCL, SDA), Reserved0, Reserved1, VCC, GND

AWG 24-20

Cable Diameter rigid 0.14-0.5  $\text{mm}^2$

Cable Diameter flexible 0.2-0.5  $\text{mm}^2$  (with ferrule)

Recommended cables

Optical Interface: LC-LC OM3

Electrical Interface: The wires must follow the specification as outlined above.

Max Cable Length

30 m

Connectable MOBOTIX Sensor Modules

4K, 4MP and Thermal Sensor Modules

Multisense, IR-Light (no optical link necessary)

Certificates

EN 50121-4, EN 55032, EN 55035, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 62368-1, EN 63000, AS/NZS CISPR32, 47 CFR Part 15b, NRTL

IP protection class

No IP rating (indoor use only)

IK protection class

No IK rating (indoor use only)

Operating temperature range

0 to 40  $^{\circ}\text{C}$ /32 to 149  $^{\circ}\text{F}$

Max. frame rate (fps)

Optical sensors only:

15 @ 4K WDR on

30 @ 4K WDR off

LEDs

2 Multicolor LEDs: power status (left), transmission status of optical link (right)

# MOBOTIX

BeyondHumanVision

EN\_06/26

MOBOTIX AG • Am Stundenstein 2 • D-67722 Winnweiler • Tel.: +49 6302 9816-103 • sales@mobotix.com • www.mobotix.com  
MOBOTIX is a trademark of MOBOTIX AG registered in the European Union, the U.S.A., and in other countries. Subject to change without notice. MOBOTIX do not assume any liability for technical or editorial errors or omissions contained herein. All rights reserved. © MOBOTIX AG 2019