



Technical Specifications

MOBOTIX S ONE DUAL

MOBOTIX S ONE DUAL - Invisible Power. Visible Results.

With the MOBOTIX S ONE DUAL, MOBOTIX presents the next generation of modular premium dual cameras. It builds on the success of the S16 DualFlex and takes the concept to a new level of performance: two freely positionable 4K UHD sensor modules for 8K dual images, a compact, concealed camera housing, and AI-based edge analysis that runs simultaneously on both sensor channels for the first time.

The S ONE DUAL was developed for industrial requirements, mobile applications, and security-critical environments—it is robust, weatherproof, durable, and energy-efficient (PoE, <10 W).

- Two modular 4K UHD sensor modules – freely positionable for one or two viewing angles
- Compact, concealed camera housing – protected against tampering and external access
- Exceptionally robust: IP66 / NEMA 4X, IK10, NEMA 4X, operating temperature –40 to 65 °C/–40 to 149 °F–20 to 40 °C/–4 to 104 °F–40 to 65 °C/–40 to 149 °F–10 to 50 °C/–14 to 122 °F0 to 40 °C/32 to 149 °F
- AI-ready with built-in MxActivitySensorONE for reliable object detection
- Up to 2 TB internal storage, with 64 GB microSD card pre-installed
- Comprehensive codec support: H.264, H.265, MxPEG+, MJPEG
- Versatile deployment options: e.g. vehicles (buses, trains, etc.), industrial machines and production systems, video-controlled access or barrier systems, warehouse logistics and discreet surveillance applications



BeyondHumanVision

MOBOTIX

Table of Contents

Order Information

Hardware

Image and Video Properties

General Software Features

Video Analysis

Video Management Software

Accessories

Dimensions

2

2

4

5

6

6

6

8

Order Information

Name	MOBOTIX S ONE DUAL
Order Code:	Mx-ONE-S1A-D (Body only)

Hardware

Feature	Properties
Image sensor (color or B&W sensor)	Up to 4K UHD 3840x2160, 16:9, 1/1.8"
Available Lenses	See Sensormodules Standard (4K Day & Night) , p. 6
Light sensitivity	Color sensor: 0.1 lx @ 1/60 s; 0.005 lx @ 1 s
Exposure control	Manual and automatic mode 1 s to 1/16.000 s
IK protection class	Sensor modules: IK10
IP / NEMA protection class	Housing: IP66 / NEMA 4X Sensor modules: IP66 / NEMA 4X/NEMA 4X
Intended use	Do not use in hazardous areas (Ex area)
Operating temperature range	−40 to 65 °C/−40 to 149 °F
Min. cold start temperature	−30 °C/−22 °F

Feature	Properties								
Relative Humidity	5% to 95%, non-condensing								
Internal DVR Storage	Internal microSD card (SDHC/SDXC), 64 GB out-of-the-box, max. 2 TB.								
I/Os	INPUT ■ Contact Closure (no galvanic isolation necessary) or up to 30 Vrms AC / 50 V DC ■ Switching thresholds ■ Input >1.6 V leads to a detected HIGH ■ Input <0.9 V leads to a detected LOW (after a high) ■ Max. length for cables: 50 m OUTPUT ■ 3x Dry contact, form A (max 30 Vrms / max, 50 V DC / 60 W / 2 A DC)								
Microphone	■ Microphone (integrated in ONE sensor modules): ■ Sensitivity: -41 dB FS ±1 dB ■ SNR 68 dBA ■ AOP 133 dB SPL								
Speaker	■ External speaker required: 1.8 W @ 8 Ω								
Allowed cable dimensions for cables connected to the PCB terminals	<table> <tr> <td><i>Conductor cross section</i></td><td></td></tr> <tr> <td>AWG</td><td>26 - 20</td></tr> <tr> <td>Rigid</td><td>0.14 mm² - 0.5 mm²</td></tr> <tr> <td>Flexible</td><td>0.14 mm² - 0.5 mm²</td></tr> </table>	<i>Conductor cross section</i>		AWG	26 - 20	Rigid	0.14 mm ² - 0.5 mm ²	Flexible	0.14 mm ² - 0.5 mm ²
<i>Conductor cross section</i>									
AWG	26 - 20								
Rigid	0.14 mm ² - 0.5 mm ²								
Flexible	0.14 mm ² - 0.5 mm ²								
Tampering Detection	Integrated Shock Sensor								
PoE standard	PoE (802.3af-2003) / Class 3								
Power consumption	Max. 12.95 W/270 mA (average can be significantly lower) Average in dual operation: 9.0 W Dual operation, WDR off: approx. 5.63 W Dual operation, WDR on: approx. 6.27 W MxActivitySensorONE per Sensor: approx. 1.4 W								
Electrical surge protection	Overvoltage Protection Box (not part of the scope of delivery)								
Interfaces	■ Ethernet 1000Base-T (RJ45 according to EIA/TIA-568B) ■ Sensor Modules M1, M2 ■ USB 2.0/3.0 via USB-C connector ■ 12-24 V DC power supply ■ Input / Output ■ Ext. Speaker ■ microSD card, max. 2 TB								
Status LED	Multicolor (8 colors)								

Technical Specifications

MOBOTIX S ONE DUAL

Feature	Properties
Mounting Options	Wall, ceiling, hidden installation; extensive selection of mounting accessories available (see Mounts, p. 7)
Dimensions (height x width x depth)	137.5 x 115 x 33 mm
Weight	0.54 kg
Housing	Aluminum, PBT-30GF
Detailed technical documentation	www.mobotix.com > Services > Download Center > Marketing & Documentation
MTBF	100,000 hours
Certificates	EN 55032, EN 55035, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 62368-1, EN 63000, AS/NZS CISPR32, 47 CFR Part 15b, NRTL
Protocols	DHCP (client and server), DNS, ICMP, IGMP v3, IPv4, IPv6, HTTP, HTTPS, FTP, FTPS, NFS, NTP (client and server), MQTT, RTP, RTCP, RTSP, SFTP, SIP (client and server), SMB/CIFS, SNMP, SMTP, SSL/TLS 1.3, TCP, UDP, VLAN, VPN, Zeroconf/mDNS
Manufacturer warranty	5 years

Image and Video Properties

Feature	Properties
Available video codecs	H.264, H.265, MxPEG+, MJPEG
Image resolutions	VGA 640x360, XGA 1024x576, HD 1280x720, FullHD 1920x1080, QHD 2560x1440, 4K UHD 3840x2160 (8MP)
Multi streaming	H.264, H.265 with up to 4 streams (2 per sensor)
Multicast stream via RTSP	Yes
Max. frame rate	MxPEG: 20@4K, H.264: 30@4K, H.265: 30@4K

General Software Features

Feature	Properties
WDR	Up to 120 dB
Software features	■ H.264, H.265 Multistreaming ■ Multicast stream via RTSP ■ Digital pan, tilt, zoom/vPTZ (up to 8x zoom) ■ Genetec protocol integration ■ Programmable exposure zones ■ Snapshot recording (pre/post-alarm images) ■ Continuous recording ■ Event recording ■ Time-controlled flexible event logic ■ Weekly schedules for recordings and actions ■ Event video and image transfer via FTP and email ■ Playback and QuadView via web browser ■ Animated logos on the image ■ Master/Slave functionality ■ Privacy zone scheduling ■ Remote alarm notification (network message) ■ Programming interface (HTTP API) ■ MxMessageSystem ■ MQTT (Message Queuing Telemetry Transport)
ONVIF compatibility	Profile G, S, T
Master/Slave functionality	Yes
Remote alarm notification	Email, MQTT, MxMessageSystem, network message (HTTP/HTTPS), SNMP, SIP
DVR/image storage management	■ On internal microSD card ■ On external USB and NAS devices ■ Different streams for live image and recording ■ MxFFS with buffered archive, pre- and post-alarm images, storage monitoring with error reporting
Camera and data security	FIPS 140-3 validated encryption (OpenSSL 3.1.2, NIST CMVP #4985), VPN with FIPS-certified library, HTTPS with custom X.509 certificates (TLS), AES encryption at rest (microSD / NAS), role-based access control, IP-level access control list, audit trail / web server access log, intrusion detection with automatic IP lockout, IEEE 802.1X port-based network access control, digital image signature
Firmware Tampering Detection	Digital Signature

Video Analysis

Feature	Properties
Video motion detection	Yes
MxActivitySensor	Version 1.0, 2.1
MxActivitySensorONE	Motion and Loitering Detection of Person and Vehicles

Video Management Software

Feature	Properties
MOBOTIX HUB	Supported, compatible with MOBOTIX HUB NurseAssist Dashboard Services > Download Center > Software Downloads">www.mobotix.com > Services > Download Center > Software Downloads
MxManagementCenter	Yes (latest version recommended) Services > Download Center > Software Downloads">www.mobotix.com > Services > Download Center > Software Downloads
MOBOTIX LIVE App	Yes (available in Google Play Store (Android) and Apple App Store (iOS)).
3rd Party VMS Software	See ONVIF Profile S, T and G specification

Accessories

Sensormodules Standard (4K Day & Night)

NOTE!

Lenses or sensors are not part of the scope of delivery.

Lens	Sensor	Order Code
Fixed lens 120° WIDE	4K Sensor as D/N IR Cut / Microphone	Mx-ONE-SMA-8DN040
Fixed lens 95° WIDE	4K Sensor as D/N IR Cut / Microphone	Mx-ONE-SMA-8DN050
Fixed lens 60° WIDE	4K Sensor as D/N IR Cut / Microphone	Mx-ONE-SMA-8DN080
Fixed lens 45° STANDARD	4K Sensor as D/N IR Cut / Microphone	Mx-ONE-SMA-8DN100
Fixed lens 30° TELE	4K Sensor as D/N IR Cut / Microphone	Mx-ONE-SMA-8DN150
Fixed lens 15° TELE	4K Sensor as D/N IR Cut / Microphone	Mx-ONE-SMA-8DN280

Module Cables

NOTE!

The module cables are not part of the scope of delivery.

Module Cable	Description	Order Code:
Sensor cable 1m straight-angled	Sensor cable straight-angled, length 1 m/3.3 ft. - For connecting optical sensor modules and thermal sensor modules to the ONE S1x camera body. - Required for audio signals from the microphone in the sensor module.	Mx-ONE-CBL-S01-AN
Sensor cable 2m straight-angled	Sensor cable straight-angled, length 2 m/6.6 ft. - For connecting optical sensor modules and thermal sensor modules to the ONE S1x camera body. - Required for audio signals from the microphone in the sensor module.	Mx-ONE-CBL-S02-AN

Mounts


The following mounts of the sensors from previous camera models are compatible.

NOTE!

- The mounts are not part of the scope of delivery.
- There may be color deviations in the mounts of earlier camera generations.
- An already installed S16 PT-Mount (purchased before January 2020) is not compatible with an S ONE DUAL module.

Mount Type	Description	Order Code:
On-Wall Kit for PTMount, white	On-Wall Kit for PTMount, white incl. mounting parts.	Mx-M-PTMA-OW
PTMount, white	Three axis adjustable mount	Mx-M-PTMA
SingleMount, white	For surveillance of one area with one sensor module	Mx-M-SLMA
DualMount, white	For surveillance of one to two areas with two sensor modules	Mx-M-DLMA

Dimensions



NOTE!

Drilling template: www.mobotix.com > Services > Download Center > Marketing & Documentation > Drilling Templates.



EN_08/26

MOBOTIX AG • Am Stundenstein 2 • D-67722 Winnweiler • Tel.: +49 6302 9816-103 • sales@mobotix.com • www.mobotix.com
MOBOTIX is a trademark of MOBOTIX AG registered in the European Union, the U.S.A., and in other countries. Subject to change without notice. MOBOTIX do not assume any liability for technical or editorial errors or omissions contained herein. All rights reserved. © MOBOTIX AG 2025