Product Overview

29.10.2026 English EUR



Video Systems IoT Outdoor

BeyondHumanVision

MOBOTIX

M ONE M1A Single IP Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-ONE-M1A-S-8DN040 **M ONE with 4K DN040 (Day/Night), 120°x60°** M ONE Single IP camera equipped with one premium wide-angle lens B040 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)	4047438048446 85258900 1.500 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
		
Mx-ONE-M1A-S-8DN050 **M ONE with 4K DN050 (Day/Night), 95°x50°** M ONE Single IP camera equipped with one premium wide-angle lens B050 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)	4047438048453 85258900 1.500 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
		
Mx-ONE-M1A-S-8DN080 **M ONE with 4K DN080 (Day/Night), 60°x33°** M ONE Single IP camera equipped with one premium wide-angle lens B080 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)	4047438048460 85258900 1.500 g	29,6 cm 19,6 cm 18,0 cm 10,4 l



Mx-ONE-M1A-S-8DN100

M ONE with 4K DN100 (Day/Night), 45°x25°

M ONE Single IP camera equipped with one premium normal lens B100 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048477 29,6 cm
85258900 19,6 cm
1.500 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8DN150

M ONE with 4K DN150 (Day/Night), 30°x17°

M ONE Single IP camera equipped with one premium tele lens B150 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048484 29,6 cm
85258900 19,6 cm
1.500 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8DN280

M ONE with 4K DN280 (Day/Night), 15°x8,5°

M ONE Single IP camera equipped with one premium tele lens B280 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048491 29,6 cm
85258900 19,6 cm
1.500 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8DNTELE

M ONE with 4K DN Tele Varifocal (Day/Night), 42° - 15°

M ONE Single IP camera equipped with one premium motorized tele varifocal lens and IR cut filter for day and night use, aperture: f/1,7, image angle H: 42° -15°, V:22,8°-8,4° • focal length: 11-29 mm • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048422 29,6 cm
85258900 19,6 cm
1.550 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8DNWIDE

M ONE with 4K DN Wide Varifocal (Day/Night), 112° - 47,5°

M ONE Single IP camera equipped with one premium motorized wide varifocal lens and IR cut filter for day and night use, aperture: f/1.3, image angle H: 112° -47,5°, V:58°-26,6° • focal length: 4.3-9.3 mm • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048439 29,6 cm
85258900 19,6 cm
1.500 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8N040

M ONE with 4K Night sensor, 120°x60°

M ONE Single IP camera equipped with one premium wide-angle lens B040 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 120° x60° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048521 29,6 cm
85258900 19,6 cm
1.500 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8N050

M ONE with 4K Night sensor, 95°x50°

M ONE Single IP camera equipped with one premium wide-angle lens B050 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 95°x50° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048538 29,6 cm
85258900 19,6 cm
1.500 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8N080

M ONE with 4K Night sensor, 60°x33°

M ONE Single IP camera equipped with one premium wide-angle lens B080 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 60°x33° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048545 29,6 cm
85258900 19,6 cm
1.500 g 18,0 cm
10,4 l



Mx-ONE-M1A-S-8N100

M ONE with 4K Night sensor, 45°x25°

M ONE Single IP camera equipped with one premium normal lens B100 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 45°x25° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x Audio Out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048552	29,6 cm
85258900	19,6 cm
1.500 g	18,0 cm
	10,4 l



Mx-ONE-M1A-S-8N150

M ONE with 4K Night sensor, 30°x17°

M ONE Single IP camera equipped with one premium tele lens B150 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 30°x17° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x mic In, 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048569	29,6 cm
85258900	19,6 cm
1.500 g	18,0 cm
	10,4 l



Mx-ONE-M1A-S-8N280

M ONE with 4K Night sensor, 15°x8,5°

M ONE Single IP camera equipped with one premium tele lens B280 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/0 (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048576	29,6 cm
85258900	19,6 cm
1.500 g	18,0 cm
	10,4 l

ONE S1A Dual Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-ONE-S1A-D	4047438050609	19,6 cm
MOBOTIX S ONE Dual S1A-D for two sensor modules	85258900	14,8 cm
	540 g	9,0 cm
		2,6 l
MOBOTIX S ONE Dual camera module (body) for connecting one or two MOBOTIX ONE sensor modules (4K/8MP UHD, Day&Night, 3840x2160, 15° /30°/45°/60°/95°/120°, 180° (2160x2160px), can be ordered separately) or in combination with a thermal module (640R050 50°x40° VGA (640x480px) or 640R100 95° x 76° (640x480px), can be ordered separately) • ONVIF-compliant MOBOTIX ONE system platform (profile G, S, T) with H.264, H.265, MxPEG+ and M-JPEG • WDR: up to 120dB • Max. frame rate: MxPEG: 20@4K, H.264: 30@4K, H.265: 30@4K • Temperature sensor, MxActivitySensor ONE, vibration sensor • Operating conditions: IP66 and NEMA 4X, –40 to +65 °C / –40 to +149 °F • Internal DVR: 64 GB microSD • Max. power consumption: 12.95 W, power supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24 V DC external power supply • Connections: 2x sensor module connection (M1, M2), 1x RJ45 socket for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT, EIA/TIA-568B), I/O (1x input, 3x outputs), 1x audio out, 1x 12–24 V DC input, 1x USB-C • Software interface for MOBOTIX camera apps (based on deep learning) • Housing: PBT-30GF • Color: white • Dimensions (HxWxD): 137.5 x 115 x 33 mm • Weight (body): 540 g • Manufacturer's warranty: 5 years (optionally extendable to up to 8 years) • MTBF: 100,000 h • Approvals: EN 55032, EN 55035, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 62368 -1, EN 63000, AS/NZS CISPR32, 47 CFR Part 15b, NRTL • Sensor cable can be ordered separately (1 m length: Mx-ONE-CBL-S01-AN • 2 m length: Mx-ONE-CBL-S02-AN • 5 m length: Mx-ONE-CBL-S05-AN)		

M73A

MOBOTIX 7 Solution Platform

Weatherproof (IP66) Fixed Network Camera (Body) in two color variants, modular design with separately orderable optical 4K UHD image sensor modules (optimized for day, night or day & night use) and separately orderable function modules for easy insertion in the front panel (3 module openings, can be assigned as required), module connection via MOBOTIX sensor cables pre-positioned in the camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-M73A-LSA	4047438036825	29,6 cm
M73 Body with LSA Connector Box (white)	85258900	26,8 cm
M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA terminal for weatherproof network connection via laying cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)	2.500 g	18,0 cm 14,3 l

		
Mx-M73A-RJ45	4047438034982	29,6 cm
M73 Body with RJ45 Connector Box (white)	85258900	26,8 cm
M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)	2.500 g	18,0 cm 14,3 l

D71B Dome Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
 **Mx-D71B-4DN050** **D71B Complete Camera 4MP Ultra LowLight DN050 (Day(Night), 95°x50°** D71B 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438050036 85258900 1.180 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-D71B-4DN080** **D71B Complete Camera 4MP Ultra LowLight DN080 (Day(Night), 60°x33°** D71B 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438050043 85258900 1.180 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-D71B-4DN100** **D71B Complete Camera 4MP Ultra LowLight DN100 (Day(Night), 45°x25°** D71B 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438050050 85258900 1.180 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-D71B-4DN150** **D71B Complete Camera 4MP Ultra LowLight DN150 (Day(Night), 30°x17°** D71B 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438050067 85258900 1.180 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-D71B-4DN280** **D71B Complete Camera 4MP Ultra LowLight DN280 (Day(Night), 15°x8,5°** D71B 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	4047438050074 85258900 1.180 g	19,6 cm 18,0 cm 14,8 cm 5,2 l



Mx-D71B-8DN050

D71B Complete Camera 4K DN050 (Day(Night), 95°x50°

D71B 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438050081 19,6 cm
85258900 18,0 cm
1.180 g 14,8 cm
5,2 l



Mx-D71B-8DN080

D71B Complete Camera 4K DN080 (Day(Night), 60°x33°

D71B 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438050098 19,6 cm
85258900 18,0 cm
1.180 g 14,8 cm
5,2 l



Mx-D71B-8DN100

D71B Complete Camera 4K DN100 (Day(Night), 45°x25°

D71B 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438050104 19,6 cm
85258900 18,0 cm
1.180 g 14,8 cm
5,2 l



Mx-D71B-8DN150

D71B Complete Camera 4K DN150 (Day(Night), 30°x17°

D71B 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438050111 19,6 cm
85258900 18,0 cm
1.180 g 14,8 cm
5,2 l



Mx-D71B-8DN280

D71B Complete Camera 4K DN280 (Day(Night), 15°x8,5°

D71B 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438050128 19,6 cm
85258900 18,0 cm
1.180 g 14,8 cm
5,2 l

Q71B Hemispheric Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-Q71B-12DN016	4047438050135	19,6 cm
Q71B Complete Camera 12MP, DN016 (Day/Night), 360°	85258900	18,0 cm
	1.050 g	14,8 cm
		5,2 l
Q71B camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 • 12MP image sensor • 4K effective resolution: 2880x2880 (hemispheric original image) • Max. Frame rate (4K): 20 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR and white light LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • IP66 • IK10 except on the lens • Operating temperature range: -40 to +65 °C • Built-in speaker and microphone - Line In & Out - Input & Output • USB-C • 8GB memory card included		

Video Systems IoT Indoor

BeyondHumanVision

MOBOTIX

c1A ONE Indoor Camera

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-ONE-c1A-S-8DN016**	4047438051422	19,6 cm
	MOBOTIX c ONE 4K, DN016 (Day/Night)	85258900	14,8 cm
		440 g	9,0 cm
			2,6 l
	c ONE IP camera with hemispheric lens and IR-cut filter for day and night use, aperture: f/1.8 • Max. image size: 2160 x 2160 pixels, 1:1 • Max. frame rate: 30 fps @ 4K • ONVIF-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+, and M-JPEG • WDR: up to 120 dB, IR LEDs (up to 25m²), White Light LEDs (Emergency Light) • HD audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, vibration sensor • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 expansion boxes • Operating conditions: IP40, -20 to 40 °C / –4 to 104 °F • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. power consumption: 12.95 W, powered via network cable, PoE Class 3 (IEEE 802.3af) or 12/24 VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 1x output), 1x audio out, 1x 12/24 VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on deep learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable to up to 8 years)		

p71B Indoor Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
 **Mx-p71B-4DN040** **p71B Indoor Complete Camera 4MP Ultra LowLight DN040 (Day(Night), 120°x60°** p71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050227 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-p71B-4DN050** **p71B Indoor Complete Camera 4MP Ultra LowLight DN050 (Day(Night), 95°x50°** p71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050234 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-p71B-4DN080** **p71B Indoor Complete Camera 4MP Ultra LowLight DN080 (Day(Night), 60°x33°** p71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050241 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-p71B-4DN100** **p71B Indoor Complete Camera 4MP Ultra LowLight DN100 (Day(Night), 45°x25°** p71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050258 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-p71B-4DN150** **p71B Indoor Complete Camera 4MP Ultra LowLight DN150 (Day(Night), 30°x17°** p71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050265 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l



Mx-p71B-4DN280

p71B Indoor Complete Camera 4MP Ultra LowLight DN280 (Day(Night), 15°x8,5°

p71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050272 19,6 cm
85258900 18,0 cm
1.175 g 14,8 cm
5,2 l



Mx-p71B-8DN040

p71B Indoor Complete Camera 4K DN040 (Day/Night), 120°x60°

p71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050289 19,6 cm
85258900 18,0 cm
1.175 g 14,8 cm
5,2 l



Mx-p71B-8DN050

p71B Indoor Complete Camera 4K DN050 (Day/Night), 95°x50°

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050296 19,6 cm
85258900 18,0 cm
1.175 g 14,8 cm
5,2 l



Mx-p71B-8DN080

p71B Indoor Complete Camera 4K DN080 (Day(Night), 60°x33°

p71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050302 19,6 cm
85258900 18,0 cm
1.175 g 14,8 cm
5,2 l



Mx-p71B-8DN100

p71B Indoor Complete Camera 4K DN100 (Day(Night), 45°x25°

p71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050319 19,6 cm
85258900 18,0 cm
1.175 g 14,8 cm
5,2 l



Mx-p71B-8DN150

p71B Indoor Complete Camera 4K DN150 (Day(Night), 30°x17°

p71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050326 19,6 cm
85258900 18,0 cm
1.175 g 14,8 cm
5,2 l



Mx-p71B-8DN280

p71B Indoor Complete Camera 4K DN280 (Day(Night), 15°x8,5°

p71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050333	19,6 cm
85258900	18,0 cm
1.175 g	14,8 cm
	5,2 l

v71B Indoor Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
 **Mx-v71B-4DN050** **v71B Indoor Complete Camera 4MP Ultra LowLight DN050 - 95°x50° (Day(Night)** v71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050340 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-v71B-4DN080** **v71B Indoor Complete Camera 4MP Ultra LowLight DN080 - 60°x33° (Day(Night)** v71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050357 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-v71B-4DN100** **v71B Indoor Complete Camera 4MP Ultra LowLight DN100 - 45°x25° (Day(Night)** v71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050364 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-v71B-4DN150** **v71B Indoor Complete Camera 4MP Ultra LowLight DN150 - 30°x17° (Day(Night)** v71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050371 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
 **Mx-v71B-4DN280** **v71B Indoor Complete Camera 4MP Ultra LowLight DN280 - 15°x8,5° (Day(Night)** v71B 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438050388 85258900 1.050 g	19,6 cm 18,0 cm 14,8 cm 5,2 l



Mx-v71B-8DN050

v71B Indoor Complete Camera 4K DN050 - 95°x50° (Day/Night)

v71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050395 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l



Mx-v71B-8DN080

v71B Indoor Complete Camera 4K DN080 - 60°x33° (Day (Night)

v71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050401 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l



Mx-v71B-8DN100

v71B Indoor Complete Camera 4K DN100 - 45°x25° (Day (Night)

v71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050418 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l



Mx-v71B-8DN150

v71B Indoor Complete Camera 4K DN150 - 30°x17° (Day (Night)

v71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050425 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l



Mx-v71B-8DN280

v71B Indoor Complete Camera 4K DN280 - 15°x8,5° (Day(Night)

v71B 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438050432 19,6 cm
85258900 18,0 cm
1.050 g 14,8 cm
5,2 l

Video Systems IoT Thermal

BeyondHumanVision

MOBOTIX

M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-M16TB-R079-VDS	4047438041607	29,6 cm
M16B Thermographic Camera TR, 50 mK, R079 (45°) - VDS Bundle	90251900	26,8 cm
VdS-Bundle • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request	2.170 g	18,0 cm 14,3 l
		
Mx-M16TB-R119-VDS	4047438041614	29,6 cm
M16B Thermographic Camera TR, 50 mK, R119 (25°) - VDS Bundle	90251900	26,8 cm
VdS Bundle • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request	2.170 g	18,0 cm 14,3 l
		
Mx-M16TB-R079-EN54-V2	4047438048330	29,6 cm
M16B Thermographic Camera TR, 50 mK, R079 (45°) - EN54 V2 Bundle	90251900	26,8 cm
EN54 V2 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)	2.170 g	18,0 cm 14,3 l



Mx-M16TB-R119-EN54-V2

M16B Thermographic Camera TR, 50 mK, R119 (25°) - EN54 V2 Bundle

EN54 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438048347	29,6 cm
90251900	26,8 cm
2.170 g	18,0 cm
	14,3 l

M73A Thermal Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-M73TA-C320R100-EN54-V3 **M73A Thermographic Camera TR(B), CIF, R100 (50°) - EN54 Bundle V3** EN54 V3 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S/T/G-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (320 x 240 Pixel), with Thermal Radiometry+, 50° x 40° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TC-640R050, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA	4047438052696 90251900 3.550 g	41,0 cm 31,0 cm 20,0 cm 25,4 l
		
Mx-M73TA-C640R050-EN54-V3 **M73A Thermographic Camera TR(B), VGA, R050 (95°) - EN54 Bundle V3** EN54 V3 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S/T/G-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry+, 95° x 76° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TC-640R050, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA	4047438051811 90251900 3.550 g	41,0 cm 31,0 cm 20,0 cm 25,4 l
		
Mx-M73TA-C640R050-FM **M73A Thermographic Camera TR(B), VGA, R050 (95°) - FM3260 Bundle** FM3260 approved M73A IP camera bundle for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S/T/G-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry+, 95° x 76° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -30 to 65°C (-22 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at); 12-24VAC (via NPAA box) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output + 4x input, 4x output via 4IO box), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TC-640R050, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA	4047438051934 90251900 3.550 g	41,0 cm 31,0 cm 20,0 cm 25,4 l



Mx-M73TA-C640R100-EN54-V3

M73A Thermographic Camera TR(B), VGA, R100 (50°) - EN54 Bundle V3

EN54 V3 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S/T/G-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry+, 50° x 40° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TC-640R050, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438051859 41,0 cm
90251900 31,0 cm
3.550 g 20,0 cm
25,4 l



Mx-M73TA-B336R100-EN54-V2

M73A Thermographic Camera TR(B), CIF, R100 (45°) - EN54 Bundle V2

EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R100, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438049849 41,0 cm
90251900 31,0 cm
3.550 g 20,0 cm
25,4 l



Mx-M73TA-B336R150-EN54-V2

M73A Thermographic Camera TR(B), CIF, R150 (25°) - EN54 Bundle V2

EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R150, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438049856 41,0 cm
90251900 31,0 cm
3.550 g 20,0 cm
25,4 l



Mx-M73TA-B640R150-EN54-V2

M73A Thermographic Camera TR(B), VGA, R150 (32°) - EN54 Bundle V2

EN54 V2 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/0 (1x input, 1x output), 1x line in,1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R150, Mx-F-MSA, Mx-O-M7SA-Blind, Mx-F-4IOA, Mx-F-NPAA

4047438049900 41,0 cm
90251900 31,0 cm
3.550 g 20,0 cm
25,4 l



Mx-M73TA-IRIS-INT-T040

MOBOTIX M73TA T040 Irisity Intrusion Bundle, 105° /120°, 9 Hz

MOBOTIX M73TA Irisity Intrusion Bundle, consisting of: M73 Body with RJ45 connection box (Mx-M73A-RJ45), 105° Thermal Module ECO 320 - T040 (Mx-O-M7SA-320T040, 50 mk, max 9 fps (9 Hz), 120° 4K IR-Cut Day & Night Sensor Module WIDE (Mx-O-M7SA-8DN040), IR Light Module for Wide Lens (Mx-F-IRA-S) and pre-installed Irisity Iris Core Intrusion App (Mx-APP-IRIS-C-INT)

4047438050517 29,6 cm
90251900 26,8 cm
2.800 g 18,0 cm
14,3 l



Mx-M73TA-IRIS-INT-T080

MOBOTIX M73TA T080 Irisity Intrusion Bundle, 56°/60°, 9 Hz

MOBOTIX M73TA Irisity Intrusion Bundle, consisting of: M73 Body with RJ45 connection box (Mx-M73A-RJ45), 56° Thermal Module ECO 320 - T080 (Mx-O-M7SA-320T080, 50 mk, max 9 fps (9 Hz)), 60° 4K IR-Cut Day & Night Sensor Module WIDE (Mx-O-M7SA-8DN080), IR Light Module for Wide Lens (Mx-F-IRA-S) and pre-installed Irisity Iris Core Intrusion App (Mx-APP-IRIS-C-INT)

4047438050500 29,6 cm
90251900 26,8 cm
2.800 g 18,0 cm
14,3 l



Mx-M73TA-IRIS-INT-T150

MOBOTIX M73TA T150 Irisity Intrusion Bundle, 24°/30°, 9 Hz

MOBOTIX M73TA Irisity Intrusion Bundle, consisting of: M73 Body with RJ45 connection box (Mx-M73A-RJ45), 24° Thermal Module ECO 320 - T150 (Mx-O-M7SA-320T150, 50 mk, max 9 fps (9 Hz)), 30° 4K IR-Cut Day & Night Sensor Module TELE (Mx-O-M7SA-8DN150), IR Light Module for Tele Lens (Mx-F-IRA-T) and pre-installed Irisity Iris Core Intrusion App (Mx-APP-IRIS-C-INT)

4047438049436 29,6 cm
90251900 26,8 cm
2.800 g 18,0 cm
14,3 l

p71B ECO Thermal Camera

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-p71TB-320T080	4047438050456	19,6 cm
p71TB Thermal ECO 320 - T080, 56 x 42°, 9 Hz	90251900	18,0 cm
p71TB Indoor camera with Thermal ECO 320-T080. CIF 320x240 • 9 fps (9 Hz) • 56 x 42°; 3mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C - Built-in speaker and microphone • USB-C • 8GB memory card included	1.175 g	14,8 cm 5,2 l

ONE Thermal Modules

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-ONE-SMA-640R050** **MOBOTIX S ONE Thermal Module 640-R050 95° x 76°** Thermal module for MOBOTIX ONE S1x • VGA (640 x 480 Pixel) • with Thermal Radiometry and Thermal Distance Compensation • 95° x 76° • 30 mK • max. 30 frames/s (30 Hz)	4047438051781 90275000 320 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-ONE-SMA-640R100** **MOBOTIX S ONE Thermal Module 640-R100 50° x 40°** Thermal module for MOBOTIX ONE S1x • VGA (640 x 480 Pixel) • with Thermal Radiometry and Thermal Distance Compensation • 50° x 40° • 30 mK • max. 30 frames/s (30 Hz)	4047438051774 90275000 320 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

Sensor Module Thermal for MOBOTIX 7

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-O-M73TB-336R100** **Thermal module 336-R100 for M73 (B model) 45° x 35°, 9 Hz** CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate • 50 mk, max 9 fps (9 Hz)	4047438040198 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	**Mx-O-M73TB-336R150** **Thermal module 336-R150 for M73 (B model) 25° x 19°, 9 Hz** CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate • 50 mk, max 9 fps (9 Hz)	4047438040204 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	**Mx-O-M73TB-640R150** **Thermal module 640-R150 for M73 (B model) 32° x 26°, 9 Hz** VGA (640 x 480 Pixel) • with Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate • 50 mk, max 9 fps (9 Hz)	4047438040259 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	**Mx-O-M73TB-640T050** **Thermal module 640-T050 for M73 (B model) 90° x 69°, 9 Hz** VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate • 50 mk, max 9 fps (9 Hz)	4047438040150 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	**Mx-O-M73TB-640T150** **Thermal module 640-T150 for M73 (B model) 32° x 26°, 9 Hz** VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate • 50 mk, max 9 fps (9 Hz)	4047438040181 90275000 450 g	19,6 cm 18,0 cm 14,8 cm 5,2 l



Mx-O-M73TC-320R100

Thermal module 320-R100 with front plate for M73 (C model) 50° x 40°

CIF (320 x 240 Pixel) • with Thermal Radiometry • 50° x 40° • incl. M73 replacement front plate

4047438050524 19,6 cm
90275000 18,0 cm
405 g 14,8 cm
5,2 l



Mx-O-M73TC-320T280

Thermal module 320-T280 with front plate for M73 (C model) 12° x 10°

CIF (320 x 240 Pixel) • w/o Thermal Radiometry • 12° x 10° • incl. M73 replacement front plate

4047438050531 19,6 cm
90275000 18,0 cm
440 g 14,8 cm
5,2 l



Mx-O-M73TC-640R050

Thermal module 640-R050 for M73 (C model) 95° x 76°, 30 Hz

VGA (640 x 480 Pixel) • with Thermal Radiometry and Thermal Distance Compensation • 95° x 76° • incl. M73 frontplate • 30 mK • max. 30 frames/s (30 Hz)

4047438050548 19,6 cm
90275000 18,0 cm
410 g 14,8 cm
5,2 l



Mx-O-M73TC-640R100

Thermal module 640-R100 with front plate for M73 (C model) 50° x 40°

VGA (640 x 480 Pixel) • with Thermal Radiometry • 50° x 40° • incl. M73 replacement front plate

4047438050555 19,6 cm
90275000 18,0 cm
450 g 14,8 cm
5,2 l



Mx-O-M73TC-640T280

Thermal module 640-T280 with front plate for M73 (C model) 18° x 14°

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 18° x 14° • incl. M73 replacement front plate

4047438050562 19,6 cm
90275000 18,0 cm
460 g 14,8 cm
5,2 l



Mx-O-M7SA-320T040

Thermal Module ECO 320 - T040 (105° x 75°), 9 Hz

MOBOTIX 7 Thermal Module 320-T040 for M73/S74, CIF 320x240 • 9 fps (9 Hz) • 105° x 75°; 5,23mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040648 9,8 cm
90275000 7,5 cm
106 g 9,0 cm
0,7 l



Mx-O-M7SA-320T080

Thermal Module ECO 320 - T080 (56° x 42°), 9 hz

MOBOTIX 7 Thermal Module 320-T080 for M73/S74, CIF 320x240 • 9 fps (9 Hz) • 56° x 42°; 3,00mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040655	9,8 cm
90275000	7,5 cm
106 g	9,0 cm
	0,7 l



Mx-O-M7SA-320T150

Thermal module ECO 320 - T150 (24° x 18°), 9 Hz

MOBOTIX 7 Thermal Module 320-T150 for M73/S74, CIF 320x240 • 9 fps (9 Hz) • 24° x 18°; 1.32 mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438045193	9,8 cm
90275000	7,5 cm
106 g	9,0 cm
	0,7 l

Video Systems MOVE

BeyondHumanVision

MOBOTIX

MOBOTIX MOVE Speed Dome Cameras

MOBOTIX MOVE Speed Dome Cameras

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-SD1A-540-IR-VA** **MOBOTIX MOVE SpeedDome SD-540-IR-VA (DNN Analytics)** MOBOTIX MOVE SpeedDome Network Camera SD-540-IR-VA •Weatherproof motor-driven ONVIF S / G /T/M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 40x optical zoom • Image sensor: 5MP SONY STARVIS II IMX675 (2608 x 1964), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.95: 4.3 to 170 mm, viewing angle HxV: 62,6 ° - 1,9 ° x 48,8 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles)•2D & 3D Motion Compensated Noise Reduction (MCTF) •IR LEDs (working distance up to 300m)• IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 5MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 59.05 W / 87.12 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	4047438045049 85258900 5.950 g	40,2 cm 25,0 cm 37,0 cm 37,2 l
	**Mx-SD1A-831-LIR-VA** **MOBOTIX MOVE SpeedDome SD-831-LIR-VA LIDAR (DNN Analytics)** MOBOTIX MOVE SpeedDome Network Camera SD-831-LIR-VA • Weatherproof motor-driven ONVIF S / G /T/M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 31x optical zoom • Precise LiDAR Focusing System • Image sensor: 8MP SONY STARVIS II IMX678 (3856 x 2180) 4K, 1/1.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.35-F4.6: 6.9 to 214.6 mm, viewing angle HxV: 61.8 ° - 2.2 ° x 35.9 ° -1.3 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IR LEDs (working distance up to 300 m) • IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 8MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	4047438045056 85258900 7.640 g	33,0 cm 33,0 cm 54,0 cm 58,8 l
	**Mx-SD2A-230-LL-FM-VA** **MOBOTIX MOVE SpeedDome SD-230-LL-FM-VA Low Light Flush Mount (DNN Analytics)** MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-FM-VA •Weatherproof motor-driven ONVIF S / G /T/M Indoor Dome PTZ camera for ceiling flush mount • 10 Integrated Video Analytic Function incl. DNN Face- and Licen10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3 ° - 2.3 ° x 34.9 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) •2D & 3D Motion Compensated Noise Reduction (MCTF) • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE+ IEEE802.3at, max. 17.71 W, AC24V max. 17.10 W / 32.76 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h	4047438045032 85258900 3.970 g	31,0 cm 31,0 cm 38,0 cm 36,5 l



Mx-SD2A-230-LL-VA

MOBOTIX MOVE SpeedDome SD-230-LL-VA Low Light (DNN Analytics)

MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-VA •Weatherproof motor-driven ONVIF S / G /T/M Dome PTZ camera •10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3 ° - 2.3 ° x 34.9 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Human, Vehicles) •2D & 3D Motion Compensated Noise Reduction (MCTF) •IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE+ IEEE802.3at, max. 25.5 W, AC24V max. 29.04 W / 53.24 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h

4047438045025	42,5 cm
85258900	26,2 cm
5.150 g	35,0 cm
	39,0 l

MOBOTIX MOVE Vandal Dome Cameras

MOBOTIX MOVE Vandal Dome Cameras

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-VD2A-5-IR-VA**	4047438040457	17,5 cm
	MOBOTIX MOVE VandalDome VD2-5-IR-VA (Video Analytics)	85258900	17,5 cm
	MOBOTIX MOVE Vandal Dome Network Camera VD2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5 °, V: 70.3 °-22.7 °) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 5MP H.264, H.265 30 fps • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	1.210 g	17,0 cm 5,2 l

MOBOTIX MOVE Bullet Cameras

MOBOTIX MOVE Bullet Cameras

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-BC2A-2-IR** **MOBOTIX MOVE BulletCamera BC2-2-IR** MOBOTIX MOVE Bullet Network Camera BC2-2-IR • Image Resolution: 2MP (1920x1080), 1/2.7" Progressive CMOS • Weatherproof ONVIF S/G/T bullet camera with built-in IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 96.67° - 34.13° - V: 52.21° - 19.24°) • IP66 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 95% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af • MTBF: 95.000h • Warranty: 5 years	4047438038966 85258900 580 g	29,6 cm 20,0 cm 17,5 cm 10,4 l
	**Mx-VB1A-8-IR-VA** **MOBOTIX MOVE VandalBullet VB-8-IR-VA (DNN Analytics)** MOBOTIX MOVE Vandal Bullet Network Camera VB-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5 °, V: 61.2 °-27.0 °) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max 12.95 W, DC12V, 15.59 W, AC24V, max 13.31 W, max 25.08 VA • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	4047438040358 85258900 1.793 g	28,5 cm 19,6 cm 17,4 cm 9,7 l
	**Mx-VB2A-5-IR-VA** **MOBOTIX MOVE VandalBullet VB2-5-IR-VA (Video Analytics)** MOBOTIX MOVE Vandal Bullet Network Camera VB2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5 °, V: 70.3 °-22.7 °) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C (heater on), humidity 10 to 90% non-condensing• Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W• Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	4047438040464 85258900 1.710 g	29,6 cm 20,0 cm 17,5 cm 10,4 l

MOBOTIX MOVE Hemispheric Vandal Dome

MOBOTIX MOVE Hemispheric Vandal Dome Camera

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-VH1A-12-IR-VA**	4047438038317	17,3 cm
	MOBOTIX MOVE 12MP Vandal Hemispheric	85258900	17,3 cm
	MOBOTIX MOVE Vandal Hemispheric Network Camera Mx-VH1A-12-IR-VA • Image sensor: 12MP (4072 x 3046), 1/1.7" Progressive CMOS • Indoor • ONVIF S/G/T/M • Hemispheric camera with built-in IR LED illumination (up to 10 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • focal length 1.65 mm • IK10 • Ambient temperature -10 to 55°C (14° to 131°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Max. Frame rate: 12MP@20 fps (Backend dewarping) 8.9MP@27 fps (Edge dewarping) • Power supply: PoE IEEE 802.3af • Warranty: 5 years • MTBF: 95,000h	640 g	10,7 cm 3,2 l

MOBOTIX MOVE Fixed Domes

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-MD1A-5-IR**	4047438042475	16,5 cm
	MOBOTIX MOVE Indoor MicroDome Mx-MD-5-IR	85258900	16,5 cm
	MOBOTIX MOVE Indoor MicroDome Network Camera Mx-MD-5-IR • Max. Image Resolution: 5M (2720x1976), 1/2.7" Progressive CMOS • ONVIF S/G/T dome camera with integrated IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F2.0: 2.8 mm), viewing angle H: 108.3°, V: - 76.5 °) • 3-axis lens adjustment • Indoor, IK8 • Ambient temperature -30 to 55°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max. 5.09 W • MTBF: 95.000h • Warranty: 5 years	450 g	13,5 cm 3,7 l

MOBOTIX MOVE Multi Sensor Cameras

MOBOTIX MOVE Multi Sensor Cameras

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-VM1A-20-IR-VA** **MOBOTIX MOVE Vandal Multisensor VM-20-IR-VA** MOBOTIX MOVE Vandal Multisensor Network Camera Mx-VM1A-20-IR-VA • Image sensor: 4x5MP (2608x1964), 1/2.8" Progressive CMOS IMX 675 SONY STARVIS II • Up to 3x optical zoom • ONVIF S/G/T/M •10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition• Auto Object Tracking • Multisensor camera with built-in IR LED illumination (up to 30 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter)•FIPS140-2 level 2-compliant IT-Secure TPM chipset • NEMA-4x compliant •M.2 SATA 3 SSD support •2D & 3D Motion Compensated Noise Reduction (MCTF)• Motor-controlled Zoom lens (F1.6 x 4: 2,8mm to 8 mm, viewing angle HxV: 111,5° - 53,7° x 79° - 40,2°) with autofocus and P-Iris with automatic adaptation to changing light situations • IK10 / IP66 • Ambient temperature -40 to 60°C (22° to 122°F), humidity 10 to 90% •Video codecs: H.264, H.265, MJPEG (up to 9 Video-Streams simultaneously - 4x2 per sensor module + 1 quadview stream) • Wide Dynamic Range (130 dB)• Max. Frame rate: 5MP@30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps• Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA •Opt. Integrated Microphone & Loudspeaker (bi-directional communication) •Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 95000h • Warranty: 5 years	4047438045063 85258900 3.740 g	32,3 cm 30,5 cm 15,6 cm 15,4 l
	**Mx-VMSD1A-2021-VA** **MOBOTIX MOVE Vandal Multisensor PTZ Combo VMSD -2021-VA** MOBOTIX MOVE Vandal Multisensor PTZ Combo Network Camera Mx-VMSD1A-2021-VA • Image sensor Multi: 4x5MP (2560x1920), 1/2.7" Progressive CMOS • Image sensor PTZ: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M • Pre-Installed AI-VMD DNN based Video-Motion Detection • Auto Object Tracking by PTZ-Unit • Automatic changeover from color to B / W image (mechanical IR cut filter) • FIPS140-2 level 3 certified IT-Security TPM chipset • Intelligent Encoding, "Smart Low Bitrate Control" • Multisensor: 4x Fixed Focal Lens 3.2mm (viewing angle HxV: 97 °x 71 ° • PTZ: 21x Motorized Zoom /Focus Lens 4.0 – 84.6mm with Autofokus & P-Iris (Viewing angle HxV: 3.7 ° - 77 ° x 2.2 ° -44 °) • IK10 / IP66/ IP67 •NNDAA conformant • NEMA-4x conformant • Ambient temperature -40 to 55°C (-4° to 131°F), humidity 10 to 100% • Video codecs: H.264, H.265, MJPEG • Wide Dynamic Range up to 108 dB for Multisensor / 144 dB for PTZ-Unit • 1 Micro SD/SDHC/SDXC Card support up to 512 GB on each Multisensor/ PTZ • Max. Frame rate Multisensor: 5MP@15 fps H.264, MJPEG: 1080p @ 15 fps, max. Frame rate PTZ: 2MP@60 fps H.264, MJPEG: 1080p @ 60 fps • Power supply: PoE++ IEEE802.3bt, DC 54 V max. 35.6 W • Audio Line In/Out • MTBF: 95000h	4047438047524 85258900 4.950 g	34,0 cm 28,7 cm 34,5 cm 33,7 l

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-VT1A-2-IR** **MOBOTIX MOVE Vandal Turret Mx-VT-2-IR** MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-2-IR • Max. Image Resolution: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F1.6: 2.8 mm), viewing angle H: 105°, V: 56 °) • 3-axis adjustment (Pan/Tilt/Rotation)• IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone• True WDR (120 dB) • Max. Frame rate: 2MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	4047438048200 85258900 950 g	16,5 cm 16,5 cm 15,4 cm 4,2 l
	**Mx-VT1A-5-IR** **MOBOTIX MOVE Vandal Turret Mx-VT-5-IR** MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-5-IR • Max. Image Resolution: 5MP (2592x1944), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F1.6: 2.8 mm), viewing angle H: 97°, V: 70.5 °) • 3-axis adjustment (Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	4047438048255 85258900 950 g	16,5 cm 16,5 cm 15,4 cm 4,2 l
	**Mx-VT1A-503-IR** **MOBOTIX MOVE Vandal Turret Mx-VT-503-IR** MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-503-IR • Max. Image Resolution: 5MP (2592x1944), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Motor-controlled varifocal lens (F1.4-2.8: 2.7 to 13.5 mm, viewing angle H: 103 °-31 °, V: 76 °-23.5 °) • 3-axis adjustment(Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	4047438048279 85258900 980 g	16,5 cm 16,5 cm 15,4 cm 4,2 l

Optics

BeyondHumanVision

MOBOTIX

ONE Sensor Modules 4K

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-ONE-SMA-8DN016-V	4047438052733	9,8 cm
MOBOTIX ONE 4k Hemispheric Day & Night Sensor module (Vandal) with Cover	85299096	7,5 cm
MOBOTIX ONE Dual sensor module (Vandal) with hemispheric lens with cover and IR-cut filter for day and night use, aperture: f/1.8, max. resolution: 2160 x 2160, IP66, IK10, color: white	120 g	9,0 cm
		0,7 l
		
Mx-ONE-SMA-8DN040	4047438050616	9,8 cm
MOBOTIX ONE 120° 4K Day & Night Sensor Module WIDE	85299096	7,5 cm
MOBOTIX ONE dual sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120° x 60°, max. resolution: 4K UHD (3840x2160), IP66, IK10, color: white	160 g	9,0 cm
		0,7 l
		
Mx-ONE-SMA-8DN050	4047438050623	9,8 cm
MOBOTIX ONE 95° 4K Day & Night Sensor Module WIDE	85299096	7,5 cm
MOBOTIX ONE Dual sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x 50°, max. resolution: 4K UHD (3840x2160), IP66, IK10, color: white	160 g	9,0 cm
		0,7 l
		
Mx-ONE-SMA-8DN080	4047438050661	9,8 cm
MOBOTIX ONE 60° 4K Day & Night Sensor Module WIDE	85299096	7,5 cm
MOBOTIX ONE Dual Sensor Module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60° x 33°, max. resolution: 4K UHD (3840x2160), IP66, IK10, color: white	160 g	9,0 cm
		0,7 l
		
Mx-ONE-SMA-8DN100	4047438050630	9,8 cm
MOBOTIX ONE 45° 4K Day & Night Sensor Module STANDARD	85299096	7,5 cm
MOBOTIX ONE Dual Sensor Module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45° x 25°, max. resolution: 4K UHD (3840x2160), IP66, IK10, color: white	160 g	9,0 cm
		0,7 l



Mx-ONE-SMA-8DN150

MOBOTIX ONE 30° 4K Day & Night Sensor Module TELE

MOBOTIX ONE Dual Sensor Module with premium telephoto lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30° x 17°, max. resolution: 4K UHD (3840x2160), IP66, IK10, color: white

4047438050647	9,8 cm
85299096	7,5 cm
160 g	9,0 cm
	0,7 l



Mx-ONE-SMA-8DN280

MOBOTIX ONE 15° 4K Day & Night Sensor Module TELE

MOBOTIX ONE Dual Sensor Module with premium telephoto lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15° x 8.5°, max. resolution: 4K UHD (3840x2160), IP66, IK10, color: white

4047438050654	9,8 cm
85299096	7,5 cm
160 g	9,0 cm
	0,7 l

Sensor Modules 4K for MOBOTIX 7

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-O-M7SA-12DN016** **12MP Hemispheric Day & Night Sensor Module** 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, white	4047438040631 85299096 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-12DN016-b** **12MP Hemispheric Day & Night Sensor Module black** 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, black	4047438041379 85299096 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-8D500** **8° 4K Day Sensor mod. TELE** M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438047265 85299096 210 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-8DN040-b** **120° 4K IR Cut Day & Night Sensor Module WIDE black** M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041386 85299096 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-8DN050-b** **95° 4K IR Cut Day & Night Sensor Module WIDE black** M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041393 85299096 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



Mx-O-M7SA-8DN080-b

60° 4K IR Cut Day & Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041409	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8DN100-b

45° 4K IR Cut Day & Night Sensor Module STANDARD black

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041416	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8DN150-b

30° 4K IR Cut Day & Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041423	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8DN280-b

15° 4K IR Cut Day & Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041430	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8L040

120° 4K LPF Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438040310	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8L500

8° 4K LPF Sensor mod. TELE

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438044080	9,8 cm
85299096	7,5 cm
210 g	9,0 cm
	0,7 l



Mx-O-M7SA-8N040-b

120° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041447 | 85299096 | 140 g | 9,8 cm | 7,5 cm | 9,0 cm | 0,7 l



Mx-O-M7SA-8N050-b

95° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041454 | 85299096 | 140 g | 9,8 cm | 7,5 cm | 9,0 cm | 0,7 l



Mx-O-M7SA-8N080-b

60° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041461 | 85299096 | 140 g | 9,8 cm | 7,5 cm | 9,0 cm | 0,7 l



Mx-O-M7SA-8N100-b

45° 4K Night Sensor Module STANDARD black

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041478 | 85299096 | 140 g | 9,8 cm | 7,5 cm | 9,0 cm | 0,7 l



Mx-O-M7SA-8N150-b

30° 4K Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041485 | 85299096 | 140 g | 9,8 cm | 7,5 cm | 9,0 cm | 0,7 l



Mx-O-M7SA-8N280-b

15° 4K Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041492 | 85299096 | 140 g | 9,8 cm | 7,5 cm | 9,0 cm | 0,7 l



Mx-O-M7SA-8N500

8° 4K Night Sensor mod. TELE

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438047272
85299096
210 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8DN040

120° 4K IR Cut Day & Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034968
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8DN050

95° 4K IR Cut Day & Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034814
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8DN080

60° 4K IR Cut Day & Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035941
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8DN100

45° 4K IR Cut Day & Night Sensor Module STANDARD

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034821
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8DN150

30° 4K IR Cut Day & Night Sensor Module TELE

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035958
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8DN280

15° 4K IR Cut Day & Night Sensor Module TELE

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034838	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8D040

120° 4K Day Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034944	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8D050

95° 4K Day Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034845	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8D080

60° 4K Day Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035989	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8D100

45° 4K Day Sensor Module STANDARD

M73/S74 sensor module with premium standard-angle lens for day, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034852	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8D150

30° 4K Day Sensor Module TELE

M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035996	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8D280

15° 4K Day Sensor Module TELE

M73/S74 sensor module with premium tele lens for day, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034869
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8N040

120° 4K Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034951
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8N050

95° 4K Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034876
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8N080

60° 4K Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035965
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8N100

45° 4K Night Sensor Module STANDARD

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034883
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8N150

30° 4K Night Sensor Module TELE

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035972
85299096
140 g
9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-O-M7SA-8N280

15° 4K Night Sensor Module TELE

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034890		9,8 cm
85299096		7,5 cm
	140 g	9,0 cm
		0,7 l



Mx-O-M7SA-8L150

30° 4K LPF Sensor Module TELE

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037730		9,8 cm
85299096		7,5 cm
	140 g	9,0 cm
		0,7 l



Mx-O-M7SA-8L280

15° 4K LPF Sensor Module TELE

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037723		9,8 cm
85299096		7,5 cm
	140 g	9,0 cm
		0,7 l

Sensor Modules 4MP Low Light for MOBOTIX

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-O-M7SA-4D045-f1.0** **109° f/1,0 4MP Day Sensor module** M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 109° x 55°, max. resolution: 4MP (2688x1512), IP66, white	4047438044387 85299096 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-4D050-f1.0** **94° f/1,0 4MP Day Sensor module** M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 94°x49,5°, max. resolution: 4MP (2688x1512), IP66, white	4047438044370 85299096 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-4D080-f1.0** **57° f/1,0 4MP Day Sensor module** M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 57°x32°, max. resolution: 4MP (2688x1512), IP66, white	4047438044363 85299096 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-4D115-f1.0** **37° f/1,0 4MP Day Sensor module** M73/S74 sensor module with premium normal lens for day use, aperture: f/1.0, max. image angle (HxV): 37,5°x22°, max. resolution: 4MP (2688x1512), IP66, white	4047438044356 85299096 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-O-M7SA-4DN040** **120° 4MP IR Cut Day & Night Ultra LowLight Sensor Module WIDE** M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120° x 60°, max. resolution: 4MP (2688x1512), IP66, white	4047438037167 85299096 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



Mx-O-M7SA-4DN050

95° 4MP IR Cut Day & Night Ultra LowLight Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP (2688x1512), IP66, white

4047438037174	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-4DN080

60° 4MP IR Cut Day & Night Ultra LowLight Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP (2688x1512), IP66, white

4047438037181	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-4DN100

45° 4MP IR Cut Day & Night Ultra LowLight Sensor Module STANDARD

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP (2688x1512), IP66, white

4047438037198	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-4DN150

30° 4MP IR Cut Day & Night Ultra LowLight Sensor Module TELE

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP (2688x1512), IP66, white

4047438037204	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-4DN280

15° 4MP IR Cut Day & Night Low Light Sensor Module TELE

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP (2688x1512), IP66, white

4047438037211	9,8 cm
85299096	7,5 cm
140 g	9,0 cm
	0,7 l

Sensor Modules 6MP For S16A/S16B And

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-O-SMA-S-6D036	4047438029117	9,8 cm
Sensor Module 6MP, B036 (Day), White	85299096	7,5 cm
Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	9,0 cm
		0,7 l
		
Mx-O-SMA-S-6D079	4047438029148	9,8 cm
Sensor Module 6MP, B079 (Day), White	85299096	7,5 cm
Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	9,0 cm
		0,7 l
		
Mx-O-SMA-S-6D237	4047438029162	9,8 cm
Sensor Module 6MP, B237 (Day), White	85299096	7,5 cm
Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	9,0 cm
		0,7 l
		
Mx-O-SMA-S-6D500	4047438029179	9,8 cm
Sensor Module 6MP, B500 (Day), White	85299096	7,5 cm
Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	9,0 cm
		0,7 l
		
Mx-O-SMA-S-6N036	4047438029193	9,8 cm
Sensor Module 6MP, B036 (Night), White	85299096	7,5 cm
Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	170 g	9,0 cm
		0,7 l



Mx-O-SMA-S-6N079

Sensor Module 6MP, B079 (Night), White

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029223 | 9,8 cm
85299096 | 7,5 cm
144 g | 9,0 cm
0,7 l



Mx-O-SMA-S-6N237

Sensor Module 6MP, B237 (Night), White

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029247 | 9,8 cm
85299096 | 7,5 cm
144 g | 9,0 cm
0,7 l



Mx-O-SMA-S-6N500

Sensor Module 6MP, B500 (Night), White

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029254 | 9,8 cm
85299096 | 7,5 cm
144 g | 9,0 cm
0,7 l



Mx-O-SMA-S-6L237

Sensor Module 6MP, B237 (Night LPF), White

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029322 | 9,8 cm
85299096 | 7,5 cm
144 g | 9,0 cm
0,7 l






Mx-O-SMA-S-6L500


Sensor Module 6MP, B500 (Night LPF), White

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029339 | 9,8 cm
85299096 | 7,5 cm
144 g | 9,0 cm
0,7 l

BlockFlexMounts 4K for ONE S1x

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-ONE-BFA-8DN040** **MOBOTIX ONE 120° 4K Day & Night BlockFlexMount WIDE** MOBOTIX ONE S1 Dual BlockFlexMount with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120° x 60°, max. resolution: 4K UHD (3840x2160), black aluminum housing	4047438051699 85299096 125 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-ONE-BFA-8DN050** **MOBOTIX ONE 95° 4K Day & Night BlockFlexMount WIDE** MOBOTIX ONE S1 Dual BlockFlexMount with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95° x 50°, max. resolution: 4K UHD (3840x2160), black aluminum housing	4047438051705 85299096 125 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-ONE-BFA-8DN080** **MOBOTIX ONE 60° 4K Day & Night BlockFlexMount WIDE** MOBOTIX ONE S1 Dual BlockFlexMount with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60° x 33°, max. resolution: 4K UHD (3840x2160), black aluminum housing	4047438051804 85299096 125 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-ONE-BFA-8DN100** **MOBOTIX ONE 45° 4K Day & Night BlockFlexMount STANDARD** MOBOTIX ONE S1 Dual BlockFlexMount with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45° x 25°, max. resolution: 4K UHD (3840x2160), black aluminum housing	4047438051712 85299096 125 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-ONE-BFA-8DN150** **MOBOTIX ONE 30° 4K Day & Night BlockFlexMount TELE** MOBOTIX ONE S1 Dual BlockFlexMount with premium telephoto lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30° x 17°, max. resolution: 4K UHD (3840x2160), black aluminum housing	4047438051729 85299096 125 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



Mx-ONE-BFA-8DN280

MOBOTIX ONE 15° 4K Day & Night BlockFlexMount TELE

MOBOTIX ONE S1 Dual BlockFlexMount with premium telephoto lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15° x 8.5°, max. resolution: 4K UHD (3840x2160), black aluminum housing

4047438051736	9,8 cm
85299096	7,5 cm
125 g	9,0 cm
	0,7 l

Camera Accessories

BeyondHumanVision

MOBOTIX

ONE S1x Sensor Cables

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-ONE-CBL-S01-AN	4047438051408	14,0 cm
Sensor cable 1 m for ONE S1x straight-angled	85444210	3,5 cm
Sensor cable, straight-angled, length 1 m/3.3 ft • For connecting sensor modules incl. BlockFlexMount to the S ONE Dual camera housing (Mx-ONE-S1A-D)	70 g	15,0 cm
		0,7 l
		
Mx-ONE-CBL-S02-AN	4047438051415	14,0 cm
Sensor cable 2m for ONE S1x straight-angled	85444210	3,5 cm
Sensor cable, straight-angled, length 2 m/6.6 ft • For connecting sensor modules including BlockFlexMount to the S ONE Dual camera housing (Mx-ONE-S1A-D)	100 g	15,0 cm
		0,7 l
		
Mx-ONE-CBL-S05-AN	4047438052702	10,0 cm
Sensor cable 5 m for ONE S1x straight-angled	85444210	7,5 cm
Sensor cable, straight-angled, length 5 m/16.4 ft • For connecting sensor modules incl. BlockFlexMount to the S ONE Dual camera housing (Mx-ONE-S1A-D)	220 g	9,0 cm
		0,7 l

Camera Mounts ONE M


Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-M-CM-M1	4047438048415	15,0 cm
Ceiling Mount for M1 ONE Cameras	90079100	9,5 cm
Suitable for: M1 ONE Cameras • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw , washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically • Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)	160 g	9,0 cm 1,3 l

Camera Mounts ONE c


	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-ONE-M-CM-c1** **Corner Mounting Set for ONE c1x** Suitable for ONE c1x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g, ONE c1x with hemispheric lens) to capture an entire room • Color: White	4047438052672 90079100 448 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	**Mx-ONE-M-OWL-c1** **On-Wall Mounting Set (Large) for ONE c1x** Suitable for ONE c1x • Consists of on-wall mount (large) and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g, two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White	4047438052689 90079100 514 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

Other ONE Accessories

Other ONE Accessories

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-ONE-A-IO-c1**	4047438052726	12,0 cm
	c1A IO Connector	85299096	8,0 cm
	c1A IO connector for connecting input/output, an external speaker, and 12–24 VDC	4 g	1,0 cm
			0,1 l

Camera Mounts (M7)

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-M-CM-M73** **Ceiling Mount for M73 models** Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	4047438039819 90079100 631 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	**Mx-M-IC-DQ** **In-Ceiling Set for MOBOTIX 7 Single Lens Models** In-Ceiling Set for MOBOTIX 7 Single Lens Models	4047438040761 90079100 665 g	39,5 cm 29,6 cm 9,0 cm 10,5 l
	**Mx-M-OW-DQ** **On-Wall Set for MOBOTIX 7 Single Lens Models** On-Wall Set for MOBOTIX 7 Single Lens Models	4047438040662 90079100 410 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	**Mx-M-OW-DQ-10DEG** **On-Wall Set 10° for MOBOTIX 7 Single Lens Models** On-Wall Set 10° inclined for MOBOTIX 7 Single Lens Models	4047438043373 90079100 500 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	**Mx-M-OW-M73** **On-Wall Mount for M73 models** Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	4047438039802 90079100 502 g	19,6 cm 18,0 cm 14,8 cm 5,2 l



Mx-M-PM-M73

Pole mount for M73 models

Suitable for: M73 Cameras • 2 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438035064	20,0 cm
90079100	18,2 cm
1.247 g	9,0 cm
	3,3 l




Mx-M-WM-DQ

Wall Mount for MOBOTIX 7 Single Lens Models

Wall Mount for MOBOTIX 7 Single Lens Models

4047438040778	29,6 cm
90079100	19,6 cm
835 g	18,0 cm
	10,4 l



Mx-M-WPM-DQ

Wall & Pole/Corner Mount Set For D7x/Q7x

Suitable for: D7x and Q7x • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (Mx-M-WM-DQ) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438041348	41,0 cm
90079100	31,0 cm
3.380 g	20,0 cm
	25,4 l

Mounts For S74

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-M-DLMA	4047438036887	19,6 cm
DualMount S74/S ONE Dual	90079100	15,0 cm
Detection of one to two areas with two sensor modules • Suitable for all screw-mountable sensor modules of the S74 and S ONE Dual • Concealed cable routing, weatherproof from -30 to 60 °C • Suitable for ceiling mounting, lens tilt 25° • Color: white	450 g	9,0 cm
		2,6 l
		
Mx-M-DLMA-b	4047438041553	19,6 cm
DualMount S7x, black	90079100	15,0 cm
For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	450 g	9,0 cm
		2,6 l
		
Mx-M-PTMA	4047438036894	19,6 cm
PTMount S74/S ONE Dual	90079100	18,0 cm
Manually adjustable dome mount for one sensor module (not included) • Features three axes, allowing it to compensate for lateral tilt error during wall mounting and realign the image horizon horizontally • Suitable for all screw-mountable sensor modules for the S74 and S ONE Dual • Concealed cable routing, weatherproof from -30 to 60 °C • Suitable for ceiling or wall mounting • Color: white	620 g	14,8 cm
		5,2 l
		
Mx-M-PTMA-b	4047438036900	19,6 cm
PTMount S7x, black	90079100	18,0 cm
Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideway tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	620 g	14,8 cm
		5,2 l
		
Mx-M-PTMA-OW	4047438039826	9,8 cm
Surface-mounted kit for PTMount	90079100	7,5 cm
Surface-mounted mounting kit for PTMount S74/S ONE Dual, white, incl. mounting accessories • Enables connection to a MOBOTIX sensor cable laid above the surface • Color: White	75 g	9,0 cm
		0,7 l



Mx-M-PTMA-OW-b
On-Wall Kit for PTMount S7x, black

On-Wall Kit for PTMount S7x, black incl. Mounting parts

4047438039833
90079100
75 g

9,8 cm
7,5 cm
9,0 cm
0,7 l



Mx-M-SLMA
SingleMount S74/S ONE Dual

Detection of an area with one sensor module • Suitable for all screw-mountable sensor modules of the S74 and S ONE Dual • Concealed cable routing, weatherproof from -30 to 60 °C • Suitable for ceiling mounting, lens tilt 25° • Color: White

4047438036870
90079100
240 g

14,8 cm
9,8 cm
9,0 cm
1,3 l



Mx-M-SLMA-b
SingleMount S7x, black

For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black

4047438037921
90079100
240 g

14,8 cm
9,8 cm
9,0 cm
1,3 l

S7x Sensor Cables

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-A-S7A-CBL01	4047438035583	14,0 cm
MOBOTIX USB-C cable 1m straight-straight	85444210	3,5 cm
Special MOBOTIX USB-C cable (straight-straight) • For connecting the 4IO and GPSA boxes to the following cameras: S ONE Dual, M ONE, S74, D71, Q71, c71, p71, v71 • For connecting optical and thermal sensor modules to the S74 • Length 1 m/3.3 ft	70 g	15,0 cm
		0,7 l
		
Mx-A-S7A-CBL01-AN	4047438035897	14,0 cm
Sensor cable 1m for S7x straight-angled	85444210	3,5 cm
Sensor cable straight-angled, lenght 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts	70 g	15,0 cm
		0,7 l
		
Mx-A-S7A-CBL02	4047438035590	14,0 cm
MOBOTIX USB-C cable 2m straight-straight	85444210	3,5 cm
Special MOBOTIX USB-C cable (straight-straight) • For connecting the 4IO and GPSA boxes to the following cameras: S ONE Dual, M ONE, S74, D71, Q71, c71, p71, v71 • For connecting optical and thermal sensor modules to the S74 • Length 2 m/6.6 ft	90 g	15,0 cm
		0,7 l
		
Mx-A-S7A-CBL02-AN	4047438035903	14,0 cm
Sensor cable 2m for S7x straight-angled	85444210	3,5 cm
Sensor cable straight-angled, lenght 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts	90 g	15,0 cm
		0,7 l
		
Mx-A-S7A-CBL03	4047438035606	14,0 cm
MOBOTIX USB-C cable 3m straight-straight	85444210	3,5 cm
Special MOBOTIX USB-C cable (straight-straight) • For connecting the 4IO and GPSA boxes to the following cameras: S ONE Dual, M ONE, S74, D71, Q71, c71, p71, v71 • For connecting optical and thermal sensor modules to the S74 • Length 3 m/9.9 ft	110 g	15,0 cm
		0,7 l



Mx-A-S7A-CBL03-AN

Sensor cable 3m for S7x straight-angled

Sensor cable straight-angled, lenght 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts

4047438035910 14,0 cm
85444210 3,5 cm
110 g 15,0 cm
0,7 l



Mx-CBL-MUC-AB-1

S74 Cable MiniUSB-C to USB-A 1m

MiniUSB-C straight > USB-A straight • Length 1 m /3,3 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037129 10,0 cm
85444210 7,5 cm
102 g 9,0 cm
0,7 l



Mx-CBL-MUC-AB-5

S74 Cable MiniUSB-C to USB-A 5m

MiniUSB-C straight > USB-A straight • Length 5 m /16,4 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037136 14,8 cm
85444210 9,8 cm
220 g 9,0 cm
1,3 l



Mx-CBL-MUC-AN-AB-1

S7x Cable MiniUSB-C to USB-A angled-straight 1m

MiniUSB-C angled > USB-A straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040556 10,0 cm
85444210 7,5 cm
102 g 9,0 cm
0,7 l



Mx-CBL-MUC-AN-AB-5

S7x Cable MiniUSB-C to USB-A angled-straight 5m

MiniUSB-C angled > USB-A straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040563 14,8 cm
85444210 9,8 cm
220 g 9,0 cm
1,3 l



Mx-CBL-MUC-AN-MU-1

S7x Cable MiniUSB-C to MiniUSB angled-straight 1m

MiniUSB-C angled > MiniUSB straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040532 10,0 cm
85444210 7,5 cm
75 g 9,0 cm
0,7 l



Mx-CBL-MUC-AN-MU-5

S7x Cable MiniUSB-C to MiniUSB angled-straight 5m

MiniUSB-C angled > MiniUSB straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040549	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l



Mx-CBL-MUC-MU-5

S74 Cable MiniUSB-C to MiniUSB 5m

MiniUSB-C straight > MiniUSB straight • Length 5 m/16,4 ft • For S74 • To connect RS232-IO-Box (MX-OPT-RS1-EXT)

4047438037150	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l


Domes & Housings

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
MX-OPT-DK-L11	4047438016469	9,0 cm
Replacement Cover Hemispheric	90079100	7,5 cm
Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	24 g	5,0 cm
		0,3 l

Mounts For S16A/S16B

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
MX-S14-OPT-MK-CW	4047438016384	10,0 cm
Extension Set Sensor Module, 40 mm and 15° wedges	90079100	7,5 cm
Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x and S7x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut	96 g	9,0 cm 0,7 l
		
MX-S14-OPT-MK-EX	4047438016391	9,8 cm
Extension Sensor Module, 40 mm	90079100	7,5 cm
1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions	62 g	9,0 cm 0,7 l

Camera Mounts

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
MX-MT-TUBE **MxTubeMount Ceiling Suspension System** For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4“ according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color: white	4047438027557 90079100 870 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
		
MX-MT-TUBE100 **MxTube, 1 m** Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	4047438027687 90079100 700 g	106,0 cm 4,0 cm 4,0 cm 1,7 l
		
MX-MT-TUBE200 **MxTube, 2 m** Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	4047438027564 90079100 1.390 g	212,5 cm 4,0 cm 4,0 cm 3,4 l
		
MX-D15-OPT-WHMH-Set **Wall & Pole/Corner Mount Set For D1x** Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	4047438018159 90079100 6.280 g	41,0 cm 31,0 cm 39,0 cm 49,6 l
		
MX-OPT-WHMH-Set **Wall & Pole/Corner Mount Set For Q2x/D2x/ExtIO** Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	4047438011396 90079100 3.380 g	41,0 cm 31,0 cm 20,0 cm 25,4 l



MX-WH-Dome

Wall Mount For D1x

Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts

4047438002233 39,5 cm
90079100 29,6 cm
2.020 g 18,0 cm
21,0 l




MX-OPT-WH

Wall Mount For Q2x/D2x/ExtIO

Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts

4047438011372 29,6 cm
90079100 19,6 cm
886 g 18,0 cm
10,4 l



MX-MH-Dome-ESWS

Pole/Corner Mount For MX-WH-Dome

Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002240 34,0 cm
90079100 18,5 cm
3.000 g 11,5 cm
7,2 l




MX-MH-SecureFlex-ESWS

Pole Mount For M1x/M2x

Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002226 20,0 cm
90079100 15,2 cm
1.230 g 8,0 cm
2,4 l



MX-OPT-MH

Pole/Corner Mount For MX-OPT-WH

Suitable for: D7x, Q7x, Q2x, D2x, ExtIO • Mount for fastening the wall mount Mx-M-WM-DQ and MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WHMH-Set) for the Q2x/D2x und ExtIO • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm • Wall mounts (Mx-M-WM-DQ or MX-OPT-WH) are not included in the scope of delivery and must be ordered separately

4047438011389 21,0 cm
90079100 20,0 cm
2.050 g 17,0 cm
7,1 l



MX-OPT-TW-Demo-1

Demo Table/Wall Mount For Q2x/D2x

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055 14,8 cm
90079100 9,8 cm
170 g 9,0 cm
1,3 l

MOBOTIX Cables

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
MX-OPT-CBL-LAN-1-SP	4047438041591	23,5 cm
Ethernet Patch Cable for MOBOTIX M73, 1 m	85444210	15,0 cm
Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	40 g	2,0 cm
		0,7 l
		
MX-OPT-CBL-LAN-10-SP	4047438041560	27,0 cm
Ethernet Patch Cable for MOBOTIX M73, 10 m	85444210	17,0 cm
Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 10 m/32,8 ft □ 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	465 g	4,0 cm
		1,8 l
		
MX-OPT-CBL-LAN-2-SP	4047438041584	23,5 cm
Ethernet Patch Cable for MOBOTIX M73, 2 m	85444210	15,0 cm
Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	65 g	2,0 cm
		0,7 l
		
MX-OPT-CBL-LAN-5-SP	4047438041577	23,5 cm
Ethernet Patch Cable for MOBOTIX M73, 5 m	85444210	15,0 cm
Ethernet Patch Cable for MOBOTIX M73 systems • Lenght 5 m/16,4 ft □ 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	240 g	4,0 cm
		1,4 l
		
MX-FLEX-OPT-CBL-015	4047438019941	9,8 cm
Sensor Module Cable For M15/M16, 0.15 m	85444210	7,5 cm
Lenght: 0.15 m/0,5 ft, to connect one sensor module (inside camera housing), angled plugs, only for M15/M16	16 g	9,0 cm
		0,7 l



MX-OPT-CBL-LAN-1

Ethernet Patch Cable, 1 m

Ethernet Patch Cable for MOBOTIX systems • Lenght 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012300 23,5 cm
85444210 15,0 cm
36 g 2,0 cm
0,7 l



MX-OPT-CBL-LAN-10

Ethernet Patch Cable, 10 m

Ethernet Patch Cable for MOBOTIX systems • Lenght 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012331 27,0 cm
85444210 17,0 cm
462 g 4,0 cm
1,8 l



MX-OPT-CBL-LAN-2

Ethernet Patch Cable, 2 m

Ethernet Patch Cable for MOBOTIX systems • Lenght 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012317 23,5 cm
85444210 15,0 cm
62 g 2,0 cm
0,7 l



MX-OPT-CBL-LAN-5

Ethernet Patch Cable, 5 m

Ethernet Patch Cable for MOBOTIX systems • Lenght 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012324 23,5 cm
85444210 15,0 cm
237 g 4,0 cm
1,4 l





MX-FLEX-IO-CBL-015

IO Connection Cable For M15/M16, 0.15 m

Lenght: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15/M16 (inside camera housing)

4047438019958 13,5 cm
85444210 8,0 cm
10 g 2,0 cm
0,2 l

Other Camera Accessories

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-M-SEC-SCREWS-SET	4047438045209	9,0 cm
Security Screw Set With Allen Bit For M73	90079100	7,5 cm
Triple set of anti-theft screws (1 pcs M6x65, 4 pcs M6x16, 2 pcs M6x13) to securely attach the M73. Incl. Allen bit for power screwdrivers (1/4“ in drive with hole for security pin)	68 g	4,6 cm
		0,3 l
		
Mx-O-M7SA-Blind	4047438035415	9,0 cm
Blind Module M73	90079100	7,5 cm
For M73 • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.	50 g	5,0 cm
		0,3 l
		
MX-OPT-Ring-L10-L12-BL	4047438021241	7,5 cm
Sealing Ring For Hemispheric Sensor Modules, Black	90079100	4,9 cm
Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black	16 g	9,0 cm
		0,3 l
		
MX-OPT-Ring-L10-L12-PW	4047438021234	7,5 cm
Sealing Ring For Hemispheric Sensor Modules, White	90079100	4,9 cm
Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white	16 g	9,0 cm
		0,3 l
		
MX-OPT-SEC-SCREWS-SET	4047438021265	7,5 cm
Security Screw Set With Allen Bit For M1x/M2x	90079100	4,9 cm
Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4“ in drive with hole for security pin)	120 g	9,0 cm
		0,3 l



MX-SM-Blind-PW

Blind Module M1x

For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.

4047438019965	9,0 cm
90079100	7,5 cm
46 g	5,0 cm
	0,3 l

MOBOTIX MOVE Accessories

MOBOTIX MOVE Accessories

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-A-SD-DBC-EC** **Dome-Bubble EverClear (Clear) for MOBOTIX MOVE SD -230/330** Dome Bubble EverClear (Clear) for MOBOTIX MOVE PTZ SD-230/330	4047438041508 90079100 580 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	**MX-A-SD-DBT-EC** **Dome Bubble EverClear (Tinted) for MOBOTIX MOVE SD-230/330** Dome Bubble EverClear (Tinted) for MOBOTIX MOVE PTZ SD-230/330	4047438041515 90079100 580 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	**Mx-A-SD-DCS** **Tinted Dome For MOBOTIX MOVE SD-330** Tinted replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330 • For particularly bright environments	4047438031776 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	**Mx-A-SD-DCT** **Dome (Standard) For MOBOTIX MOVE SD-330** Standard replacement dome suitable for MOBOTIX MOVE SpeedDome SD -330	4047438031783 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	**Mx-A-VB-FGK-EC** **Frontglass Kit EverClear for MOBOTIX MOVE VandalBullet - VA model** Frontglass Kit EverClear for MOBOTIX MOVE VB VandalBullet VB (model > Nov. 21)	4047438041546 90079100 56 g	12,0 cm 11,0 cm 3,0 cm 0,4 l



Mx-A-VB1A-2-IR-ALPR-FGK-EC
MOVE - Frontglas Kit EC VB1A-2-IR-ALPR-FGK-EC

Frontglass Kit EverClear for MOBOTIX MOVE Vandal Bullet 2MP ALPR Mx-VB1A-2-IR-ALPR

4047438048651 9,8 cm
90079100 7,5 cm
56 g 9,0 cm
0,7 l



Mx-A-VB1A-2-IR-D-ALPR-FGK-EC
MOVE - Frontglas Kit EC VB1A-2-IR-D-ALPR-FGK-EC

Frontglass Kit EverClear for MOBOTIX MOVE Vandal Bullet 2MP ALPR Mx-VB1A-2-IR-D-ALPR

4047438050494 9,8 cm
90079100 7,5 cm
56 g 9,0 cm
0,7 l



Mx-A-VD-DBC-EC
Dome Bubble EverClear (Clear) For MOBOTIX MOVE VandalDome
Dome Bubble EverClear (Clear) For MOBOTIX MOVE VD VandalDomes

4047438041522 17,0 cm
90079100 17,0 cm
240 g 13,0 cm
3,8 l



Mx-A-VD-DBT-EC
Dome -Bubble EverClear (Tinted) For MOBOTIX MOVE VandalDome
Dome Bubble EverClear (Tinted) For MOBOTIX MOVE VD VandalDomes

4047438041539 17,0 cm
90079100 17,0 cm
240 g 13,0 cm
3,8 l



Mx-A-VD-DCS
Tinted Dome For MOBOTIX MOVE VandalDome

Tinted replacement dome for particularly bright environments • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031714 16,1 cm
90079100 16,1 cm
210 g 11,5 cm
3,0 l



Mx-A-VD-DCT
Dome (Standard) For MOBOTIX MOVE VandalDome

VD Standard replacement dome • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031721 16,1 cm
90079100 16,1 cm
250 g 11,5 cm
3,0 l




Mx-A-VM-DBC

Dome-Bubble (Clear) for MOBOTIX MOVE Vandal Multisensor

VM Standard replacement dome • Suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047685 26,6 cm
90079100 25,0 cm
530 g 8,5 cm
5,7 l




Mx-A-VM-DBT

Dome-Bubble (Tinted) For MOBOTIX MOVE Vandal Multisensor

Tinted replacement dome for particularly bright environments • Suitable for MOBOTIX MOVE Vandal Multiisensor camera Mx-VM1A-20-IR-VA

4047438047692 26,6 cm
90079100 25,0 cm
530 g 8,5 cm
5,7 l




Mx-M-BC-P

Pole Mount For MOBOTIX MOVE BulletCamera

BC Pole Mount suitable for all MOBOTIX MOVE BulletCameras (except Mx-BC1A-2-IR)

4047438031677 17,3 cm
90079100 17,3 cm
1.000 g 16,7 cm
5,0 l




Mx-M-BC-W

Wall Mount For MOBOTIX MOVE BulletCamera

BC Wall Mount suitable for MOBOTIX MOVE BulletCamera (except Mx-BC1A -2-IR)

4047438031660 17,3 cm
90079100 17,3 cm
840 g 10,7 cm
3,2 l




Mx-M-NVR16-RM

19“ Rack Mounting Brackets for MOVE NVR 16CH

2x metal mounting brackets for imstalling MOBOTIX MOVE NVR 16CH in a 19" rack

4047438037075 14,5 cm
85299096 11,0 cm
447 g 6,0 cm
1,0 l




Mx-M-NVR8-RM

19“ Rack Mounting Brackets for MOVE NVR 8CH

2x metal mounting brackets for installing MOBOTIX MOVE NVR 8CH in an 19" rack

4047438037068 14,5 cm
85299096 11,0 cm
544 g 6,0 cm
1,0 l



Mx-M-SD-C

Corner Mount For MOBOTIX MOVE Speeddomes

SD Corner Mount suitable for MOBOTIX MOVE SpeedDomes • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031769
90079100
2.170 g

21,0 cm
12,5 cm
25,0 cm
6,6 l



Mx-M-SD-GN

MOBOTIX MOVE SD Parapet Mount

MOBOTIX MOVE SD Parapet Mount(Gooseneck) with integrated junction Box for MOBOTIX MOVE SpeedDomes

4047438038997
90079100
14.800 g

90,0 cm
57,0 cm
20,0 cm
102,6 l



Mx-M-SD-P

Pole Mount For MOBOTIX MOVE Speeddomes

SD Pole Mount suitable for MOBOTIX MOVE SpeedDomes • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031752
90079100
1.580 g

31,0 cm
15,5 cm
26,0 cm
12,5 l



Mx-M-SD-PM

MOBOTIX MOVE SpeedDomes Pendant Mount Kit

MOBOTIX MOVE SD Pendant Mount Kit 25 cm icl. Base-Mount for MOBOTIX MOVE SpeedDomes, 25 cm pendant pipe, installation material and safety wires 50cm & 1m. Max. extendable pendant mount lenght 1m by usage of additional pendant mount extension Mx-M-SD-PMEXT

4047438039000
90079100
2.295 g

64,0 cm
22,0 cm
22,0 cm
31,0 l



Mx-M-SD-PMEXT

MOBOTIX MOVE SD PM Extension

MOBOTIX MOVE SD Pendant Mount 25cm extension for Mx-M-SD-PM

4047438039017
90079100
800 g

14,4 cm
14,5 cm
28,0 cm
5,8 l



Mx-M-SD-W

Wall Mount For MOBOTIX MOVE Speeddomes

SD Wall Mount suitable for MOBOTIX MOVE SpeedDomes • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)

4047438031745
90079100
840 g

21,6 cm
12,7 cm
14,8 cm
4,1 l



Mx-M-SD-WL

Wall Mount long for MOBOTIX MOVE Speeddomes and Multisensor VMxx

Wall Mount long for MOBOTIX MOVE Speeddomes SD and Multisensor VMxx • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)

4047438048194 34,8 cm
90079100 10,4 cm
1.500 g 13,8 cm
5,0 l



Mx-M-SD-WM

Wall Mount for MOBOTIX MOVE SpeedDome

MOBOTIX MOVE SD Wall Mount supporting optional Junction Box Mx-M-SD-WMJB, suitable for MOBOTIX MOVE SpeedDomes

4047438038973 33,0 cm
90079100 15,0 cm
1.300 g 23,0 cm
11,4 l




Mx-M-SD-WMJB

MOBOTIX MOVE SD Junction Box

MOBOTIX MOVE SD Wall Mount Junction Box for use with Wall Mount Mx-M-SD-WM

4047438038980 29,0 cm
90079100 32,0 cm
4.800 g 19,0 cm
17,6 l



Mx-M-VD-C

Corner Mount For MOBOTIX MOVE VandalDome

VD Corner Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031738 21,0 cm
90079100 12,5 cm
2.170 g 25,0 cm
6,6 l



Mx-M-VD-IC

In-Ceiling Set For MOBOTIX MOVE VandalDome

VD In-Ceiling Set suitable for all MOBOTIX MOVE VandalDome cameras

4047438031684 23,4 cm
90079100 23,4 cm
800 g 12,8 cm
7,0 l



Mx-M-VD-P

Pole Mount For MOBOTIX MOVE VandalDome

VD-Pole Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031707 31,0 cm
90079100 15,5 cm
1.580 g 26,0 cm
12,5 l




Mx-M-VD-W

Wall Mount For MOBOTIX MOVE VandalDome

VD Wall Mount Set (2-piece) suitable for all MOBOTIX MOVE VandalDome cameras

4047438031691 31,0 cm
90079100 22,0 cm
1.400 g 18,0 cm
12,3 l



Mx-M-VH1A-IC

In-Ceiling Set For MOBOTIX MOVE 12MP Vandal Hemispheric

In-Ceiling Set suitable for MOBOTIX MOVE 12MP Vandal Hemispheric Mx-VH1A-12-IR-VA

4047438050593 41,0 cm
90079100 31,0 cm
2.100 g 20,0 cm
25,4 l



Mx-M-VM-AP

Adapter Mountig Plate for MOBOTIX MOVE Vandal Multisensor

Adaptor Mounting Plate suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047678 36,4 cm
90079100 34,5 cm
1.950 g 12,8 cm
16,1 l



Mx-M-VM-IC

In-Ceiling Set For MOBOTIX MOVE Vandal Multisensor

In-Ceiling Set suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047661 31,6 cm
90079100 34,5 cm
965 g 12,8 cm
14,0 l



Mx-M-VMSD-AP

Adapter Mounting-Plate for MOBOTIX MOVE Vandal Multisensor PTZ Combo

VMSD Adaptor Mounting -Plate suitable for MOBOTIX MOVE Vandal Multisensor PTZ Combo camera Mx-VMSD1A-2021-VA

4047438047517 32,2 cm
90079100 32,2 cm
1.570 g 11,9 cm
12,3 l



Mx-M-VMSD-IC

In-Ceiling Set For MOBOTIX MOVE Vandal Multisensor PTZ Combo

VMSD In-Ceiling Set suitable for MOBOTIX MOVE Vandal Multisensor PTZ Combo camera Mx-VMSD1A-2021-VA

4047438047708 40,9 cm
90079100 38,9 cm
3.500 g 22,6 cm
36,0 l



Mx-M-VT-AP

Adapter Mountig-Plate for MOBOTIX MOVE Vandal Turret Camera

Adapter Mounting Plate suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT-5-IR, VT-203-IR, VT-503-IR

4047438049009
90079100
600 g
16,2 cm
17,2 cm
14,3 cm
4,0 l




Mx-M-VT-JB

Junction Box for MOBOTIX MOVE Vandal Turret Camera

Junction Box suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT -5-IR, VT-203-IR, VT-503-IR

4047438049016
90079100
950 g
17,3 cm
17,1 cm
13,4 cm
4,0 l



Mx-M-VT-WM

Wall Mount for MOBOTIX MOVE Vandal Turret Camera

Wall Mount suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT -5-IR, VT-203-IR, VT-503-IR

4047438048996
90079100
600 g
22,6 cm
10,3 cm
15,5 cm
3,6 l

MOVE Other Accessories

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-A-ETP1A-2601-POW **Plug-type Power-supply for Mx-A-ETP1A-2601-SET** Plug-type power supply for Mx-A-ETP1A-2601-SET • Output: 57V DC +/-3% / 1.2 A • Input: 90-260V AC (47-63Hz) • 68,4 Watt • Operating Temperature: 0-40 °C	4047438042581 85365019 490 g	19,4 cm 14,2 cm 4,0 cm 1,1 l
		
Mx-A-ETP1A-2601-SET **Media converter set Ethernet(PoE+) – Twisted-Pair** Mx-ETP1A-2601-SET Complete set consisting of two two-wire transmitting and receiving units for realising an Ethernet transmission path via Twisted Pair cable. • Transmission of Ethernet and PoE+ power supply via two-wire line according to IEEE1901. • Simple connection of 10/100 Mbps Ethernet end devices • Max. 95 Mbps transmission bandwidth, range up to 600m for data / 300m for PoE depending on the quality of the Twisted-Pair link • 128 bit AES network data encryption • Power supply 2-wire transmitter (Tx) and receiver (Rx) as well as end device via PoE+ network switch or external power supply 56VDC / 1.2A (not included!) • Connected end devices are supplied via PoE switch IEEE802.3af(PoE), IEEE802.3at (PoE+), UPoE up to 60W (requires ext. power supply unit). • Status LEDs (data, power supply, data link, PoE) • Integrated Overvoltage protection (IEC 61000-4-5 4kV(1.2 / 50us), 2kA(8 / 20us)) • Power Supply: TX: T-Linx or DC12V~57V, RX: PoE Switch or DC48V~57V • Operational temperature: -20 to 60 ¡C • Dimensions: 80.4(L) x 61.6(W) x 24(H)mm • Weight: RX/TX: 102g • Warranty: 2 years	4047438041317 85299030 368 g	20,7 cm 12,5 cm 7,0 cm 1,8 l
		
Mx-A-KBD1A-PTZ-JOG **MOBOTIX USB Keyboard with PTZ Joystick & Jog-Shuttle** USB control panel for operating MOBOTIX MxMC 2.6 and higher and MOBOTIX HUB incl. Control of software PTZ and motorized PTZ cameras and pan/tilt devices • Integrated 3-axis joystick • Integrated jog shuttle • 38 control keys with backlight predefined for MxMC functions or freely definable for MOBOTIX HUB • Integrated alarm buzzer • Suitable for operation as HID device on MOBOTIX VMS with Windows and MAC based operating systems via USB2.0 • Suitable for right- and left-handed users • Power supply: USB, max. 350 mA • Operating temperature: 0° - 45 °C (32 °F- 113 °F)	4047438040754 85299030 1.900 g	42,5 cm 27,0 cm 17,5 cm 20,1 l

System Components

BeyondHumanVision

MOBOTIX

Functional Modules for MOBOTIX 7 Cameras

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-F-AUDA** **M73/S74 Audio Module equipped with microphone / loudspeaker** Weatherproof audio module (IP66, -30 to 65 °C, IK07) with integrated microphone and speaker for connection to the MOBOTIX M73 camera, no camera removal required • In connection with the audio cable Mx-A-S7A-AUCBL05-AN and the IO plug-in board Mx-F-S7A-INT01, the audio module can also be operated at the S74 (compatible with S74 module mounts)	4047438034937 85299030 150 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-F-IRA-S** **M73/S74 IR Light Module for Standard Lens (45° - 60°)** Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 45°-60° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses: up to 70 m	4047438034913 85299030 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-F-IRA-T** **M73/S74 IR Light Module for Tele Lens (15° - 30°)** Infrared illuminator module for MOBOTIX M73/S74 cameras night sensor modules with 15°-30° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses up to 100 m	4047438034920 85299030 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-F-IRA-W** **M73/S74 IR Light Module for Wide Lens (95°)** Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 95° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with W-IR illuminator: up to 40 m	4047438034906 85299030 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	**Mx-F-MSA** **MOBOTIX 7 MultiSense Outdoor** Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (max ±0.4°C / 0.72° F) and microphone • Camera connection and supply via MOBOTIX 7 sensor cable (up to 3m): power consumption approx. 100 mW • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Protection class IP66 • IK05 • Housing color: white	4047438035545 85299030 100 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



Mx-F-WLA-S

M73/S74 White Light for Standard lens 45-60°

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 45-60° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses with illuminator: up to 60 m

4047438042529	9,8 cm
85395200	7,5 cm
145 g	9,0 cm
	0,7 l



Mx-F-WLA-T

M73/S74 White Light for tele lens 15-30°

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 15-30° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses with illuminator: up to 80 m

4047438042536	9,8 cm
85395200	7,5 cm
145 g	9,0 cm
	0,7 l





Mx-F-WLA-W

M73/S74 White Light for Wide Lens 95°

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 95° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with illuminator: up to 40 m

4047438042512	9,8 cm
85395200	7,5 cm
145 g	9,0 cm
	0,7 l

Interface Boxes

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-F-4IOA	4047438048309	10,0 cm
Input/Output Box MOBOTIX 7/ONE	85299030	7,5 cm
	130 g	9,0 cm
		0,7 l
Weatherproof connection of external sensors and switching of external devices via MOBOTIX 7 and ONE cameras • Camera connection via USB-C cable Mx-A-S7A-CBL01/02/03 • 4 galvanically isolated inputs, 4 relay outputs • Protection class IP66/IK08, -30 to 60 °C • Connection of external devices/switches/relays with cables of specification AWG26–AWG20 (0.14–0.5 mm2)		
		
Mx-F-GPSA	4047438048316	10,5 cm
GPS Box MOBOTIX 7/ONE	85299030	6,8 cm
	120 g	10,5 cm
		0,7 l
Weatherproof GPS timer for all MOBOTIX 7 and MOBOTIX ONE cameras • Supports GPS and Glonass • Camera connection via USB-C cable Mx-A-S7A-CBL01/02/03 • Protection class IP66/IK08, –30 to 60 °C		
		
Mx-F-NPAA	4047438048323	10,0 cm
Power Adapter for MOBOTIX cameras	85299030	7,5 cm
	140 g	9,0 cm
		0,7 l
Weatherproof power supply with up to 25.5W and network connector • Requires power supply via power adapters and batteries from 12 to 24 V DC (min. 35W) • Protection class IP66/IK08, -30 to 50 °C • Important note: Only MOBOTIX patch cables may be used to connect to MOBOTIX cameras		
		
MX-Overvoltage-Protection-Box-LSA	4047438018470	10,0 cm
Network Connector with Surge Protection, LSA Version	85299030	7,5 cm
	146 g	9,0 cm
		0,7 l
Weatherproof connection of one MOBOTIX patch cable (RJ45, from the camera) and the network cable		
		
MX-Overvoltage-Protection-Box-RJ45	4047438018463	10,0 cm
Network Connector with Surge Protection, RJ45 Version	85299030	7,5 cm
	150 g	9,0 cm
		0,7 l
Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects a MOBOTIX camera from overvoltages of up to 4 kV on the PoE network cable • Protection class IP66/IK08, -30 to 60 °C		

Functional Enhancement & IR Illuminators

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-A-IRA-120 **MxIRLight Infrared Illuminator (860 nm), 120°x120°** Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	4047438030342 85394900 1.098 g	20,5 cm 17,5 cm 12,5 cm 4,5 l
		
Mx-A-IRA-90 **MxIRLight Infrared Illuminator (860 nm), 90°x90°** Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	4047438030359 85394900 1.112 g	20,5 cm 17,5 cm 12,5 cm 4,5 l
		
Mx-A-IRA-60 **MxIRLight Infrared Illuminator (860 nm), 60°x60°** Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	4047438030366 85394900 1.116 g	20,5 cm 17,5 cm 12,5 cm 4,5 l
		
Mx-A-IRA-45 **MxIRLight Infrared Illuminator (860 nm), 45°x45°** Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	4047438030373 85394900 1.124 g	20,5 cm 17,5 cm 12,5 cm 4,5 l
		
Mx-A-IRA-30 **MxIRLight Infrared Illuminator (860 nm), 30°x30°** Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white	4047438030380 85394900 1.096 g	20,5 cm 17,5 cm 12,5 cm 4,5 l



Mx-A-IRA-15

MxIRLight Infrared Illuminator (860 nm), 15°x15°

Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030397 20,5 cm
85394900 17,5 cm
1.090 g 12,5 cm
4,5 l



Mx-M-IRA-ML

MxIRLight Mounting Brackets For M1x

Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030403 19,6 cm
85399010 5,5 cm
216 g 3,5 cm
0,4 l



Mx-M-IRA-M

MxIRLight Mounting Brackets For M2x

Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030410 14,0 cm
85399010 5,5 cm
150 g 3,5 cm
0,3 l

PoE Power Supply

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
		
Mx-NPA-PoE1A-60W-BT	4047438047531	17,0 cm
PoE++ Power Network Injektor 60 Watt	85043180	7,0 cm
PoE++ 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • -10º to 40ºC @60W • -10º to 50ºC, humidity 10 to 90% @30W • IEEE 802.3bt compliant • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation • Full Protection OVP, OCP • Additional required power cord C14-type not included • Warranty: 1 year	318 g	4,7 cm
		0,6 l
		
Mx-NPA-UPoE1A-60W	4047438039024	20,5 cm
UPoE Power Injector 60W	85043180	11,5 cm
UPoE (PoE++) 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • 14º to 113ºF @60W • 14º to 131ºF @30W • IEEE 802.3at compliant with 2-event classification • IEEE 802.3af backward compatible • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation	450 g	6,5 cm
		1,5 l

MOBOTIX Storage & Recording Solutions






	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-S-NVR1A-64-POE24** **MOBOTIX MOVE NVR Network Video Recorder 64 Channels 24 PoE** MOBOTIX MOVE NVR Network Video Recorder for recording and Display up to 64 IP Cameras (Resolution up to 12MP) • 24 integrated PoE+ Ports for cetralized powering of connected IP-Cameras • 8x 3.5" SATA3 locklable HDD cartridge-slots (Delivery without hard disks (not available via MOBOTIX) • Harddrives "Hot-Swappable" • RAID 0/1/5/10 Support for Data recovering in case of HDD Failure • Optional Failover-Server functionality withing MOVE NVR System • IP-Data-Throughput (Live & Recording): avrg.: 480 Mbps, peak 2upt to 540 Mbps • Video-Codecs : H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support • 19"-Rack mount kit included.• Environmental Temperature 0 to 40°C • Power Supply: AC AC 100~240V, ATX 520W (53V/360W for PoE; 12V/160W for HDD/System) • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • Warranty: 5 Years (excl. HDD's)	4047438040365 85219000 12.510 g	58,0 cm 58,0 cm 25,0 cm 84,1 l
	**Mx-S-NVR1B-16-POE** **MOBOTIX MOVE NVR Network Video Recorder 16 Channels (8GB model)** MOBOTIX MOVE NVR Network Video Recorder with 16 integrated PoE IP camera channels (support of up to 24 IP cameras in total) • 8GB RAM integrated • Max. Storage capacity net: 28 TB (2x 3.5" SATA3) • Supplied without hard disks (not available via MOBOTIX) • IP data throughput (live & recording): max. 240 Mbps • Recording compression: H.264 / H.265 • Supports ONVIF S compliant third-party cameras • APP remote access (IOS / Android), live, playback • CMS (Central Monitoring Software) Remote Zugriff • Integrierated in MOBOTIX HUB VMS • iSCSI NAS storage support • Incl. power connection cable with EU plug (cable with US/GB/AU plug available on request) • Warranty: 5 Years (excl. HDD's)	4047438047623 85219000 8.500 g	49,5 cm 34,5 cm 18,1 cm 30,9 l


MOBOTIX Cloud

BeyondHumanVision

MOBOTIX

MOBOTIX Cloud Subscriptions

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
 **Mx-CL-Sub-ED001-1** **1 Month MOBOTIX CLOUD Subscription, update to Professional Edition** 1 Month subscription for using the Account function of the Professional Editon in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month	4047438048002 g	cm cm cm l
 **Mx-CL-Sub-ED002-1** **1 Month MOBOTIX CLOUD Subscription, update to Enterprise Edition** 1 Month subscription for using the Account function of the Enterprise Editon in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month.	4047438048040 g	cm cm cm l
 **Mx-CL-Sub-HD15-D1095-1** **MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1095 Days** Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.	4047438047128 g	cm cm cm l
 **Mx-CL-Sub-HD15-D14-1** **MOBOTIX CLOUD Monthly Camera Subscription, 15MP/14 Days** Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud. com • Cancellation/adjustment possible at any time at the end of the subscription period.	4047438046848 g	cm cm cm l
 **Mx-CL-Sub-HD15-D180-1** **MOBOTIX CLOUD Monthly Camera Subscription, 15MP/180 Days** Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud. com • Cancellation/adjustment possible at any time at the end of the subscription period.	4047438047005 g	cm cm cm l




Mx-CL-Sub-HD15-D1825-1

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438047166

cm
cm
g cm
l




Mx-CL-Sub-HD15-D30-1

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438046886

cm
cm
g cm
l




Mx-CL-Sub-HD15-D365-1

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438047043

cm
cm
g cm
l




Mx-CL-Sub-HD15-D60-1

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438046923

cm
cm
g cm
l




Mx-CL-Sub-HD15-D7-1

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438046800

cm
cm
g cm
l




Mx-CL-Sub-HD15-D730-1

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438047081

cm
cm
g cm
l




Mx-CL-Sub-HD15-D90-1

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438046961

cm
cm
g
cm
l




Mx-CL-Sub-M10-1

MOBOTIX CLOUD Camera license, only live stream, NO recording

Monthly subscription for using a single camera in the MOBOTIX CLOUD •Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438040327

cm
cm
g
cm
l




Mx-CL-Sub-PR1-D180-1

MOBOTIX CLOUD monthly Camera Subscription,for preview recording with 1 fps / 180 Days (only in

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438049146

cm
cm
g
cm
l




Mx-CL-Sub-PR1-D30-1

MOBOTIX CLOUD monthly Camera Subscription for preview recording with 1 fps / 30 Days (only in

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438049023

cm
cm
g
cm
l




Mx-CL-Sub-PR1-D365-1

MOBOTIX CLOUD monthly Camera Subscription,for preview recording with 1 fps / 365 Days (only in

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438049184

cm
cm
g
cm
l




Mx-CL-Sub-PR1-D60-1

MOBOTIX CLOUD monthly Camera Subscription,for preview recording with 1 fps / 60 Days (only in

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438049061

cm
cm
g
cm
l



Mx-CL-Sub-PR1-D730-1


MOBOTIX CLOUD monthly Camera Subscription,for preview recording with 1 fps / 730 Days (only in

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438049221

g

cm
cm
cm
l



Mx-CL-Sub-PR1-D90-1


MOBOTIX CLOUD monthly Camera Subscription,for preview recording with 1 fps / 90 Days (only in

Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438049108

g

cm
cm
cm
l



Mx-CL-Sub-SP01-M30-1


MOBOTIX CLOUD Monthly SIP Audio-Support Subscription

Monthly Subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period

4047438047203

g

cm
cm
cm
l



Mx-CL-Sub-SD1-D7-1


MOBOTIX CLOUD Camera Subscription, VGA/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036375

g

cm
cm
cm
l



Mx-CL-Sub-SD1-D14-1


MOBOTIX CLOUD Camera Subscription, VGA/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX CLoud access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036382

g

cm
cm
cm
l



Mx-CL-Sub-SD1-D30-1


MOBOTIX CLOUD Camera Subscription, VGA/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036399

g

cm
cm
cm
l




Mx-CL-Sub-SD1-D60-1

MOBOTIX CLOUD Camera Subscription, VGA/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036405

cm
cm
g
cm
l




Mx-CL-Sub-SD1-D90-1

MOBOTIX CLOUD Camera Subscription, VGA/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036412

cm
cm
g
cm
l




Mx-CL-Sub-SD1-D180-1

MOBOTIX CLOUD Camera Subscription, VGA/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036429

cm
cm
g
cm
l




Mx-CL-Sub-SD1-D365-1

MOBOTIX CLOUD Camera Subscription, VGA/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036436

cm
cm
g
cm
l




Mx-CL-Sub-SD1-D730-1

MOBOTIX CLOUD Camera Subscription, VGA/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036443

cm
cm
g
cm
l




Mx-CL-Sub-SD1-D1095-1

MOBOTIX CLOUD Camera Subscription, VGA/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036450

cm
cm
g
cm
l




Mx-CL-Sub-SD1-D1825-1

MOBOTIX CLOUD Camera Subscription, VGA/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036467

cm cm g cm l




Mx-CL-Sub-HD1-D7-1

MOBOTIX CLOUD Camera Subscription, 720p/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036023

cm cm g cm l




Mx-CL-Sub-HD1-D14-1

MOBOTIX CLOUD Camera Subscription, 720p/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036030

cm cm g cm l




Mx-CL-Sub-HD1-D30-1

MOBOTIX CLOUD Camera Subscription, 720p/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036047

cm cm g cm l




Mx-CL-Sub-HD1-D60-1

MOBOTIX CLOUD Camera Subscription, 720p/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036054

cm cm g cm l




Mx-CL-Sub-HD1-D90-1

MOBOTIX CLOUD Camera Subscription, 720p/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036061

cm cm g cm l




Mx-CL-Sub-HD1-D180-1

MOBOTIX CLOUD Camera Subscription, 720p/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036078

cm
cm
g cm
l




Mx-CL-Sub-HD1-D365-1

MOBOTIX CLOUD Camera Subscription, 720p/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036085

cm
cm
g cm
l




Mx-CL-Sub-HD1-D730-1

MOBOTIX CLOUD Camera Subscription, 720p/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036092

cm
cm
g cm
l




Mx-CL-Sub-HD1-D1095-1

MOBOTIX CLOUD Camera Subscription, 720p/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036108

cm
cm
g cm
l




Mx-CL-Sub-HD1-D1825-1

MOBOTIX CLOUD Camera Subscription, 720p/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036115

cm
cm
g cm
l




Mx-CL-Sub-HD2-D7-1

MOBOTIX CLOUD Camera Subscription, 1080p/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036122

cm
cm
g cm
l




Mx-CL-Sub-HD2-D14-1

MOBOTIX CLOUD Camera Subscription, 1080p/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036139

cm
cm
g cm
l




Mx-CL-Sub-HD2-D30-1

MOBOTIX CLOUD Camera Subscription, 1080p/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036146

cm
cm
g cm
l




Mx-CL-Sub-HD2-D60-1

MOBOTIX CLOUD Camera Subscription, 1080p/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036153

cm
cm
g cm
l




Mx-CL-Sub-HD2-D90-1

MOBOTIX CLOUD Camera Subscription, 1080p/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036160

cm
cm
g cm
l




Mx-CL-Sub-HD2-D180-1

MOBOTIX CLOUD Camera Subscription, 1080p/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036177

cm
cm
g cm
l




Mx-CL-Sub-HD2-D365-1

MOBOTIX CLOUD Camera Subscription, 1080p/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036184

cm
cm
g cm
l




Mx-CL-Sub-HD2-D730-1

MOBOTIX CLOUD Camera Subscription, 1080p/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036191

cm
cm
g cm
l




Mx-CL-Sub-HD2-D1095-1

MOBOTIX CLOUD Camera Subscription, 1080p/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036207

cm
cm
g cm
l




Mx-CL-Sub-HD2-D1825-1

MOBOTIX CLOUD Camera Subscription, 1080p/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036214

cm
cm
g cm
l




Mx-CL-Sub-HD3-D7-1

MOBOTIX CLOUD Camera Subscription, 3MP/7 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https: //mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036221

cm
cm
g cm
l




Mx-CL-Sub-HD3-D14-1

MOBOTIX CLOUD Camera Subscription, 3MP/14 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud. com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036238

cm
cm
g cm
l




Mx-CL-Sub-HD3-D30-1

MOBOTIX CLOUD Camera Subscription, 3MP/30 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud. com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036245

cm
cm
g cm
l




Mx-CL-Sub-HD3-D60-1

MOBOTIX CLOUD Camera Subscription, 3MP/60 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036252

cm
cm
g cm
l




Mx-CL-Sub-HD3-D90-1

MOBOTIX CLOUD Camera Subscription, 3MP/90 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036269

cm
cm
g cm
l




Mx-CL-Sub-HD3-D180-1

MOBOTIX CLOUD Camera Subscription, 3MP/180 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036276

cm
cm
g cm
l




Mx-CL-Sub-HD3-D365-1

MOBOTIX CLOUD Camera Subscription, 3MP/365 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036283

cm
cm
g cm
l




Mx-CL-Sub-HD3-D730-1

MOBOTIX CLOUD Camera Subscription, 3MP/730 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX CLoud access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036290

cm
cm
g cm
l




Mx-CL-Sub-HD3-D1095-1

MOBOTIX CLOUD Camera Subscription, 3MP/1095 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036306

cm
cm
g cm
l




Mx-CL-Sub-HD3-D1825-1

MOBOTIX CLOUD Camera Subscription, 3MP/1825 Days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036313

cm cm g cm l




Mx-CL-Sub-HD4-D7-1

MOBOTIX CLOUD Camera Subscription, 4MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036481

cm cm g cm l




Mx-CL-Sub-HD4-D14-1

MOBOTIX CLOUD Camera Subscription, 4MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036498

cm cm g cm l




Mx-CL-Sub-HD4-D30-1

MOBOTIX CLOUD Camera Subscription, 4MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036504

cm cm g cm l




Mx-CL-Sub-HD4-D60-1

MOBOTIX CLOUD Camera Subscription, 4MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036511

cm cm g cm l




Mx-CL-Sub-HD4-D90-1

MOBOTIX CLOUD Camera Subscription, 4MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036528

cm cm g cm l




Mx-CL-Sub-HD4-D180-1

MOBOTIX CLOUD Camera Subscription, 4MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036535

cm
cm
g
cm
l




Mx-CL-Sub-HD4-D365-1

MOBOTIX CLOUD Camera Subscription, 4MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036542

cm
cm
g
cm
l




Mx-CL-Sub-HD4-D730-1

MOBOTIX CLOUD Camera Subscription, 4MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036559

cm
cm
g
cm
l




Mx-CL-Sub-HD4-D1095-1

MOBOTIX CLOUD Camera Subscription, 4MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036566

cm
cm
g
cm
l




Mx-CL-Sub-HD4-D1825-1

MOBOTIX CLOUD Camera Subscription, 4MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036573

cm
cm
g
cm
l




Mx-CL-Sub-HD5-D7-1

MOBOTIX CLOUD Camera Subscription, 5MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036580

cm
cm
g
cm
l




Mx-CL-Sub-HD5-D14-1

MOBOTIX CLOUD Camera Subscription, 5MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036597

cm
cm
g cm
l




Mx-CL-Sub-HD5-D30-1

MOBOTIX CLOUD Camera Subscription, 5MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036603

cm
cm
g cm
l




Mx-CL-Sub-HD5-D60-1

MOBOTIX CLOUD Camera Subscription, 5MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036610

cm
cm
g cm
l




Mx-CL-Sub-HD5-D90-1

MOBOTIX CLOUD Camera Subscription, 5MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036627

cm
cm
g cm
l




Mx-CL-Sub-HD5-D180-1

MOBOTIX CLOUD Camera Subscription, 5MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036634

cm
cm
g cm
l




Mx-CL-Sub-HD5-D365-1

MOBOTIX CLOUD Camera Subscription, 5MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036641

cm
cm
g cm
l




Mx-CL-Sub-HD5-D730-1

MOBOTIX CLOUD Camera Subscription, 5MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036658

cm
cm
g cm
l




Mx-CL-Sub-HD5-D1095-1

MOBOTIX CLOUD Camera Subscription, 5MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036665

cm
cm
g cm
l




Mx-CL-Sub-HD5-D1825-1

MOBOTIX CLOUD Camera Subscription, 5MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036672

cm
cm
g cm
l




Mx-CL-Sub-HD10-D7-1

MOBOTIX CLOUD Camera Subscription, 10MP/7 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036689

cm
cm
g cm
l




Mx-CL-Sub-HD10-D14-1

MOBOTIX CLOUD Camera Subscription, 10MP/14 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036696

cm
cm
g cm
l




Mx-CL-Sub-HD10-D30-1

MOBOTIX CLOUD Camera Subscription, 10MP/30 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036702

cm
cm
g cm
l




Mx-CL-Sub-HD10-D60-1

MOBOTIX CLOUD Camera Subscription, 10MP/60 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036719

cm
cm
g cm
l




Mx-CL-Sub-HD10-D90-1

MOBOTIX CLOUD Camera Subscription, 10MP/90 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036726

cm
cm
g cm
l




Mx-CL-Sub-HD10-D180-1

MOBOTIX CLOUD Camera Subscription, 10MP/180 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036733

cm
cm
g cm
l




Mx-CL-Sub-HD10-D365-1

MOBOTIX CLOUD Camera Subscription, 10MP/365 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036740

cm
cm
g cm
l




Mx-CL-Sub-HD10-D730-1

MOBOTIX CLOUD Camera Subscription, 10MP/730 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036757

cm
cm
g cm
l




Mx-CL-Sub-HD10-D1095-1

MOBOTIX CLOUD Camera Subscription, 10MP/1095 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036764

cm
cm
g cm
l



Mx-CL-Sub-HD10-D1825-1


MOBOTIX CLOUD Camera Subscription, 10MP/1825 days

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036771

g

cm
cm
cm
l



Mx-CL-Sub-ANA-001-1


MOBOTIX CLOUD Analytics Subscription, Line Cross

Monthly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation of subscription possible at any time at the end of the month

4047438036320

g

cm
cm
cm
l



Mx-CL-Sub-ANA-002-1


MOBOTIX CLOUD Analytics Subscription, Counting

Monthly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation of subscription possible at any time at the end of the month

4047438036337

g

cm
cm
cm
l



Mx-CL-Sub-ANA-003-1


MOBOTIX CLOUD Analytics Subscription, Area Intrusion

Monthly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion • Cancellation of subscription possible at any time at the end of the month

4047438036344

g

cm
cm
cm
l



Mx-CL-Sub-ANA-004-1


MOBOTIX CLOUD Analytics Subscription, Camera Tamper Detect

Monthly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation of subscription possible at any time at the end of the month

4047438036351

g

cm
cm
cm
l



Mx-CL-Sub-ANA-005-1

MOBOTIX CLOUD Analytics Subscription, Loitering

Monthly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation of subscription possible at any time at the end of the month

4047438036368

g

cm
cm
cm
l





Software & Services


BeyondHumanVision

MOBOTIX

MOBOTIX HUB Video Management System

MOBOTIX HUB


	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-HUB-IncidentManager-Bas** **MOBOTIX HUB Incident Manager Base License** MOBOTIX HUB Incident Manager Base Licence • Combines video recording with incident information • Record, document, track and analyse incidents • Only one Base Licence required per HUB installation • Permanent licence • Licence required for MOBOTIX HUB L3 and L4 (included in L5)	4047438051989 g	cm cm cm l
	**Mx-HUB-MgmtSrvFailover** **MOBOTIX HUB Management Server Failover - Redundancy System** Enables support for a failover server in the MOBOTIX HUB for the HUB Management Server • It provides HUB users with an always available high availability cluster with real • time replication and failover • It is a complete solution that protects the management server (and the event, log and SQL servers if they are installed on the same physical server) from hardware, software and human errors • Its efficient design and easy configuration give you the ability to seamlessly and automatically switch to a reliable backup management server if the primary server fails. • Its efficient design and simple configuration give you the ability to seamlessly and automatically switch to a reliable backup management server if the primary server fails. It offers real-time synchronous file replication, automatic application failover and automatic failback after a server failure • Licence is issued via MOBOTIX Sales • Licence is non-transferable • One licence per MOBOTIX HUB VMS is required. • Usable from MOBOTIX HUB L4 • Only 1 server pair per location is supported	4047438049580 g	cm cm cm l
	**Mx-HUB-TRAD-ASP1M-BAS-L4-L5** **ASP monthly upgrade (trade-in) - Required for HUB upgrades with active ASP from Base L4 to L5** Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per base licence is required.	4047438050937 g	cm cm cm l
	**Mx-HUB-TRAD-ASP1M-DEV-L4-L5** **ASP monthly upgrade (trade-in) - Required for HUB upgrades with active ASP from L4 to L5** Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required.	4047438050944 g	cm cm cm l
	**Mx-HUB-TRAD-ASP1M-L2-L3** **ASP monthly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L3** Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L3 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required.	4047438050685 g	cm cm cm l



Mx-HUB-TRAD-ASP1M-L2-L4 4047438050739 cm

ASP monthly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L4 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1M-L2-L5 4047438050784 cm

ASP monthly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L5 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1M-L3-L4 4047438050838 cm

ASP monthly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L4 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1M-L3-L5 4047438050883 cm

ASP monthly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L5 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1Y-BAS-L4-L5 4047438050951 cm

ASP yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from Base L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per base licence is required. g cm l



Mx-HUB-TRAD-ASP1Y-DEV-L4-L5 4047438050968 cm

ASP yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1Y-L2-L3 4047438050692 cm

ASP yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L3 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L3 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1Y-L2-L4 4047438050746 cm

ASP yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L4 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1Y-L2-L5 4047438050791 cm

ASP yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L5 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1Y-L3-L4 4047438050845 cm

ASP yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L4 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP1Y-L3-L5 4047438050890 cm

ASP yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L5 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP2Y-BAS-L4-L5 4047438050975 cm

ASP 2 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from Base L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per base licence is required. g cm l



Mx-HUB-TRAD-ASP2Y-DEV-L4-L5 4047438050982 cm

ASP 2 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP2Y-L2-L3 4047438050708 cm

ASP 2 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L3 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L3 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP2Y-L2-L4 4047438050753 cm

ASP 2 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L4 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP2Y-L2-L5 4047438050807 cm

ASP 2 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L5 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP2Y-L3-L4 4047438050852 cm

ASP 2 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L4 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP2Y-L3-L5 4047438050906 cm

ASP 2 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L5 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP3Y-BAS-L4-L5 4047438050999 cm

ASP 3 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from BASE L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per base licence is required. g cm l



Mx-HUB-TRAD-ASP3Y-DEV-L4-L5 4047438051002 cm

ASP 3 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP3Y-L2-L3 4047438050715 cm

ASP 3 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L3 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L3 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP3Y-L2-L4 4047438050760 cm

ASP 3 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L4 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP3Y-L2-L5 4047438050814 cm

ASP 3 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L5 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP3Y-L3-L4 4047438050869 cm

ASP 3 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L4 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP3Y-L3-L5 4047438050913 cm

ASP 3 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L5 cm


Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP5Y-BAS-L4-L5 4047438051019 cm

ASP 5 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from BASE L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per base licence is required. g cm l



Mx-HUB-TRAD-ASP5Y-DEV-L4-L5 4047438051026 cm

ASP 5 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L4 to L5 cm


Offsets the remaining term of the ASP of the HUB L4 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP5Y-L2-L3 4047438050722 cm

ASP 5 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L3 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L3 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP5Y-L2-L4 4047438050777 cm

ASP 5 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L4 cm


Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l



Mx-HUB-TRAD-ASP5Y-L2-L5 4047438050821 cm

ASP 5 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L2 to L5 cm

Offsets the remaining term of the ASP of the HUB L2 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm l




Mx-HUB-TRAD-ASP5Y-L3-L4 4047438050876 cm

ASP 5 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L4 cm

Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L4 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm

l




Mx-HUB-TRAD-ASP5Y-L3-L5 4047438050920 cm

ASP 5 yearly upgrade (trade-in) - Required for HUB upgrades with active ASP from L3 to L5 cm

Offsets the remaining term of the ASP of the HUB L3 against the additional price of the ASP of a HUB L5 • Investment security by using the already purchased and remaining ASP term instead of purchasing a new ASP • Customer only pays the difference • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per device licence is required. g cm

l




Mx-HUB-TRAD-MgmtSrvFailover-W 4047438049597 cm

MOBOTIX HUB Management Server Failover - Trade-in SL w/ ASP cm

Product Upgrade of the MOBOTIX HUB Management Server Failover license, which are in possession of an Advanced Service Product (ASP). • Usable from MOBOTIX HUB L4 • Only 1 server pair per location is supported g cm

l



Mx-SW-HUB-LayoutBuilder 4047438051033 cm

Custom View Layout Builder Plug In - Creates customised views cm

Activates the Milestone Custom View Layout Builder plugin in the MOBOTIX HUB from our technology partner Milestone • Custom View Layout Builder allows the administrator to create customised Desk Client view layouts • The created layouts are automatically available in the HUB Desk Client for creating new views • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • Usable from MOBOTIX HUB L2 • Independent of the number of integrated cameras • Permanent licence g cm

l



Mx-SW-HUB-SuspectTrack 4047438049474 cm

Milestone Suspect Tracking Plug In - Virtual Patrol Support cm

Activates the Milestone Suspect Tracking plugin in the MOBOTIX HUB from our technology partner Milestone • Suspect Tracking offers a user-friendly way to track objects of interest between the cameras in the MOBOTIX HUB Desk Client or simply move around the camera area in a logical way • Suspect Tracking supports all integrated cameras in the MOBOTIX HUB , Independent of the manufacturer • Main application areas are: Virtual patrol for the user • Licence is issued via MOBOTIX Sales • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • Usable from MOBOTIX HUB L2 • Independent of the number of integrated cameras • Permanent licence g cm

l



Mx-HUB-L2-BAS 4047438038584 cm

MOBOTIX HUB L2 Base License (BL) cm

MOBOTIX HUB L2 for smaller companies with one location manages up to 100 surveillance cameras g cm

l



Mx-HUB-L2-DEV

MOBOTIX HUB L2 Device License (DL)

Device licenses for MOBOTIX HUB L2. Up to 100 device licenses can be linked to the HUB L2

4047438038591

cm
cm
g cm
l



Mx-HUB-L2-1MDEV

1 Month Advanced Services for MOBOTIX HUB L2 Device License

1 Month MOBOTIX HUB L2 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L2 Advanced Service for 1, 3 and 5 years.

4047438039215

cm
cm
g cm
l



Mx-HUB-L2-1YDEV

1 Year MOBOTIX HUB Advanced Services for L2 Device License

1 Year MOBOTIX HUB L2 Advanced Services (Device license) provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038607

cm
cm
g cm
l



Mx-HUB-L2-3YDEV

3 Years MOBOTIX HUB Advanced Services for L2 Device License

3 Years MOBOTIX HUB L2 Advanced Services (Device license) provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038621

cm
cm
g cm
l



Mx-HUB-L2-5YDEV

5 Years MOBOTIX HUB Advanced Services for L2 Device License

5 Years MOBOTIX HUB L2 Advanced Service (Device license) provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038638

cm
cm
g cm
l



Mx-HUB-L3-BAS

MOBOTIX HUB L3 Base License (BL)

MOBOTIX HUB L3 is the solution for medium-sized companies. The number of cameras is unlimited and can be distributed across multiple locations.

4047438038645

cm
cm
g cm
l



Mx-HUB-L3-DEV 4047438038652 cm

MOBOTIX HUB L3 Device License (DL) cm

g cm

Device licenses for MOBOTIX HUB L3. Unlimited number of devices can be integrated into one L3 installation. l



Mx-HUB-L3-1MDEV 4047438039222 cm

1 Month Advanced Services for MOBOTIX HUB L3 Device License cm

g cm

1 Month MOBOTIX HUB L3 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L3 Advanced Service for 1, 3 and 5 years. l



Mx-HUB-L3-1YDEV 4047438038669 cm

1 Year MOBOTIX HUB Advanced Services for L3 Device License cm

g cm

1 Year MOBOTIX HUB L3 Advanced Services (Device license) provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution. l



Mx-HUB-L3-3YDEV 4047438038683 cm

3 Years MOBOTIX HUB Advanced Services for L3 Device License cm

g cm

3 Years MOBOTIX HUB L3 Advanced Services (Device license) provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution. l



Mx-HUB-L3-5YDEV 4047438038690 cm

5 Years MOBOTIX HUB Advanced Services for L3 Device License cm

g cm

5 Years MOBOTIX HUB L3 Advanced Service (Device License) provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution. l



Mx-HUB-TRAD-BAS-L2-L3-W 4047438039369 cm

Trade-in BL L2->L3 w/ ASP cm

g cm

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP). l



Mx-HUB-TRAD-DEV-L2-L3-W

Trade-in DL L2->L3 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).

4047438039376

cm
cm
g cm
l



Mx-HUB-L4-BAS

MOBOTIX HUB L4 Base License (BL)

MOBOTIX HUB L4 is made for medium and large installations. In addition to the features of MOBOTIX HUB L3, L4 provides access to failover recording servers in case of server failure. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.

4047438038706

cm
cm
g cm
l



Mx-HUB-L4-DEV

MOBOTIX HUB L4 Device License (DL)

Device licenses for MOBOTIX HUB L4. Unlimited number of devices can be integrated into one L4 installation. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.

4047438038713

cm
cm
g cm
l



Mx-HUB-L4-1MDEV

1 Month Advanced Services for MOBOTIX HUB L4 Device License

1 Month MOBOTIX HUB L4 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 3 and 5 years.

4047438039246

cm
cm
g cm
l



Mx-HUB-L4-1YDEV

1 Year MOBOTIX HUB Advanced Services for L4 Device License

1 year MOBOTIX HUB L4 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution

4047438038768

cm
cm
g cm
l



Mx-HUB-L4-3YDEV

3 Years MOBOTIX HUB Advanced Services for L4 Device License

3 Years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038782

cm
cm
g cm
l



Mx-HUB-L4-5YDEV 4047438038799 cm

5 Years MOBOTIX HUB Advanced Services for L4 Device License cm

5 Years MOBOTIX HUB L4 Advanced Service (Device license) provides 5 year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution. g cm

l



Mx-HUB-TRAD-BAS-L2-L4-W 4047438039406 cm

Trade-in BL L2->L4 w/ ASP cm

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP). g cm

l



Mx-HUB-TRAD-DEV-L2-L4-W 4047438039413 cm

Trade-in DL L2->L4 w/ ASP cm

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP). g cm

l



Mx-HUB-TRAD-BAS-L3-L4-W 4047438039444 cm

Trade-in BL L3->L4 w/ ASP cm

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP). g cm

l



Mx-HUB-TRAD-DEV-L3-L4-W 4047438039451 cm

Trade-in DL L3->L4 w/ ASP cm

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP). g cm

l



Mx-HUB-L5-BAS 4047438038805 cm

MOBOTIX HUB L5 Base License (BL) cm

MOBOTIX HUB L5 is the video management platform for large and extremely security-oriented applications. In addition to centralized management of all servers, cameras and users across multiple sites, L5 also includes control for a professional video wall as standard. The use of MOBOTIX HUB L5 requires an Advanced Service (base + devices) of at least one year. g cm

l



Mx-HUB-L5-DEV 4047438038812 cm

MOBOTIX HUB L5 Device License (DL) cm

g cm

Device licenses for MOBOTIX HUB L5. Unlimited number of devices can be integrated into one L5 installation. l



Mx-HUB-L5-INTCON 4047438038829 cm

MOBOTIX HUB Interconnect Device License (DL) cm

g cm

Interconnect licenses for MOBOTIX HUB L5. Unlimited number of Interconnect licenses can be used into one L5 installation. l



Mx-HUB-L5-1MDEV 4047438039260 cm

1 Month Advanced Services for MOBOTIX HUB L5 Device License cm

1 Month MOBOTIX HUB L5 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 3 and 5 years. g cm l



Mx-HUB-L5-1YDEV 4047438038874 cm

1 Year MOBOTIX HUB Advanced Services for L5 Device License cm

1 Year MOBOTIX HUB L5 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution g cm l



Mx-HUB-L5-3YDEV 4047438038898 cm

3 Years MOBOTIX HUB Advanced Services for L5 Device License cm

3 Years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution g cm l



Mx-HUB-L5-5YDEV 4047438038904 cm

5 Years MOBOTIX HUB Advanced Services for L5 Device License cm

5 Years MOBOTIX HUB L5 Advanced Service (Device license) provides 5 years periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution g cm l



Mx-HUB-TRAD-BAS-L2-L5-W 4047438039482 cm
Trade-in BL L2->L5 w/ ASP cm
g cm
l

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).



Mx-HUB-TRAD-DEV-L2-L5-W 4047438039499 cm
Trade-in DL L2->L5 w/ ASP cm
g cm
l

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).



Mx-HUB-TRAD-BAS-L3-L5-W 4047438039529 cm
Trade-in BL L3->L5 w/ ASP cm
g cm
l

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).



Mx-HUB-TRAD-DEV-L3-L5-W 4047438039536 cm
Trade-in DL L3->L5 w/ ASP cm
g cm
l

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).




Mx-HUB-TRAD-BAS-L4-L5-W 4047438039567 cm
Trade-in BL L4->L5 w/ ASP cm
g cm
l

Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).



Mx-HUB-TRAD-DEV-L4-L5-W 4047438039574 cm
Trade-in DL L4->L5 w/ ASP cm
g cm
l

Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).




Mx-HUB-ACC-WALL 4047438039116 cm

MOBOTIX HUB Video Wall Base License (BL) cm

g cm

l

MOBOTIX HUB Video Wall is an advanced add-on video wall product that improves response time by displaying all the video data in your installation and giving a complete overview of large surveillance centers.




Mx-HUB-ACC-WALL-UP 4047438039604 cm

Version Upgrade HUB Video Wall BL w/o ASP cm

g cm

l

Software update for MOBOTIX HUB Video Wall license that are not in possession of an Advanced Service Product




Mx-HUB-ACS-BASE 4047438039178 cm

MOBOTIX HUB Access Base License (BL) cm

g cm

l

MOBOTIX HUB Access is an Add-on product that video enables physical security through integration of access control and intrusion systems




Mx-HUB-ACS-DOOR 4047438039185 cm

MOBOTIX HUB Access Door License (DL) cm

g cm

l

Device license for MOBOTIX HUB Access.




Mx-HUB-XP-TRA-BAS 4047438039154 cm

Xprotect Transaction Base License Server incl. 1 Connection License cm

g cm

l

XProtect Transact Base Server incl. 1 Connection License. XProtect Transact video enables different types of transaction-based processes.Combining transaction data from point of sales systems, scanners, cash point machines, or similar systems with corresponding video, XProtect Transact enables real-time monitoring, exception handling and documentation of transactions.



Mx-HUB-XP-TRA-CON 4047438039161 cm

Xprotect Transaction Connection License cm

g cm

l

Connection licence for Xprotect Transact.



Mx-HUB-XP-LPR-BAS 4047438039123 cm

Xprotect LPR Base License incl. 5 Country Modules cm

XProtect LPR Base License, incl. 5 Country Modules. XProtect LPR is license plate recognition (LPR) software that detects license plate information from any vehicle around the world and links the license plate number with video.

g cm

l



Mx-HUB-XP-LPR-DEV 4047438039130 cm

XProtect LPR Device License (DL) cm

Device licence for Xprotect LPR.

g cm

l



Mx-HUB-XP-LPR-CTY 4047438039147 cm

Xprotect LPR Country Modul cm

Country modul for Xprotect LPR.

g cm


l

MxManagementCenter and Additional

ONVIF-compliant Video Managemnt System

MxManagementCenter (MxMC) is a powerful, intuitive video management system for Windows and macOS systems. MxMC can be utilized for projects and security installations of all sizes and with any number of cameras orstorage media. It was designed to be user-friendly, high-performing and secure.

Please follow this link for further license-related informations: https://www.mobotix.com/de/support/download-center/software-downloads/lizenz-portal

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-SW-MC-ADCON-VM** **MxMC Advanced Config License for virtual machines (VM)** Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required) • released for virtual machines (VM)	4047438035071 0 g	0,0 cm 0,0 cm 0,0 cm 0,0 l
	**Mx-SW-MC** **MxManagementCenter VMS For Windows/macOS** Free-of-charge MOBOTIX video management software MxManagementCenter (MxMC) • Certified ONVIF conformity (Profile S) • Language packs: English, German, French, Spanish, Italian, Russian, Turkish, Portuguese, Japanese • System requirements: 2 GHz processor (min.), at least 2 GB RAM, video card with support for OpenGL V2.1 • Download free of charge: www.mobotix.com > Services > Download Center > Software Downloads > MxManagementCenter	4047438034456 0 g	0,0 cm 0,0 cm 0,0 cm 0,0 l
	**Mx-SW-MC-ADCON** **MxMC Advanced Config License** Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034197 0 g	0,0 cm 0,0 cm 0,0 cm 0,0 l
	**Mx-SW-MC-STARTER** **MxMC Integration Starter License** MOBOTIX license for the general use of H.264 with a MxMC workstation (as of MxMC 2.0) for live images, playback and/or export • Unlimited number of users per workstation • No time limit for use • One additional video channel for a third-party ONVIF-S camera included • Download via external license portal (access data required)	4047438034142 0 g	0,0 cm 0,0 cm 0,0 cm 0,0 l
	**Mx-SW-MC-CHAN** **MxMC Integration Channel License** MOBOTIX license for using an additional video channel from an external ONVIF S compliant IP camera with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034159 0 g	0,0 cm 0,0 cm 0,0 cm 0,0 l



Mx-SW-MC-SDATA 4047438034449 0,0 cm

MxMC Smart Data License 0,0 cm

0 g 0,0 cm

MOBOTIX license for connectiong an external data source (Smart Data Source) to a MxMC workstation (as of MxMC 2.1) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

0,0 l



Mx-SW-MC-POS 4047438031615 0,0 cm

MxMC POS Single Cash Point License 0,0 cm

0 g 0,0 cm

MOBOTIX license for connecting a cash register to a MxMC workstation (as of MxMC 1.7) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

0,0 l



Mx-SW-MC-AS-1 4047438034166 0,0 cm

MxMC Advanced Service License, 1 Year 0,0 cm

0 g 0,0 cm

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 1 year/12 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0,0 l



Mx-SW-MC-AS-2 4047438034173 0,0 cm

MxMC Advanced Service License, 2 Years 0,0 cm

0 g 0,0 cm

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 2 years/24 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0,0 l



Mx-SW-MC-AS-5 4047438034180 0,0 cm

MxMC Advanced Service License, 5 Years 0,0 cm

0 g 0,0 cm

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 5 years/60 months • Unlimited number of users per workstation • Download via external license portal (access data required)

0,0 l

Certified Apps for MOBOTIX 7

Certified Apps for MOBOTIX 7

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-APP-IRIS-ANO** **Irisity Iris Anonymization App** Irisity Iris Anonymization App including the following features: • patented dynamic pixelation of people in the camera's field of view • designed to address GDPR and privacy regulations • Configurable option to force switch to black/white image to ensure maximum privacy • applicable in indoor and outdoor camera operation • pixelation of persons from a minimum height of 20 pixels	4047438045230 g	cm cm cm l
	**Mx-APP-IRIS-C-INT** **Irisity Iris Core Intrusion App** Irisity Iris Core Intrusion App including the following features: • Detects the intrusion of objects of interest into user-defined detection zones / areas • Designed for reliable detection of people and vehicles covering only small portions of the field of view • Reduction of false alarms to a minimum by filtering out non-critical motion (e.g. trees, clouds, etc.) • simultaneous detection on one or more image sensors • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB	4047438040693 g	cm cm cm l
	**Mx-APP-MX-ARA** **MOBOTIX Advanced Radiometry App** MOBOTIX Advanced Radiometry App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON	4047438044998 g	cm cm cm l
	**Mx-APP-MX-BAR** **MOBOTIX Barcode Reader App** MOBOTIX Barcode Reader App including the following features: • Reader supports more than 40 common 1D, 2D and Stacked barcode types (e.g. QR Code, Data Matrix Code, Dot Code, etc.) • Optimized for difficult barcode reads (e.g. damaged, faded or distorted barcodes, barcodes on difficult surfaces, DPM codes) • Quick reading of one or multiple barcodes in motion • Definition of up to 20 detection areas within the camera's field of view • MOBOTIX events via MxMessageSystem • reporting of barcode reads via generic XML, JSON and MODBUS/TCP	4047438044981 g	cm cm cm l
	**Mx-APP-MX-COR** **MOBOTIX Color Recognition App** MOBOTIX Color Recognition including the following features: • Detection of user-specified color values within customized detection areas • Definition of up to 20 detection areas within the camera's field of view • Supports the recognition of all RGB color values • Set sensitivity, required percentage within the defined detection area and duration of the associated condition • MOBOTIX events via MxMessageSystem	4047438042567 g	cm cm cm l



Mx-APP-MX-THD 4047438045087 cm

MOBOTIX Thermal Heat Detection App cm

g cm

l

MOBOTIX Thermal Heat Detection App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (according to CNPP France 19005 certification) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • the MOBOTIX Thermal Heat Detection App is required in any case to fulfill the requirements for CNPP France 19005 certification (Thermal Camera Heat Detection Systems)



Mx-APP-MX-TVA 4047438045216 cm

MOBOTIX Thermal Validation App cm

g cm

l

MOBOTIX Thermal Validation App including the following features: • App optimizes MOBOTIX Thermal Radiometry cameras for use in the fields of waste management and logistics • Enables filtering of vehicles (e.g. construction vehicles und forklifts) as a non-critical source of high temperatures (e.g. by measuring hot body parts such as the exhaust or engine cover) • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON / XML via HTTP(S)



Mx-APP-VX-ADR 4047438037815 cm

VAXTOR App License Plate and Dangerous Goods Recognition cm

g cm

l

VAXTOR App for License Plate and Dangerous Goods Recognition including the following features: • License plate recognition of one- and two-line license plates • read conventional and dangerous good plates simultaneously • support of latin, hebrew and arabic characters for global application • recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and trigger mode for LPR/ADR



Mx-APP-VX-AIN 4047438040518 cm

VAXTOR Aircraft Identification Number Recognition App cm

g cm

l

VAXTOR Aircraft Identification Number Recognition App including the following features: • Recognition of ICAO- and FAA-issued identification numbers • Operations up to a speed of 50 km/h • Real-time results: Aircraft ID, Aircraft Type, Country, etc. • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.)



Mx-APP-VX-CON 4047438037938 cm

VAXTOR App for Cargo Container Code Recognition cm

g cm

l

VAXTOR App for Container Code Recognition including the following features: • Recognition of cargo container codes according to ISO 6346 • Real time results: • Container Code • Property Code • Owner • Container Type • Container Dimensions • Control Digit • Control Digit Validation • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode



Mx-APP-VX-GEN 4047438042543 cm

VAXTOR Genesis Optical Character Recognition App cm

g cm

l

VAXTOR Genesis Optical Character Recognition App including the following features: • generic optical character recognition to read any combination of uppercase Latin characters and/or numbers • reads characters arranged in up to three lines • user-defined specification of the required code format • recognition log • MOBOTIX events via MxMessageSystem • numerous integration options for further processing of the generated metadata (generic as well as native reporting interfaces) • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode



Mx-APP-VX-LPR 4047438037358 cm

VAXTOR License Plate Recognition App cm

g cm

l

VAXTOR License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • Recognition log • MOBOTIX events via MxMessageSystem • Global country coverage



Mx-APP-VX-LPR-M 4047438040402 cm

VAXTOR License Plate Recognition App (multi-lens application) for S74 cm

g cm

l

VAXTOR License Plate Recognition App (multi-lens application) for S74 with two optical sensor moduels including the following features: • License plate recognition of one- and two-line license plates • simultaneous recognition on both image sensors • monitoring the dwell time of license plates in the detection area • support of latin, hebrew and arabic characters for global application • Recognition log • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode



Mx-APP-VX-MMC 4047438038324 cm

VAXTOR License Plate Recognition App incl. Vehicle Make, Model, Color and Class cm

g cm

l

VAXTOR License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • support of latin, hebrew and arabic characters for global application • Additional recognition of vehicle make, model, color and class • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode



Mx-APP-VX-UIC 4047438040266 cm

VAXTOR App for UIC Railway Code Recognition cm

g cm

l

VAXTOR App for UIC Railway Code Recognition including the following features: • Recognition of the International Union of Railways Wagon and Coach numbers (UIC Codes) • Real time results: UIC Code, Country Code, Vehicle Type, Control Digit, Direction of travel • Stop / Go and slow speed (<10 km/h) applications (depending on installation and module selection) • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode



Mx-APP-VX-USD 4047438041638 cm


VAXTOR USDOT Number Recognition App cm

VAXTOR USDOT Number Recognition App including the following features: • Recognition of USDOT identification numbers • Operations up to a vehicle speed of 50 km/h • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled operation mode

g cm

l

Desktop Apps


	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-SW-HUB-Disco-Bas** **MOBOTIX HUB Plug In - Discovery Base License for L2 MOBOTIX HUB** Activates MOBOTIX Discovery support in the MOBOTIX HUB L2 • An ideal tool for administrators to add new MOBOTIX cameras to the system more quickly and easily • Supports firmware update and password change • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • One licence supports 32 cameras • Additional cameras require MOBOTIX Discovery Device licence • Permanent licence	4047438051279 g	cm cm cm l
	**Mx-SW-HUB-Disco-Dev** **MOBOTIX HUB Plug In - Discovery Device License for L2 MOBOTIX HUB** Activates additional cameras in MOBOTIX HUB L2 for MOBOTIX Discovery PlugIn • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • 16 additional cameras are supported with one licence • Additional cameras require further MOBOTIX Discovery Device licence • Permanent licence	4047438051286 g	cm cm cm l
	**Mx-SW-HUB-DualV-Bas** **MOBOTIX HUB Plug In - DualVision Base License for L2 MOBOTIX HUB** Activates MOBOTIX DualVision in MOBOTIX HUB L2 • the dual view of a MOBOTIX camera can be split in the MOBOTIX HUB Desk Client • display of the left, right or both eyes possible • the eyes can be arranged separately in the camera layout. Split into live and playback view possible • Optimised for MOBOTIX DUAL cameras • 3rd party cameras are also supported • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MOBOTIX HUB VMS is required. • With one license, 8 Dual Cameras will be supported • Additional Dual Cameras require a MOBOTIX Device license • Permanent license	4047438051149 g	cm cm cm l
	**Mx-SW-HUB-DualV-Dev** **MOBOTIX HUB Plug In - DualVision Device License for L2 MOBOTIX HUB** Activates MOBOTIX DualVision in MOBOTIX HUB L2 • the dual view of a MOBOTIX camera can be split in the MOBOTIX HUB Desk Client • display of the left, right or both eyes possible • the eyes can be arranged separately in the camera layout. Split into live and playback view possible • Optimised for MOBOTIX DUAL cameras • 3rd party cameras are also supported • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MOBOTIX HUB VMS is required. • With one license, 8 Dual Cameras will be supported • Additional Dual Cameras require a MOBOTIX Device license • Permanent license	4047438051156 g	cm cm cm l
	**Mx-SW-HUB-FishE-Bas** **MOBOTIX HUB Plug In - Fisheye Base License for L2 MOBOTIX HUB** Activates MOBOTIX Fisheye support in the MOBOTIX HUB L2• the Fisheye view of a MOBOTIX camera can be corrected in the MOBOTIX HUB Desk Client • Various equalisation modes are available • Correction in Live and Playback view possible • Correction in Desk Client Export Player possible • MOBOTIX Fisheye and 3rd party Fisheye cameras are supported • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • 8 fisheye cameras are supported with one licence • Additional fisheye cameras require MOBOTIX Fisheye Device licence • Permanent licence	4047438051163 g	cm cm cm l



Mx-SW-HUB-FishE-Dev 4047438051170 cm cm

MOBOTIX HUB Plug In - Fisheye Device License for L2 MOBOTIX HUB g cm l


Activates MOBOTIX Fisheye in MOBOTIX HUB L2 further 16 cameras • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • 16 fisheye cameras are supported with one licence • Additional fisheye cameras require further MOBOTIX Fisheye Device licence • Permanent licence



Mx-SW-HUB-ImagP-Bas 4047438051187 cm cm

MOBOTIX HUB Plug In - Imaging Pro Base License for L2 MOBOTIX HUB g cm l

Activates MOBOTIX Imaging Pro support in the MOBOTIX HUB L2 • Imaging Pro offers a wealth of image optimisation tools for the MOBOTIX HUB Desk Client • The obvious image effects are magnifying glass, contrast, brightness, sharpness and some types of pixelation, there are also other image effects / filters • The tools are available in live and playback view • It can be used on MOBOTIX and 3rd party cameras • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • One licence supports 8 cameras • Additional cameras require further MOBOTIX Imaging Pro Device licence • Permanent licence



Mx-SW-HUB-ImagP-Dev 4047438051194 cm cm

MOBOTIX HUB Plug In - Imaging Pro Base Device for L2 MOBOTIX HUB g cm l

Activates additional cameras in MOBOTIX HUB L2 for MOBOTIX Imaging Pro support • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • 16 additional cameras are supported with one licence • Additional cameras require MOBOTIX Imaging Pro Device licence • Permanent licence



Mx-SW-HUB-SoftB-Bas 4047438051293 cm cm

MOBOTIX HUB Plug In - Softbuttons Base License for L2 MOBOTIX HUB g cm l

Activates MOBOTIX Softbuttons support in the MOBOTIX HUB L2 • Trigger API commands via buttons - Large number of predefined API commands selectable for MOBOTIX cameras - External devices controllable via custom API • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • One licence supports 32 cameras • Additional cameras require MOBOTIX Softbuttons Device licence • Permanent licence



Mx-SW-HUB-SoftB-Dev 4047438051309 cm cm

MOBOTIX HUB Plug In - Softbuttons Device License for L2 MOBOTIX HUB g cm l

Activates additional cameras in MOBOTIX HUB L2 for MOBOTIX Softbuttons PlugIn • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per MOBOTIX HUB VMS is required. • 16 additional cameras are supported with one licence • Additional cameras require further MOBOTIX Softbuttons Device licence • Permanent licence



Mx-SW-MC-QNAP 4047438047791 cm

QNAP QVR Pro license for activation of MxMC Playback cm

g cm

l

Enables MxMC playback support in the QVR Pro recording software on a QNAP NAS with QTS operating system. • Supports MxMC playback from ONVIF cameras such as the MOVE camera series. • Optimal combination on a QNAP NAS • IOT cameras store independently on the NAS via file sharing (SMB) and record the integrated MOVE or ONVIF cameras in parallel with the QVR Pro Recording Software. The output is done with the MxMC. • The license is activated on the QNAP NAS via the QNAP License Manager. • License is not transferable • one license per QNAP NAS with QVR Pro is required! • For camera recordings, QNAP requires additional camera channel licenses per channel, which must be obtained from QNAP!



Mx-SW-MC-Th-DB-Bas 4047438048217 cm

MOBOTIX MxMC Feature - ThermalDashboard Base License for MxMC cm

g cm

l

Activates the MOBOTIX Thermal Dashboard in the MxMC and supports the MOBOTIX Thermal Camera functions • Main applications are: • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MxMC is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX MxMC Device license per camera - Permanent license




Mx-SW-MC-Th-DB-Dev 4047438048224 cm

MOBOTIX MxMC Feature - ThermalDashboard Device License for MxMC cm

g cm

l

Activates another camera in the MOBOTIX Thermal Dashboard in the MxMC and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MxMC is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license




Mx-SW-XPro-CLOUD-Bas 4047438047876 cm

MOBOTIX HUB Plug In - MOBOTIX CLOUD Base License for Milestone XProtect cm

g cm

l

Activates the MOBOTIX CLOUD support in Milestone XProtect • Main application features in the Smart Client are • Integrating cloud cameras in the desk client layout • Additional CLOUD tab in the application • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License




Mx-SW-XPro-CLOUD-Dev 4047438048125 cm

MOBOTIX HUB Plug In - MOBOTIX CLOUD Device License for Milestone XProtect cm

g cm

l

Activates another camera in the MOBOTIX CLOUD support in Milestone XProtect • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX CLOUD Base license • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License



Mx-SW-XPro-Config 4047438047890 cm

MOBOTIX HUB Plug In - MOBOTIX camera Configuration for Milestone XProtect g cm

Activates the configuration settings for MOBOTIX cameras in Milestone XProtect - Management Client offers camera specific configuration tabs for P3/P6/P7 and MOVE cameras - License is activated via the MOBOTIX License Portal. - License is non-transferable - One license per Milestone • Activates the function for all MOBOTIX cameras registered in the system.

cm
l



Mx-SW-XPro-Config-VM 4047438051835 cm

MOBOTIX HUB Plug In - Camera Configuration License VM for Milestone XProtect g cm

Activates the configuration settings for MOBOTIX cameras in Milestone XProtect • Virtual Machine (VM) support • Management Client offers camera specific configuration tabs for P3/P6/P7 and MOVE cameras • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone • Activates the function for all MOBOTIX cameras registered in the system.

cm
l



Mx-SW-XPro-Disco-Bas 4047438051231 cm

MOBOTIX HUB Plug In - Discovery Base License for Milestone XProtect g cm

Activates MOBOTIX Discovery support in the Milestone XProtect • An ideal tool for administrators to add new MOBOTIX cameras to the system more quickly and easily • Supports firmware update and password change • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • One licence supports 32 cameras • Additional cameras require MOBOTIX Discovery Device licence • Permanent licence

cm
l



Mx-SW-XPro-Disco-Bas-VM 4047438051644 cm

MOBOTIX HUB Plug In - Discovery Base License VM for Milestone XProtect g cm

Activates MOBOTIX Discovery support in the Milestone XProtect • Virtual Machine (VM) support • An ideal tool for administrators to add new MOBOTIX cameras to the system more quickly and easily • Supports firmware update and password change • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • One licence supports 32 cameras • Additional cameras require MOBOTIX Discovery Device licence • Permanent licence

cm
l



Mx-SW-XPro-Disco-Dev 4047438051248 cm

MOBOTIX HUB Plug In - Discovery Device License for Milestone XProtect g cm

Activates additional cameras in Milestone XProtect for MOBOTIX Discovery PlugIn • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • 16 additional cameras are supported with one licence • Additional cameras require further MOBOTIX Discovery Device licence • Permanent licence

cm
l



Mx-SW-XPro-Disco-Dev-VM 4047438051651 cm

MOBOTIX HUB Plug In - Discovery Device License VM for Milestone XProtect g cm

Activates additional cameras in Milestone XProtect for MOBOTIX Discovery PlugIn • Virtual Machine (VM) support • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • 16 additional cameras are supported with one licence • Additional cameras require further MOBOTIX Discovery Device licence • Permanent licence

cm
l



Mx-SW-XPro-DualV-Bas 4047438051057 cm

MOBOTIX HUB Plug In - DualVision Base License for Milestone XProtect cm

g cm

l

Activates MOBOTIX DualVision in Milestone XProtect • the dual view of a MOBOTIX camera can be split in the Milestone XProtect Smart Client • display of the left, right or both eyes possible • the eyes can be arranged separately in the camera layout. Split into live and playback view possible • Optimised for MOBOTIX DUAL cameras • 3rd party cameras are also supported • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, 8 Dual Cameras will be supported • Additional Dual Cameras require a MOBOTIX Device license • Permanent license



Mx-SW-XPro-DualV-Dev 4047438051064 cm

MOBOTIX HUB Plug In - DualVision Device License for Milestone XProtect cm

g cm

l

Activates MOBOTIX DualVision in Milestone XProtect • the dual view of a MOBOTIX camera can be split in the MOBOTIX HUB Desk Client • display of the left, right or both eyes possible • the eyes can be arranged separately in the camera layout. Split into live and playback view possible • Optimized for MOBOTIX DUAL cameras • 3rd party cameras are also supported • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, 8 Dual Cameras will be supported • Additional Dual Cameras require further MOBOTIX Device license • Permanent license



Mx-SW-XPro-FishE-Bas 4047438051071 cm

MOBOTIX HUB Plug In - Fisheye Base License for Milestone XProtect cm

g cm

l

Activates MOBOTIX Fisheye in Milestone XProtect • the Fisheye view of a MOBOTIX camera can be corrected in the Milestone XProtect Smart Client • Various equalisation modes are available • Correction in Live and Playback view possible • Correction in Desk Client Export Player possible • MOBOTIX Fisheye and 3rd party Fisheye cameras are supported • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • 8 fisheye cameras are supported with one licence • Additional fisheye cameras require MOBOTIX Fisheye Device licence • Permanent licence




Mx-SW-XPro-FishE-Dev 4047438051088 cm

MOBOTIX HUB Plug In - Fisheye Device License for Milestone XProtect cm

g cm

l

Activates 16 further cameras for MOBOTIX Fisheye support in Milestone XProtect • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • 16 fisheye cameras are supported with one licence • Additional fisheye cameras require further MOBOTIX Fisheye Device licence • Permanent licence



Mx-SW-XPro-ForSe 4047438047913 cm

MOBOTIX HUB Plug In - ForensicSearch for Milestone XProtect cm

g cm

l

Activates the MOBOTIX ForensicSearch filters in Milestone XProtect Smart Client and supports the MOBOTIX event and app meta data for the forensic search - Intelligent search filter reduces the search in the playback to the essential - Search filter for camera apps as well as for MOBOTIX events - Support for camera models P6 / P7 and MOVE LPR models - License is activated via the MOBOTIX License Portal. - License is not transferable - One license per Milestone XProtect VMS is required. - Activates the function for all MOBOTIX cameras registered in the system.



Mx-SW-XPro-ImagP-Bas 4047438051095 cm

MOBOTIX HUB Plug In - Imaging Pro Base License for Milestone XProtect cm

g cm

l

Activates MOBOTIX Imaging Pro support in the Milestone XProtect • Imaging Pro offers a wealth of image optimisation tools for the Milestone XProtect Smart Client • The obvious image effects are magnifying glass, contrast, brightness, sharpness, and some types of pixelation, there are also other image effects / filters • The tools are available in live and playback view • It can be used on MOBOTIX and 3rd party cameras • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • One licence supports 8 cameras • Additional cameras require MOBOTIX Imaging Pro Device licence • Permanent licence



Mx-SW-XPro-ImagP-Dev 4047438051101 cm

MOBOTIX HUB Plug In - Imaging Pro Device License for Milestone XProtect cm

g cm

l

Activates additional cameras in Milestone XProtect for MOBOTIX Imaging Pro support • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • 16 additional cameras are supported with one licence • Additional cameras require further MOBOTIX Imaging Pro Device licence • Permanent licence



Mx-SW-XPro-Nurse-DB-Bas 4047438049306 cm

MOBOTIX HUB Plug In - NurseAssist Dashboard Base License for Milestone XProtect cm

g cm

l

Activates the MOBOTIX NurseAssist Dashboard in Milestone XProtect and supports the MOBOTIX C71 NurseAssist Camera functions • Main applications are • Live monitoring of patient conditions such as fall detection in a dashboard as a status tableau • Patient information •Virtual Patrol • Live image activation with intercom support • Slider too blurred the live image • Activity Log Book • Activity report for statistical analysis • Supports MOBOTIX C71 NurseAssist Kameras • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, Status Tableau from 4 NurseAssist cameras can be integrated in the layout • Additional NurseAssist cameras require one MOBOTIX Device license per camera - Permanent license



Mx-SW-XPro-Nurse-DB-Dev 4047438049320 cm

MOBOTIX HUB Plug In - NurseAssist Dashboard Device License for Milestone XProtect cm

g cm

l

Activates an additional camera for the MOBOTIX NurseAssist Dashboard in Milestone XProtect • Supports MOBOTIX C71 NurseAssist camera functions • Main application areas are • Live monitoring of patient conditions such as Fall detection in a dashboard as a status tableau • Patient information • Virtual tour • Live image activation with intercom support • Slider for live image blurring • Activity log book • Activity report for statistical evaluation • Supports MOBOTIX C71 NurseAssist cameras • Licence is activated via the MOBOTIX licence portal. • Licence is not transferable • One licence per NurseAssist camera required. • Requires a MOBOTIX NurseAssist Dashboard Base licence • With a MOBOTIX NurseAssist Dashboard Base licence, 4 NurseAssist cameras can be integrated in the Status Tableau • Additional NurseAssist cameras require a MOBOTIX Device licence per camera • Permanent licence



Mx-SW-XPro-SoftB-Bas 4047438051255 cm

MOBOTIX HUB Plug In - Softbuttons Base License for Milestone XProtect cm

g cm

l


Activates MOBOTIX Softbuttons support in the Milestone XProtect • Trigger API commands via buttons - Large number of predefined API commands selectable for MOBOTIX cameras - External devices controllable via custom API • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • One licence supports 32 cameras • Additional cameras require MOBOTIX Softbuttons Device licence • Permanent licence



Mx-SW-XPro-SoftB-Dev 4047438051262 cm cm

MOBOTIX HUB Plug In - Softbuttons Device License for Milestone XProtect g cm l


Activates additional cameras in Milestone XProtect for MOBOTIX Softbuttons PlugIn • Licence is activated via the MOBOTIX Licence Portal. • Licence is not transferable • One licence per Milestone XProtect VMS is required. • 16 additional cameras are supported with one licence • Additional cameras require further MOBOTIX Softbuttons Device licence • Permanent licence



Mx-SW-XPro-SYNC-DB-Bas 4047438047852 cm cm

MOBOTIX HUB Plug In - MOBOTIX SYNC Base License for Milestone XProtect g cm l


Activates the MOBOTIX SYNC Dashboard in Milestone XProtect Smart Client • Main applications are - Display of statistical values in diagrams • Display of lists of detected number plates • Support for MOBOTIX SYNC and Helix Vaxtor • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone XProtect VMS is required. • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence



Mx-SW-XPro-SYNC-DB-Dev 4047438048101 cm cm

MOBOTIX HUB Plug In - MOBOTIX SYNC Device License for Milestone XProtect g cm l

Activates another MOBOTIX SYNC Grafana Dashboard in the Milestone XProtect Smart Client. • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX SYNC Base license • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence



Mx-SW-XPro-Th-DB-Bas 4047438047838 cm cm

MOBOTIX HUB Plug In - ThermalDashboard Base License for Milestone XProtect g cm l


Activates the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Main applications are • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license



Mx-SW-XPro-Th-DB-Bas-VM 4047438051873 cm cm

MOBOTIX HUB Plug In - ThermalDashboard VM Base License for Milestone XProtect g cm l

Activates the MOBOTIX Thermal Dashboard in Milestone XProtect in a VM (Virtual Machine) environment and supports the MOBOTIX Thermal Camera functions • Main applications are • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license



Mx-SW-XPro-Th-DB-Dev 4047438048088 cm

MOBOTIX HUB Plug In - ThermalDashboard Device License for Milestone XProtect cm

g cm

l

Activates another camera in the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license



Mx-SW-XPro-Th-DB-Dev-VM 4047438051897 cm

MOBOTIX HUB Plug In - ThermalDashboard VM Device License for Milestone XProtect cm

g cm

l

Activates another camera in the MOBOTIX Thermal Dashboard in Milestone XProtect in a VM (Virtual Machine) environment and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license

Warranty Extensions

Warranty Extensions

	Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
	**Mx-WE-DTVS-1** **1 Year Warranty Extension For Dual Thermal Systems S74 and S16** 5+1 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031974 g	cm cm cm l
	**Mx-WE-DTVS-2** **2 Years Warranty Extension For Dual Thermal Systems S74 and S16** 5+2 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031981 g	cm cm cm l
	**Mx-WE-DTVS-3** **3 Years Warranty Extension For Dual Thermal Systems S74 and S16** 5+3 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031998 g	cm cm cm l
	**Mx-WE-IVS-1** **1 Year Warranty Extension For Indoor Video Systems** 5+1 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031820 g	cm cm cm l
	**Mx-WE-IVS-2** **2 Years Warranty Extension For Indoor Video Systems** 5+2 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031837 g	cm cm cm l



Mx-WE-IVS-3

3 Years Warranty Extension For Indoor Video Systems

5+3 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031844

cm
cm
g cm
l



Mx-WE-OVS-1

1 Year Warranty Extension For Outdoor Video Systems

5+1 Year Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031875

cm
cm
g cm
l



Mx-WE-OVS-2

2 Years Warranty Extension For Outdoor Video Systems

5+2 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031882

cm
cm
g cm
l



Mx-WE-OVS-3

3 Years Warranty Extension For Outdoor Video Systems

5+3 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031899

cm
cm
g cm
l



Mx-WE-STVS-1

1 Year Warranty Extension For Single Thermal Systems M73/S74 or M16/S16

5+1 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031929

cm
cm
g cm
l



Mx-WE-STVS-2

2 Years Warranty Extension For Single Thermal Systems M73/S74 or M16/S16

5+2 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031936

cm
cm
g cm
l



Mx-WE-STVS-3 4047438031943 cm

3 Years Warranty Extension For Single Thermal Systems M73/S74 or M16/S16 cm

5+3 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

g cm

l

Other

BeyondHumanVision

MOBOTIX

Training Courses

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
 **Mx-SE-Advanced** **MOBOTIX Seminar Advanced Course 1 (IoT) - 1 day training** Classroom Training • This one-day seminar covers the in-depth configuration of a MOBOTIX camera system and advanced features of the MxManagementCenter video management software • In this comprehensive hands-on training, you will learn how to optimize settings and manage demanding IP video projects • Includes “Video Security Professional” certificate.	4047438049689 g	cm cm cm l
 **Mx-SE-GDPR-DE** **MOBOTIX Seminar Datenschutz Video - ONLY in German** Classroom Training - Datenschutz Video • ONLY available in German language	4047438049757 g	cm cm cm l
 **Mx-SE-Grund-Video-DE** **MOBOTIX Seminar Videosicherheitstechnik - ONLY in German** Grundkurs Videosicherheitstechnik • ONLY available in German language	4047438049696 g	cm cm cm l
 **Mx-SE-HTTP-API** **MOBOTIX Seminar HTTP API & MxMessageSystem - 1 day** Classroom Training • This one-day seminar focuses on the use of the HTTP API and the MxMessageSystem via network and MxBus • Connection of the MOBOTIX 7 apps to the event logic of the IoT system • incl. “Integration Professional” certificate.	4047438049672 g	cm cm cm l
 **Mx-SE-HUB-S-D** **MOBOTIX Hub Sales & Design Seminar – 1 day online** Online training - This online training provides participants with the knowledge and skills they need to design MOBOTIX Hub video management systems. The aim is to effectively support customers' surveillance requirements and optimize the overall profitability of the video surveillance system - Prerequisite basic video security technology course - Includes “MOBOTIX Hub Sales & Design Specialist” certificate	4047438049719 g	cm cm cm l



Mx-SE-HUB-Tec-DE

MOBOTIX Seminar HUB Technical Specialist L1 - ONLY in German

Onlinetraining HUB Technical Specialist L1 • ONLY available in German language

4047438049740

cm
cm
g
cm
l



Mx-SE-HUB-Tec1-EN

MOBOTIX Seminar HUB Technical Specialist L1 - 2 days online

Online Training - This two day online training consists of a series of hands-on exercises in which participants practice configuring a MOBOTIX Hub video management system. Step-by-step instructions and a professional trainer will guide participants in configuring systems according to sample specifications.ü Prerequisite Basic Video Security Technology Course and MOBOTIX Sales & Design • Incl. “MOBOTIX Hub Technical Specialist L1” certificate.

4047438049726

cm
cm
g
cm
l



Mx-SE-HUB-Tec2-EN

MOBOTIX Seminar HUB Technical Specialist L2 - 2 days online

Online Training - This two day online training consists of a series of hands-on exercises in which participants practice configuring a MOBOTIX Hub video management system. Step-by-step instructions and a professional trainer will guide participants in configuring systems according to sample specifications.ü Prerequisite Basic Video Security Technology Course and MOBOTIX Sales & Design and HUB Technical Specialist L1 • Incl. “MOBOTIX Hub Technical Specialist L2” certificate.

4047438049733

cm
cm
g
cm
l



Mx-SE-MOVE-Expert

MOBOTIX Seminar MOVE System Expert - Online training

Online training - This training is offered in two parts. First, participants work through an intensive system workshop on eCampus. The workshop is divided into several lessons, which are completed within a week at your own pace. Following this, further live training sessions are offered online, in which specific topics are discussed. There is also the opportunity to ask current questions and receive the latest updates. - Incl. “MOBOTIX MOVE System Specialist” certificate

4047438049702

cm
cm
g
cm
l



Mx-SE-Smart-Auto

MOBOTIX Seminar Smart Automation Workshop

Classroom Training - In the seminar “Smart Automation Workshop” you will learn • Concept and development of MQTT • MQTT Broker and first client accesses • Camera as MQTT client and switching of MQTT actuators • The app service for MOBOTIX IoT cameras - Configuration and use of individual camera apps • Incl. certificate “Smart Automation Professional”

4047438049641

cm
cm
g
cm
l



Mx-SE-Thermal

MOBOTIX Seminar Thermal - 1 day training course

Classroom Training • In the “Thermal imaging technology” seminar, you will learn about the MOBOTIX thermal imaging camera product portfolio. It also covers the basics of thermal cameras and sample applications. Each participant can deepen their knowledge in practical exercises with a thermal imaging camera. • incl. certificate “MOBOTIX certified installer of thermal imaging systems”.

4047438049665

cm
cm
g
cm
l





Mx-SE-VDS-EN54


MOBOTIX Seminar VDS & EN54 - 1 day classroom training

Classroom Training - In the seminar “VdS & EN54” you will learn about the EN54-certified thermal system from MOBOTIX for early fire detection • Details about the necessary requirements to couple the MOBOTIX thermal camera with a fire alarm system • Prerequisite “Basic Course Video Security Technology” and “Advanced Course 1 Video Security Technology” • Incl. certificate “MOBOTIX certified installer of VdS-compliant early fire detection systems”

4047438049658		cm
		cm
	g	cm
		l

Professional Services

Article No. / Name / Descriptic	EAN / HS / weigh	dimen.
 **Password-Reset-Software** **Professional Services Password Reset Software** This password reset is an encrypted, time limited (will expire after 30 days) software file, specific for the factory IP of the camera directly on–site at your customers location.	4047438035392 g	cm cm cm l
 **PS-Field-Service-Day** **Professional Services Field Engineering & On-Site Support, 1 Day** Available for MOBOTIX systems of any size and for all MOBOTIX hardware and software products; fixed price flat rate for one working day. • Field Engineering: System configuration, commissioning and user training directly on site. Complete configuration and customization. • On-site Support: One working day for on-site support and troubleshooting directly at the project site. Professional health and storage check, troubleshooting through reconfiguration and re-configuration, on-site user training.	4047438035347 g	cm cm cm l
 **PS-Field-Service-Day-100** **Professional Services Onsite Field Engineering / Project Commissioning** Onsite Field Engineering / Project Commissioning for projects of over 100+ MOBOTIX cameras (excludes travel costs)	4047438048149 g	cm cm cm l
 **PS-Field-Service-Half-Day** **Professional Services Field Engineering & On-Site Support, 0.5 Days** Available for MOBOTIX systems of any size and for all MOBOTIX hardware and software products; fixed price flat rate for half a working day. • Field Engineering: System configuration, commissioning and user training directly on site. Complete configuration and customization. • On-site Support: One working day for on-site support and troubleshooting directly at the project site. Professional health and storage check, troubleshooting through reconfiguration and re-configuration, on-site user training.	4047438035354 g	cm cm cm l
 **PS-PreConfig-9plus1free** **Professional Services Every 10th Pre-Configuration per PO is free** Every 10th Pre-Configuration per PO is free (Buy 9 get 1 Free)	4047438048163 g	cm cm cm l



PS-PreConfig-IoT


Professional Services Pre-Configuration per IoT-Camera

Pre-Configuration of all MOBOTIX IoT Cameras incl. Function Guarantee direct from production

4047438035316

g

cm
cm
cm
l



PS-PreConfig-IoT-Doorstation


Professional Services Pre-Configuration per Doorstation

Pre-Configuration of all MOBOTIX DoorStations incl. Function Guarantee direct from production

4047438035323

g

cm
cm
cm
l



PS-PreConfig-MxMove

Professional Services Pre-Configuration per MOVE-Camera

Pre-Configuration of all MOBOTIX MOVE Cameras incl. Function Guarantee direct from production

4047438035330

g

cm
cm
cm
l



PS-Remote-Service-Half-Hour

Professional Services Remote Support Half-Hourly Rate

Half Hour professional troubleshooting, rectification and system optimization via secure IP remote connection by MOBOTIX specialists

4047438035385

g

cm
cm
cm
l



PS-Remote-Service-Hour

Professional Services Remote Support Hourly Rate

One Hour professional troubleshooting, rectification • and system optimization via secure IP remote connection by MOBOTIX specialists

4047438035378

g

cm
cm
cm
l



PS-Remote-Support-Opt

Professional Services Remote Support System Optimization

Remote Support System Optimization • 1 hr Remote Support free for every 20 Pre-Configurations per PO

4047438048156

g

cm
cm
cm
l



PS-Travelcost 4047438035361 cm

Professional Services Travel & Accommodation Costs cm

Costs for travel expenses of the MOBOTIX specialist. Maximum 2000€. g cm

l



PS-Travelcost-plus 4047438048170 cm

Professional Services Increased Travel & Accommodation Costs cm

Increase the maximum chargeable for travel costs to €3000 g cm

l